


# ENGINEERING TEST REPORT



**Cube**

**Model No.: 800-xxx**

**FCC ID: T78-WL18**

**IC: 6656A-WL18**

Tested For

**Librestream Technologies**

895 Waverly Street, Suite 110

Winnipeg, Manitoba

Canada. R3T 5P4

In accordance with

**SAR (Specific Absorption Rate) Requirements using guidelines established in  
IEEE C95.1-2010, FCC OET Bulletin 65 (Supplement C) and Industry Canada RSS-102 (Issue 5)**

**EN 50360 (Council Recommendation 1999/519/EC)**

**ARPANSA Radio Protection Series Publication No. 3**

**EN 50566:2013 & EN 62479:2010**

**UltraTech's File No.: LIBT-085Q-SAR**

This Test report is Issued under the Authority of:

Tri M. Luu, BASc,  
Vice President of Engineering  
UltraTech Group of Labs

Date: September 18, 2018

Report Prepared by: Ketav Jani

Tested by: Ketav Jani

Issued Date: September 18<sup>th</sup>, 2018

Test Dates: August 30 ~ September 13th, 2018

*The results in this Test Report apply only to the sample(s) tested, which has been randomly selected.*

## UltraTech Group of Labs

3000 Bristol Circle, Oakville, Ontario, Canada, L6H 6G4

Tel.: (905) 829-1570 Fax.: (905) 829-8050

Website: [www.ultratech-labs.com](http://www.ultratech-labs.com), Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Email: [tri@ultratech-labs.com](mailto:tri@ultratech-labs.com)



91038



1309



46390-2049



AT-1945



SL2-IN-E-1119R



Korea  
KCC-RRR  
CA2049

## TABLE OF CONTENTS

|   |           |
|---|-----------|
| <b>EXHIBIT 1. INTRODUCTION .....</b>  | <b>1</b>  |
| 1.1. SCOPE.....   | 1         |
| 1.2. REFERENCES .....   | 2         |
| <b>EXHIBIT 2. PERFORMANCE ASSESSMENT.....</b>                                 | <b>3</b>  |
| 2.1. CLIENT AND MANUFACTURER INFORMATION .....                                | 3         |
| 2.2. DEVICE UNDER TEST (D.U.T.) DESCRIPTION .....                             | 4         |
| 2.2.1. Photographs of D.U.T.....  | 5         |
| 2.3. LIST OF D.U.T.'S ACCESSORIES:.....                                       | 11        |
| 2.4. SPECIFIC OPERATING AND TEST CONDITIONS.....                              | 12        |
| 2.4.1. Mounting Hardware .....  | 13        |
| 2.4.2. Distance from Antenna to Body.....                                     | 15        |
| 2.4.3. Device Variations .....  | 15        |
| 2.4.4. SAR Test Operation .....   | 16        |
| 2.5. CONNECT UUT TO PC.....   | 16        |
| 2.6. CONNECTING TO UUT WITH ADB.....  | 16        |
| 2.6.1. Set the Wifi radio in the SAR Test Mode.....                           | 17        |
| 2.6.2. Simultaneous Transmission Conditions.....                              | 17        |
| 2.6.3. RSS-102 2.5.1 Exemption Limits for Routine Evaluation .....            | 18        |
| 2.6.4. FCC KDB 447498 D01 General RF Exposure Guidance v06 - Appendix A ..... | 18        |
| 2.6.5. Test Channel Selection.....  | 19        |
| <b>EXHIBIT 3. SUMMARY OF TEST RESULTS .....</b>                               | <b>20</b> |
| 3.1. LOCATION OF TESTS .....  | 20        |
| 3.2. APPLICABILITY & SUMMARY OF SAR RESULTS .....                             | 20        |
| 3.2.1. 2.45GHz Reported SAR for standalone transmissions (scaled).....        | 21        |
| <b>EXHIBIT 4. SAR SYSTEM CONFIGURATION .....</b>                              | <b>22</b> |
| 4.1. DASY5 SYSTEM OVERVIEW.....   | 22        |
| 4.1.1. DASY5 System Specification.....  | 22        |
| 4.1.2. DASY5 SAR SYSTEM block diagram.....                                    | 25        |
| 4.2. SAR TEST PHANTOMS .....  | 26        |
| 4.2.1. SAM Twin Phantom .....   | 26        |
| 4.2.2. ELI 4.0 Phantom.....   | 26        |
| <b>EXHIBIT 5. SAR DATA ACQUISITION METHODOLOGY .....</b>                      | <b>27</b> |
| 5.1. SAR MEASUREMENT PROCEDURE.....   | 27        |
| 5.1.1. Interpolation, Extrapolation and Detection of Maxima.....              | 29        |
| 5.1.2. Averaging and Determination of Spatial Peak SAR .....                  | 30        |
| 5.1.3. Evaluation Errors .....  | 30        |
| <b>EXHIBIT 6. MEASUREMENTS, EXAMINATIONS &amp; TEST DATA.....</b>             | <b>32</b> |
| 6.1. TEST CONFIGURATIONS .....  | 32        |
| 6.1.1. Wifi 802.11 a/b/g/n 2450 MHz.....                                      | 32        |
| 6.1.2. Wifi 802.11 a/b/g/n 5200-5825 MHz.....                                 | 33        |
| 6.2. GENERAL TEST SETUP .....   | 34        |
| 6.2.1. Equipment Configuration.....   | 34        |
| 6.2.2. Exercising Equipment.....  | 34        |
| 6.3. PHOTOGRAPHS OF TISSUE DEPTH.....   | 35        |

### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

|                    |   |           |
|--------------------|---|-----------|
| 6.4.               | PHOTOGRAPHS OF D.U.T. POSITION.....   | 36        |
| 6.4.1.             | <i>Head Configuration for Back Side Exposure</i> .....                                      | 36        |
| <b>EXHIBIT 7.</b>  | <b>SAR MEASUREMENT SYSTEM VERIFICATION .....</b>  | <b>37</b> |
| 7.1.               | STANDARD SOURCE.....  | 37        |
| 7.2.               | STANDARD SOURCE INPUT POWER MEASUREMENT .....   | 38        |
| 7.3.               | SYSTEM VALIDATION PROCEDURE .....   | 38        |
| 7.4.               | VERIFICATION RESULTS .....  | 39        |
| 7.4.1.             | <i>Reference Dipole SAR measurements</i> .....  | 39        |
| 7.4.2.             | <i>Verification at 2450 MHz</i> .....   | 40        |
| 7.4.3.             | <i>Verification at 5200 MHz</i> .....   | 41        |
| 7.4.4.             | <i>Verification at 5400 MHz File Name: System Verification - D5400MHz_Head.da52:0</i> ..... | 42        |
| 7.4.5.             | <i>Verification at 5600 MHz</i> .....   | 43        |
| 7.4.6.             | <i>Verification at 5800 MHz</i> .....   | 44        |
| <b>EXHIBIT 8.</b>  | <b>D.U.T. POWER MEASUREMENT .....</b>   | <b>45</b> |
| 8.1.1.             | <i>RF Conducted output power measurement</i> .....  | 46        |
| <b>EXHIBIT 9.</b>  | <b>TISSUE DIELECTRIC PARAMETER CALIBRATION .....</b>  | <b>47</b> |
| 9.1.               | SIMULATED TISSUE .....  | 47        |
| 9.2.               | MEASUREMENT OF ELECTRICAL CHARACTERISTICS OF SIMULATED TISSUE .....                         | 48        |
| 9.2.1.             | <i>Equipment set-up</i> .....   | 48        |
| 9.2.2.             | <i>Measurement procedure</i> .....  | 49        |
| 9.3.               | SIMULATED TISSUE MEASUREMENT RESULTS .....  | 50        |
| 9.3.1.             | <i>2450 MHz Muscle Tissue</i> .....   | 50        |
| 9.3.2.             | <i>5500 MHz Muscle Tissue</i> .....   | 50        |
| <b>EXHIBIT 10.</b> | <b>SAR MEASUREMENT UNCERTAINTY .....</b>  | <b>51</b> |
| 10.1.              | MEASUREMENT UNCERTAINTY EVALUATION FOR SAR TEST .....                                       | 51        |
| <b>EXHIBIT 11.</b> | <b>ADDITIONAL TEST INSTRUMENTS LIST .....</b>   | <b>52</b> |
| <b>EXHIBIT 12.</b> | <b>SAR MEASUREMENT DATA .....</b>   | <b>52</b> |
| <b>EXHIBIT 13.</b> | <b>SAR CALIBRATION CERTIFICATES .....</b>   | <b>52</b> |

## EXHIBIT 1. INTRODUCTION

### 1.1. SCOPE

|                                |   |
|--------------------------------|---|
| <b>Reference:</b>              | SAR (Specific Absorption Rate) Requirements<br>IEEE C95.1-2010,<br>FCC OET Bulletin 65 (Supplement C Edition 01-01)<br>Industry Canada RSS-102 (Issue 5).                 |
| <b>Title</b>                   | Safety Levels with respect to human exposure to Radio Frequency Electromagnetic Fields<br>Guideline for Evaluating the Environmental Effects of Radio Frequency Radiation |
| <b>Purpose of Test:</b>        | To verify compliance with Federal regulated SAR requirements in Canada and the US.  |
| <b>Method of Measurements:</b> | IEEE C95.1-2010, FCC OET Bulletin 65 (Supplement C Edition 01-01) and Industry Canada<br>RSS-102 (Issue 5)  |
| <b>Device Category</b>         | Portable  |
| <b>Exposure Category</b>       | General/un-controlled   |

---

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## 1.2. REFERENCES

The methods and procedures used for the measurements contained in this report are details in the following reference standards:

| Publications                  | Year | Title   |
|-------------------------------|------|---|
| IEEE Std. 1528                | 2013 | Draft Recommended practice for determining the Peak Spatial-Average Specific Absorption rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.   |
| Industry Canada RSS-102       | 2015 | “Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada’s Safety Code 6 for Exposure of Humans to Radio Frequency Fields”  |
| NCRP Report No.86             | 1986 | “Biological Effects and Exposure Criteria for radio Frequency Electromagnetic Fields”   |
| FCC OET Bulletin 65           | 2001 | “Evaluating Compliance with FCC Guidelines for Human Exposure to radio Frequency Fields”  |
| ANSI/IEEE C95.3               | 2002 | “Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave”   |
| ANSI/IEEE C95.1               | 2010 | “Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300GHz”  |
| ARPANSA                       | 2002 | RADIATION PROTECTION STANDARD<br>Maximum Exposure Levels to Radiofrequency Fields — 3 kHz to 300 GHz<br>Radiation Protection Series Publication No. 3   |
| EN 50566                      | 2013 | Product standard to demonstrate compliance of radio frequency fields from handheld and body-mounted wireless communication devices used by the general public (30 MHz - 6 GHz)  |
| EN 62479                      | 2010 | Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)   |
| IEC 62209-2                   | 2010 | Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)             |
| FCC KDB                       | 2017 | 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04<br>248227 D01 802.11 Wi-Fi SAR v02r02<br>648474 D04 Handset SAR v01r02<br>447498 D01 General RF Exposure Guidance v06<br>447498 D03 Supplement C Cross-Reference<br>388624 D02 Pre-Approval Guidance List v16r02<br>865664 D02 RF Exposure Reporting v01r01<br>690783 D01 SAR Listings on Grants v01r0 |
| Health Canada’s Safety Code 6 | 2015 | Limits of Human Exposure to Radiofrequency Electromagnetic Energy in the Frequency Range from 3 kHz to 300 GHz  |

### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 2. PERFORMANCE ASSESSMENT

### 2.1. CLIENT AND MANUFACTURER INFORMATION

| APPLICANT:      |   |
|-----------------|---|
| Name:           | Librestream Technologies, Inc.  |
| Address:        | 895 Waverley Street, Suite 110<br>Winnipeg, Manitoba<br>Canada, R3T 5P4   |
| Contact Person: | Mr. Elwood Friesen<br>Phone #: +1.204.487.0612 ext 212<br>Email Address: <a href="mailto:elwood.friesen@librestream.com">elwood.friesen@librestream.com</a> |

| MANUFACTURER:   |   |
|-----------------|---|
| Name:           | Librestream Technologies, Inc.  |
| Address:        | 895 Waverley Street, Suite 110<br>Winnipeg, Manitoba<br>Canada, R3T 5P4   |
| Contact Person: | Mr. Elwood Friesen<br>Phone #: +1.204.487.0612 ext 212<br>Email Address: <a href="mailto:elwood.friesen@librestream.com">elwood.friesen@librestream.com</a> |

---

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## 2.2. DEVICE UNDER TEST (D.U.T.) DESCRIPTION

The following is the information provided by the applicant.

|   |  |
|---|--|
| <b>Trade Name</b>                       | Cube   |
| <b>Product Description</b>              | Wearable Camera  |
| <b>Type/Model Number</b>                | 800-xxx (where xxx specifies Rugged or EX variant)   |
| <b>Serial Number</b>                    | 04A3164B488A   |
| <b>Frequency of Operation</b>           | 2412 ~ 2462 MHz; 5180MHz ~ 5850MHz   |
| <b>Maximum RF Output Power</b>          | 802.11b: 16.5dBm average conducted<br>802.11g: 18.0dBm average conducted<br>802.11a: 18.0dBm average conducted<br>802.11n: 18.0dBm average conducted       |
| <b>Modulation Employed</b>              | 802.11b: DBPSK(1Mbps), DQPSK(2Mbps), CCK(5.5/11Mbps)<br>802.11g: OFDM(6M-54Mbps)<br>802.11a: BPSK, QPSK, 16QAM, 64QAM<br>802.11n: BPSK, QPSK, 16QAM, 64QAM |
| <b>Antenna</b>                          | Ethertronic P/N 1000146  |
| <b>Power Supply</b>                     | External Power Supply Adapter: 120/230Vac 50/60 Hz (AC/DC Adaptor, Phihong, M/N: PSA10F-050Q)<br>Integrated Li-Ion Battery (3.7Vdc, 2200mAh)               |
| <b>Primary User Functions of D.U.T.</b> | Provide Head or Helmet mounted wireless video and audio data communications  |

---

### ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### 2.2.1. Photographs of D.U.T

< Front View >



#### **ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

**File #: LIB-085Q-SAR**

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



< Back View >



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

<Top View>



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

< Bottom View >



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

**File #: LIB-085Q-SAR**

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

< Right Side View >




**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

< Left Side View >



**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>


File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



### 2.3. LIST OF D.U.T.'S ACCESSORIES:

#### Cube Head Worn, Helmet mounted magnetic Accessories List:



#### **ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

**File #: LIB-085Q-SAR**

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## 2.4. SPECIFIC OPERATING AND TEST CONDITIONS

Device under tests supporting:

- WiFi 802.11abgn
- Bluetooth BLE

### Radio Features

- 20MHz and 40MHz SISO
- 2.4-GHz MRC Support for Extended Range and 5-GHz (SISO)

### 2.4GHz Wifi Tx Modes

#### Antenna 1 only (SISO)

##### Supported Modes

- 802.11b, DSSS, 1, 2, 5.5, 11Mbps (2.4GHz)
- 802.11g, OFDM, 6, 9, 12, 18, 24, 36, 48, 54 (2.4GHz)
- 802.11n, OFDM, 20MHz, MCS0-7
- 802.11n, OFDM, 40MHz, MCS0 and MCS7

### 5GHz Wifi Tx Modes

#### Ant1 (SISO)

##### Supported Modes

- 802.11a, OFDM 6, 9, 12, 18, 36, 48, 54 (5GHz)
- 802.11n, OFDM, 20MHz, MCS0-MCS7
- 802.11n, OFDM, 40MHz, MCS0 and MCS7

### 2.4GHz Bluetooth

#### Antenna 1

The device is a head worn or helmet mounted high definition video streaming device used in video conferencing and remote consulting sessions. The device's primary operating mode and design is intended to be used in a head worn or helmet mounted position in front of an operator or mounted on a fixed supporting camera tripod. All accessories provided are designed only for use head worn or helmet mounted. FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02 test reduction will be followed to reduce the number of SAR scans required to determine compliance.

During the Initial SAR tests, it was determined that the SAR readings were very low when the mounting cradle was employed. In order to provide a more conservative measurement, the SAR tests were carried out without the mounting cradle with the back of the camera directly touching the phantom surface to provide the lowest separation distance possible.

There are two model variations of the Cube for use in hazardous and non-hazardous environments. The internal components and PCB are identical with the major difference being the addition of PCB metal shields and potting compounds. The Cube Rugged was selected for final qualification tests as pre-scan between the two models revealed no significant difference in SAR as the measured SAR was found to be extremely low in both models.

---


## ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

The Cube is a wearable device that incorporates a dual band WiFi and Bluetooth radio. The distance between the user's head and the transmitting RF antenna is controlled by the mounting hardware and should be used for Specific Absorption Rate testing.



*Figure 1. Antenna Location in Device Under Test*

#### **2.4.1. Mounting Hardware**

There are three mounting accessories that are used for three types of mount:

1. Headband
2. Hardhat Mount
3. Climbing Helmet Mount

Each mount uses a common proprietary magnetic cradle that holds the device and locates the device in front of the user's forehead. The plastics, springs and magnets that are used to build these cradles are identical for all variations and are unique to this device. Only the Headband mounts directly to the user head. Both the hardhat and the climbing helmet mount are attached to helmets that place additional distance between the user head and the device. The mount that guarantees the minimum separation between RF antenna and the user head is the Headband.






Figure 2. Mounting Variations: Headband, Hardhat, Climbing Helmet (top to bottom)




Figure 3. Mounting Variations: Headband, Hardhat, Climbing Helmet (top to bottom)

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

2.4.2. Distance from Antenna to Body

Using the CAD model for the device under test and the associated mounting hardware, we can measure the minimum distance between the transmitting antenna element and the users head. The minimum separation distance between the antenna and the user is 54mm.




Figure 4. Separation between antenna element and user head

2.4.3. Device Variations

The Cube device is manufactured in two major variations:

1. Cube Rugged – designed for use in rugged, industrial environments
2. Cube EX – designed for use in Hazardous Locations with Class/Div ratings.

The majority of components in the device are consistent between the two variations. The differences are highlighted in the table below:

| Cube Rugged   | Cube EX   | Common | Different |
|---|---|--------|-----------|
| Antenna Element and Cable (Ethertronics 1000146 + UFL coax) |   | ✓      |           |
| Aluminum Frame and Heatsink                                 |   | ✓      |           |
| Plastic Front and Back Housing (EXL9330 grey)               |   | ✓      |           |
| Multilayer PCBs (Core, Interface, Illumination)             |   | ✓      |           |
| Magnetic USB Cable and Charger                              |   | ✓      |           |
| Battery Cell (ICP103450)                                    |   | ✓      |           |
| Battery Wire Harness attaches with connector                | Battery Wire Harness attaches with connector and soldered wires |        | ✓         |
| PCB level shields (qty 1)                                   | PCB level shields (qty 3)                                       |        | ✓         |
| No encapsulation  | Insulating encapsulation under PCB and shields                  |        | ✓         |

#### 2.4.4. SAR Test Operation

This section describes how to place the UUT in the SAR test mode.

### 2.5. CONNECT UUT TO PC

Connect a USB cable between the PC and the USB port of the UUT (see pictures below) and power up the UUT.



### 2.6. CONNECTING TO UUT WITH ADB

Sending commands to the UUT is done via the Android Debug Bridge (ADB). With ADB you can access the UUT's command shell and issue commands. To access the command shell on the UUT type the following command in the command prompt window: `adb shell` (wait until the UUT is fully booted).

If you are successful, you will see the UUT's command prompt `root@cubex:/ #` as shown in the image below.

```
SDK Command Prompt - adb shell
C:\Temp>
C:\Temp>
C:\Temp>adb shell
* daemon not running. starting it now on port 5037 *
* daemon started successfully *
root@cubex:/ #
```

In order to run the test scripts to control the WiFi radio, you will need to change the directory using the command

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### **2.6.1. Set the Wifi radio in the SAR Test Mode.**

A script has been installed in the /cache directory of the UUT to help with SAR testing. The script called sar\_setup will configure the UUT for SAR testing including setting the correct power level.

In order to run the test scripts to control the WiFi radio, you will need to change the directory using the command: cd cache  
To set the correct TX power level, run the sar\_setup script.

The command format is:

```
. /sar_setup [CHANNEL] [RATE] [BANDWIDTH] [REG_DOMAIN] [POWER]
```

### **2.6.2. Simultaneous Transmission Conditions**

The device supports Wifi 802.11 abgn transmissions and/or BLE transmissions.


WLAN is tested on the channel with the highest measured average conducted power

SAR evaluation of 802.11g and 802.11n channels is not required when the maximum average output power is less than 0.25dB higher than the measured corresponding 802.11a and 802.11n channels.

The Bluetooth (+4.9mW FCC Grant Listing) transmissions coupled with the separation distance of 54mm are below the test exclusion threshold and SAR evaluation and is not required under FCC KDB 447498 and FCC KDB 648474 or RSS-102. According to FCC KDB 447498 and FCC KDB 648474, simultaneous SAR evaluation is not required because the sum of 1g SAR values measured for all simultaneous transmitting antennas is less than 1.6W/kg limit.


### 2.6.3. RSS-102 2.5.1 Exemption Limits for Routine Evaluation

| Separation Distances (mm) | Exemption Limits 2450 MHz (mW) |
|---------------------------|--------------------------------|
| 0                         | 0.00                           |
| 5                         | 4.00                           |
| 9                         | 5.72                           |
| 10                        | 7.00                           |
| 15                        | 15.00                          |
| 20                        | 30.00                          |
| 25                        | 52.00                          |
| 30                        | 83.00                          |
| 35                        | 123.00                         |
| 40                        | 173.00                         |
| 45                        | 235.00                         |
| 50                        | 309.00                         |



### 2.6.4. FCC KDB 447498 D01 General RF Exposure Guidance v06 - Appendix A

| Separation Distances (mm) | Exclusion Thresholds Limits 2450 MHz (mW) | Calculated Thresholds 2450 MHz (mW) |
|---------------------------|---|-------------------------------------|
| 0                         | 0.00                                      | 0.00                                |
| 5                         | 10.00                                     | 9.58                                |
| 9                         | 17.29                                     | 17.25                               |
| 10                        | 19.00                                     | 19.17                               |
| 15                        | 29.00                                     | 28.75                               |
| 20                        | 38.00                                     | 38.33                               |
| 25                        | 48.00                                     | 47.92                               |
| 30                        | 57.00                                     | 57.50                               |
| 35                        | 67.00                                     | 67.08                               |
| 40                        | 77.00                                     | 76.67                               |
| 45                        | 86.00                                     | 86.25                               |
| 50                        | 96.00                                     | 95.83                               |



### 2.6.5. Test Channel Selection

| GHz   | Chan | Turbo Chan   | Default Test Channels - Antenna 2 |       |         |       |         |       |         |       |         |       |
|-------|------|--------------|-----------------------------------|-------|---------|-------|---------|-------|---------|-------|---------|-------|
|       |      |              | 15.247                            |       |         |       |         |       | UNII    |       |         |       |
|       |      |              | 802.11b                           |       | 802.11g |       | 802.11n |       | 802.11a |       | 802.11n |       |
|       |      |              | Rated                             | Meas  | Rated   | Meas  | Rated   | Meas  | Filed   | Meas  | Filed   | Meas  |
| 2412  | 1    |              | 18                                | 18.60 | 18      | 18.53 | 20      | 19.45 | N/A     | N/A   | N/A     | N/A   |
| 2437  | 6    | 6            | 18                                | 18.00 | 18      | 19.42 | 20      | 19.89 | N/A     | N/A   | N/A     | N/A   |
| 2462  | 11   |              | 18                                | 17.83 | 18      | 18.81 | 20      | 19.57 | N/A     | N/A   | N/A     | N/A   |
| 5180  | 36   |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 15.71   | 15.84 | 15.54   | 15.66 |
| 5200  | 40   | 42(5.21GHz)  | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 15.27 |         | 15.23 |
| 5220  | 44   |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 15.82   | 15.36 | 15.53   | 15.26 |
| 5240  | 48   | 50(5.25GHz)  | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 15.56   | 15.06 | 15.48   | 14.56 |
| 5260  | 52   |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 13.3    | 13.62 | 13.44   | 13.87 |
| 5280  | 56   | 58(5.29GHz)  | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 13.85 |         | 13.76 |
| 5300  | 60   |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 13.48   | 13.88 | 13.87   | 13.95 |
| 5320  | 64   |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 13.28   | 13.34 | 13.37   | 13.51 |
| 5500  | 100  | Unknown      | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 14.52   | 14.66 | 14.93   | 14.63 |
| 5520  | 104  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 14.90 |         | 15.64 |
| 5540  | 108  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 15.50 |         | 16.15 |
| 5560  | 112  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 16.22 |         | 16.33 |
| 5580  | 116  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 18.44   | 16.89 | 17.52   | 16.30 |
| 5600  | 120  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 16.80 |         | 16.09 |
| 5620  | 124  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 16.95 |         | 16.71 |
| 5640  | 128  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 16.69 |         | 16.35 |
| 5660  | 132  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 16.71 |         | 16.50 |
| 5680  | 136  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 17.05 |         | 16.41 |
| 5700  | 140  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 11.94   | 11.78 | 12.19   | 12.21 |
| 5745  | 149  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 12.82   | 10.25 | 12.72   | 10.51 |
| 5765  | 153  | 152(5.76GHz) | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 15.21 |         | 14.67 |
| 5785  | 157  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 17.88   | 14.66 | 17.56   | 14.45 |
| 5805  | 161  | 160(5.8GHz)  | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   |         | 14.41 |         | 14.12 |
| 5.825 | 165  |              | N/A                               | N/A   | N/A     | N/A   | N/A     | N/A   | 14.03   | 13.87 | 13.87   | 12.83 |

### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 3. SUMMARY OF TEST RESULTS

### 3.1. LOCATION OF TESTS

All of the measurements described in this report were performed at UltraTech Group of Labs located at:

3000 Bristol Circle, city of Oakville, Province of Ontario, Canada.

All measurements were performed in UltraTech's shielded chamber, 16' x 13' x 8'.

### 3.2. APPLICABILITY & SUMMARY OF SAR RESULTS

| SAR LIMITS - GENERAL POPULATION |                  |                            |                    |                  |                        |
|---------------------------------|------------------|----------------------------|--------------------|------------------|------------------------|
|                                 | Australia<br>ACA | North America<br>ANSIC95.1 | Europe<br>ENV50166 | Japan<br>TTC/MPT | New Zealand<br>NZS2772 |
| Whole Body                      | 0.08 W/kg        | 0.08 W/kg                  | 0.08 W/kg          | 0.04 W/kg        | 0.08 W/kg              |
| Spatial Peak                    | 2 W/kg           | 1.6 W/kg                   | 2 W/kg             | 2 W/kg           | 2 W/kg                 |
| Extremities                     | 4.0 W/Kg         | 4.0 W/Kg                   | 4.0 W/Kg           | 4.0 W/Kg         | 4.0 W/Kg               |
| Averaging Time                  | 6 min            | 30 min                     | 6 min              | 6 min            | 6 min                  |
| Averaging Time                  | 10g              | 1g                         | 10g                | 10g              | 10g                    |
| Shape                           | Cube             | Cube                       | Cube               | Cube             | Cube                   |

The maximum peak spatial – 1g average SAR reported was found to be 0.007 W/Kg for Head configuration.

The maximum peak spatial – 10g average SAR reported was found to be 0.003 W/Kg for Head configuration.

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**3.2.1. 2.45GHz Reported<sup>1</sup> SAR for standalone transmissions (scaled)**

|          |    | 802.11b |       |       | 802.11g |        |       | 802.11n(HT20) |        |        | 802.11n(HT40) |        |       | Maximums |        |        |        |
|----------|----|---------|-------|-------|---------|--------|-------|---------------|--------|--------|---------------|--------|-------|----------|--------|--------|--------|
|          |    | Channel | Power | SAR1g | SAR10g  | Power  | SAR1g | SAR10g        | Power  | SAR1g  | SAR10g        | Power  | SAR1g | SAR10g   | SAR1g  | SAR10g |        |
|          |    | #       | (MHz) | (dBm) | (mW/g)  | (mW/g) | (dBm) | (mW/g)        | (mW/g) | (dBm)  | (mW/g)        | (mW/g) | (dBm) | (mW/g)   | (mW/g) | (mW/g) | (mW/g) |
| 2450 MHz | 1  | 2,412   | 15.97 |       |         |        | 17.93 |               |        | 17.09  |               |        | 17.29 |          |        | 0.003  | 0.000  |
|          | 6  | 2,437   | 18.72 | 0.003 | 0.000   | 19.04  | 0.001 | 0.000         | 19.06  | <0.001 | <0.001        | 19.42  | 0.002 | 0.000    |        |        |        |
|          | 11 | 2,462   | 15.88 |       |         | 17.78  |       |               | 17.35  |        |               | 17.26  |       |          |        |        |        |

|         |          |     | 802.11a |       |                | 802.11n         |                  |                | Maximums        |                  |                 |                  |
|---------|----------|-----|---------|-------|----------------|-----------------|------------------|----------------|-----------------|------------------|-----------------|------------------|
|         |          |     | Channel |       | Power<br>(dBm) | SAR1g<br>(mW/g) | SAR10g<br>(mW/g) | Power<br>(dBm) | SAR1g<br>(mW/g) | SAR10g<br>(mW/g) | SAR1g<br>(mW/g) | SAR10g<br>(mW/g) |
|         |          |     | #       | (MHz) |                |                 |                  |                |                 |                  |                 |                  |
| 5500MHz | U-NII-1  | 36  | 5180    | 12.76 | < 0.001        | < 0.001         | 11.82            | 0.000          | < 0.001         | 0.007            | 0.003           |                  |
|         |          | 40  | 5200    | 12.57 |                |                 | 11.94            |                |                 |                  |                 |                  |
|         |          | 44  | 5220    | 14.76 | < 0.001        | < 0.001         | 15.08            | < 0.001        | < 0.001         |                  |                 |                  |
|         |          | 48  | 5240    | 14.19 |                |                 | 14.90            |                |                 |                  |                 |                  |
|         | U-NII-2  | 52  | 5260    | 14.35 | < 0.001        | < 0.001         | 14.57            | < 0.001        | < 0.001         |                  |                 |                  |
|         |          | 56  | 5280    | 15.44 |                |                 | 15.21            |                |                 |                  |                 |                  |
|         |          | 60  | 5300    | 13.54 | < 0.001        | < 0.001         | 12.14            | < 0.001        | < 0.001         |                  |                 |                  |
|         |          | 64  | 5320    | 13.49 |                |                 | 12.35            |                |                 |                  |                 |                  |
|         | U-NII-2C | 100 | 5500    | 15.53 | < 0.001        | < 0.001         | 13.84            | < 0.001        | < 0.001         |                  |                 |                  |
|         |          | 104 | 5520    | 14.50 |                |                 | 12.08            |                |                 |                  |                 |                  |
|         |          | 108 | 5540    | 14.93 | < 0.001        | < 0.001         | 13.38            | 0.007          | 0.003           |                  |                 |                  |
|         |          | 112 | 5560    | 13.86 |                |                 | 14.82            |                |                 |                  |                 |                  |
|         |          | 116 | 5580    | 15.22 | < 0.001        | < 0.001         | 14.72            | 0.01           | 0.00            |                  |                 |                  |
|         |          | 120 | 5600    | 13.26 |                |                 | 15.06            |                |                 |                  |                 |                  |
|         |          | 124 | 5620    | 14.49 | < 0.001        | < 0.001         | 14.73            | < 0.001        | < 0.001         |                  |                 |                  |
|         |          | 128 | 5640    | 13.87 |                |                 | 14.66            |                |                 |                  |                 |                  |
|         |          | 132 | 5660    | 14.70 | 0.00           | 0.00            | 15.27            | < 0.001        | < 0.001         |                  |                 |                  |
|         |          | 136 | 5680    | 13.59 |                |                 | 12.65            |                |                 |                  |                 |                  |
|         |          | 140 | 5700    | 15.64 | < 0.001        | < 0.001         | 13.96            | < 0.001        | < 0.001         |                  |                 |                  |
|         | U-UNII-3 | 149 | 5745    | 13.84 |                |                 | 12.47            |                |                 |                  |                 |                  |
|         |          | 153 | 5765    | 12.88 | < 0.001        | < 0.001         | 11.44            | < 0.001        | < 0.001         |                  |                 |                  |
|         |          | 157 | 5785    | 16.80 |                |                 | 14.25            |                |                 |                  |                 |                  |
|         |          | 161 | 5805    | 15.58 | < 0.001        | < 0.001         | 13.70            | < 0.001        | < 0.001         |                  |                 |                  |
|         |          | 165 | 5.825   | 14.04 |                |                 | 13.92            |                |                 |                  |                 |                  |

<sup>1</sup> Reported SAR is scaled for power drift and maximum RF power specifications



## EXHIBIT 4. SAR SYSTEM CONFIGURATION

### 4.1. DASY5 SYSTEM OVERVIEW



#### 4.1.1. DASY5 System Specification

| Positioning Equipment   | Computer   |
|---|--|
| DASAY5 Measurement Server<br>Data Acquisition Electronics (DAE)<br>Light Beam Unit<br>Device Holder<br>Robot (STAUBLI TX90) | Type: HP Compaq dc7800p Convertible<br>CPU : Intel® Core™ 2 Duo E8500<br>Memory : 2GB RAM<br>Operating System : Windows XP Professional<br>Monitor : HP L1950g LCD |

##### 4.1.1.1. DASY5 Measurement Server

The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz Intel ULV Celeron, 128MB chipdisk and 128MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

#### **4.1.1.2. Data Acquisition Electronics**


The data acquisition electronics (DAE4 or DAE3) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200M $\Omega$ ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

#### **4.1.1.3. Dosimetric Probes**

These probes are specially designed and calibrated for use in liquids with high permittivity. They should not be used in air, since the spherical isotropy in air is poor (-2 dB). The dosimetric probes have special calibrations in various liquids at different frequencies.



---

#### **ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**4.1.1.3.1. ES3DV3 Isotropic E-Filed Probe**

|                      |  |
|----------------------|--|
| <b>Construction</b>  | Symmetrical design with triangular core<br>Interleaved sensors<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |
| <b>Calibration</b>   | Basic Broad Band Calibration in air<br>Conversion Factors (CF) for HSL 900 and HSL 1750<br>Additional CF for other liquids and frequencies   |
| <b>Frequency</b>     | 10 MHz to 4 GHz<br>Linearity $\pm 0.2$ dB (30 MHz to 4 GHz)  |
| <b>Directivity</b>   | $\pm 0.2$ dB in HSL (rotation around probe axis)<br>$\pm 0.3$ dB in tissue material (rotation normal to probe axis)  |
| <b>Dynamic Range</b> | 5 $\mu$ W/g to $> 100$ mW/g<br>Linearity: $\pm 0.2$ dB   |
| <b>Dimensions</b>    | Overall length: 330 mm (Tip: 20 mm)<br>Tip diameter: 3.9 mm (Body: 12 mm)<br>Distance from probe tip to dipole centers: 2.0 mm   |

**4.1.1.3.2. EX3DV4 Isotropic E-Filed Probe**

|                      |   |
|----------------------|---|
| <b>Construction</b>  | Symmetrical design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |
| <b>Calibration</b>   | Basic Broad Band Calibration in air<br>Conversion Factors (CF) for HSL 900 and HSL 1750<br>Additional CF for other liquids and frequencies                  |
| <b>Frequency</b>     | 10 MHz to $> 6$ GHz<br>Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)  |
| <b>Directivity</b>   | $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in tissue material (rotation normal to probe axis)   |
| <b>Dynamic Range</b> | 10 $\mu$ W/g to $> 100$ mW/g<br>Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)  |
| <b>Dimensions</b>    | Overall length: 330 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                        |


**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

#### 4.1.2. DASY5 SAR SYSTEM block diagram



## ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)


## **4.2. SAR TEST PHANTOMS**

### **4.2.1. SAM Twin Phantom**



For Head mounted devices placed next to the ear, the phantom used in the evaluation of the RF exposure of the user of the wireless device is an IEEE P1528 compliant SAM Twin phantom, shaped like a human head and filled with a mixture simulating the dielectric characteristics of the brain. A left sided head and a right sided head are evaluated to determine the worst case orientation for SAR.

### **4.2.2. ELI 4.0 Phantom**



For body mounted and frontal held push-to-talk devices, an IEC 62209-2 compliant Oval Flat Phantom (ELI 4.0) with a base plate thickness of 2mm is used.

---

## **ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>


File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 5. SAR DATA ACQUISITION METHODOLOGY

### 5.1. SAR MEASUREMENT PROCEDURE

The goal of the measurement process is to scan the phantom over a selected area in order to find the region of highest levels of RF energy and then to obtain a single value for the peak spatial-average of SAR over a volume that would contain one gram (in the shape of a cube) of biological tissue. The test procedure, of course, measures SAR in the simulated tissue.



#### < Area scan >


The software requests the user to move the probe to locations at two extreme corners of a rectangle that encloses the area to be scanned. An arbitrary origin and the spatial resolution for the scan are also specified. Under program control, the scan is performed automatically by the robot-guided probe.

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



< Zoom Scan >

The DASY5 software includes all numerical procedures necessary to evaluate the spatial peak SAR values.

Based on the Draft: SCC-34, SC-2, WG-2 - Computational Dosimetry, IEEE P1529/D0.0 (Draft Recommended Practice for Determining the Spatial-Peak Specific Absorption Rate (SAR) Associated with the Use of Wireless Handsets - Computational Techniques), a new algorithm has been implemented. The spatial-peak SAR can be computed over any required mass.

The base for the evaluation is a "cube" measurement in a volume of (30mm) <sup>3</sup> (7x7x7 points). The measured volume must include the 1 g and 10 g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan. If the 10g cube or both cubes are not entirely inside the measured volumes, the system issues a warning regarding the evaluated spatial peak values within the post processing engine (SEMCAD X). This means that if the measured volume is shifted, higher values might be possible. To get the correct values you can use a finer measurement grid for the area scan. In complicated field distributions, large grid spacing for the area scan might miss some details and give an incorrectly interpolated peak location.

The entire evaluation of the spatial peak values is performed within the post processing engine (SEMCAD X). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. extraction of the measured data (grid and values) from the Zoom Scan
2. calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
3. generation of a high-resolution mesh within the measured volume
4. interpolation of all measured values from the measurement grid to the high-resolution grid
5. extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface

**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



6. calculation of the averaged SAR within masses of 1 g and 10 g

The significant parts are outlined in more detail within the following sections.

#### 5.1.1. *Interpolation, Extrapolation and Detection of Maxima*

The probe is calibrated at the center of the dipole sensors which is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated.

In DASY5, the choice of the coordinate system defining the location of the measurement points has no influence on the uncertainty of the interpolation, Maxima Search and extrapolation routines. The interpolation, extrapolation and maximum search routines are all based on the modified Quadratic Shepard's method.

Thereby, the interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation. The DASY5 routines construct a once-continuously differentiable function that interpolates the measurement values as follows:

- For each measurement point a trivariate (3-D) / bivariate (2-D) quadratic is computed. It interpolates the measurement values at the data point and forms a least-square fit to neighboring measurement values.
- the spatial location of the quadratic with respect to the measurement values is attenuated by an inverse distance weighting. This is performed since the calculated quadratic will fit measurement values at nearby points more accurate than at points located further away.
- After the quadratics are calculated for at all measurement points, the interpolating function is calculated as a weighted average of the quadratics.

There are two control parameters that govern the behavior of the interpolation method . One specifies the number of measurement points to be used in computing the least-square fits for the local quadratics. These measurement points are the ones nearest the input point for which the quadratic is being computed. The second parameter specifies the number of measurement points that will be used in calculating the weights for the quadratics to produce the final function. The input data points used there are the ones nearest the point at which the interpolation is desired. Appropriate defaults are chosen for each of the control parameters

The trivariate quadratics that have been previously computed for the 3-D interpolation and whose input data are at the closest distance from the phantom surface, are used in order to extrapolate the fields to the surface of the phantom.

In order to determine all the field maxima in 2-D (Area Scan) and 3-D (Zoom Scan), the measurement grid is refined by a default factor of 10 and the interpolation function is used to evaluate all field values between corresponding measurement points. Subsequently, a linear search is applied to find all the candidate maxima. In a last step, non physical maxima are removed and only those maxima which are within 2 dB of the global maximum value are retained.

**Important:** To be processable by the interpolation/extrapolation scheme, the Area Scan requires at least 6 measurement points. The Cube Scan requires at least 10 measurement points to allow an application of these algorithms.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extrema of the SAR distribution. The uncertainty on the locations of the extrema is less than 1/20 of the grid size. Only local maxima within -2 dB of the global maximum are searched and passed for the Cube Scan measurement.



In the Cube Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5mm.

### **5.1.2. Averaging and Determination of Spatial Peak SAR**

The interpolated data is used to average the SAR over the 1g and 10g cubes by spatially discretizing the entire measured volume. The resolution of this spatial grid used to calculate the averaged SAR is 1mm or about 42875 interpolated points. The resulting volumes are defined as cubical volumes containing the appropriate tissue parameters that are centered at the location. The location is defined as the center of the incremental volume (voxel).

The spatial-peak SAR must be evaluated in cubical volumes containing a mass that is within 5% of the required mass. The cubical volume centered at each location, as defined above, should be expanded in all directions until the desired value for the mass is reached, with no surface boundaries of the averaging volume extending beyond the outermost surface of the considered region. In addition, the cubical volume should not consist of more than 10% of air. If these conditions are not satisfied then the center of the averaging volume is moved to the next location. Otherwise, the exact size of the final sampling cube is found using an inverse polynomial approximation algorithm, leading to results with improved accuracy. If one boundary of the averaging volume reaches the boundary of the measured volume during its expansion, it will not be evaluated at all. Reference is kept of all locations used and those not used for averaging the SAR. All average SAR values are finally assigned to the centered location in each valid averaging volume.

All locations included in an averaging volume are marked to indicate that they have been used at least once. If a location has been marked as used, but has never been assigned to the center of a cube, the highest averaged SAR value of all other cubical volumes which have used this location for averaging is assigned to this location. Only those locations that are not part of any valid averaging volume should be marked as unused. For the case of an unused location, a new averaging volume must be constructed which will have the unused location centered at one surface of the cube. The remaining five surfaces are expanded evenly in all directions until the required mass is enclosed, regardless of the amount of included air. Of the six possible cubes with one surface centered on the unused location, the smallest cube is used, which still contains the required mass.

If the final cube containing the highest averaged SAR touches the surface of the measured volume, an appropriate warning is issued within the postprocessing engine.

### **5.1.3. Evaluation Errors**

#### **5.1.3.1. Cube shape**

The mentioned procedures search for the maximum averaged 1g and 10g volumes of cubical shape according to the ANSI and ICNIRP standard. A density of 1000 kg/m<sup>3</sup> is used to represent the head tissue density and not the tissue simulating liquid density.

#### **5.1.3.2. Extrapolation**

For the extrapolation the distance must be specified in the Area Scan and Zoom Scan Jobs. The distance is defined as the distance between the probe sensor center and the phantom surface. The recommended distance is 4-5 mm.

#### **5.1.3.3. *Boundary effects***

The dosimetric probes are calibrated in a gradient field with energy flow and decay in direction of the probe axis. During calibration the probe tip is completely surrounded by the simulating solution. If the probe is used in the immediate vicinity of a media boundary, the field in the probe is altered due to interaction with the field in the boundary and the probe sensitivity changes. The influence of the boundary effect depends on the probe construction, the media parameters and the probe orientation with respect to the boundary. It disappears at a distance of 1mm (E1D-probe) to 5mm (ET3D-probes) between the probe tip and the boundary. The boundary effect must be considered in the extrapolation to the surface.

## EXHIBIT 6. MEASUREMENTS, EXAMINATIONS & TEST DATA

### 6.1. TEST CONFIGURATIONS

#### 6.1.1. Wifi 802.11 a/b/g/n 2450 MHz

| D.U.T. Information                         |   | Condition               |                                   |
|--|---|-------------------------|-----------------------------------|
| Product Name                               | Cube  | Robot Type              | 6 Axis                            |
| Model Number                               | 800-xxx   | Scan Type               | SAR – Area/Zoom/Att. Vs Depth     |
| Serial Number                              | 04A3164B88A2  | Measured Field          | E                                 |
| Frequency Band [MHz]                       | 802.11 abgn 2.45/5 GHz  | Phantom Type            | 2 <sub>mm</sub> base Flat Phantom |
| Frequency Tested [MHz]                     | 2412, 2437, 2462 MHz<br>5180, 5220, 5240, 5260, 5300, 5320, 5500,<br>5540, 5580, 5620, 5660, 5765, 5805 MHz | Phantom Position        | Waist                             |
| Maximum Conducted Power                    | 18/16 dBm ± 1.5dB <sup>2</sup>  | Room Temperature [°C]   | 24.0 ± 1                          |
| Antenna Type                               | PIFA. Ethertronics P/N 1000146  | Room Humidity [%]       | 40 ± 10                           |
| Modulation                                 | BPSK, QPSK, QAM, OFDM   | Tissue Temperature [°C] | 21.4 ± 1                          |
| Worst Case Duty Cycle                      | 100 %   |                         |                                   |
| Duty Cycle Tested                          | 100%  |                         |                                   |
| Source(or Usage)-Based Time-Average Factor | 1   |                         |                                   |

|  |                  |
|--|------------------|
| Type of Tissue                                 | Muscle           |
| Test Frequency [MHz]                           | 2450             |
| Target Conductivity [S/m]                      | 1.95             |
| Measured Conductivity [S/m]                    | 1.92 (-1.7 %)    |
| Target Dielectric Constant                     | 52.7             |
| Measured Dielectric Constant                   | 51.9 (-1.4 %)    |
| Penetration Depth (Plane Wave Excitation) [mm] | 20.1             |
| Probe Model Number                             | EX3DV4           |
| Probe Serial Number                            | 3673             |
| Probe Orientation                              | Isotropic        |
| Probe Sensor Offset [mm]                       | 1                |
| Probe Tip Diameter [mm]                        | 2.5              |
| Conversion Factor (γ)                          | 7.26 (+/- 12.0%) |

<sup>2</sup> Tolerance specified is obtained from the manufacturer's tune-up procedures

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

**6.1.2. Wifi 802.11 a/b/g/n 5200-5825 MHz**

| D.U.T. Information                         |   | Condition               |                               |
|--|---|-------------------------|-------------------------------|
| Product Name                               | Cube  | Robot Type              | 6 Axis                        |
| Model Number                               | 800-xxx   | Scan Type               | SAR – Area/Zoom/Att. Vs Depth |
| Serial Number                              | 04A3164B88A2  | Measured Field          | E                             |
| Frequency Band [MHz]                       | 802.11 abgn 2.45/5 GHz  | Phantom Type            | 2mm base Flat Phantom         |
| Frequency Tested [MHz]                     | 2412, 2437, 2462 MHz<br>5180, 5220, 5240, 5260, 5300, 5320, 5500,<br>5540, 5580, 5620, 5660, 5765, 5805 | Phantom Position        | Waist                         |
| Maximum Conducted Power                    | 18/16 dBm $\pm$ 1.5dB <sup>3</sup>  | Room Temperature [°C]   | 24.0 $\pm$ 1                  |
| Antenna Type                               | PIFA, Ethertronics P/N 1000146,<br>2.45GH 1.5dBi, 5GHz 2.6dBi   | Room Humidity [%]       | 40 $\pm$ 10                   |
| Modulation                                 | BPSK, QPSK, QAM, OFDM   | Tissue Temperature [°C] | 21.4 $\pm$ 1                  |
| Worst Case Duty Cycle                      | 100 %   |                         |                               |
| Duty Cycle Tested                          | 100%  |                         |                               |
| Source(or Usage)-Based Time-Average Factor | 1   |                         |                               |

|  |  |
|--|--|
| Type of Tissue                                 | Muscle   |
| Test Frequency [MHz]                           | 5500   |
| Target Conductivity [S/m]                      | 5.65   |
| Measured Conductivity [S/m]                    | 6.0 (6.1 %)  |
| Target Dielectric Constant                     | 48.6   |
| Measured Dielectric Constant                   | 46.3 (-4.7 %)  |
| Penetration Depth (Plane Wave Excitation) [mm] | 6.2  |
| Probe Model Number                             | EX3DV4   |
| Probe Serial Number                            | 3673   |
| Probe Orientation                              | Isotropic  |
| Probe Sensor Offset [mm]                       | 1  |
| Probe Tip Diameter [mm]                        | 2.5  |
| Conversion Factor ( $\gamma$ )                 | 5200MHz - 4.66 (+/- 12.0%)<br>5300MHz - 4.76 (+/- 12.0%)<br>5500MHz - 4.96 (+/- 12.0%)<br>5600MHz – 5.07 (+/- 12.0%)<br>5800MHz – 5.27 (+/- 12.0%) |

<sup>3</sup> Tolerance specified is obtained from the manufacturer's tune-up procedures

**ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## **6.2. GENERAL TEST SETUP**

### **6.2.1. *Equipment Configuration***

Power and signal distribution, grounding, interconnecting cabling and physical placement of equipment of a test system shall simulate the typical application and usage in so far as is practicable, and shall be in accordance with the relevant product specifications of the manufacturer.

The configuration that tends to maximize the D.U.T's emission or minimize its immunity is not usually intuitively obvious and in most instances selection will involve some trial and error testing. For example, interface cables may be moved or equipment re-orientated during initial stages of testing and the effects on the results observed.


Only configurations within the range of positions likely to occur in normal use need to be considered.

The configuration selected shall be fully detailed and documented in the test report, together with the justification for selecting that particular configuration.

### **6.2.2. *Exercising Equipment***

The exercising equipment and other auxiliary equipment shall be sufficiently decoupled from the D.U.T. so that the performance of such equipment does not significantly influence the test results.

### 6.3. PHOTOGRAPHS OF TISSUE DEPTH



< Phantom filled with Head tissue liquid: liquid level = 150mm  $\pm$  5mm >

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)




## 6.4. PHOTOGRAPHS OF D.U.T. POSITION

### 6.4.1. Head Configuration for Back Side Exposure

< Back Side Exposure >

Remark: Distance between Back side of the EUT and the phantom = 0 mm




## ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 7. SAR MEASUREMENT SYSTEM VERIFICATION



### 7.1. STANDARD SOURCE

A half-wave dipole is positioned below the bottom of the phantom and centered with its axis parallel to the longest side of the phantom. The distance between the liquid filled phantom bottom surface and the center of the dipole axis,  $s$ , is chosen as specified IEEE 1528 at the specific test frequency (i.e. 15 mm at 835 MHz). A low loss and low dielectric constant spacer is used to establish the correct distance between the top surface of the dipole and the bottom surface of the phantom.



### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>


File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



## 7.2. STANDARD SOURCE INPUT POWER MEASUREMENT

The system validation is performed as shown below or in Figure 7.1 in IEEE 1528.



First the power meter PM1 (including attenuator Att1) is connected to the cable to measure the forward power at the location of the dipole connector (X). The signal generator is adjusted for the desired forward power at the dipole connector (taking into account the attenuation of Att1) as read by power meter PM2. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter PM2. If the signal generator does not allow adjustment in 0.01dB steps, the remaining difference at PM2 must be taken into consideration. PM3 records the reflected power from the dipole to ensure that the value is not changed from the previous value. The reflected power was verified to be at least 20dB below the forward power.

## 7.3. SYSTEM VALIDATION PROCEDURE

A complete 1g-averaged SAR measurement is performed. The measured 1g-averaged SAR value is normalized to a forward power of 1W to a half-wave dipole and compared with the reference SAR value for the reference dipole and flat phantom shown in columns 2 and 3 of Table 7.1 in IEEE 1528.

### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## 7.4. VERIFICATION RESULTS

### 7.4.1. Reference Dipole SAR measurements

|      |                    | SAR1g               |               |            | SAR10g              |          |            |
|------|--------------------|---------------------|---------------|------------|---------------------|----------|------------|
|      | Frequency<br>(MHz) | Reference<br>(mw/g) | Measured<br>* | Delta<br>% | Reference<br>(mw/g) | Measured | Delta<br>% |
| Head | 2450               | 53.80               | 53.20         | -1.12%     | 25.20               | 25.00    | -0.79%     |
|      | 5200               | 76.60               | 78.50         | -2.48%     | 21.90               | 22.50    | -2.74%     |
|      | 5400 <sup>4</sup>  | 76.70               | 75.30         | 1.83%      | 21.40               | 21.50    | -0.47%     |
|      | 5600 <sup>5</sup>  | 76.10               | 73.50         | 3.42%      | 21.20               | 20.90    | 1.42%      |
|      | 5800               | 77.70               | 78.30         | -0.77%     | 22.10               | 22.20    | -0.45%     |

<sup>4</sup> Numerical Calculated Target Values provided by SPEAG

<sup>5</sup> Numerical Calculated Target Values provided by SPEAG

## ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

#### 7.4.2. Verification at 2450 MHz

File Name: [System Verification - D2450MHz Head.da52:0](#)

DUT: D2450V2; Type: SA AAD 245BB; Serial: 821

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.849$  S/m;  $\epsilon_r = 39.397$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section;  
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(7.23, 7.23, 7.23); Calibrated: 8/23/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/14/2018
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

**System Verification at 2.45GHz Head/d=10mm, Pin=250mW, dist=1.4mm (EX-Probe)/Zoom Scan (7x7x7)**

(7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.2 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 27.8 W/kg


**SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.25 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 22.3 W/kg

**System Verification at 2.45GHz Head/d=10mm, Pin=250mW, dist=1.4mm (EX-Probe)/Area Scan (61x81x1):**

Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 23.5 W/kg



0 dB = 22.3 W/kg = 13.48 dBW/kg

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### 7.4.3. Verification at 5200 MHz

File Name: [System Verification - D5200MHz\\_Head.da52:0](#)

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:xxx

Communication System: UID 0, CW (0); Frequency: 5200 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5200$  MHz;  $\sigma = 4.566$  S/m;  $\epsilon_r = 38.301$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section;  
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(4.86, 4.86, 4.86); Calibrated: 8/23/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/14/2018
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

**System Verification at 5.2GHz\_Head/d=10mm, Pin=100mW (EX-Probe)/Zoom Scan (8x8x7) (9x9x8)/Cube 0:**

Measurement grid: dx=4mm, dy=4mm, dz=3mm

Reference Value = 53.19 V/m; Power Drift = 0.21 dB

Peak SAR (extrapolated) = 31.1 W/kg


**SAR(1 g) = 7.85 W/kg; SAR(10 g) = 2.25 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 18.5 W/kg

**System Verification at 5.2GHz\_Head/d=10mm, Pin=100mW (EX-Probe)/Area Scan (41x61x1):** Interpolated grid:

dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 13.7 W/kg



### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

#### 7.4.4. Verification at 5400 MHz

File Name: [System Verification - D5400MHz\\_Head.da52:0](#)

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:xxx**

Communication System: UID 0, CW (0); Frequency: 5400 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5400$  MHz;  $\sigma = 4.788$  S/m;  $\epsilon_r = 37.985$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section;  
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(4.68, 4.68, 4.68); Calibrated: 8/23/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/14/2018
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

**System Verification at 5.4GHz\_Head/d=10mm, Pin=100mW (EX-Probe)/Zoom Scan (8x8x7) (9x9x8)/Cube 0:**

Measurement grid: dx=4mm, dy=4mm, dz=3mm

Reference Value = 51.27 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 31.0 W/kg


**SAR(1 g) = 7.53 W/kg; SAR(10 g) = 2.15 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 18.4 W/kg

**System Verification at 5.4GHz\_Head/d=10mm, Pin=100mW (EX-Probe)/Area Scan (41x61x1):** Interpolated grid:

dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 15.4 W/kg



0 dB = 18.4 W/kg = 12.64 dBW/kg

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

#### 7.4.5. Verification at 5600 MHz

File Name: [System Verification - D5600MHz Head.da52:0](#)

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:xxx

Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5600$  MHz;  $\sigma = 4.991$  S/m;  $\epsilon_r = 37.687$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section ;  
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(4.78, 4.78, 4.78); Calibrated: 8/23/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/14/2018
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

**System Verification at 5.6GHz\_Head/d=10mm, Pin=100mW (EX-Probe)/Zoom Scan (8x8x7) (9x9x8)/Cube 0:**

Measurement grid: dx=4mm, dy=4mm, dz=3mm

Reference Value = 49.37 V/m; Power Drift = 0.41 dB

Peak SAR (extrapolated) = 31.5 W/kg


**SAR(1 g) = 7.35 W/kg; SAR(10 g) = 2.09 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 18.8 W/kg

**System Verification at 5.6GHz\_Head/d=10mm, Pin=100mW (EX-Probe)/Area Scan (41x61x1):** Interpolated grid:

dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 14.8 W/kg



#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

#### 7.4.6. Verification at 5800 MHz

File Name: [System Verification - D5800MHz Head.da52:0](#)

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:xxx

Communication System: UID 0, CW (0); Frequency: 5800 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5800$  MHz;  $\sigma = 5.203$  S/m;  $\epsilon_r = 37.416$ ;  $\rho = 1000$  kg/m<sup>3</sup>; Phantom section: Flat Section ;  
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: EX3DV4 - SN3673; ConvF(4.38, 4.38, 4.38); Calibrated: 8/23/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn874; Calibrated: 8/14/2018
- Phantom: ELI 4.0; Type: QD OVA 001 BB; Serial: 1057
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

**System Verification at 5.8GHz\_Head/d=10mm, Pin=100mW (EX-Probe)/Zoom Scan (8x8x7) (9x9x8)/Cube 0:**

Measurement grid: dx=4mm, dy=4mm, dz=3mm

Reference Value = 55.22 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 35.1 W/kg


**SAR(1 g) = 7.83 W/kg; SAR(10 g) = 2.22 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 20.5 W/kg

**System Verification at 5.8GHz\_Head/d=10mm, Pin=100mW (EX-Probe)/Area Scan (41x61x1):** Interpolated grid:

dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 15.4 W/kg



#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>


File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



## **EXHIBIT 8. D.U.T. POWER MEASUREMENT**

Whenever possible, a conducted power measurement is performed. To accomplish this, we utilize a fully charged battery, a calibrated power meter and a cable adapter provided by the manufacturer. The data of the cable and related circuit losses are also provided by the manufacturer. The power measurement is then performed across the operational band and the channel with the highest output power is recorded.



Power measurement is performed before and after the SAR to verify if the battery was delivering full power at the time of testing. A difference in output power would determine a need for battery replacement and to repeat the SAR test.

---

### **ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

**File #: LIB-085Q-SAR**

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

### 8.1.1. RF Conducted output power measurement

Scaling Factors user to obtain Reported SAR data are derived from the maximum tune-up power divided by the measured average conducted power. The measured SAR is only scaled up to obtain the Reported SAR.

#### Antenna 1 Power Measurements

| GHZ        | Chan       | 15.247 (Peak Measurement) |                    |                      |                      | UNII 15.407 (Average) |                 |
|------------|------------|---------------------------|--------------------|----------------------|----------------------|-----------------------|-----------------|
|            |            | 802.11b<br>11Mb/s         | 802.11g<br>6Mbps/s | 802.11n<br>HT20 MCS0 | 802.11n<br>HT40 MCS0 | 802.11a<br>6Mb/s      | 802.11n<br>MCS0 |
| Meas (dBm) | Meas (dBm) | Meas (dBm)                | Meas (dBm)         | Meas (dBm)           | Meas (dBm)           | Meas (dBm)            | Meas (dBm)      |
| 2412       | 1 (3)      | 15.97                     | 17.93              | 17.09                | 17.29                |                       |                 |
| 2437       | 6          | 18.72                     | 19.04              | 19.06                | 19.42                |                       |                 |
| 2462       | 11 (9)     | 15.88                     | 17.78              | 17.35                | 17.26                |                       |                 |
| 5180       | 36         |                           |                    |                      |                      | 12.76                 | 11.82           |
| 5200       | 40         |                           |                    |                      |                      | 12.57                 | 11.94           |
| 5220       | 44         |                           |                    |                      |                      | 14.76                 | 15.08           |
| 5240       | 48         |                           |                    |                      |                      | 14.19                 | 14.90           |
| 5260       | 52         |                           |                    |                      |                      | 14.35                 | 14.57           |
| 5280       | 56         |                           |                    |                      |                      | 15.44                 | 15.21           |
| 5300       | 60         |                           |                    |                      |                      | 13.54                 | 12.14           |
| 5320       | 64         |                           |                    |                      |                      | 13.49                 | 12.35           |
| 5500       | 100        |                           |                    |                      |                      | 15.53                 | 13.84           |
| 5520       | 104        |                           |                    |                      |                      | 14.50                 | 12.08           |
| 5540       | 108        |                           |                    |                      |                      | 14.93                 | 13.38           |
| 5560       | 112        |                           |                    |                      |                      | 13.86                 | 14.82           |
| 5580       | 116        |                           |                    |                      |                      | 15.22                 | 14.72           |
| 5600       | 120        |                           |                    |                      |                      | 13.26                 | 15.06           |
| 5620       | 124        |                           |                    |                      |                      | 14.49                 | 14.73           |
| 5640       | 128        |                           |                    |                      |                      | 13.87                 | 14.66           |
| 5660       | 132        |                           |                    |                      |                      | 14.70                 | 15.27           |
| 5680       | 136        |                           |                    |                      |                      | 13.59                 | 12.65           |
| 5700       | 140        |                           |                    |                      |                      | 15.64                 | 13.96           |
| 5745       | 149        |                           |                    |                      |                      | 13.84                 | 12.47           |
| 5765       | 153        |                           |                    |                      |                      | 12.88                 | 11.44           |
| 5785       | 157        |                           |                    |                      |                      | 16.80                 | 14.25           |
| 5805       | 161        |                           |                    |                      |                      | 15.58                 | 13.70           |
| 5825       | 165        |                           |                    |                      |                      | 14.04                 | 13.92           |

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 9. TISSUE DIELECTRIC PARAMETER CALIBRATION

### 9.1. SIMULATED TISSUE

Simulated Tissue: Suggested in a paper by George Hartsgrrove and colleagues in University of Ottawa Ref.: Bioelectromagnetics 8:29-36 (1987)

| Ingredient  | Quantity |
|-------------|----------|
| Water       | 40.4 %   |
| Sugar       | 56.0 %   |
| Salt        | 2.5 %    |
| HEC         | 1.0 %    |
| Bactericide | 0.1 %    |

Table 9.1 Example of composition of simulated tissue

This simulated tissue is mainly composed of water, sugar and salt. At higher frequencies, in order to achieve the proper conductivity, the solution does not contain salt. Also, at these frequencies, D.I. water and alcohol is preferred.

| Target Frequency<br>(MHz) | Head         |                | Body         |                |
|---------------------------|--------------|----------------|--------------|----------------|
|                           | $\epsilon_r$ | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) |
| 150                       | 52.3         | 0.76           | 61.9         | 0.80           |
| 300                       | 45.3         | 0.87           | 58.2         | 0.92           |
| 450                       | 43.5         | 0.87           | 56.7         | 0.94           |
| 835                       | 41.5         | 0.90           | 55.2         | 0.97           |
| 900                       | 41.5         | 0.97           | 55.0         | 1.05           |
| 915                       | 41.5         | 0.98           | 55.0         | 1.06           |
| 1450                      | 40.5         | 1.20           | 54.0         | 1.30           |
| 1610                      | 40.3         | 1.29           | 53.8         | 1.40           |
| 1800 – 2000               | 40.0         | 1.40           | 53.3         | 1.52           |
| 2450                      | 39.2         | 1.80           | 52.7         | 1.95           |
| 3000                      | 38.5         | 2.40           | 52.0         | 2.73           |
| 5800                      | 35.3         | 5.27           | 48.2         | 6.00           |

( $\epsilon_r$  = relative permittivity,  $\sigma$  = conductivity and  $\rho = 1000 \text{ Kg/m}^3$ \*)

\* The actual mass density of the equivalent tissue varies based on the composition of the tissue from  $990 \text{ Kg/m}^3$  to  $1,300 \text{ Kg/m}^3$ .

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## 9.2. MEASUREMENT OF ELECTRICAL CHARACTERISTICS OF SIMULATED TISSUE

HP Dielectric Strength Probe System (open-ended coaxial transmission-line probe/sensor) was used.

### 9.2.1. Equipment set-up

The equipment consists of a probe connected to one port of a vector network analyzer. The probe is an open-ended coaxial line, as shown in Figure 9.2.1.1. Cylindrical coordinates ( $\rho$ ,  $\phi$ ,  $z$ ) are used where  $\rho$  is the radial distance from the axis,  $\phi$  is the angular displacement around the axis,  $z$  is the displacement along the axis,  $a$  is the inner conductor radius, and  $b$  is the outer conductor inner radius.

The sample holder is a non-metallic container that is large compared with the size of the probe immersed in it. A probe with an outer diameter  $b$  of 2 to 4 mm is suitable for the measurement of tissue-equivalent materials in the 300 MHz to 3 GHz frequency range. This probe size is commensurate with sample volumes of 50 cc or higher. Larger probes of up to 7 mm outer diameter  $b$  may be used with larger sample volumes. A flange is typically included to better represent the infinite ground-plane assumption used in admittance calculations.




Figure 9.2.1. An open-ended coaxial probe with inner and outer radii  $a$  and  $b$ , respectively

The accuracy of the short-circuit measurement should be verified for each calibration at a number of frequencies. A short circuit can be achieved by gently pressing a piece of aluminum foil against the open end. For best electrical contact, the probe end should be flat and free of oxidation. Larger the sensors generally have better foil short-circuit repeatability. It is possible to obtain good contact with some commercial 4.6 mm probes using the metal-disk short-circuit supplied with the kit. For best repeatability, it may be necessary to press the disk by hand.

The network analyzer is configured to measure the magnitude and phase of the admittance. A one-port reflection calibration is performed at the plane of the probe by placing materials for which the reflection coefficient can be calculated in contact with the probe. Three standards are needed for the calibration, typically a short circuit, air, and de-ionized water at a well-defined temperature (other reference liquids such as methanol or ethanol may be used for calibration). The calibration is a key part of the measurement procedure, and it is therefore important to ensure that it has been performed correctly. It can be checked by re-measuring the short circuit to ensure that a reflection coefficient of  $\Gamma = -1.0$  (linear units) is obtained consistently.

### **9.2.2. Measurement procedure**

- a) Configure and calibrate the network analyzer and probe system.
- b) Place the sample in a non-metallic container and immerse the probe. A fixture or clamp is recommended to stabilize the probe, mounted such that the probe face is at an angle with respect to the liquid surface to minimize trapped air bubbles beneath the flange.
- c) Measure the complex admittance with respect to the probe aperture.
- d) Compute the complex relative permittivity  $\epsilon_r = \epsilon'_r - j\sigma/\omega\epsilon_0$ .

### 9.3. SIMULATED TISSUE MEASUREMENT RESULTS

|  |   |  |
|--|---|--|
| Tissue calibration type                        | HP Dielectric Strength Probe System (M/N: 85070C)                               |  |
| Tissue calibration date [MM/DD/YYYY]           | 31/08/2018  | 07/09/2018   |
| Tissue calibrated by                           | Ketav   | Ketav  |
| Room temperature [°C]                          | 21  | 21   |
| Room humidity [%]                              | 40  | 35   |
| Simulated tissue temperature (°C)              | 21  | 21   |
| Tissue calibration frequency [MHz]             | 2450  | 5500   |
| Tissue Type                                    | Muscle  | Muscle   |
| Target conductivity [S/m]                      | 1.95  | 6.0  |
| Target dielectric constant                     | 52.7  | 48.2   |
| Composition (by weight) [%]                    | DGBE (13.80 %)<br>Salt (0.19 %)<br>Triton X-100 (13.59 %)<br>DI Water (72.42 %) | DGBE (3.50 %)<br>Salt (0.1 %)<br>Triton X-100 (37 %)<br>DI Water (64%) |
| Measured conductivity [S/m]                    | 1.92 (-1.7%)  | 6.0 (6.1%)   |
| Measured dielectric constant                   | 51.9 (-1.7%)  | 46.3 (-4.7%)   |
| Penetration depth (plane wave excitation) [mm] | 20.1  | 6.2  |

#### 9.3.1. 2450 MHz Muscle Tissue

| Frequency [MHz] | Meas. after 5min |              |                | DI Water at 20°C |              |                | Init. Meas. |              |                |
|-----------------|------------------|--------------|----------------|------------------|--------------|----------------|-------------|--------------|----------------|
|                 | $\epsilon'$      | $\epsilon''$ | $\sigma$ [S/m] | $\epsilon'$      | $\epsilon''$ | $\sigma$ [S/m] | $\epsilon'$ | $\epsilon''$ | $\sigma$ [S/m] |
| 2350.000        | 52.1625          | 13.7771      | 1.80           | 78.0052          | 9.9624       | 1.30           | 52.1349     | 13.6995      | 1.79           |
| 2450.000        | 51.9375          | 14.0686      | 1.92           | 77.8430          | 10.3546      | 1.41           | 51.8976     | 14.0256      | 1.91           |
| 2550.000        | 51.6323          | 14.4439      | 2.05           | 77.6736          | 10.7362      | 1.52           | 51.6094     | 14.3982      | 2.04           |

#### 9.3.2. 5500 MHz Muscle Tissue

| Frequency [MHz] | Meas. after 5min |              |                | DI Water at 20°C |              |                | Init. Meas. |              |                |
|-----------------|------------------|--------------|----------------|------------------|--------------|----------------|-------------|--------------|----------------|
|                 | $\epsilon'$      | $\epsilon''$ | $\sigma$ [S/m] | $\epsilon'$      | $\epsilon''$ | $\sigma$ [S/m] | $\epsilon'$ | $\epsilon''$ | $\sigma$ [S/m] |
| 5200.000        | 47.1315          | 19.0898      | 5.52           | 73.3272          | 20.6980      | 5.99           | 46.8185     | 19.0131      | 5.50           |
| 5500.000        | 46.2976          | 19.5976      | 6.00           | 72.5631          | 21.8469      | 6.68           | 45.8167     | 19.5359      | 5.98           |
| 5800.000        | 45.3885          | 20.0550      | 6.47           | 71.9775          | 22.6209      | 7.30           | 45.1122     | 20.0550      | 6.47           |

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

## EXHIBIT 10. SAR MEASUREMENT UNCERTAINTY

### 10.1. MEASUREMENT UNCERTAINTY EVALUATION FOR SAR TEST

| Error Description            | Uncertainty value | Prob. Dist. | Div.       | (c <sub>i</sub> ) 1g | (c <sub>i</sub> ) 10g | Std. Unc. (1g) | Std. Unc. (10g) | (v <sub>i</sub> ) v <sub>eff</sub> |
|------------------------------|-------------------|-------------|------------|----------------------|-----------------------|----------------|-----------------|------------------------------------|
| <b>Measurement System</b>    |                   |             |            |                      |                       |                |                 |                                    |
| Probe Calibration            | ±5.5 %            | N           | 1          | 1                    | 1                     | ±5.5 %         | ±5.5 %          | ∞                                  |
| Axial Isotropy               | ±4.7 %            | R           | $\sqrt{3}$ | 0.7                  | 0.7                   | ±1.9 %         | ±1.9 %          | ∞                                  |
| Hemispherical Isotropy       | ±9.6 %            | R           | $\sqrt{3}$ | 0.7                  | 0.7                   | ±3.9 %         | ±3.9 %          | ∞                                  |
| Boundary Effects             | ±1.0 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±0.6 %         | ±0.6 %          | ∞                                  |
| Linearity                    | ±4.7 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±2.7 %         | ±2.7 %          | ∞                                  |
| System Detection Limits      | ±1.0 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±0.6 %         | ±0.6 %          | ∞                                  |
| Readout Electronics          | ±0.3 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±0.3 %         | ±0.3 %          | ∞                                  |
| Response Time                | ±0.8 %            | N           | 1          | 1                    | 1                     | ±0.5 %         | ±0.5 %          | ∞                                  |
| Integration Time             | ±2.6 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±1.5 %         | ±1.5 %          | ∞                                  |
| RF Ambient Noise             | ±3.0 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±1.7 %         | ±1.7 %          | ∞                                  |
| RF Ambient Reflections       | ±3.0 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±1.7 %         | ±1.7 %          | ∞                                  |
| Probe Positioner             | ±0.4 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±0.2 %         | ±0.2 %          | ∞                                  |
| Probe Positioning            | ±2.9 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±1.7 %         | ±1.7 %          | ∞                                  |
| Max. SAR Eval.               | ±1.0 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±0.6 %         | ±0.6 %          | ∞                                  |
| <b>Test Sample Related</b>   |                   |             |            |                      |                       |                |                 |                                    |
| Device Positioning           | ±2.9 %            | N           | 1          | 1                    | 1                     | ±2.9 %         | ±2.9 %          | 145                                |
| Device Holder                | ±3.6 %            | N           | 1          | 1                    | 1                     | ±3.6 %         | ±3.6 %          | 5                                  |
| Power Drift                  | ±5.0 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±2.9 %         | ±2.9 %          | ∞                                  |
| <b>Phantom and Setup</b>     |                   |             |            |                      |                       |                |                 |                                    |
| Phantom Uncertainty          | ±4.0 %            | R           | $\sqrt{3}$ | 1                    | 1                     | ±2.3 %         | ±2.3 %          | ∞                                  |
| Liquid Conductivity (target) | ±5.0 %            | R           | $\sqrt{3}$ | 0.64                 | 0.43                  | ±1.8 %         | ±1.2 %          | ∞                                  |
| Liquid Conductivity (meas.)  | ±2.5 %            | N           | 1          | 0.64                 | 0.43                  | ±1.6 %         | ±1.1 %          | ∞                                  |
| Liquid Permittivity (target) | ±5.0 %            | R           | $\sqrt{3}$ | 0.6                  | 0.49                  | ±1.7 %         | ±1.4 %          | ∞                                  |
| Liquid Permittivity (meas.)  | ±2.5 %            | N           | 1          | 0.6                  | 0.49                  | ±1.5 %         | ±1.2 %          | ∞                                  |
| Combined Std. Uncertainty    |                   |             |            |                      |                       | ±10.7 %        | ±10.5 %         | 387                                |
| Expanded STD Uncertainty     |                   |             |            |                      |                       | ±21.4 %        | ±21.0 %         |                                    |

#### ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

File #: LIB-085Q-SAR

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)



## **EXHIBIT 11. ADDITIONAL TEST INSTRUMENTS LIST**

| <b>Name</b>                                | <b>Type</b>    | <b>Serial Number (SN)</b> | <b>Calibration Due Date</b> |
|--|----------------|---------------------------|-----------------------------|
| <b>Signal Generator</b> (Rohde & Schwartz) | SMIQ06B        | DE26709                   | Jul 24, 2019                |
| <b>Dipole Antenna</b> (Speag)              | D2450V2        | 821                       | Aug 16, 2019                |
| <b>Dipole Antenna</b> (Speag)              | D5GHzV2        | 1069                      | Aug 16, 2019                |
| <b>SAR Probe</b> (Speag)                   | EX3DV4         | 3673                      | Aug 23, 2019                |
| <b>Power Meter</b> (HP)                    | Agilent E4419B | MY50000168                | Dec 13, 2018                |
| <b>Directional Coupler</b> (narda)         | Model 3020A    | 35482                     | Cal on use                  |
| <b>Network Analyzer</b> (HP)               | 8753D          | 3410J02042                | Aug 17, 2019                |
| <b>Ophir Amplifier</b> 0.8-4.2GHz 13W      | Model GRF5058  | 1009                      | N/A                         |
| <b>Hughes TWT Amplifier</b> 3-8GHz 10W     | 1177H13F000    | 071                       | N/A                         |

## **EXHIBIT 12. SAR MEASUREMENT DATA**

See Appendix 1.

## **EXHIBIT 13. SAR CALIBRATION CERTIFICATES**

See Appendix 2.

---

### **ULTRATECH GROUP OF LABS**

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4  
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: [vic@ultratech-labs.com](mailto:vic@ultratech-labs.com), Website: <http://www.ultratech-labs.com>

**File #: LIB-085Q-SAR**

- All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)