

# TEST REPORT

## Part 74 Subpart H

**Equipment under test** MIC Karaoke

**Model name** TKR-373MU

**Derivation Model** TKR-373MP

**FCC ID** TO8-TKR-373MP

**Applicant** TJ Media Co., Ltd.

**Manufacturer** TJ Media Co., Ltd.

**Date of test(s)** 2017.06.12 ~ 2017.06.26

**Date of issue** 2017.07.05

**Issued to**

**TJ Media Co., Ltd.**

640-8, Deungchon-Dong, Gangseo-Gu, Seoul, South Korea

Tel: +82-31-382-2803 / Fax: +82-31-382-5511



**Issued by**

**KES Co., Ltd.**

C-3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,  
Gyeonggi-do, Korea

473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea

Tel: +82-31-425-6200 / Fax: +82-31-424-0450

| Test and report completed by :  | Report approval by :   |
|---|--|
|  |  |
| Kwon-se Kim<br>Test engineer  | Jeff Do<br>Technical manager   |



**KES Co., Ltd.**  
C-3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Test report No.:  
KES-RF-17T0064  
Page ( 2 ) of (33)

---

### Revision history

| Revision | Date of issue | Test report No. | Description |
|----------|---------------|-----------------|-------------|
| -        | 2017.07.05    | KES-RF-17T0064  | Initial     |

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.



---

## TABLE OF CONTENTS

|             |   |    |
|-------------|---|----|
| 1.          | General information .....                   | 4  |
| 1.1.        | EUT description .....                       | 4  |
| 1.2.        | Test configuration .....                    | 4  |
| 1.3.        | Device modifications.....                   | 4  |
| 1.4.        | Frequency/channel operations .....          | 4  |
| 1.5.        | Accessory information.....                  | 5  |
| 1.6.        | Information about derivative model .....    | 5  |
| 2.          | Summary of tests .....                      | 6  |
| 3.          | Test results.....                           | 7  |
| 3.1.        | RF output power.....                        | 7  |
| 3.2.        | Modulation characteristics.....             | 8  |
| 3.3.        | Occupied bandwidth and emission mask.....   | 16 |
| 3.4.        | Frequency stability .....                   | 19 |
| 3.5.        | Field strength of spurious radiation .....  | 22 |
| 3.6.        | Spurious emission at antenna terminals..... | 30 |
| Appendix A. | Measurement equipment .....                 | 32 |
| Appendix B. | Test setup photos .....                     | 33 |

## 1. General information

Applicant: TJ Media Co., Ltd.  
Applicant address: 640-8, Deungchon-Dong, Gangseo-Gu, Seoul, South Korea  
Test site: KES Co., Ltd.  
Test site address: C-3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, Korea  
473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea  
FCC rule part(s): Part 74  
FCC ID: TO8-TKR-373MP  
Test device serial No.: ☐ Production ☒ Pre-production ☐ Engineering

### 1.1. EUT description

Equipment under test MIC Karaoke  
Frequency range 494.0 MHz ~ 505.2 MHz  
Model TKR-373MU  
Derivation Model TKR-373MP  
Modulation technique FM  
Number of channels 16 ch  
Antenna specification UHF Antenna type: Helical, Peak gain: -0.52 dBi  
Power source DC 3.0 V

### 1.2. Test configuration

The **TJ Media Co., Ltd. MIC Karaoke FCC ID: TO8-TKR-373MP** was tested according to the specification of EUT, the EUT must comply with following standards.

FCC Part 74.861  
FCC Part 2  
TIA-603-E (2016)  
ANSI C63.4-2014

### 1.3. Device modifications

N/A

### 1.4. Frequency/channel operations

| Ch. | Frequency (MHz) | Mode |
|-----|-----------------|------|
| 01  | 494.0           | FM   |
| .   | .               | .    |
| 08  | 499.4           | FM   |
| .   | .               | .    |
| 16  | 505.2           | FM   |





### 1.5. Accessory information

| Equipment         | Manufacturer                     | Model  | Serial No. | Power source      |
|-------------------|----------------------------------|--------|------------|-------------------|
| Remote controller | Sinsunglim electronics Co., Ltd. | TR-20P | -          | Battery (1.5V *2) |

### 1.6. Information about derivative model

Derivative model use the same software of basic model. In case of derivative model, the IR socket is removed in basic model and added button key.

For detailed information, refer to the following:

| Basic model   | Derivative model   |
|---|--|
|   |   |
|  |  |



## 2. Summary of tests

| Reference                 | Parameter                               | Test results |
|---------------------------|---|--------------|
| 74.861(e)(1)<br>2.1046    | RF output power                         | Pass         |
| 74.861(e)(3)<br>2.1047    | Modulation characteristics              | Pass         |
| 74.861(e)(5)(6)<br>2.1049 | Occupied bandwidth and emission mask    | Pass         |
| 74.861(e)(4)<br>2.1055    | Frequency stability                     | Pass         |
| 74.861(e)(6)<br>2.1053    | Field strength of spurious radiation    | Pass         |
| 74.861(e)(6)<br>2.1051    | Spurious emissions at antenna terminals | Pass         |

### 3. Test results

#### 3.1. RF output power

##### Test procedure


TIA-603-E – Section 2.2.1

##### Limit

According to §74.861(e)(1)(ii), the operating frequency at 470 ~ 608 MHz, 614 ~ 698 MHz shall not exceed 250 mW conducted power.

##### Test results

| Frequency(MHz) | Peak output power(dBm) | Limit(dBm) |
|----------------|------------------------|------------|
| 494.0          | 9.79                   | 23.98      |
| 499.4          | 10.12                  |            |
| 505.2          | 10.25                  |            |



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.



### 3.2. Modulation characteristics

#### Test procedure

TIA-603-E – Section 2.2.3, 2.2.6, FCC Part 2.1047(a) & (b)

#### (a) Audio frequency response

Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low pass filter, a curve showing the frequency response of the filter, or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.

#### Section 2.2.6

1. Connect the equipment as illustrated.
2. Set the test receiver to measure peak positive deviation. Set the audio bandwidth for  $\leq 50$  Hz to  $\geq 15000$  Hz. Turn the de-emphasis function off.
3. Adjust the transmitter per the manufacturer's procedure for full rated system deviation.
4. Apply a 1000 Hz tone and adjust the audio frequency generator to produce 20% of the rated system deviation.
5. Set the test receiver to measure rms deviation and record the deviation reading as  $DEV_{REF}$ .
6. Set the audio frequency generator to the desired test frequency between 300 Hz and 3000 Hz.
7. Record the test receiver deviation reading as  $DEV_{FREQ}$ .
8. Calculate the audio frequency response at the present frequency as:

$$\text{audio frequency response} = 20 \log_{10} \left( \frac{DEV_{FREQ}}{DEV_{REF}} \right)$$

9. Repeat steps 6 through 8 for all the desired test frequencies.

#### (b) Modulation limiting

Equipment which employs modulation limiting. A curve or family of curves showing the percentage of modulation versus the modulation input voltage shall be supplied. The information submitted shall be sufficient to show modulation limiting capability throughout the range of modulating frequencies and input modulating signal levels employed.

#### Section 2.2.3

1. Connect the equipment as illustrated.
2. Adjust the transmitter per the manufacturer's procedure for full rated system deviation.
3. Set the test receiver to measure peak positive deviation. Set the audio bandwidth for  $\leq 0.25$  Hz to  $\geq 15000$  Hz. Turn the de-emphasis function off.
4. Apply a 1000 Hz modulating signal to the transmitter from the audio frequency generator, and adjust the level to obtain 60% of full rated system deviation.
5. Increase the level from the audio frequency generator by 20dB in on step (rise time between the 10% and 90% points shall be 0.1 second maximum).
6. Measure both the instantaneous and steady-state deviation at and after the time of increasing the audio input level.
7. With the level from the audio frequency generator held constant at the level obtained in step 5, slowly vary the audio frequency from 100 Hz to 3000 Hz and observe the steady-state deviation. Record the maximum deviation.
8. Set the test receiver to measure peak negative deviation and repeat steps 4 through 7.
9. The values recorded in steps 7 and 8 are the modulation limiting.





---

### **Limit**


According to §74.861(e)(3), Any form of modulation may be used. A maximum deviation of  $\pm 75$  kHz is permitted when frequency modulation is employed.

## Test results

### (a) Audio frequency response

Frequency: 494.0 MHz  
Channel: 01


| Audio frequency(Hz) | Frequency deviation(kHz) | 1kHz Reference deviation(kHz) | Audio frequency response (dB) |
|---------------------|--------------------------|-------------------------------|-------------------------------|
| 100                 | 0.56                     | 2.58                          | -13.27                        |
| 200                 | 0.57                     | 2.58                          | -13.11                        |
| 300                 | 0.95                     | 2.58                          | -8.68                         |
| 400                 | 1.40                     | 2.58                          | -5.31                         |
| 500                 | 1.80                     | 2.58                          | -3.13                         |
| 600                 | 2.12                     | 2.58                          | -1.71                         |
| 700                 | 2.37                     | 2.58                          | -0.74                         |
| 800                 | 2.53                     | 2.58                          | -0.17                         |
| 900                 | 2.60                     | 2.58                          | -0.07                         |
| 1000                | 2.58                     | 2.58                          | 0.00                          |
| 1500                | 2.30                     | 2.58                          | -1.00                         |
| 2000                | 2.02                     | 2.58                          | -2.13                         |
| 2500                | 1.77                     | 2.58                          | -3.27                         |
| 3000                | 1.54                     | 2.58                          | -4.48                         |
| 4000                | 1.12                     | 2.58                          | -7.25                         |
| 5000                | 0.83                     | 2.58                          | -9.85                         |



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.

Frequency: 499.4 MHz  
Channel: 08


| Audio frequency(Hz) | Frequency deviation(kHz) | 1kHz Reference deviation(kHz) | Audio frequency response (dB) |
|---------------------|--------------------------|-------------------------------|-------------------------------|
| 100                 | 0.63                     | 2.75                          | -12.80                        |
| 200                 | 0.69                     | 2.75                          | -12.01                        |
| 300                 | 1.03                     | 2.75                          | -8.53                         |
| 400                 | 1.50                     | 2.75                          | -5.26                         |
| 500                 | 1.91                     | 2.75                          | -3.17                         |
| 600                 | 2.25                     | 2.75                          | -1.74                         |
| 700                 | 2.54                     | 2.75                          | -0.69                         |
| 800                 | 2.70                     | 2.75                          | -0.16                         |
| 900                 | 2.76                     | 2.75                          | 0.03                          |
| 1000                | 2.75                     | 2.75                          | 0.00                          |
| 1500                | 2.46                     | 2.75                          | -0.97                         |
| 2000                | 2.16                     | 2.75                          | -2.10                         |
| 2500                | 1.90                     | 2.75                          | -3.21                         |
| 3000                | 1.65                     | 2.75                          | -4.44                         |
| 4000                | 1.18                     | 2.75                          | -7.35                         |
| 5000                | 0.88                     | 2.75                          | -9.90                         |



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.

Frequency: 505.2 MHz  
Channel: 16

| Audio frequency(Hz) | Frequency deviation(kHz) | 1kHz Reference deviation(kHz) | Audio frequency response (dB) |
|---------------------|--------------------------|-------------------------------|-------------------------------|
| 100                 | 0.78                     | 3.19                          | -12.23                        |
| 200                 | 0.80                     | 3.19                          | -12.01                        |
| 300                 | 1.14                     | 3.19                          | -8.94                         |
| 400                 | 1.79                     | 3.19                          | -5.02                         |
| 500                 | 2.24                     | 3.19                          | -3.07                         |
| 600                 | 2.63                     | 3.19                          | -1.68                         |
| 700                 | 2.94                     | 3.19                          | -0.71                         |
| 800                 | 3.14                     | 3.19                          | -0.14                         |
| 900                 | 3.20                     | 3.19                          | 0.03                          |
| 1000                | 3.19                     | 3.19                          | 0.00                          |
| 1500                | 2.86                     | 3.19                          | -0.95                         |
| 2000                | 2.51                     | 3.19                          | -2.08                         |
| 2500                | 2.20                     | 3.19                          | -3.23                         |
| 3000                | 1.93                     | 3.19                          | -4.36                         |
| 4000                | 1.39                     | 3.19                          | -7.22                         |
| 5000                | 1.04                     | 3.19                          | -9.74                         |




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.

## (b) Modulation limiting


Operating frequency: 494.0 MHz  
Channel: 01

| Audio level (dB) | Deviation 300 Hz | Deviation 1 kHz | Deviation 3 kHz | Limit (kHz) |
|------------------|------------------|-----------------|-----------------|-------------|
| -52.6            | 1.87             | 5.05            | 2.56            | ±75         |
| -47.6            | 2.30             | 6.56            | 3.30            | ±75         |
| -42.6            | 3.01             | 8.65            | 4.43            | ±75         |
| -37.6            | 4.14             | 11.48           | 5.83            | ±75         |
| -32.6            | 5.70             | 15.43           | 7.62            | ±75         |
| -27.6            | 8.00             | 20.72           | 10.11           | ±75         |
| -22.6            | 12.21            | 27.75           | 13.30           | ±75         |
| -17.6            | 20.43            | 37.03           | 17.74           | ±75         |
| -12.6            | 36.30            | 50.00           | 23.56           | ±75         |



Operating frequency: 499.4 MHz  
Channel: 08


| Audio level (dB) | Deviation 300 Hz | Deviation 1 kHz | Deviation 3 kHz | Limit (kHz) |
|------------------|------------------|-----------------|-----------------|-------------|
| -52.6            | 1.89             | 5.23            | 2.66            | ±75         |
| -47.6            | 2.51             | 6.89            | 3.39            | ±75         |
| -42.6            | 3.17             | 9.07            | 4.61            | ±75         |
| -37.6            | 4.18             | 12.04           | 6.05            | ±75         |
| -32.6            | 5.64             | 16.05           | 7.96            | ±75         |
| -27.6            | 8.33             | 21.41           | 10.50           | ±75         |
| -22.6            | 12.43            | 28.76           | 13.93           | ±75         |
| -17.6            | 21.33            | 38.66           | 18.53           | ±75         |
| -12.6            | 36.74            | 52.33           | 24.66           | ±75         |



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.

Operating frequency: 505.2 MHz  
Channel: 16

| Audio level (dB) | Deviation 300 Hz | Deviation 1 kHz | Deviation 3 kHz | Limit (kHz) |
|------------------|------------------|-----------------|-----------------|-------------|
| -52.6            | 2.25             | 6.24            | 3.09            | ±75         |
| -47.6            | 2.98             | 8.21            | 4.29            | ±75         |
| -42.6            | 3.84             | 10.87           | 5.50            | ±75         |
| -37.6            | 5.20             | 14.43           | 7.18            | ±75         |
| -32.6            | 8.07             | 19.23           | 9.50            | ±75         |
| -27.6            | 12.19            | 25.75           | 12.58           | ±75         |
| -22.6            | 17.41            | 34.35           | 16.68           | ±75         |
| -17.6            | 28.08            | 45.90           | 22.14           | ±75         |
| -12.6            | 44.43            | 62.10           | 29.47           | ±75         |





### 3.3. Occupied bandwidth and emission mask

#### Test procedure

TIA-603-E – Section 2.2.11, FCC Part 2.1049

#### TIA-603-E – Section 2.2.11

1. Adjust the spectrum analyzer for the following settings:
  - RBW : 3 kHz
  - VBW : 10 kHz
  - Sweep speed slow enough to maintain measurement calibration.
  - Detector mode : Peak
  - Span that will allow proper viewing of the test bandwidth
2. Set the center frequency of the spectrum analyzer to the assigned transmitter frequency. Turn on the transmitter, and set the level of the unmodulated carrier to a full scale reference line. This is the 0 dB reference for the measurement.
3. Modulate the transmitter with a 2500 Hz sine wave at input level 16 dB greater than that necessary to produce 50% of rated system deviation. The input level shall be established at the frequency of maximum response of the audio modulating circuit. Transmitters employing digital modulation techniques that bypass the limiter and the audio low pass filter shall be modulated as specified by the manufacturer.

#### FCC Part 2.1049

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions as applicable:

(1) Other than single sideband or independent sideband transmitters – when modulated by a 2500 Hz tone at an input level 16 dB greater than that necessary to produce 50 percent modulation. The input level shall be established at the frequency of maximum response of the audio modulating circuit.

#### Limit

According to §74.861(e)(5),(6) the operating bandwidth shall not exceed 200 kHz.

**At least 25 dB** on any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth.

**At least 35 dB** on any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth.

**At least  $43 + 10 \log_{10}(P)$  dB** on any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth.

#### Note.

1. P is mean in watts.




---

**Test results**


| Frequency(MHz) | 99% bandwidth(kHz) | Limit(kHz) |
|----------------|--------------------|------------|
| 494.0          | 123.01             | 200        |
| 499.4          | 138.93             |            |
| 505.2          | 153.40             |            |

### 494.0 MHz

#### Occupied bandwidth




#### Emission mask




### 499.4 MHz

#### Occupied bandwidth




#### Emission mask




### 505.2 MHz

#### Occupied bandwidth



#### Emission mask



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.

### 3.4. Frequency stability

#### Test procedure

TIA-603-E – Section 2.2.2, FCC Part 2.1055

#### TIA-603-E – Section 2.2.2

1. Connect the equipment as illustrated.
2. Operate the equipment in standby conditions for 15 minutes before proceeding.
3. Record the carrier frequency of the transmitter as  $MCF_{MHz}$ .
4. Calculate the ppm frequency error by the following:

$$ppm\ error = \left( \frac{MCF_{MHz}}{ACF_{MHz}} - 1 \right) * 10^6$$

Where

$MCF_{MHz}$  is the Measured Carrier Frequency in MHz

$ACF_{MHz}$  is the Assigned Carrier Frequency in MHz

5. The value recorded in step 4 is the carrier frequency stability.

#### FCC Part 2.1055

- (1) From -30° to + 50° centigrade for all equipment except that specified in paragraphs (a)(2) and (3) of this section.

#### Limit

According to §74.861(e)(4), the frequency tolerance of the transmitter shall be 0.005 percent.



## Test results

Operating frequency: 494.0 MHz

Channel: 01

| Test voltage (%)  | Test voltage (V) | Temperature (°C) | Measure frequency (MHz) | Frequency deviation (Hz) | Deviation (%) |
|-------------------|------------------|------------------|-------------------------|--------------------------|---------------|
| 100 %             | DC 3.0           | -30              | 494.007 742             | 7 742                    | 0.001 567     |
| 100 %             |                  | -20              | 494.007 699             | 7 699                    | 0.001 558     |
| 100 %             |                  | -10              | 494.006 252             | 6 252                    | 0.001 266     |
| 100 %             |                  | 0                | 494.004 284             | 4 284                    | 0.000 867     |
| 100 %             |                  | 10               | 494.001 795             | 1 795                    | 0.000 363     |
| 100 %             |                  | 20               | 493.995 631             | -4 369                   | -0.000 884    |
| 100 %             |                  | 30               | 493.996 035             | -3 965                   | -0.000 803    |
| 100 %             |                  | 40               | 493.992 562             | -7 438                   | -0.001 506    |
| 100 %             |                  | 50               | 493.991 751             | -8 249                   | -0.001 670    |
| Battery end point | DC 2.4           | 23               | 493.993 277             | -6 723                   | -0.001 361    |

Operating frequency: 499.4 MHz

Channel: 08

| Test voltage (%)  | Test voltage (V) | Temperature (°C) | Measure frequency (MHz) | Frequency deviation (Hz) | Deviation (%) |
|-------------------|------------------|------------------|-------------------------|--------------------------|---------------|
| 100 %             | DC 3.0           | -30              | 499.407 709             | 7 709                    | 0.001 544     |
| 100 %             |                  | -20              | 499.407 709             | 7 709                    | 0.001 544     |
| 100 %             |                  | -10              | 499.406 493             | 6 493                    | 0.001 300     |
| 100 %             |                  | 0                | 499.404 207             | 4 207                    | 0.000 842     |
| 100 %             |                  | 10               | 499.401 949             | 1 949                    | 0.000 390     |
| 100 %             |                  | 20               | 499.395 524             | -4 476                   | -0.000 896    |
| 100 %             |                  | 30               | 499.395 958             | -4 042                   | -0.000 809    |
| 100 %             |                  | 40               | 499.392 398             | -7 602                   | -0.001 522    |
| 100 %             |                  | 50               | 499.391 906             | -8 094                   | -0.001 621    |
| Battery end point | DC 2.4           | 23               | 499.395 664             | -4 336                   | -0.000 868    |




Operating frequency: 505.2 MHz  
Channel: 16

| Test voltage (%)  | Test voltage (V) | Temperature (°C) | Measure frequency (MHz) | Frequency deviation (Hz) | Deviation (%) |
|-------------------|------------------|------------------|-------------------------|--------------------------|---------------|
| 100 %             | DC 3.0           | -30              | 505.207 781             | 7 781                    | 0.001 540     |
| 100 %             |                  | -20              | 505.207 781             | 7 781                    | 0.001 540     |
| 100 %             |                  | -10              | 505.206 638             | 6 638                    | 0.001 314     |
| 100 %             |                  | 0                | 505.203 918             | 3 918                    | 0.000 776     |
| 100 %             |                  | 10               | 505.202 094             | 2 094                    | 0.000 414     |
| 100 %             |                  | 20               | 505.195 495             | -4 505                   | -0.000 892    |
| 100 %             |                  | 30               | 505.195 929             | -4 071                   | -0.000 806    |
| 100 %             |                  | 40               | 505.192 311             | -7 689                   | -0.001 522    |
| 100 %             |                  | 50               | 505.189 884             | -10 116                  | -0.002 002    |
| Battery end point | DC 2.4           | 23               | 505.195 577             | -4 423                   | -0.000 876    |


### 3.5. Field strength of spurious radiation

#### Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.




The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



The diagram below shows the test setup for substituted method





---

#### **Test procedure above 30 MHz**

1. On a test site, the EUT shall be placed at 80cm height on a turn table, and in the position closest to normal use as declared by the applicant.
2. The test antenna shall be oriented initially for vertical polarization located 3m from EUT to correspond to the frequency of the transmitter.
3. The output of the test antenna shall be connected to the measuring receiver and the peak detector is used for the measurement.
4. The transmitter shall be switched on, the measuring receiver shall be tuned to the frequency of the transmitter under test.
5. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
6. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
7. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
8. The maximum signal level detected by the measuring receiver shall be noted.
9. The transmitter shall be replaced by a horn (substitution antenna).
10. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
11. The substitution antenna shall be connected to a calibrated signal generator.
12. In necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
13. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
14. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, which is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
15. The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
16. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
17. The measure of the effective radiated power is the large of the two levels recorded, at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.

---

### Limit

According to §2.1053, measurements shall be made to detect spurious emission that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal condition of installation and operation. Information submitted shall include the relative radiated power of spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from a half wave dipole antenna.

According to §74.861(e)(ii)(6), the mean power of emission shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- (i) 470 ~ 608 MHz and 614 ~ 698 MHz : 250 mW (23.98 dBm)
- (ii) on any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth : at least 25 dB
- (iii) on any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth : at least 23 dB
- (iv) on any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth shall be attenuated below the unmodulated carrier by at least  $43 + 10\log(P)$  dB.

### Test results (Below 1 000 MHz)

Mode: FM  
Distance of measurement: 3 meter  
Channel: 01

| Frequency<br>(MHz) | Ant. Pol.<br>(H/V) | E.R.P. |           |
|--------------------|--------------------|--------|-----------|
|                    |                    | (dBm)  | (W)       |
| 494.00             | H                  | -13.50 | 0.000 045 |
| 494.00             | V                  | 10.11  | 0.010 257 |

Mode: FM  
Distance of measurement: 3 meter  
Channel: 08

| Frequency<br>(MHz) | Ant. Pol.<br>(H/V) | E.R.P. |           |
|--------------------|--------------------|--------|-----------|
|                    |                    | (dBm)  | (W)       |
| 499.40             | H                  | -14.71 | 0.000 034 |
| 499.40             | V                  | 10.19  | 0.010 447 |

Mode: FM  
Distance of measurement: 3 meter  
Channel: 16

| Frequency<br>(MHz) | Ant. Pol.<br>(H/V) | E.R.P. |           |
|--------------------|--------------------|--------|-----------|
|                    |                    | (dBm)  | (W)       |
| 505.20             | H                  | -13.20 | 0.000 048 |
| 505.20             | V                  | 10.50  | 0.011 220 |



## Test results (Above 1 000 MHz)

Mode: FM  
Distance of measurement: 3 meter  
Channel: 01

| Frequency<br>(MHz) | Ant. Pol.<br>(H/V) | Spurious attenuation<br>(dBc) | Limit<br>(dBm) | Margin<br>(dB) |
|--------------------|--------------------|-------------------------------|----------------|----------------|
| 988.10             | H                  | 66.26                         | -13.00         | 43.15          |
| 988.10             | V                  | 55.50                         | -13.00         | 32.39          |
| 1 483.40           | H                  | 77.93                         | -13.00         | 54.82          |
| 1 483.40           | V                  | 66.11                         | -13.00         | 43.00          |
| 1 836.50           | H                  | 79.19                         | -13.00         | 56.08          |
| 1 975.40           | V                  | 66.35                         | -13.00         | 43.24          |
| 2 455.86           | V                  | 66.65                         | -13.00         | 43.54          |
| 3 457.30           | H                  | 66.84                         | -13.00         | 43.73          |
| 3 457.30           | V                  | 64.49                         | -13.00         | 41.38          |

Note.

1. Spurious attenuation = EUT max. output power(dBm) - absolute level
2. Spurious attenuation limit in dB =  $43 + 10\log(\text{power in watts})$

Mode: FM  
Distance of measurement: 3 meter  
Channel: 08

| Frequency<br>(MHz) | Ant. Pol.<br>(H/V) | Spurious attenuation<br>(dBc) | Limit<br>(dBm) | Margin<br>(dB) |
|--------------------|--------------------|-------------------------------|----------------|----------------|
| 998.778            | H                  | 55.40                         | -13.00         | 32.21          |
| 998.778            | V                  | 55.53                         | -13.00         | 32.34          |
| 1 498.167          | H                  | 58.49                         | -13.00         | 35.30          |
| 1 498.167          | V                  | 66.50                         | -13.00         | 43.31          |
| 1 997.556          | H                  | 60.35                         | -13.00         | 37.16          |
| 1 997.556          | V                  | 59.77                         | -13.00         | 36.58          |
| 2 496.945          | H                  | 60.17                         | -13.00         | 36.98          |
| 2 496.945          | V                  | 72.28                         | -13.00         | 49.09          |
| 2 996.334          | H                  | 60.41                         | -13.00         | 37.22          |
| 2 996.334          | V                  | 65.05                         | -13.00         | 41.86          |
| 3 495.723          | H                  | 67.19                         | -13.00         | 44.00          |
| 3 495.723          | V                  | 62.42                         | -13.00         | 39.23          |

Note.

1. Spurious attenuation = EUT max. output power(dBm) - absolute level
2. Spurious attenuation limit in dB =  $43 + 10\log(\text{power in watts})$



Mode: FM  
Distance of measurement: 3 meter  
Channel: 16

| Frequency<br>(MHz) | Ant. Pol.<br>(H/V) | Spurious attenuation<br>(dBc) | Limit<br>(dBm) | Margin<br>(dB) |
|--------------------|--------------------|-------------------------------|----------------|----------------|
| 1 010.384          | H                  | 71.52                         | -13.00         | 48.02          |
| 1 010.384          | V                  | 57.63                         | -13.00         | 34.13          |
| 1 515.576          | H                  | 76.68                         | -13.00         | 53.18          |
| 1 515.576          | V                  | 65.45                         | -13.00         | 41.95          |
| 2 020.768          | H                  | 67.56                         | -13.00         | 44.06          |
| 2 020.768          | V                  | 60.21                         | -13.00         | 36.71          |
| 2 525.960          | H                  | 67.91                         | -13.00         | 44.41          |
| 2 525.960          | V                  | 77.24                         | -13.00         | 53.74          |
| 3 031.152          | H                  | 67.26                         | -13.00         | 43.76          |
| 3 536.344          | H                  | 66.15                         | -13.00         | 42.65          |
| 3 536.344          | V                  | 60.71                         | -13.00         | 37.21          |

Note.

1. Spurious attenuation = EUT max. output power(dBm) - absolute level
2. Spurious attenuation limit in dB =  $43 + 10\log(\text{power in watts})$



---

### **3.6. Spurious emission at antenna terminals**

#### **Test procedure**

TIA-603-E – Section 2.2.13, FCC Part 74.861(e)(6)(iii)

#### **TIA-603-E –Section 2.2.13**

1. Set the center frequency of the spectrum analyzer to the assigned transmitter frequency, key the transmitter, and set the level of the carrier to the full scale reference line.
2. Modulate the transmitter with a 2500 Hz sine wave at an input level 16 dB greater than that necessary to produce 50% of rated system deviation.  
The input level shall be established at the frequency of maximum response of the audio modulating circuit.
3. Record the frequencies and levels of spurious emissions.


#### **FCC Part 74.861(e)(6)(iii)**

1. On any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth : at least  $43 + 10\log(P)$  dB.

#### **Note.**

1. P is mean in watts.

## Test results



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The test results in the report only apply to the tested sample.



## Appendix A. Measurement equipment

| Equipment                           | Manufacturer       | Model     | Serial No.   | Calibration interval | Calibration due. |
|-------------------------------------|--------------------|-----------|--------------|----------------------|------------------|
| Spectrum Analyzer                   | R&S                | FSV30     | 101389       | 1 year               | 2018.01.23       |
| 8360B Series Swept Signal Generator | HP                 | 83630B    | 3844A00786   | 1 year               | 2018.01.23       |
| MXG Vector Signal Generator         | Agilent            | N5182A    | MY50143829   | 1 year               | 2018.01.19       |
| DC Power Supply                     | Agilent            | 6632B     | US36351824   | 1 year               | 2018.01.19       |
| Attenuator                          | KEYSIGHT           | 8493C     | 82507        | 1 year               | 2018.01.23       |
| Modulation Analyzer                 | HP                 | 8901B     | 3438A05094   | 1 year               | 2018.01.20       |
| Audio Analyzer                      | HP                 | 8903B     | 3413A14728   | 1 year               | 2018.07.03       |
| Trilog-broadband antenna            | SCHWARZBECK        | VULB 9163 | 9168-714     | 2 years              | 2018.11.28       |
| Dipole antenna                      | SCHWARZBECK        | VHA9103   | 3093         | 2 years              | 2019.05.19       |
| Dipole antenna                      | SCHWARZBECK        | UHA9105   | 2703         | 2 years              | 2019.05.19       |
| Dipole antenna                      | SCHWARZBECK        | VHA9103   | 3101         | 2 years              | 2019.05.19       |
| Dipole antenna                      | SCHWARZBECK        | UHA9105   | 2702         | 2 years              | 2019.05.19       |
| Horn Antenna                        | A.H.               | SAS-571   | 781          | 2 years              | 2019.05.02       |
| Horn Antenna                        | A.H SYSTEMS        | SAS-571   | 414          | 2 years              | 2019.02.15       |
| High Pass Filter                    | Mini-Circuits      | NHP-800+  | 15542        | 1 year               | 2018.07.03       |
| Preamplifier                        | SCHWARZBECK        | BBV-9718  | 9718-246     | 1 year               | 2017.10.14       |
| Preamplifier                        | HP                 | 8447F     | 2805A02570   | 1 year               | 2018.01.19       |
| EMI Test Receiver                   | R&S                | ESU26     | 100552       | 1 year               | 2018.04.19       |
| Temperature & Humidity Chamber      | Daehan Engineering | DH-1000   | DH1000060628 | 1 year               | 2018.02.03       |

## Peripheral devices

| Device | Manufacturer | Model No. | Serial No. |
|--------|--------------|-----------|------------|
| -      | -            | -         | -          |