

Report Number: F690501/RF-RTL010524 Page: 1 of 6

# **TEST REPORT**

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: TQ8-ADBC0H8EE

Equipment Under Test : DISPLAY CAR SYSTEM

Model Name : ADBC0H8EE

Variant Model Names : ADB10H8GG, ADB10H8GN, ADB10H8GE,

ADB11H8GG, ADB12H8GG, ADB11H8EE

Applicant : Hyundai MOBIS Co., Ltd.

Manufacturer : Hyundai MOBIS Co., Ltd.

Date of Receipt : 2016.10.19

Date of Test(s) : 2016.11.01 ~ 2016.11.08

Date of Issue : 2016.11.09

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Patrick Kang

Date: 2016.11.09

Technical Manager: Date: 2016.11.09

Logan Lee



Report Number: F690501/RF-RTL010524 Page: 2 of 6

## **INDEX**

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	5



Report Number: F690501/RF-RTL010524 Page: 3 of 6

### 1. General Information

## 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

-Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

## 1.2. Details of applicant

Applicant : Hyundai MOBIS Co., Ltd.

Address : 203, Teheran-ro, Gangnam-gu, Seoul, 06141, Republic of Korea

Contact Person : Kwon, Heung-Chul Phone No. : +82 31 260 2714

## 1.3. Description of EUT

Kind of Product	DISPLAY CAR SYSTEM	
Model Name	ADBC0H8EE	
Variant Model Names	ADB10H8GG, ADB10H8GN, ADB10H8GE, ADB11H8GG, ADB12H8GG, ADB11H8EE	
Power Supply	DC 14.4 V (Vehicle battery)	
Frequency Range	2 402 MHz ~ 2 480 MHz	
Modulation Technique	GFSK, π/4DQPSK, 8DPSK	
Number of Channels	79 channels	
Antenna Type	Chip antenna	
Antenna Gain	-0.10 dBi	



Report Number: F690501/RF-RTL010524 Page: of 6

## 1.4. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL010524	2016.11.09	Initial

## 1.5. Information of Variant Model

YB-D Audio		Bluetooth	DAB	RDS	Country
Basic Model	ADBC0H8EE	0	0	0	Europe (Europe Band)
	ADB10H8GG	0	Х	Х	General (General Band)
	ADB10H8GN	0	Х	Х	General (US Band)
Variant	ADB10H8GE	0	Х	Х	General (Europe Band)
Models	ADB11H8GG	0	Х	Х	General (General Band)
	ADB12H8GG	0	Х	0	General (Europe Band)
	ADB11H8EE	0	Х	Х	Europe (Europe Band)



Report Number: F690501/RF-RTL010524 Page: 5 of 6

## 2. RF Exposure Evaluation

# 2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (썐)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (ﷺ/ﷺ	Average Time		
(A) Limits for Occupational/Controlled Exposure						
0.3 – 3.0	614	1.63	*100	6		
3.0 – 30	1842/f	4.89/f	*900/f <sup>2</sup>	6		
30 - 300	61.4	0.163	1.0	6		
300 – 1 500	-	-	f/300	6		
1 500 – 100 000	-	-	5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3 – 1.34	614	1.63	*100	30		
1.34 – 30	824/f	2.19/f	*180/f <sup>2</sup>	30		
30 - 300	27.5	0.073	0.2	30		
300 – 1 500	-	-	f/1500	30		
1 500 – 100 000	-	-	1.0	<u>30</u>		

### 2.1.1. Friis transmission formula: $Pd = (Pout*G)/(4*pi*R^2)$

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Report Number: F690501/RF-RTL010524 Page: 6 of 6

### 2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

### 2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

#### **Bluetooth**

- Maximum tune up tolerance

Channel	Channel Frequency (쌘)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm²)	Limits (nW/cm²)
0	2 402	4	-0.10	0.000 488	1

#### Note:

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².

- End of the Test Report -