

## FCC MPE REPORT

### Certification

**Applicant Name:**  
HYUNDAI MOBIS CO., LTD.

**Date of Issue:**  
March 20, 2019

**Address:**  
203, Teheran-ro, Gangnam-gu, Seoul, 135-977, South Korea

**Test Site/Location:**  
HCT CO., LTD., 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

**Report No.:** HCT-RF-1901-FC018-R2

**FCC ID:** TQ8-ADC15DVGN

**APPLICANT:** HYUNDAI MOBIS CO., LTD.

According to the Evaluation report, all of the data contained herein is reused from the reference  
FCC ID : TQ8-ADC10DWAU report.

**Model:** ADC15DVGN

**Additional Model:** ADC10DVRP, ADC10DVGG, ADC11DVGG, ADC12DVGG, ADC13DVGG, ADC14DVGN, ADC16DVGL, ADC10DVMG, ADC10DVEG, ADC11DVEG, ADC12DVEG, ADC10DVUG, ADC14DVEP, ADC15DVEP, ADC16DVEP, ADCC0DVEP, ADC10DVTP

**EUT Type:** Car Audio System

**Frequency Range:** 2402 MHz - 2480 MHz

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)



**Report prepared by : Se Wook Park**  
**Engineer of Telecommunication testing center**



**Approved by : Yong Hyun Lee**  
**Manager of Telecommunication testing center**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1901-FC018	January 23, 2019	- First Approval Report
HCT-RF-1901-FC018-R1	March 06, 2019	- Added the Reuse statement on page 1
HCT-RF-1901-FC018-R2	March 20, 2019	- Added the Additional Model on page 1

# RF Exposure Statement

## 1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

### (B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f <sup>2</sup> )	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	.....	.....	f/1500	30
1500 - 100.000.....	.....	.....	1.0	30

F = frequency in MHz

\* = Plane-wave equivalent power density

## 2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

### 3. RESULTS

#### 3-1. Bluetooth

Average output Power at antenna input terminal	4.00	dBm
Average output Power at antenna input terminal	2.512	mW
Prediction distance	20.00	cm
Prediction frequency	2402 ~ 2480	MHz
Antenna Gain(typical)	0.07	dBi
Antenna Gain(numeric)	1.016	-
Power density at prediction frequency( S)	0.00051	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	1.00	mW/cm <sup>2</sup>

#### 2.1091

EIRP	4.07 (dBm)
ERP	1.92 (dBm)
ERP	0.002 (W)
ERP Limit	3.00 (W)
MARGIN	32.85 (dB)