

Report Number: F690501/RF-RTL012021 Page: 1 of 6

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310 FCC ID:TQ8- ACB10A0GG

Equipment Under Test : DIGITAL CAR AUDIO SYSTEM

Model Name : ACB10A0GG

Variant Model Names : ACB10A0GN, ACB10A0GE, ACB10A0GL, ACB11A0GG,

ACB11A0GN, ACB10A0MG, ACB11A0MG

Applicant : Hyundai Mobis Co., Ltd.

Manufacturer : Hyundai Mobis Co., Ltd.

Date of Receipt : 2017.10.31

Date of Test(s) : 2017.11.14 ~ 2017.11.17

Date of Issue : 2017.11.17

In the configuration tested, the EUT complied with the standards specified above.

Tested By:

Date:

2017.11.17

Jinhyuong Cho

Harim Lee

Technical Manager:

Date:

2017.11.17

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL012021 Page: 2 of 6

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	5



Report Number: F690501/RF-RTL012021 Page: of 6

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

-Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

1.2. Details of Applicant

Hyundai Mobis Co., Ltd. **Applicant**

Address 203, Teheran-ro, Gangnam-gu, Seoul, 06141, Korea

Contact Person : Hyun Sae-Romy Phone No. +82 31 260 2714

1.3. Details of manufacturer

Company Same as applicant Address Same as applicant

1.4. Description of EUT

Kind of Product	DIGITAL CAR AUDIO SYSTEM
Model Name	ACB10A0GG
Variant Model Names	ACB10A0GN, ACB10A0GE, ACB10A0GL, ACB11A0GG, ACB11A0GN, ACB10A0MG, ACB11A0MG
Power Supply	DC 14.4 V
Frequency Range	2 402 Mb ~ 2 480 Mb (Bluetooth)
Modulation Technique	GFSK, π/4DQPSK, 8DPSK
Number of Channels	79 channels
Antenna Type	Dielectric Chip Antenna
Antenna Gain	-0.10 dBi

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL012021 Page: 4 of 6

1.5. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL012021	2017.11.17	Initial

1.6. Information of Variant models

Мо	del name	Frequency	RHD/ LHD	ВТ	USB	BT APP	RDS	DRM
Basic model	ACB10A0GG	General	LHD	0	0	Х	Х	Х
	ACB10A0GN	North America	LHD	0	0	Х	Х	Х
	ACB10A0GE	Europe	LHD	0	0	Х	Х	Х
	ACB10A0GL	Colombia	LHD	0	0	Х	Х	Х
Variant models	ACB11A0GG	General/ South Africa	LHD	0	0	Х	0	Х
	ACB11A0GN	North America	LHD	0	0	Х	Х	Х
	ACB10A0MG	General	LHD	0	0	Х	Х	Х
	ACB11A0MG	General	LHD	0	0	Х	0	Х



Report Number: F690501/RF-RTL012021 Page: 5 of 6

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (脈)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time		
(A) Limits for Occupational/Controlled Exposure						
0.3 – 3.0	614	1.63	*100	6		
3.0 – 30	1842/f	4.89/f	*900/f ²	6		
30 – 300	61.4	0.163	1.0	6		
300 – 1 500	-	-	f/300	6		
1 500 – 100 000	-	-	5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3 – 1.34	614	1.63	*100	30		
1.34 – 30	824/f	2.19/f	*180/f ²	30		
30 – 300	27.5	0.073	0.2	30		
300 – 1 500	-	-	f/1500	30		
<u>1 500 – 100 000</u>	-	-	<u>1.0</u>	<u>30</u>		

2.1.1. Friis transmission formula: $Pd = (Pout*G)/(4*pi*R^2)$

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



Report Number: F690501/RF-RTL012021 Page: 6 of 6

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Bluetooth

- Maximum tune up tolerance

Operating Frequency (쌘)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm²)	Limits (nW/cn²)
2 402 ~ 2 480	4	-0.10	0.000 488	1

Note:

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 $\,$ cm $\,$ between the radiator and your body.
- The antenna gain of this transmitter is less than 6 $\,\mathrm{dB}$ i and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

- End of the Test Report -