

# **MPE CALCULATION**

For *HYUNDAI MOBIS CO., LTD* - ; Model: PA710RBLSBT  
FCC ID: TQ8-PA710RBLSBT

RF Exposure Requirements:	47 CFR §1.1307(b)
RF Radiation Exposure Limits:	47 CFR §1.1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65 / 47 CFR §2.1091
EUT Frequency Band:	2402 – 2480 MHz
Limits for General Population/Uncontrolled Exposure in the band of:	1500 – 100,000 MHz
Power Density Limit:	1.0mW/ cm <sup>2</sup> ;

Equation:  $S = PG / 4\pi R^2$  or  $R = \sqrt{PG / 4\pi S}$   
Where, S = Power Density  
P = Power Input to Antenna  
G = Antenna Gain  
R = distance to the center of radiated antenna

---

Low Channel (2480 MHz): Power = 2.57 dBm, Antenna Gain = -5.47 dBi, Prediction distance 20cm  
 $S = 0.0001 \text{ mW/cm}^2$

## Result

The Above Result had shown that Device complied with 1.0 mW/cm<sup>2</sup> Power density requirement for distance of 20cm.

Completed By : Hyo Sun Kwak

Date : June 29, 2010