

## MPE Calculations : (Bluetooth)

- Frequency range : 2402 MHz ~ 2480 MHz
- Measured RF output power : 3.43 dBm
- Target Power & Tolerance : 2.00 dBm  $\pm$  1.5 dB ( Max. 3.5 dBm & Min. 0.5 dBm )
- Maximum antenna peak gain : 3.50 dBi
- **Maximum output power for the calculation 3.50 dBm**

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE calculation for this exposure is shown below.

<ul style="list-style-type: none"> <li>▪ <b>EIRP</b> = P + G</li> <li>= 3.50 dBm + 3.50 dBi</li> <li>= <b>7.00 dBm</b> = <b>5.012 mW</b></li> </ul>	<ul style="list-style-type: none"> <li>- <b>Note</b></li> <li>P = Power input to the antenna(dBm)</li> <li>G = Power gain of the antenna(dBi)</li> </ul>
---	--

### - Power density at the specific separation

<ul style="list-style-type: none"> <li>▪ <b>S</b> = EIRP / ( 4 R<sup>2</sup> π )</li> <li>= <b>5.012</b> / ( 4 X 20<sup>2</sup> X π )</li> <li>= <b>0.000998</b> mW/cm<sup>2</sup></li> </ul>	<ul style="list-style-type: none"> <li>- <b>Note</b></li> <li>S = Maximum power density(mW/cm<sup>2</sup>)</li> <li>EIRP = Equivalent Isotropic Radiated Power(mW)</li> <li>R = Distance to the center of the radiation of the antenna(20cm)</li> </ul>
---	---

**Conclusion : The exposure condition of this device is compliant with FCC rules.**

The maximum permissible exposure(MPE) of the general population/Uncontrolled for this device is 1.0 mW/cm<sup>2</sup>.