# RF Exposure Statement

## 1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

### (B) Limits for General Population/Uncontrolled Exposures

| Frequency range (MHz) | Electric field Strength (V/m) | Magnetic field Strength (A/m) | Power density (mW/cm²) | Averaging time (minutes) |
|---|---|---|---|---|
| 0.3 - 1.34..................................... | 614 | 1.63 | *(100) | 30 |
| 1.34 - 30..................................... | 824/f | 2.19/f | *(180/ f²) | 30 |
| 30 - 300...................................... | 27.5 | 0.073 | 0.2 | 30 |
| 300 - 1500.................................... | .............. | .............. | f/1500 | 30 |
| 1500 - 100.000............................... | .............. | .............. | 1.0 | 30 |

F = frequency in MHz

* = Plane-wave equivalent power density

## 2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

## 2. RESULTS

| Max Average output Power at antenna input terminal (dBm) | 3.2190 |
|---|---|
| Max Average output Power at antenna input terminal (mW) | 2.098 |
| Prediction distance (cm) | 20.00000 |
| Prediction frequency (MHz) | 2441.00000 |
| Antenna Gain(Peak) (dBi) | −0.10000 |
| Antenna Gain(numeric) | 0.97724 |
| Power density at prediction frequency (mW/cm²) | 0.000408 |
| MPE limit for uncontrolled exposure at prediction frequency (mW/cm²) | 1.00000 |

HCT CO., LTD
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea
TEL : + 82 31 645 6467     FAX : + 82 31 645 6401     www.hct.co.kr
2 of 2