## **MPE CALCULATION**

For HYUNDAI MOBIS CO., LTD - ; Model: AC240INAN1

FCC ID: TQ8-AC240INAN1

RF Exposure Requirements: 47 CFR §1.1307(b)

RF Radiation Exposure Limits: 47 CFR §1.1310

RF Radiation Exposure Guidelines: FCC OST/OET Bulletin Number 65 / 47 CFR §2.1091

EUT Frequency Band: 2402 – 2480 MHz
Limits for General Population/Uncontrolled Exposure in the band of: 1500 – 100,000 MHz

Power Density Limit: 1.0mW/ cm<sup>2</sup>;

Equation:  $S = PG / 4\pi R^2 \text{ or } R = \sqrt{PG / 4\pi S}$ 

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

Low Channel (2480 MHz): Power =2.07 dBm, Antenna Gain = 3.5 dBi, Prediction distance 20cm  $S = 0.000717 \text{ mW/cm}^2$ 

## Result

The Above Result had shown that Device complied with 1.0 mW/cm<sup>2</sup> Power density requirement for distance of 20cm.

Completed By: Jong Suk LEE

Date: November 11,2011