

MPE CALCULATION

For *HYUNDAI MOBIS CO., LTD -* ; Model: AV130A7AN

FCC ID: TQ8-AV130A7AN

| | |
|---|---|
| RF Exposure Requirements: | 47 CFR §1.1307(b) |
| RF Radiation Exposure Limits: | 47 CFR §1.1310 |
| RF Radiation Exposure Guidelines: | FCC OST/OET Bulletin Number 65 / 47 CFR §2.1091 |
| EUT Frequency Band: | 2402 – 2480 MHz |
| Limits for General Population/Uncontrolled Exposure in the band of: | 1500 – 100,000 MHz |
| Power Density Limit: | 1.0mW/ cm ² ; |

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$
Where, S = Power Density
P = Power Input to Antenna
G = Antenna Gain
R = distance to the center of radiated antenna

Low Channel (2402 MHz): Power =3.73 dBm, Antenna Gain = 3.5 dBi, Prediction distance 20cm

$S = 0.001051 \text{ mW/cm}^2$

Result

The Above Result had shown that Device complied with 1.0 mW/cm² Power density requirement for distance of 20cm.

Completed By : Jong Suk LEE

Date : January 10,2011