

Report Number: F690501/RF-RTL01269

Page:

1

of

6

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: TQ8-ACB11C7IG

Equipment Under Test : DIGITAL CAR AUDIO SYSTEM

Model Name : ACB11C7IG

Variant Model Name : ACB00C7GG, ACB00C7GN, ACB00C7GE, ACB00C7GL,

ACB01C7GG

Applicant : Hyundai MOBIS Co., Ltd.

Manufacturer : Hyundai MOBIS Co., Ltd.

Date of Receipt : 2017.04.11

Date of Test(s) : 2017.04.25 ~ 2017.05.08

Date of Issue : 2017.05.12

In the configuration tested, the EUT complied with the standards specified above.

Tested By: Date: 2017.05.12

Brant Jang

Hyunchae You

Technical Manager:

Date:

2017.05.12



Report Number: F690501/RF-RTL01269 Page: 2 of 6

INDEX

Table of Contents	Page
1. General Information	3
2. RF Exposure Evaluation	5



Report Number: F690501/RF-RTL01269 Page: 3 of 6

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

-Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.

Phone No. : +82 31 688 0901 Fax No. : +82 31 688 0921

1.2. Details of Applicant

Applicant : Hyundai MOBIS Co., Ltd.

Address : 203, Teheran-ro, Gangnam-gu, Seoul, 06141, Korea

Contact Person : Hyun, Sae-Rom Phone No. : +82 31 260 2716

1.3. Description of EUT

Kind of Product	DIGITAL CAR AUDIO SYSTEM		
Model Name	ACB11C7IG		
Variant Model Name	ACB00C7GG, ACB00C7GN, ACB00C7GE, ACB00C7GL, ACB01C7GG		
Power Supply	DC 14.4 V		
Frequency Range	2 402 Mb ~ 2 480 Mb (Bluetooth)		
Modulation Technique	GFSK, π/4DQPSK, 8DPSK		
Number of Channels	79 channels		
Antenna Type	Dielectric Chip Antenna		
Antenna Gain	-0.10 dBi		

1.4. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL01269	2017.05.12	Initial



Report Number: F690501/RF-RTL01269 Page: 4 of 6

1.5. Information of Variant model

Model	name	Bluetooth	USB/AUX	RDS	Frequency
Basic model	ACB11C7IG	0	0	Х	General
Variant model	ACB00C7GG	0	0	Х	General
	ACB00C7GN	0	0	Х	North America
	ACB00C7GE	0	0	Х	Europe
	ACB00C7GL	0	0	Х	Colombia
	ACB01C7GG	0	0	0	General



Report Number: F690501/RF-RTL01269 Page: 5 of 6

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (脈)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time		
	(A) Limits for Occupational/Controlled Exposure					
0.3 – 3.0	614	1.63	*100	6		
3.0 – 30	1842/f	4.89/f	*900/f ²	6		
30 – 300	61.4	0.163	1.0	6		
300 – 1 500	-	-	f/300	6		
1 500 – 100 000	-	-	5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3 – 1.34	614	1.63	*100	30		
1.34 – 30	824/f	2.19/f	*180/f ²	30		
30 – 300	27.5	0.073	0.2	30		
300 – 1 500	-	-	f/1500 30			
1 500 – 100 000	-	-	1.0	<u>30</u>		

2.1.1. Friis transmission formula: $Pd = (Pout*G)/(4*pi*R^2)$

Where Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.



Report Number: F690501/RF-RTL01269 Page: 6 of 6

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Bluetooth

- Maximum tune up tolerance

Operating Frequency (脈)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm²)	Limits (mW/cm²)
2 402 ~ 2 480	4	-0.10	0.000 488	1

Note:

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your body.
- The antenna gain of this transmitter is less than 6 dBi and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

- End of the Test Report -