

Tranzeo EMC Labs Inc. 19473 Fraser Way Pitt Meadows, B.C. V3Y 2V4

Bulldog Technologies Inc. 515-00054 2.4 GHz Wireless Monitor EMC Test Report

7 November 2005

Report Number: TRL071105.1

Bruce Balston, EMC Lab Manager

Andrew Marles, Technical Writer

andrew arranly

Tranzeo EMC Labs Inc. Page 2 of 2

MFE Evaluation

FCC 1.1310 states the criteria listed in the table below shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Sec. 2.1093 of this chapter. Further information on evaluating compliance with these limits can be found in the FCC's OST/OET Bulletin Number 65, "Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation."

Frequency Range (MHZ)	Electric Field Strength (V/m)	Magnetic Field Strength (A/M)	Power Density (mW/cm ²)	Average Time			
(A) Limits for Occupational/Control Exposures							
300-1500			F/300	6			
1500-100,000			5	6			
(B) Limits for General Population/Uncontrolled Exposures							
300-1500			F/1500	6			
1500-100,000			1	30			

9.1 Fries Formula

Fries transmission formula: $Pd = (P_{out}*G)/(4 \cdot \Box *r^2)$ Where

 $Pd = power density in mW/cm^2$

 P_{out} = output power to antenna in mW.

G = gain of antenna in the direction of interest relative to an isotropic radiator.

R =the distance between the observation point and the center of the radiator in cm.

Pd is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna we can calculate the distance r where the MPE limit is reached.

9.2 EUT Operating Condition

The maximum antenna gain is 9 dBi as stated by the manufacturer.

9.3 RF exposure evaluation distance calculation

EUT with 9 dBi antenna

	Freq	Output Power to Antenna	Output Power to Antenna	Antenna Gain	r
Chan	(MHz)	(dBm)	(mW)	(dBi)	(cm)
1	2409	8.51	7	9	1.0
6	2444	8.39	7	9	1.0
11	2474	8.35	7	9	1.0

As shown above, the minimum distance where the MPE limit is reached is 1 cm for the EUT.