FCC TEST REPORT

The Reputation of LG Defense Industry Continues with NEX1 Future.

Locations & Offices

NEX1 GUMI

133 Gongdan-dong, Gumi, Gyongsangbuk-do,
730-030, Korea

Tel : +82-54-469-8213
Fax : +82-54-469-8065

Network Navigation

- SEOUL
YONGIN
- GUMI

July 10, 2006

NEX 1 Future Co., Ltd.

TEST   REPROT CERTIFICATION

Applicant   : Enustech,.Inc

Adderss   : JnJ Bldg,5th Yeoksam 2-dong,785-12,Gangnam_gu,Seoul,
                 Republic of Korea

EUT Name   : imFONE CP
Model No.   : CP100L
Serial No.   : Engineering Sample
FCCID   : TT2CP100L
Testing location   : Nex1 Future Co., Ltd.
                 133, Kongdan-Dong, Gumi-City, Kyeongsangbuk-Do, 730-030, R.O.K
**Applied
specification**   : FCC Part 15
Test result   : The above mentioned test item passed.

Test Date	July 10, 2006	**Review Date**	July 10, 2006
Tested by	Hyo-Jeung, Cho	**Reviewed by**	Jeong-Hi, Jin
Title	Engineer	**Title**	EMC Manager
Signature		**Signature**	

I HEREBY CERTIFY THAT the data shown in this report were made in accordance with the procedures given in the applied specification and I assume full responsibility for accuracy and completeness of these data.

Note : This test report relates to the a. m. test item. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products.

Contents

1. General Information

1.1 Product Description
Product Name   : imFONE CP
Product ID   : CP100L
Serial No.   : Prototype
FCC ID   : TT2CP100L

1.2 Project data
Receipt of EUT   : June 20, 2006
Date of Test   : July 10, 2006
Data of report   : July 10, 2006

1.3 Applicant
Company Name   : Enustech,.Inc
Address   : JnJ Bldg,5th Yeoksam 2-dong, 785-12, Gangnam-gu,
         Seoul, Republic of Korea
Contact Person   : Mr. Seok-Jin Kim

1.4 Manufacturer
Company Name   : Enustech,.Inc
Address   : JnJ Bldg,5th Yeoksam 2-dong, 785-12, Gangnam-gu,
         Seoul, Republic of Korea
Contact Person   : Mr. Seok-Jin Kim

NEX1 Future Co., Ltd.

2. EUT Information

2.1 General EUT Information

Type	Transmitter	Receiver
FCC Classification	FHSS Sequence Spread Spectrum (FHSS)	FHSS Sequence Spread Spectrum (FHSS)
Operating frequency range	2402 – 2480 MHz	2402 – 2480 MHz
Bands of operation	2.400 – 2.4835 GHz	2.400 – 2.4835 GHz
Number of Channels	79	79
Channel Separation	1MHz	1MHz
Type of Antenna	Chip Antenna	Chip Antenna
Power Supply	DC 3.7 V Lithum Ion Battery	DC 3.7 V Lithum Ion Battery

2.2 Center Frequency of Tested Channel

Frequency	Tx (MHz)	Rx (MHz)
Lowest	2402	2402
Middle	2441	2441
Highest	2480	2480

2.3 Test Environment

Temperature	25ºC
Relative Humidity	30 ~ 60%
DC Voltage	DC 3.7V

2.4 Accessories and Ancillary Equipment

Equipment	Model No.	Serial Number	Maker
Laptop PC	PS428L-OE142	30014068J	Toshiba

3. Testing Facilities

Nex1 Future Co., Ltd.

133, Kongdan-Dong, Gumi-City, Kyeongsangbuk-Do, 730-030, R.O.K

4. EUT Description and Operational Description

* Description

ImFONE CP is a cordless internet phone which you can use as an internet phone in conjunction with your PC. With this easy to install phone by and its stylish, mobile phone-like design, you can place a crystal clear phone call through the internet network.

The small, lightweight design is perfect for VoIP(Internet Phone) service at home or in the office. imFONE CP is a wireless client device for VoIP (Internet Phone) service running on your PC. You can also select from buddy list or dial directly using the keypad to make the call. ImFONE CP lets you make internet phone calls, through internet phone programs such as SKYPE or imTEL or Naver (Korean version internet phone solution)

Long range 2.4GHz wireless technology allows to you use your imFONE CP up to a distance of 30 meters to provide you maximum freedom, control and flexibility.

Equipped with a built-in laser pointer, imFONE CP also functions as a wireless presenter. You can navigate through your presentation pages using the arrow key of the keypad.

* Features

① Free internet phone calls between VoIP Softphone buddies

② Crystal clear sound through echo cancellation

③ Making calls/ Receiving calls

④ Multi-functions

⑤ Conference and video call functionality

* Specifications

- Bluetooth® Qualified: Bluetooth Ver. 1.2 Compliant (Class1)

- Radio Frequency Range: 2.402 ~ 2.480 GHz

- Transmit Power & Receive Sensitivity: 20dBm(Typical 17dBm), -85dBm

- Service Distance: Up to 50 meters (164feet) on an open field

- Service Profile: Cordless Telephone Profile

- Security: 56 bit encryption

- Display: 32X128 pixels, Monochrome

- Power Source: Battery-Rechargeable 840mA Lithium-Ion Polymer

                    Charger-USB charger (Current:460mA/h, Voltage:4.6~5.0V DC)

                    TTA 24pin standard charger (for mobile phone)

- Charging Time: USB Charger-3 hours

  ※ TTA 24pin standard charger(for mobile phone): 2.5 hours

  ※ Charging time can depend on the PC's system capacity.

- Operating Time: Standby-Up to 38 hours

                  Talk Time-Up to 8 hours

- System Requirements: 2000/XP

5. Test Set-up

5.1 Principle of configuration

Conducted : The equipment under test (EUT) was configured with a temporary SMA Connector and EUT transmits the related packet type with PRBS 9 as payload.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes and test settings were adapted accordingly in reference to the instructions for use.

For details, please refer to the Operation mode in chapter 7.

5.2 Operational Modes

Page Scan,

Inquiry Scan

Hopping Mode

Fixed mode (2402Mhz, 2441Mhz and 2480Mhz)

5.3 Applied Specification

FCC Part 15

NEX1 Future Co., Ltd.

6. Test Report Summary

Related Clause	Test Cases	FCC Part Sections	Result (Note1)
7.1	Antenna Connector Requirements	15.203 15.204	C
7.2	AC Connected Emission	15.107&15.207	Pass
7.3	Carrier Frequency Separation	15.247	Pass
7.4	Time of Occupancy(Dwell time)	15.247	Pass
7.5	20dB Bandwidth	15.247	Pass
7.6	Number of Hopping Frequencies Requirements	15.247	C
7.7	Pseudorandom Frequency Hopping Sequence and Equal Hopping Frequency use Requirements	15.247	C
7.8	Receiver Input Bandwidth Requirements	15.247	C
7.9	Peak Output Power	15.247	Pass
7.10	Band-edge Compliance	15.247	Pass
7.11	Spurious Conducted emissions	15.247	Pass
7.12	Spurious Radiated emissions	15.109&15.247	Pass

* Note1: C: Complies, Pass: Passed, Fail : Failed and   NA : Not Applicable

7. Test Results
7.1 Antenna Connector Requirements

Requirements   **Subclause 15.203 and 15.204(c)**

According to the Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to the Part 15.204(c), only the antenna with which an intentional radiator is authorized may be used with the intentional radiator.

Test results

RESULT: **Complies**

The antenna is permanently attached on the PCB.
The EUT has a Chip Antenna soldered to the circuit board.
For more information on the antenna:

Antenna gain   : 0 dBi
Manufacturer   : AMOTECH Co., Ltd.
Model No.   : ALA931
Type   : Surface Chip Antenna

7.2 AC Connected Emission

Test Mode and conditions
The power is supplied by a USB port.

Requirements   **Subclause 15.107&15.207(a)**

For an intentional radiator that is designed to be connected to the public utility (AC) power line,
the radio frequency voltage that is conducted back onto the AC power line on any frequency or
frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table,
as measured using a 50 µH/50 ohms line impedance stabilization network (LISN).

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5	56	46
5-30	60	50

  * Decreases with the logarithm of the frequency.

Test results

NEX1 Future Co., Ltd.

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.205	0.11	-0.23	N	63.41	39.4	39.28	53.41	40.1	39.98	24.12	13.42
0.305	0.11	-0.17	N	60.11	32.0	31.94	50.11	31.8	31.74	28.16	18.36
0.915	0.14	-0.23	N	56.00	25.4	25.31	46.00	23.9	23.81	30.69	22.19
1.220	0.15	-0.25	N	56.00	27.7	27.60	46.00	27.5	27.40	28.40	18.60
2.340	0.19	-0.26	N	56.00	29.7	29.63	46.00	29.7	29.63	26.37	16.37
2.950	0.22	-0.15	L1	56.00	29.6	29.67	46.00	29.5	29.57	26.33	16.43
3.660	0.24	-0.14	L1	56.00	31.1	31.20	46.00	31.0	31.10	24.80	14.90
4.985	0.28	-0.16	N	56.00	29.1	29.22	46.00	27.6	27.72	26.78	18.28
6.815	0.33	-0.11	N	60.00	29.8	30.03	50.00	25.8	26.03	29.97	23.97
13.730	0.55	0.10	N	60.00	28.6	29.26	50.00	27.3	27.96	30.74	22.04
19.525	0.74	0.00	L1	60.00	27.5	28.24	50.00	25.3	26.04	31.76	23.96
29.415	0.86	0.12	L1	60.00	26.4	27.38	50.00	22.2	23.18	32.62	26.82

*Comment : Pol : L1 (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

< Fig 1.Conducted emission-Hot line>

< Fig 2. Conducted emission-Neut line >

7.3 Carrier Frequency Separation

Test Mode and conditions

Mode of operation	:	Tx mode (hopping on), DH1 packet with PRBS9 payload
Measurement Method	:	Conducted
Detector	:	PK
Trace	:	Max hold
RBW/VBW	:	100kHz/300kHz

Requirements　　　　　　　　　　　　　　　　**Subclause 15.247(a)(1)**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

Test results

Reference frequency (MHz)	Channel Separation (kHz)	Limit	Results
2441.000	990.0	Minimum of 25kHz or the 20dB bandwidth	Pass

NEX1 Future Co., Ltd.

Carrier Frequency Separation Plot


```
                                              *RBW 100 kHz    Delta 1 [T1 ]
                                              *VBW 300 kHz              -0.61 dB
 Ref  20 dBm              *Att  30 dB     SWT 2.5 ms        990.000000000 kHz

 20                                               Marker 1 [T1 ]
                                                             -1.48 dBm
-10                                               2.441024000 GHz
                                                  Delta 2 [T1 ]
                                                             -0.26 dB
 0                                                1.020000000 MHz

-10

-20

-30

-40

-50

-60

-70

-80

 Center 2.441 GHz            300 kHz/              Span 3 MHz
```

1 PK MAXH

A

PRN

Date: 6.JUL.2006 17:43:32

7.4 Time of Occupancy(Dwell time)

Test Mode and conditions

Mode of operation   :   Hopping on , DH5 packet with PRBS9 payload
Measurement Method :   Conducted
Detector   :   PK
Trace   :   Max hold
RBW/VBW   :   1MHz/300kHz

Requirements   **Subclause 15.247(a)(1)(iii)**

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 75 hopping frequencies. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

Test results

The system makes 1600 hops per second or has a length of 625us.
Let take DH5 packet in worst case. A DH5 packet has 5 slots for transmitting and 1 slot for receiving. It means it can have maximum 266.67 (=1600/6)hops per second.
Therefore it has 3.38 hops(=266.67/79) per second for each channel.
And it has 106.81hops appearance for 31.6 seconds (= 0.4x79channels).

Length per slot(L)	Number slots (N)	Dwell Time (=L*N)	Limit	Results
2.91ms	106.81	310.8171ms	0.4 seconds	Pass

Time of Occupancy Plot

7.5 20dB Bandwidth

Test Mode and conditions

Mode of operation   :   Tx mode (2402MHz, 2441MHz, 2480MHz),
                           DH5 packet with PRBS9 payload
Measurement Method :   Conducted
Detector   :   PK
Trace   :   Max hold
RBW/VBW   :   30kHz/100kHz

Requirements   **Subclause**   **15.247(a)(1)**

It is mentioned implicitly as the maximum 20dB bandwidth of the hopping channel is 1Mhz.

Test results

Operating frequency (MHz)	20dB Bandwidth (MHz)	Limit	Results
2402	0.676	< 1 Mhz	Pass
2441	0.696	< 1 Mhz	Pass
2480	0.696	< 1 Mhz	Pass

20dB Bandwidth Plot – 2402Mhz


```
                                        * RBW 30 kHz    Delta 1 [T1 ]
                                          VBW 100 kHz              -0.31 dB
  Ref  20 dBm          * Att  30 dB       SWT 2.5 ms      676.000000000 kHz

  20                                              Marker 1 [T1 ]
                                                            -7.75 dBm     A
  10                          2                        2.401680000 GHz
                                                  Marker 2 [T1 ]
   0                                                        13.13 dBm
                                                      2.401848000 GHz
  D1 -7.9 dBm            1                  1
 -10
                                                                         PRN
 -20
 -30
 -40
 -50
 -60
 -70
 -80
  Center 2.402 GHz          200 kHz/              Span 2 MHz
```

1 PK MAXH

Date: 6.JUL.2006 17:28:20

20dB Bandwidth Plot – 2441Mhz


```
                                              *RBW 30 kHz     Delta 1 [T1 ]
                                               VBW 100 kHz            0.04 dB
       Ref  20 dBm           *Att  30 dB       SWT 2.5 ms      696.000000000 kHz

        20                                              Marker 1 [T1 ]
                                    2                                   -7.74 dBm
       -10                         ▽                            2.440664000 GHz        A
                                                       Marker 2 [T1 ]
   1 PK                                                                 13.05 dBm
   MAXH  -0                                                     2.440844000 GHz

            D1 -7.9 dBm         1                          1
       --10                     ▽                          ▲

       --20                                                                           PRN

       --30

       --40

       --50

       --60

       --70

       --80
        Center 2.441 GHz            200 kHz/                    Span 2 MHz
```

Date: 6.JUL.2006 17:31:40

20dB Bandwidth Plot – 2480Mhz

7.6 Number of Hopping Frequencies Requirements

Test Mode and conditions

Mode of operation	:	Hopping, DH1 with PRBS9 payload
Measurement Method	:	Conducted
Detector	:	PK
Trace	:	Max hold
RBW/VBW	:	100kHz/100kHz

Requirements   **15.247(a)(1)(iii)**

Frequency hopping systems in the 2400-2483.5 Mhz band shall use at least 15 non-overlapping Channels.

Test results

Operating frequency (MHz)	Number of Hopping	Limit	Results
2402~2480	79	$\geq$ 15	Pass

Number of Hopping Frequencies Plot

```
                                          *RBW 100 kHz    Marker 1 [T1 ]
                                          *VBW 100 kHz              0.65 dBm
       Ref   20 dBm          *Att  30 dB   SWT 10 ms       2.403818000 GHz
```



```
Start 2.4 GHz              8.3 MHz/              Stop 2.483 GHz
```

Date: 6.JUL.2006 17:38:55

7.7 Pseudorandom FHS and Equal Hopping Frequency use Requirements

Requirements   **Subclause 15.247 (a)(1)**

The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter.

RESULT   **Complies**

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master. For details, refer to the figure 1. The X input determines the phase in the 32-hop segment, whereas Y1 and Y2 selects between master-to-slave and slave-to-master transmission. The inputs A to D determine the ordering within the segment, the inputs E and F determine the mapping onto thehop frequencies.

The algorism in the Bluetooth specifications shows the each of its hoping channels
Is used equally on average also.

< Figure 1 : Block diagram of hop selection kernel for 79 hop system >

7.8 Receiver Input Bandwidth Requirements

Requirements   **Subclause 15.247 (a)(1)**

The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in the synchronization with the transmitted signals.

RESULT   **Complies**

The receiver bandwidth is equal to the receiver bandwidth in the 79 hopping channel mode, which is 1 MHz. The receiver bandwidth is indirectly verified during Bluetooth RF conformance testing.

7.9 Peak Output Power

Test Mode and conditions

Mode of operation : Tx mode (2402MHz, 2441MHz, 2480MHz),
DH1 packet with PRBS 9 payload

Measurement Method : Conducted

Detector   : PK

Trace   : Max hold

RBW/VBW   : 1MHz/3MHz

Requirements   **Subclause 15.247(b)(1)**

For frequency hopping systems operating in the 2400~2483.5 Mhz band employing at least 75hopping channels, the maximum output power of the intentional radiator shall not exceeded 1 watt.

Test results

Operating Frequency (MHz)	Reading (dBm)	Cable attenuation (dB)	Actual Value (W)	Limit (W)	Results
2402	13.20	1.80	0.031622777	<1.0	Pass
2441	13.08	1.83	0.030974200	<1.0	Pass
2480	13.47	1.85	0.034040819	<1.0	Pass

NEX1 Future Co., Ltd.

Peak Output Power Plot - 2402

```
                                        *RBW 1 MHz    Marker 1 [T1 ]
                                        *VBW 3 MHz              13.20 dBm
 Ref  20 dBm          *Att  30 dB   SWT 2.5 ms    2.402140000 GHz
```



```
 Center 2.402 GHz              500 kHz/              Span 5 MHz
```

Date: 6.JUL.2006 17:46:39

Peak Output Power Plot – 2441


```
                                        * RBW  1 MHz      Marker 1 [T1 ]
                                        * VBW  3 MHz              13.08 dBm
Ref  20 dBm           * Att  30 dB        SWT 2.5 ms      2.440860000 GHz
```

Center 2.441 GHz   500 kHz/   Span 5 MHz

Date: 6.JUL.2006 17:47:12

Peak Output Power Plot – 2480

```
                                          *RBW 1 MHz      Marker 1 [T1 ]
                                          *VBW 3 MHz                13.47 dBm
        Ref   20 dBm          *Att  30 dB    SWT 2.5 ms      2.479860000 GHz
```



```
        Center 2.48 GHz              500 kHz/              Span 5 MHz
```

Date: 6.JUL.2006   17:47:45

7.10 Band-edge Compliance

Test Mode and conditions

Mode of operation	:	Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet
Measurement Method	:	Conducted
Detector	:	PK
Trace	:	Max hold
RBW/VBW	:	300kHz/1.0MHz

Requirements   **Subclause 15.247(c)**

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100k Hz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Test results

There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency.

Tx Frequency (MHz)	RF power outside 100kHz BW (MHz)	Limit	Results
2402	No peak above 20dB	20dB below	Pass
2441	No peak above 20dB	20dB below	Pass
2480	No peak above 20dB	20dB below	Pass

Band-edge Compliance Plot - 2402


```
                                    *RBW 300 kHz    Delta 1 [T1 ]
                                    *VBW 1 MHz              -52.82 dB
Ref  20 dBm        *Att  30 dB      SWT 2.5 ms      -4.080000000 MHz
```

Marker 1 [T1]
13.14 dBm
2.401920000 GHz

D1 -7.7 dBm

1 PK MAXH

A

PRN

F1

Center 2.394 GHz   2 MHz/   Span 20 MHz

Date: 6.JUL.2006 17:51:50

Band-edge Compliance Plot – 2441

```
                                                *RBW 300 kHz    Delta 1 [T1 ]
                                                *VBW 1 MHz               -66.73 dB
        Ref   20 dBm          *Att  30 dB        SWT 5 ms          51.600000000 MHz
```



```
        Center 2.441 GHz              15 MHz/              Span 150 MHz
```

Date: 6.JUL.2006 17:53:41

Band-edge Compliance Plot – 2480


```
                                        *RBW 300 kHz   Delta 1 [T1 ]
                                        *VBW 1 MHz                -54.01 dB
        Ref  20 dBm          *Att 30 dB  SWT 2.5 ms       4.400000000 MHz
```

```
  20        1                              Marker 1 [T1 ]
 -10                                              13.40 dBm
                                            2.479840000 GHz   A
  0
 1 PK
MAXH
 -10      D1 -7.1 dBm

 -20

 -30                                                          PRN

 -40              1

 -50

 -60

 -70
         F2
 -80   ←F
```

```
Center 2.488 GHz              2 MHz/              Span 20 MHz
```

Date: 6.JUL.2006 17:55:24

7.11 Spurious Conducted emissions

Test Mode and conditions

Mode of operation   :   Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet
Measurement Method :   Conducted
Detector   :   PK
Trace   :   Max hold
RBW/VBW   :   100kHz/300kHz

Requirements   Subclause 15.109&15.247(c)

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100k Hz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Test results

Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
Operating frequency : 2402MHz					
8205.4	-48.2	6.0	-42.2	-6.800	35.4
13680	-42.02	6.7	-35.32	-6.800	28.52
20000	-36.08	6.7	-29.38	-6.800	22.58

NEX1 Future Co., Ltd.

| Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
Operating frequency : 2441MHz					
8165.52	-48.62	6.0	-42.62	-6.920	35.7
15100	-42.17	6.7	-35.47	-6.920	28.55
20060	-35.79	6.7	-29.09	-6.920	22.17

| Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
Operating frequency : 2480MHz					
8783.66	-48.49	6.0	-42.49	-6.530	35.96
15100	-42.16	6.7	-35.46	-6.530	28.93
20000	-37.11	6.7	-30.41	-6.530	23.88

Spurious Conducted emissions plot- 2402 (30MHz~10GHz)


```
                                        * RBW 100 kHz    Delta 1 [T1 ]
                                        * VBW 100 kHz            -51.57 dB
        Ref  20 dBm          * Att 30 dB  * SWT 120 s     5.802540000 GHz

         20                                      Marker 1 [T1 ]                A
        -10                                              3.37 dBm
                                                 2.402860000 GHz              SGL
   1 PK                                          Marker 2 [T1 ]
   MAXH                                                 -48.20 dBm
         0                                       8.205400000 GHz

        -10

                                                                             PRN
        -20

        -30

        -40
                                                     2
        -50

        -60

        -70

        -80
        Start 30 MHz              997 MHz/              Stop 10 GHz
```

Date: 6.JUL.2006 14:48:55

Spurious Conducted emissions plot- 2402 (10GHz~20GHz)


```
                                    *RBW 100 kHz    Marker 1 [T1 ]
                                    *VBW 100 kHz            -42.02 dBm
Ref  20 dBm        *Att  30 dB      *SWT 120 s        13.680000000 GHz
```

Date: 6.JUL.2006 14:56:43

Spurious Conducted emissions plot- 2402 (20GHz~25GHz)

Date: 6.JUL.2006 14:59:21

Spurious Conducted emissions plot- 2441 (30MHz~10GHz)


```
                                    *RBW 100 kHz    Delta 1 [T1 ]
                                    *VBW 100 kHz              -50.66 dB
Ref  20 dBm              *Att  30 dB  *SWT 120 s       5.722780000 GHz
```

Marker 1 [T1]
2.04 dBm
2.442740000 GHz

A

SGL

Marker 2 [T1]
-48.62 dBm
8.165520000 GHz

1 PK
MAXH

PRN

Start 30 MHz   997 MHz/   Stop 10 GHz

Date: 6.JUL.2006   15:03:52

Spurious Conducted emissions plot- 2441 (10GHz~20GHz)

```
                                    * RBW  100 kHz    Marker 1 [T1 ]
                                    * VBW  100 kHz            -42.17 dBm
Ref  20 dBm          * Att  30 dB   * SWT 120 s       15.100000000 GHz
```



```
Start 10 GHz                    1 GHz/              Stop 20 GHz
```

Date: 6.JUL.2006 15:07:07

Spurious Conducted emissions plot- 2441 (20GHz~25GHz)

```
                                    * RBW 100 kHz    Marker 1 [T1 ]
                                    * VBW 100 kHz              -35.79 dBm
      Ref   20 dBm        * Att   30 dB   * SWT 120 s         20.060000000 GHz
```



```
Start 20 GHz                      500 MHz/                      Stop 25 GHz
```

Date: 6.JUL.2006   15:09:53

NEX1 Future Co., Ltd.

Spurious Conducted emissions plot- 2480 (30MHz~10GHz)

```
                                          *RBW 100 kHz    Delta 1 [T1 ]
                                          *VBW 100 kHz              -49.71 dB
        Ref  20 dBm          *Att  30 dB  *SWT 120 s         6.301040000 GHz

        20                                       Marker 1 [T1 ]
                                                          1.22 dBm         A
       -10                                       2.482620000 GHz          SGL
 1 PK                                            Marker 2 [T1 ]
 MAXH                                                    -48.49 dBm
        0                                        8.783660000 GHz

       -10

       -20                                                                PRN

       -30

       -40

       -50

       -60

       -70

       -80
        Start 30 MHz              997 MHz/              Stop 10 GHz
```

Date: 6.JUL.2006   15:13:15

Spurious Conducted emissions plot- 2480 (10GHz~20GHz)

```
                                          *RBW 100 kHz   Marker 1 [T1 ]
                                          *VBW 100 kHz            -42.16 dBm
   Ref  20 dBm          *Att  30 dB       *SWT 120 s      15.100000000 GHz
```



```
Start 10 GHz                   1 GHz/                      Stop 20 GHz
```

Date: 6.JUL.2006 15:15:55

Spurious Conducted emissions plot- 2480 (20GHz~25GHz)


```
                                        *RBW  100 kHz    Marker 1 [T1 ]
                                        *VBW  100 kHz              -37.11 dBm
   Ref   20 dBm          *Att  30 dB    *SWT  120 s      20.000000000 GHz
```

Date: 6.JUL.2006 15:18:39

NEX1 Future Co., Ltd.

7.12 Spurious Radiated emissions

Test Mode and conditions

Mode of operation	:	Tx mode (2402MHz, 2441MHz, 2480MHz), DH1 packet
Detector	:	PK
Trace	:	Max hold
Measurement Method	:	Radiated- Enclosure
Measurement Distance	:	3m
Measurement BW	:	1 MHz for $f \geq 1$ GHz, 100kHz for $f < 1$ GHz

Requirements   **Subclause 15.247(c)**

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to Section 15.209(a) , except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Field strength (dBμV/m)	Measurement distance (meters)
30-88	100**	20*log(100) = 40.0	3
88-216	150**	20*log(150) = 43.5	3
216-960	200	20*log(200) = 46.0	3
960-2500	500	20*log(500) = 54.0	3

** Except as provided in paragraph(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72Mhz, 76-88Mhz, 174-216Mhz or 470-806Mhz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

According to section 15.35(b), on any frequency or frequencies above 1000 MHz the radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission

measurements are specified in this part, including emission measurements below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated

Test results

Frequ-ency (MHz)	Polariz-ation (H/V)	Corr. Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)		Table Angle (Deg.)	Ant. Height (m)
			A	P	A	P	A	P		
Operating frequency : 2402Mhz										
4804	V	16.3	45.5	57.5	54	74	8.5	16.5	320	1.4
4804	H	16.3	45.9	57.9	54	74	8.1	16.1	210	1.4

Frequ-ency (MHz)	Polariz-ation (H/V)	Corr. Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)		Table Angle (Deg.)	Ant. Height (m)
			A	P	A	P	A	P		
Operating frequency : 2441Mhz										
4882	V	16.4	45.8	58.2	54	74	8.2	15.8	320	1.4
4882	H	16.4	46.5	59.7	54	74	7.5	14.3	210	1.4

Frequ-ency (MHz)	Polariz-ation (H/V)	Corr. Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)		Table Angle (Deg.)	Ant. Height (m)
			A	P	A	P	A	P		
Operating frequency : 2480Mhz										
4960	V	16.4	45.8	58.1	54	74	8.2	15.9	320	1.4
4960	H	16.4	46.2	58.7	54	74	7.8	15.3	210	1.4

Note :

1. Remark "*" means that the emission frequency is produced by local oscillator.
2. Remark"- - " means that the emission level is too low to be measured.
3. The measurement uncertainty of the radiated emission test is ±3dB
4. "A" and "P" mean average and peak measurement respectively.
5. There are no spurious emissions found between the lowest internal oscillating frequency and 30 MHz.

8. List of Test and Measurement Instruments

	Kind of Equipment	Type	Manufacturer	S/N
☒	EMI Test Receiver	ESI26	R/S	8340.0010.02
☒	Spectrum Analyzer	FSP30	R/S	1093.4495.30
☐	Tracking Generator	ESMI-B1	R/S	1033.3240.52
☐	Spectrum Analyzer	8566B	HP	3638A0857E
☐	Spectrum Analyzer	E4407B	HP	MY41310181
☐	Wave Dipole Antenna	HZ-12	R/S	842006/0012
☐	Wave Dipole Antenna	HZ-12	R/S	846556/0004
☐	Biconical Antenna	3104C	EMCO	9408-4667
☐	Biconical Antenna	3109	EMCO	9405-2812
☒	Log-Periodic Antenna	3146A	EMCO	1064
☐	Biconilog Antenna	HLP2603	EMC	080100
☐	V-Network	ESH3-Z5	R/S	847265/030
☐	V-Network	ESH3-Z6	R/S	847250/016
☐	T-Network	E-Z10	R/S	84480/011
☒	LISN	3825/2	EMCO	9502-2334
☒	Turn Table	2081	EMCO	
☒	Antenna Tower	1072-5	EMCO	9202-1651
☒	Positioning Controller	1090	EMCO	
☐	Printer	C4569A	HP	SG78K1H1FS
☐	Absorbing Clamp	MDS 21	R/S	847905/005
☐	Signal Generator	2023	MARCONI	112246067
☐	Swept Signal Generator	83620B	HP	3722A00549
☐	10dB Attenuator	23-10-34	Weinschel co	BD4316
☐	10dB Attenuator	33-10-34	Weinschel co	BB9784
☒	Loop Antenna	6507	EMCO	9408-1327
☒	Antenna	3142	EMCO	9710-1220
☒	Antenna	3115	EMCO	9202-3820
☒	Antenna	3160-08	EMCO	1168
☒	Antenna	3160-09	EMCO	1304
☒	Amplifier	HP8447F	HP	3113A06911
☒	Amplifier	HP83006	HP	3104A00611

☒	Amplifier	HP8449B	HP	3008A00859
☐	EMI test receiver	ESCS30	R&S	839809/003
☐	Artificial mains network	ESH2-Z5	R&S	829991/009
☐	Artificial hand	FCC-AH-1	Fischer custom communications Inc.	2008

9. Notes

N/A