



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822
Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>

ENUSTECH

Dates of Tests: : Apr 12~20, 2011

Test Report S/N: LR500111104F

Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.
IC
APPLICANT

TT2KLAT8-RC
6329A-KLAT8RC
ENUSTECH.,INC.

TEST REPORT

Equipment Class : Part 15 Security/Remote Control Transmitter
Manufacturing Description : Wireless Remote Controller
Manufacturer : ENUSTECH.,INC.
Model name : KLaT8-RC
Test Device Serial No.: Identification
Rule Part(s) : FCC Part 15 Subpart C ; ANSI C-63.4-2003
RSS-210 and ISSUE No.: 8 Date: 2010
Frequency Range : 433.055~434.680 MHz
Data of issue : Apr 22, 2011

This test report is issued under the authority of:

The test was supervised by:

Hyun-Chae You, Manager

Il-Shin kim, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.



NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

1. GENERAL INFORMATION'S	-----	3
2. INFORMATION'S ABOUT TEST ITEM	-----	4
3. TEST REPORT		
3.1 SUMMARY OF TESTS	-----	5
3.2 TRANSMITTER REQUIREMENTS		
3.2.1 CONDUCTED EMISSION	-----	6
3.2.2 RADIATED EMISSION-Transmitter	-----	7
3.2.3 RADIATED EMISSION-Receiver	-----	10
 APPENDIX		
APPENDIX 1	BANDWIDTH OF EMISSION -----	12
APPENDIX 2	THE EMITTING TIME OF FUNDAMENTAL FREQUENCY -----	14
APPENDIX 3	TEST EQUIPMENT USED FOR TESTS -----	16

1. General information's

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2011-09-30	ECT accredited Lab.
RRL	KOREA	KR0049	2011-09-01	EMC accredited Lab.
FCC	U.S.A	610755	2011-04-22	FCC filing
FCC	U.S.A	649054	2011-05-26	FCC CAB
VCCI	JAPAN	R2133(10m), C2307	2011-06-21	VCCI registration
VCCI	JAPAN	T-2009	2013-12-23	VCCI registration
IC	CANADA	IC5799	2012-05-14	IC filing

2. Information's about test item

2-1 Client & Manufacturer

Company name : ENUSTECH.,INC.
 Address : Dooi Bldg., 5F, 1196-2 Gaepo-4dong, Gangnam-gu, Seoul 135-240,
 Korea
 Telephone / Facsimile : +82-70-7547-7599 / +82-2-3452-3603

2-2 Equipment Under Test (EUT)

Trade name : Wireless Remote Controller
 Model name : KlaT8-RC
 Serial number : Identification
 Date of receipt : Apr 8, 2011
 EUT condition : Pre-production, not damaged
 Antenna type : Pattern Antenna
 Frequency Range : 433.055~434.680 MHz
 RF Output Power : Below 10 mW
 Type of Modulation : FSK
 Power Source : DC 3.0V By Lithium Battery Power
 Firmware version : V1.0

2-3 Tested frequency

Frequency	
Low	433.055MHz
Mid	433.580MHz
High	434.680MHz

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
-	-	-	-

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Test Condition	Status (note 1)
FCC Part 15.205/209	Restricted Bands of Operation	Radiated	C
FCC Part 15.231 a)	Operation mode		C ²⁾
FCC Part 15.231 b)	Radiated emissions		C
FCC Part 15.231 c)	20dB Bandwidth		C
15.207 /15.107	AC Conducted Emissions	Line Conducted	NA ³⁾

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2 The emitting time of fundamental frequency is less than 5seconds.

Refer to the APPENDIX 2.

Note 3: This device is only operated by battery.

Note 4: The data in this test report are traceable to the national or international standards.

A sample calculation:

COR. F (correction factor)= Antenna factor + Cable loss- Amp.gain- Distance correction

Emission Level= meter reading + COR.F

Note 1: The sample was tested according to the following specification:
RSS-210 and ISSUE No.: 8 Date: 2010

3.2 Transmitter requirements

3.2.1 Conducted Emission

Procedure:

The conducted emissions are measured in the shielded room with a spectrum analyzer in peak hold. While the measurement, EUT had its hopping function disabled at the middle channels in line with Section 15.31(m). Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9 kHz. The emissions are maximized further by cable manipulation and Exerciser operation. The highest emissions relative to the limit are listed.

Measurement Data: **Not applicable**

- The EUT operates by the Battery
- According to the rule of section 15.207(c), The EUT exempt to the power line conducted test.

LIMIT:

Frequency Range	Near-peak	Average
0.15 ~ 0.5 MHz	66 ~ 56 dBuV	56 ~ 46 dBuV
0.5 ~ 5 MHz	56 dBuV	46 dBuV
5 ~ 30 MHz	60 dBuV	50 dBuV

Note: The limits will decrease with the frequency logarithmically within 0.15MHz to 0.5MHz

3.2.2 Radiated Emission-Transmitters

Definition:

The field strength of emissions from intentional radiators was measured.

Test method	: FCC Part 15.205 / 209
Transmit Frequency	: 433.055~434.680MHz
Frequency Range	: 30 MHz ~ 10 th harmonic.
Bandwidth	: 120 kHz (F < 1GHz) 1 MHz (F > 1GHz)
Distance of antenna	: 3 meters
Test mode	: Tx mode
Result	: Complies

Measurement Data:

- No other emissions were detected at a level greater than 20dB below limit.
- Refer to the next page.

Field Strength Limit of fundamental and Harmonics: Part 15.231(b)

Frequency (MHz)	Limit @ 3m
433.055~434.680	$41.6667(433.055) - 7083.3333 = 10961 \text{ uV/m} = 80.8 \text{ dBuV/m}$ (Average) 100.8dBuV/m (Peak) $41.6667(433.580) - 7083.3333 = 10983 \text{ uV/m} = 80.8 \text{ dBuV/m}$ (Average) 100.8dBuV/m (Peak) $41.6667(434.680) - 7083.3333 = 11028 \text{ uV/m} = 80.9 \text{ dBuV/m}$ (Average) 100.9dBuV/m (Peak)
Harmonics	60.8 dBuV/m (The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.)

Part 15.209 LIMIT:

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100**
88 ~ 216	150**
216 ~ 960	200**
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Measurement Data:

Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor	Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
433.055 ³⁾	71.15	73.07	H	-9.08	80.8	100.8	62.07	63.99	18.73	36.81
866.350	33.04	35.10	H	-2.83	60.8	80.8	30.21	32.27	30.59	48.53
Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor	Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
433.580 ³⁾	70.17	72.59	H	-9.08	80.8	100.8	61.09	63.51	19.71	37.29
Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor	Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
434.680 ³⁾	70.01	72.19	H	-9.08	80.8	100.8	60.93	63.11	19.87	37.69
869.500	34.33	36.51	H	-2.83	60.8	80.8	31.50	33.68	29.30	47.12

*restricted band of operation §15.205

* Result level = Reading value + Antenna factor – Amp Gain + Cable Loss

* This EUT was tested in 3 orthogonal positions and the worst-case data was presented.

Note 1: No other emission were detected at a level greater than 20 dB below limit.

Note 2: All readings above 1GHz were taken using a peak detector function at a distance of 3 meters.

Note 3: Fundamental Frequency

Radiated Emissions

243 Jubug-ni, yangji-Myeon, Youngin-si,
Gyeonggi-do 449-822 Korea
Tel :+82-31-3236008,9
Fax:+82-31-3236010

EUT/Model No.: K1aT8-RC

TEST MODE: Wireless mode


Temp Humi : 18 / 22

Tested by: PARK.H.W

Data: 33

Level (dBuV/m)

Date: 2011-04-19



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	126.75	36.90	-10.45	26.45	43.50	17.05	198	75 HORIZONTAL
2	161.72	36.80	-9.12	27.68	43.50	15.82	247	159 HORIZONTAL
3	194.63	38.00	-11.51	26.49	43.50	17.01	214	73 HORIZONTAL
4	200.58	37.60	-11.82	25.78	43.50	17.72	149	57 HORIZONTAL
5	202.61	47.70	-11.71	35.99	43.50	7.51	183	47 HORIZONTAL
6	224.13	40.60	-10.67	29.93	46.00	16.07	124	148 HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

3.2.3 Radiated Emission-Receivers

Definition:

The field strength of emissions from intentional radiators was measured.

Test method	: FCC Part 15.209
Transmit Frequency	: 433.055~434.680MHz
Frequency Range	: 30 MHz ~ 10 th harmonic.
Bandwidth	: 120 kHz (F < 1GHz) 1 MHz (F > 1GHz)
Distance of antenna	: 3 meters
Test mode	: Rx mode
Result	: Complies

Measurement Data:

- No other emissions were detected at a level greater than 20dB below limit.
- Refer to the next page.

Field Strength Limit

Part 15.209 LIMIT:

Frequency (MHz)	Limit (uV/m) @ 3m
30 ~ 88	100**
88 ~ 216	150**
216 ~ 960	200**
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Measurement Data:

Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor	Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
339.6	42.65	44.60	H	-10.73	46	66	31.92	33.87	14.08	32.13
Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor	Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
339.6	41.38	43.54	H	-10.73	46	66	30.65	32.81	15.35	33.19
Frequency [MHz]	Reading [dBuV/m] AV / Peak		Pol.	Correction Factor	Limits [dBuV/m] AV / Peak		Result [dBuV/m] AV / Peak		Margin [dB] AV / Peak	
339.6	42.09	44.17	H	-10.73	46	66	31.36	33.44	14.64	32.56


* Result level = Reading value + Antenna factor – Amp Gain + Cable Loss

Note 1: No other emission were detected at a level greater than 20 dB below limit.

Note 2: All readings above 1GHz were taken using a peak detector function at a distance of 3 meters.

APPENDIX 1



BANDWIDTH OF EMISSION



APPENDIX 2

THE EMITTING TIME OF FUNDAMENTAL FREQUENCY

The Emitting time of Fundamental Frequency



Note . The above plots is the worst case plots generated with the full data rate.

APPENDIX 3

TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	Spectrum Analyzer	FSV-30	100757	R&S	1 year	2011-01-24
2	Spectrum Analyzer	8563E	3425A02505	HP	2 year	2010-03-29
3	Spectrum Analyzer	8594E	3710A04074	HP	2 year	2009-10-12
4	Signal Generator	8648C	3623A02597	HP	1 year	2011-03-30
5	Signal Generator	83711B	US34490456	HP	1 year	2011-03-30
6	Attenuator (3dB)	8491A	37822	HP	2 year	2010-10-08
7	Attenuator (10dB)	8491A	63196	HP	2 year	2010-10-08
8	EMI Test Receiver	ESCI7	100722	R&S	1 year	2010-10-08
9	Horn Antenna(18 ~ 40GHz)	SAS-574	154	Schwarzbeck	2 year	2010-11-25
10	Horn Antenna(18 ~ 40GHz)	SAS-574	155	Schwarzbeck	2 year	2010-11-25
11	RF Amplifier	8447D	2439A09058	HP	2 year	2010-10-08
12	RF Amplifier	8449B	3008A02126	HP	2 year	2010-03-29
13	Test Receiver	ESHS10	828404/009	R&S	1 year	2011-03-30
14	TRILOG Antenna	VULB 9160	9160-3172	SCHWARZBECK	2 year	2010-10-07
15	Horn Antenna	BBHA 9120D	9120D122	SCHWARZBECK	2 year	2010-12-24
16	Dipole Antenna	VHA9103	2116	SCHWARZBECK	2 year	2010-11-25
17	Dipole Antenna	VHA9103	2117	SCHWARZBECK	2 year	2010-11-25
18	Dipole Antenna	VHA9105	2261	SCHWARZBECK	2 year	2010-11-25
19	Dipole Antenna	VHA9105	2262	SCHWARZBECK	2 year	2010-11-25
20	Hygro-Thermograph	THB-36	0041557-01	ISUZU	2 year	2010-04-12
21	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
22	Power Divider	11636A	6243	HP	2 year	2010-10-08
23	DC Power Supply	6622A	3448A03079	HP	-	-
24	Frequency Counter	5342A	2826A12411	HP	1 year	2011-03-30
25	Power Meter	EPM-441A	GB32481702	HP	1 year	2011-03-30
26	Power Sensor	8481A	US41030291	HP	1 year	2010-10-08
27	Audio Analyzer	8903B	3729A18901	HP	1 year	2010-10-08
28	Modulation Analyzer	8901B	3749A05878	HP	1 year	2010-10-08
29	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2010-10-08
30	Stop Watch	HS-3	601Q09R	CASIO	2 year	2010-03-31
31	LISN	ENV216	100408	R&S	1 year	2010-10-08
32	UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	2 year	2010-05-13
33	Attenuator (30dB)	8498A	3318A10929	HP	2 year	2011-01-05