4   FCC §15.247 (i), §2.1091 & IC RSS-102 – RF Exposure

4.1   Applicable Standard

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* ($180/f^2$)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

   f = frequency in MHz
   * = Plane-wave equivalent power density

Before equipment certification is granted, the procedure of IC RSS-102 must be followed concerning the exposure of humans to RF fields.

According to IC RSS-102 Issue 2 section 4.1, RF limits used for general public will be applied to the EUT.

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m^2)	Time Averaging (min)
0.003 - 1	280	2.19	-	6
1 - 10	280 / f	2.19 / f	-	6
10 - 30	28	2.19 / f	-	6
30 – 300	28	0.073	2*	6
300 – 1 500	1.585 $f^{0.5}$	0.0042 $f^{0.5}$	f / 150	6
1 500 – 15 000	61.4	0.163	10	6
15 000 – 150 000	61.4	0.163	10	616000 / $f^{1.2}$
150 000- 300 000	0.158 $f^{0.5}$	4.21 x 10 -4 $f^{0.5}$	6.67 x 10^{-5} f	616000 / $f^{1.2}$

   Note: *f* is frequency in MHz
         * = Power density limit is applicable at frequencies greater than 100 MHz

4.2   MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density
P = power input to antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna

4.3   MPE Results

PTP at Highest Power Setting

Maximum peak output power at antenna input terminal (dBm):	27.93
Maximum peak output power at antenna input terminal (mW):	620.87
Prediction distance (cm):	180
Prediction frequency (MHz):	5745
Maximum Effective Antenna Gain, typical (dBi):	28
Maximum Antenna Gain (numeric):	630.96
Power density of prediction frequency at 180.0 cm (mW/cm^2):	0.9621
Power density of prediction frequency at 180.0 cm (W/m^2):	9.621
MPE limit for uncontrolled exposure at prediction frequency (mW/cm^2):	1.0
MPE limit for uncontrolled exposure at prediction frequency (W/m^2):	10

Note: the maximum effective gain is 28 dBi (antenna gain + cable loss)

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 180 cm is 0.9621 mW/cm^2 (9.621W/m^2). Limit is 1.0 mW/cm^2 (10 W/m^2).