

Prüfbericht-Nr.: Test Report No.:		16060205 001		Auftrags-Nr.: Order No.:		174023970		Seite 1 von 29 Page 1 of 29	
Kunden-Referenz-Nr.: Client Reference No.:		450812		Auftragsdatum: Order date.:		02 Jul. 2014			
Auftraggeber: Client:		Bang & Olufsen a/s Peter Bangs Vej 15, 7600 Struer, Denmark							
Prüfgegenstand: Test item:		Bluetooth Speaker		FCC ID: FCC ID:		TTUBEOPLAYA2			
Bezeichnung / Typ-Nr.: Identification / Type No.:		BeoPlay A2		IC ID: IC ID:		3775B-BEOPLAYA2			
Auftrags-Inhalt: Order content:		TUV Rheinland - EMC service							
Prüfgrundlage: Test specification:		ANSI C63.4: 2009 FCC Part 15: 2013-10 Subpart C section 15.207, 15.209 and 15.247 RSS-210: 2010-12							
Wareneingangsdatum: Date of receipt:		31.Mar.2014							
Prüfmuster-Nr.: Test sample No.:		N/A							
Prüfzeitraum: Testing period:		Refer to test report							
Ort der Prüfung: Place of testing:		Refer to section 2.1							
Prüflaboratorium: Testing laboratory:		TÜV Rheinland (Guangdong) Ltd.							
Prüfergebnis*: Test result*:		Pass							
geprüft von / tested by:				kontrolliert von / reviewed by:					
									
22 Jul. 2014 Amy Wang/ Senior Project Engineer				22 Jul. 2014 Max Y. C. Yao/ Department Manager					
Datum Date	Name/Stellung Name/Position	Unterschrift Signature		Datum Date	Name/Stellung Name/Position	Unterschrift Signature			
Sonstiges / Other:									
BT technology.									
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:				Prüfmuster vollständig und unbeschädigt Test item complete and undamaged					
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s) N/A = not applicable N/T = not tested									
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.									

V04

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 2 von 29
Page 2 of 29

Test Summary

Test items	Result
Conducted Emission	Pass
Radiated Spurious Emission	Pass
Antenna requirement	Pass
Maximum Peak Output power	Pass
20dB Bandwidth	Pass
Hopping Channel Carrier Frequency Separation	Pass
Number of Hopping Frequency Used	Pass
Time of Occupancy (Dwell Time)	Pass
Band-edge Emission	Pass
Power spectral density	N/A
Out-Of-Band Emission measurement	Pass
99% Bandwidth	Pass
Electromagnetic Fields	Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS.....	5
2	TEST SITES.....	5
2.1	TEST FACILITIES.....	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	6
2.4	CALIBRATION.....	6
2.5	MEASUREMENT UNCERTAINTY	6
2.6	LOCATION OF ORIGINAL DATA	6
2.7	STATUS OF FACILITY USED FOR TESTING.....	6
3	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE.....	7
3.2	RATINGS AND SYSTEM DETAILS	7
3.3	INDEPENDENT OPERATION MODES	7
3.4	SUBMITTED DOCUMENTS.....	8
4	TEST SET-UP AND OPERATION MODE.....	9
4.1	PRINCIPLE OF CONFIGURATION SELECTION	9
4.2	TEST OPERATION AND TEST SOFTWARE	9
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	9
4.5	TEST SET-UP	10
5	TEST RESULTS EMISSION	13
5.1	CONDUCTED EMISSION	13
5.2	RADIATED SPURIOUS EMISSION.....	14
5.3	ANTENNA REQUIREMENT	15
5.4	MAXIMUM PEAK OUTPUT POWER	16
5.5	20dB BANDWIDTH.....	17
5.6	HOPPING CHANNEL CARRIER FREQUENCY SEPARATION.....	18
5.7	NUMBER OF HOPPING FREQUENCY USED	19
5.8	TIME OF OCCUPANCY (DWELL TIME)	20
5.9	BAND-EDGE EMISSION	21
5.10	POWER SPECTRAL DENSITY	22

5.11	OUT-OF-BAND EMISSION (CONDUCTED SPURIOUS EMISSION)	23
5.12	99% BANDWIDTH.....	25
6	LIST OF TABLES	29
7	LIST OF PHOTOGRAPHS	29

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix 1: Test result

2 Test Sites

2.1 Test Facilities

EST Technology Co., Ltd.
Santun(guantai Road), Houjie Town, DongGuan City, GuangDong, China.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	July,30,13	1 year
Artificial Mains Networ	Rohde & Schwarz	ENV216	101260	July,30,13	1 year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	July,25,13	1 year
EMI Test Receiver	Rohde & Schwarz	ESVS10	100004	July,23,13	1 year
Spectrum Analyzer	Agilent	E4411B	MY50140697	July,23,13	1 year
Bilog Antenna	Teseq	CBL 6111D	27090	July,29,13	1 year
Signal Amplifier	Agilent	310N	187037	July,23,13	1 year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA9120D1002	July,29,13	1 year
Signal Amplifier	SCHWARZBECK	BBV9718	9718-212	July,23,13	1 year
Spectrum Analyzer	Agilent	E4408B	MY44211139	July,23,13	1 year
RF Cable	Hubersuhner	RG 214/U	513423	July,21,13	1 year

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications.

2.5 Measurement Uncertainty

Uncertainty for conducted emissions measurements is 2.54dB.

Uncertainty for radiated emissions measurements is 3.62dB (30M-1GHz) and 4.11dB (> 1GHz)

The reported expanded uncertainty is based on a standard uncertainty multiply by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

2.6 Location of original data

The original copies of test data taken during actual testing were attached at Appendix 1 of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Guangdong) file for certification follow-up purposes.

2.7 Status of facility used for testing

EST Technology Co., Ltd.

Santun(guantai Road), Houjie Town, DongGuan City, GuangDong, China. is listed on the US Federal Communications Commission list of facilities approved to perform measurements, the register no. 989591.

3 General Product Information

The tested sample is a "Bluetooth speaker" with model numbers "BeoPlay A2" for new approval, which is intended to enable Bluetooth connectivity with Notebook or smart phone, and play the music from Bluetooth device.

For details refer to the Technical Documentation or User manual.

3.1 Product Function and Intended Use

For details refer to the Technical Documentation or User manual.

3.2 Ratings and System Details

Type Designation:	BeoPlay A2
Frequency range:	2402MHz~2480MHz
Number of employed channels:	79 channels
Channel Spacing:	1MHz
Modulation Type:	FHSS (GFSK, $\pi/4$ -DQPSK, 8-DPSK)
Type of antenna:	Internal antenna
Power supply:	Adapter Input: 100~240Vac, 50/60Hz; Adapter Output: 15Vdc; 7.2Vdc from Internal battery
Equipment type:	Portable Equipment
Protection Class:	Class III for Internal battery Class II for AC adapter

For details refer to the Technical Documentation or User manual.

3.3 Independent Operation Modes

A. Transmitting mode.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 8 von 29
Page 8 of 29

3.4 Submitted Documents

1. Block Diagram
2. Schematics
3. Operation Description
4. Components List
5. FCC label and location
6. User Manual
7. Internal Photos
8. External Photos
9. Application form

4 Test Set-up and Operation Mode

4.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Refer to test set-up in chapter 5.

4.3 Special Accessories and Auxiliary Equipment

None.

4.4 Countermeasures to achieve EMC Compliance

The test sample, which has been tested, contained the noise suppression parts as described in the technical document. No additional measures were employed to achieve compliance.

4.5 Test set-up

Diagram 1 of Configuration for Testing Radiated Emission 30MHz -1 GHz




Diagram 2 of Configuration for Testing Radiated Emission above 1 GHz




Diagram 3 of Configuration for Testing Conducted Emission






Diagram 4 of Configuration for Testing Radiated Emission below 30MHz



Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 12 von 29
Page 12 of 29

Diagram 5 of Configuration for testing other test items



5 Test Results EMISSION

5.1 Conducted Emission

RESULT:	PASS
----------------	-------------

Date of testing:	May 28, 2014
Test specification:	FCC Part 15 Per Section 15.207(a); RSS-Gen 7.2.4
Limits:	FCC Part 15 Per Section 15.207(a); RSS-Gen 7.2.4
Test procedure:	ANSI C63.4
Deviations from Standard Test Procedures:	None
Kind of test site:	Shielded room
Operation mode:	Transmitting at fix channel with max power
Power supply:	Adapter Input: 120Vac, 60Hz
Temperature:	25.3 °C
Humidity:	58 %

Test procedure:

For tabletop device, the EUT and its peripherals were placed on a wooden table, 80cm above the horizontal reference plane and 40cm away from vertical reference plane in a shielded room. For floor-standing device, the EUT shall be placed either directly on the reference ground plane or on insulating material as described in ANSI C63.4 Clause 6.3.2.1.

The EUT was connected to input power source through a line impedance stabilization network (LISN). The excess length of the power cord between the EUT and the LISN shall be folded back and forth at the center of the lead to form a bundle not exceeding 40cm in length.

The EUT was tested in a typical model of operation in accordance with ANSI C63.4:2009, Pre-test was performed in peak and average detection mode. Final measurement was performed using quasi-peak and average detection on the live and neutral lines with the worst case.

The test software Rohde & Schwarz EMC32 was used during the test.

If the result of the measurement with the Quasi Peak detector is below the Average limit, the measurement with Average Detector may be omitted.

Refer to appendix 1 for test result.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 14 von 29
Page 14 of 29

5.2 Radiated Spurious Emission

RESULT:

PASS

Date of testing:	Jun. 03, 2014
Test specification:	FCC Part 15 Per Section 15.209(a); RSS-Gen 7.2.1
Limits:	FCC Part 15 Per Section 15.209(a); RSS-Gen 7.2.1
Test procedure:	ANSI C63.4
Deviations from Standard Test Procedures:	None
Kind of test site:	3m Semi-anechoic chamber
Operation mode:	Transmitting at fix channel with max power (High, Low, Mid)
Power supply:	Adapter Input: 120Vac, 60Hz 7.2Vdc from Internal battery
Temperature:	25.6 °C
Humidity:	56 %

Test procedure:

For tabletop device and the peripherals were placed on a wooden table, 80cm above ground plane in semi-anechoic chamber. For floor-standing equipment, the EUT and all cables shall be insulated, if required, from the ground plane by up to 12mm of insulating material in semi-anechoic chamber. The EUT was set 3 meters away from the receiving antenna, which was mounted on a variable-height antenna tower. Test shall be made with the antenna positioned in both the horizontal and vertical planes of polarization. The antenna height shall be varied from 1m to 4m. The table was rotated 360 degrees to detect the suspected emission frequency points. The position of the worst radiation case with both horizontal and vertical receiving antenna polarization was recorded together with the suspected emission frequency points above-mentioned.

The EUT was tested in a typical model of operation in accordance with ANSI C63.4:2009, Pre-test was performed in peak detection mode. Final measurement was performed using quasi-peak detection with the worst case.

The test software Rohde & Schwarz EMC32 was used during the test.

Note:

While testing, the EUT is connected with a serial port bridge board for test mode setup. The length of the communication cable between the EUT and the bridge board, which including Tx, Rx, GND serial pins, is minimized to reduce the unwanted influence to test result. The bridge board can be connected to a host computer with standard DB9 com port cable for running of the test setup software. After setup successfully, the EUT can keep the test mode with the host computer and the cable removed.

Refer to appendix 1 for test result.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 15 von 29
Page 15 of 29

5.3 Antenna requirement

RESULT:	PASS
----------------	-------------

Date of testing:

Test specification:

FCC Part 15 Per Section 15.203

FCC Part 15 Per Section 15.247(b)

RSS-Gen 7.1.4

For intentional device, according to 15.203, and intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to 15.247(b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by amount in dB than the directional gain of the antenna exceeds of 6dBi.

As the antenna is permanently printed on RF Board, there is no consideration of replacement.

And the max gain of the antenna is 2.55dBi.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 16 von 29
Page 16 of 29

5.4 Maximum Peak Output Power

RESULT:

PASS

Date of testing: Jun. 07, 2014
Test specification: FCC Part 15 Per Section 15.247(b)(3); RSS-210 A8.4
Limits: 1 Watt.
Deviations from Standard Test Procedures: None
Test procedure: Procedure specified in ANSI C63.4
Kind of test site: Shielded room
Operation mode: Transmitting at fix channel (High, Low, Mid)
Power supply: Adapter Input: 120Vac, 60Hz
7.2Vdc from Internal battery
Temperature: 25.3 °C
Humidity: 58 %

Table 2: Peak Conducted Power

Mode	Freq (MHz)	Result (dBm)	Limit		Margin (dB)
			dBm	W	
GFSK	2402	2.514	30.00	1	27.486
	2441	4.491	30.00	1	25.509
	2480	4.096	30.00	1	25.904
8-DPSK	2402	2.205	21.00	0.125	18.795
	2441	4.069	21.00	0.125	16.931
	2480	3.700	21.00	0.125	17.300

Please refer to Appendix 1 for measurement data.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 17 von 29
Page 17 of 29

5.5 20dB Bandwidth

RESULT:

PASS

Date of testing: Jun. 07, 2014
Test specification: FCC Part 15 Per Section 15.247(a)(2); RSS-210 A8.1
Limits: FCC Part 15 Per Section 15.247(a)(2); RSS-210 A8.1
Deviations from Standard Test procedures: None
Test procedure: Procedure specified in ANSI C63.4
Kind of test site: Shielded room
Operation mode: Transmitting at fix channel (High, Low, Mid)
Power supply: Adapter Input: 120Vac, 60Hz
7.2Vdc from Internal battery
Temperature: 25.3 °C
Humidity: 58 %

Test procedure:

1. Connect the antenna port of the EUT to the spectrum analyzer by a low lost cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: Centered Frequency= measured channel, RBW=30 kHz, VBW=100 kHz.
4. Mark the peak power frequency point and the -20dB upper and lower frequency points.
5. Read the frequency delta value between the -20dB upper and lower frequency points.
6. Repeat step 2 to 5 until all the channels required are finished.

Table 3: 20dB Bandwidth

Mode	Freq. (MHz)	20dB Bandwidth (MHz)	Conclusion
GFSK	2402	0.859	PASS
	2441	0.869	PASS
	2480	0.864	PASS
8-DPSK	2402	1.217	PASS
	2441	1.220	PASS
	2480	1.220	PASS

Please refer to Appendix 1 for measurement data.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 18 von 29
Page 18 of 29

5.6 Hopping Channel Carrier Frequency Separation

RESULT:

PASS

Date of testing: Jun. 07, 2014
Test specification: FCC Part 15 Per Section 15.247(a)(1); RSS-210 A8.1
Limits: FCC Part 15 Per Section 15.247(a)(1); RSS-210 A8.1
Deviations from Standard Test procedures: None
Test procedure: Procedure specified in ANSI C63.4
Kind of test site: Shielded room
Operation mode: Hopping mode
Power supply: Adapter Input: 120Vac, 60Hz
7.2Vdc from Internal battery
Temperature: 25.3 °C
Humidity: 58 %

Test procedure:

1. Connect the antenna port of the EUT to the spectrum analyzer by a low lost cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: Centered Frequency = measured channel, RBW = 30 kHz, VBW = 100 kHz, Frequency Span = wide enough to cover the adjacent channel.
4. Mark the peak power frequency point of the measured channel and its adjacent channel(s)
5. Read the frequency delta value between the measured channel and its adjacent channel(s)
6. Repeat step 3 to 5 until all the channels measured are finished.

Table 4: Hopping Channel Carrier Frequency Separation

Mode	Channel	Channel separation (MHz)	Limit	Conclusion
GFSK	Low CH	1.000	0.838 MHz	PASS
	Mid CH	1.013	0.831 MHz	PASS
	High CH	1.006	0.832 MHz	PASS
8-DPSK	Low CH	1.006	> 2/3 of the 20dB Bandwidth or 25[kHz](whichever is greater)	PASS
	Mid CH	1.006		PASS
	High CH	1.000		PASS

Please refer to Appendix 1 for measurement data.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 19 von 29
Page 19 of 29

5.7 Number of Hopping Frequency Used

RESULT:

PASS

Date of testing: Jun. 07, 2014
Test specification: FCC Part 15 Per Section 15.247(a)(1)(iii); RSS-210 A8.1
Limits: FCC Part 15 Per Section 15.247(a)(1)(iii); RSS-210 A8.1
Frequency hopping system in the 2400-2483.5 MHz band shall use at least 15 non-overlapping channels
Deviations from Standard Test procedures: None
Test procedure: Procedure specified in ANSI C63.4
Kind of test site: Shielded room
Operation mode: Hopping mode
Power supply: Adapter Input: 120Vac, 60Hz
7.2Vdc from Internal battery
Temperature: 25.3 °C
Humidity: 58 %

Test procedure:

1. Connect the antenna port of the EUT to the spectrum analyzer by a low lost cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: RBW = 100 kHz, VBW ≥ RBW, Frequency Span = wide enough to cover the channels to be plotted.
4. Set the spectrum analyzer to Max-hold mode and plot the result(s) with record of all hopping channel.

Table 5: Number of Hopping Frequency Used

Mode	Number of hopping channel	Limit	Conclusion
GFSK	79	>15	PASS
8-DPSK	79	>15	PASS

Please refer to Appendix 1 for measurement data.

5.8 Time of Occupancy (Dwell Time)

RESULT:

PASS

Date of testing: Jun. 11, 2014
Test specification: FCC Part 15 Per Section 15.247(a)(1)(iii); RSS-210 A8.1
Limits: FCC Part 15 Per Section 15.247(a)(1)(iii); RSS-210 A8.1
The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.
Deviations from Standard Test procedures: None
Test Procedure: Procedure specified in ANSI C63.4
Kind of test site: Shielded room
Operation mode: Transmitting at fix channel (Mid)
Power supply: Adapter Input: 120Vac, 60Hz
7.2Vdc from Internal battery
Temperature: 25.3 °C
Humidity: 58 %

Test procedure:

1. Connect the antenna port of the EUT to the spectrum analyzer by a low loss cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: Centered Frequency = measured channel, RBW = 1MHz, VBW ≥ RBW, Frequency Span = 0 Hz.
4. Set sweep time properly to capture the entire dwell time per hopping channel.
5. Set detector type to Peak and trace mode to Max Hold and make the measurement.
6. Repeat step 3-5 until all channels measured were complete.

Table 6: Time of Occupancy (Dwell Time)

Mode	Dwell time (ms)	Limit	Conclusion
GFSK DH1	158.00	<400ms	PASS
GFSK DH3	270.18	<400ms	PASS
GFSK DH5	321.25	<400ms	PASS
8-DPSK DH1	142.20	<400ms	PASS
8-DPSK DH3	270.18	<400ms	PASS
8-DPSK DH5	319.10	<400ms	PASS

Please refer to Appendix 1 for measurement data.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 21 von 29
Page 21 of 29

5.9 Band-edge Emission

RESULT:

PASS

Date of testing:	May 30, 2014
Test specification:	FCC Part 15 Per Section 15.247(d); RSS-210 Clause 2.2
Limits:	FCC Part 15 Per Section 15.247(d); RSS-210 Clause 2.2
	In addition: FCC Part 15 - radiated emission which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).
Deviations from Standard Test procedures:	None
Test Procedure:	Procedure specified in ANSI C63.4
Kind of test site:	Shielded room
Operation mode:	Transmitting at fix channel (High, Low, Mid)
Power supply:	Adapter Input: 120Vac, 60Hz 7.2Vdc from Internal battery
Temperature:	25.6 °C
Humidity:	56 %

Test procedure:

1. EUT was placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarizations of antenna are set on test.
2. Spectrum analyzer setting: (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

Please refer to Appendix 1 for measurement data.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 22 von 29
Page 22 of 29

5.10 Power spectral density

RESULT:	N/A
----------------	------------

Date of testing: ---

Test specification: FCC Part 15 Per Section 15.247(e); RSS-210 A8.2

Limits: FCC Part 15 Per Section 15.247(e); RSS-210 A8.2

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Deviations from Standard Test procedures: None

Test procedure: Procedure specified in ANSI C63.4

Kind of test site: Shielded room

Operation mode: ---

Power supply: ---

Temperature: ---

Humidity: ---

EUT does not use DTS technics, therefore this test is not applicable.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 23 von 29
Page 23 of 29

5.11 Out-of-Band Emission (Conducted spurious emission)

RESULT:

PASS

Date of testing: Jun. 11, 2014
Test specification: FCC Part 15 Per Section 15.247(d); RSS-210 A8.5
Limits: FCC Part 15 Per Section 15.247(d); RSS-210 A8.5

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

In addition:
FCC Part 15 - radiated emission which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Deviations from Standard Test procedures: None
Test Procedure: Procedure specified in ANSI C63.4
Kind of test site: Shielded room
Operation mode: Transmitting at fix channel (Mid)
Power supply: Adapter Input: 120Vac, 60Hz
7.2Vdc from Internal battery
Temperature: 25.3 °C
Humidity: 58 %

Test procedure:

1. Connect the antenna port of the EUT to the spectrum analyzer by a low loss cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: RBW = 100 kHz, VBW ≥ RBW.
4. Set proper frequency span respectively for out-of-band emission measurement of the band edge and the whole range (up to 10 times of the carrier frequency.)
5. Set the trace mode to Max Hold and mark the peak reading of any spurious emission recorded.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 24 von 29
Page 24 of 29

Table 7: Out-Of-Band Emission measurement (conducted spurious emission)

Emission (Carrier operating at Channel low, mid and high)	Attenuation	Limit (dB)
30MHz to 25GHz	All emission in this 100kHz bandwidth are attenuated more than 20dB from the carrier	$\Delta \geq 20$

Note: Refer to Appendix 1 for measurement data.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 25 von 29
Page 25 of 29

5.12 99% Bandwidth

RESULT:	PASS
----------------	-------------

Date of testing:	Jun. 07, 2014
Test specification:	RSS-210, A8.1 (c)
Limits:	N/A
Deviations from Standard Test procedures:	None
Test procedure:	Procedure specified in ANSI C63.4
Kind of test site:	Shielded room
Operation mode:	Transmitting at fix channel (High, Low, Mid)
Power supply:	Adapter Input: 120Vac, 60Hz 7.2Vdc from Internal battery
Temperature:	25.3 °C
Humidity:	58 %

Test procedure:

1. Connect the antenna port of the EUT to the spectrum analyzer by a low lost cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: Centered Frequency= measured channel, RBW=30kHz, VBW=100kHz.
4. Repeat step 2 to 3 until all the channels required are finished.

Please refer to Appendix 1 for measurement data.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 26 von 29
Page 26 of 29

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:	PASS
----------------	-------------

Test standard: RSS-102 Issue 4
FCC KDB Publication 447498

The maximum peak output power of the transmitter is 2.813 mW only, which less than 20mW.
Hence the EUT is exempted from routine evaluation limits (SAR Evaluation) according to clause 2.5.1 of RSS-102 Issue 4.

The minimum distance for the EUT is 5mm, since maximum peak output power of the transmitter is 2.813 mW < 10 mW, hence the EUT is excluded from SAR evaluation according to FCC KDB publication 447498 D01: Mobile and Portable RF Exposure Guidance v05.

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 27 von 29
Page 27 of 29

7. Photographs of the Test Set-Up

Photograph 1: Set-up for Power Line Conducted Emission

Prüfbericht - Nr.: 16060205 001
Test Report No.:

Seite 28 von 29
Page 28 of 29

Photograph 2: Set-up for Radiation Measurement below 1GHz

Photograph 3: Set-up for Radiation Measurement above 1GHz

6 List of Tables

Table 1: List of Test and Measurement Equipment	5
Table 2: Peak Conducted Power	16
Table 3: 20dB Bandwidth	17
Table 4: Hopping Channel Carrier Frequency Separation	18
Table 5: Number of Hopping Frequency Used	19
Table 6: Time of Occupancy (Dwell Time)	20
Table 7: Out-Of-Band Emission measurement (conducted spurious emission)	24

7 List of Photographs

Photograph 1: Set-up for Power Line Conducted Emission	27
Photograph 2: Set-up for Radiation Measurement below 1GHz	28
Photograph 3: Set-up for Radiation Measurement above 1GHz	28

Prüfbericht - Nr.:


16060205 001

Seite 1 von 86

Test Report No.

Page 1 of 86

1. POWER LINE CONDUCTED EMISSIONS



Limit : ICES-003 CLASS B QP LINE Phase : LINE
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : TX Mode

		LISN	Cable		Emission			
	Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	0.20	9.61	9.80	35.22	54.63	63.71	9.08	QP
2	0.20	9.61	9.80	15.22	34.63	53.71	19.08	Average
3	0.31	9.61	9.83	28.39	47.83	60.06	12.23	QP
4	0.31	9.61	9.83	11.39	30.83	50.06	19.23	Average
5	0.45	9.61	9.81	24.86	44.28	56.93	12.65	QP
6	0.45	9.61	9.81	17.86	37.28	46.93	9.65	Average
7	0.50	9.61	9.81	26.98	46.40	56.00	9.60	QP
8	0.50	9.61	9.81	8.98	28.40	46.00	17.60	Average
9	0.95	9.63	9.82	24.85	44.30	56.00	11.70	QP
10	0.95	9.63	9.82	4.85	24.30	46.00	21.70	Average
11	12.85	9.67	9.91	20.22	39.80	60.00	20.20	QP
12	12.85	9.67	9.91	6.22	25.80	50.00	24.20	Average


Prüfbericht - Nr.:

16060205 001

Seite 2 von 86

Test Report No.

Page 2 of 86



Limit : ICES-003 CLASS B QP LINE Phase : NEUTRAL
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	0.15	9.46	9.81	30.30	49.57	65.91	16.34	QP
2	0.15	9.46	9.81	16.30	35.57	55.91	20.34	Average
3	0.17	9.52	9.81	27.88	47.21	64.99	17.78	QP
4	0.17	9.52	9.81	13.88	33.21	54.99	21.78	Average
5	0.28	9.60	9.83	21.40	40.83	60.85	20.02	QP
6	0.28	9.60	9.83	6.40	25.83	50.85	25.02	Average
7	0.44	9.59	9.81	21.77	41.17	57.07	15.90	QP
8	0.44	9.59	9.81	10.77	30.17	47.07	16.90	Average
9	0.47	9.59	9.81	18.88	38.28	56.49	18.21	QP
10	0.47	9.59	9.81	11.88	31.28	46.49	15.21	Average
11	12.65	9.73	9.92	13.00	32.65	60.00	27.35	QP
12	12.65	9.73	9.92	4.00	23.65	50.00	26.35	Average


Prüfbericht - Nr.:

16060205 001

Seite 3 von 86

Test Report No.

Page 3 of 86



Limit : ICES-003 CLASS B QP LINE Phase : LINE
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa
 Engineer : Tony
 EUT : Portable Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : RX Mode

Emission						
	Freq.	Reading	Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dBuv/m)	(dBuv/m)	(dB)	
1	0.18	32.01	51.42	64.42	13.00	QP
2	0.18	12.01	31.42	54.42	23.00	Average
3	0.30	23.59	43.03	60.37	17.34	QP
4	0.30	9.59	29.03	50.37	21.34	Average
5	0.43	24.73	44.15	57.24	13.09	QP
6	0.43	16.73	36.15	47.24	11.09	Average
7	0.45	24.85	44.27	56.80	12.53	QP
8	0.45	16.85	36.27	46.80	10.53	Average
9	0.93	18.87	38.32	56.00	17.68	QP
10	0.93	3.87	23.32	46.00	22.68	Average
11	1.43	16.07	35.51	56.00	20.49	QP
12	1.43	1.07	20.51	46.00	25.49	Average


Prüfbericht - Nr.:

16060205 001

Seite 4 von 86

Test Report No.

Page 4 of 86



Limit : ICES-003 CLASS B QP LINE Phase : NEUTRAL
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa
 Engineer : Tony
 EUT : Portable Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 E/N : BeoPlay A2
 Test Mode : RX Mode

Emission						
	Freq. (MHz)	Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	0.16	30.73	50.04	65.38	15.34	QP
2	0.16	14.73	34.04	55.38	21.34	Average
3	0.20	31.36	50.76	63.62	12.86	QP
4	0.20	12.36	31.76	53.62	21.86	Average
5	0.41	20.99	40.40	57.64	17.24	QP
6	0.41	8.99	28.40	47.64	19.24	Average
7	0.47	20.60	40.00	56.54	16.54	QP
8	0.47	12.60	32.00	46.54	14.54	Average
9	1.61	17.69	37.14	56.00	18.86	QP
10	1.61	3.69	23.14	46.00	22.86	Average
11	4.01	14.92	34.40	56.00	21.60	QP
12	4.01	0.92	20.40	46.00	25.60	Average

Prüfbericht - Nr.:


16060205 001

Seite 5 von 86

Test Report No.

Page 5 of 86

2. RADIATED EMISSIONS (30MHz-1GHz)



Site no. : 3m Chamber Data no. : 829
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : ICES-003
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2402MHz

	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	114.39	10.85	3.26	11.77	25.88	43.50	17.62	QP
2	196.84	7.72	4.26	15.08	27.06	43.50	16.44	QP
3	334.58	13.99	5.52	14.18	33.69	46.00	12.31	QP
4	352.04	14.47	5.69	15.40	35.56	46.00	10.44	QP
5	358.83	14.45	5.73	16.50	36.68	46.00	9.32	QP
6	363.68	14.61	5.72	14.44	34.77	46.00	11.23	QP


Prüfbericht - Nr.:

16060205 001

Seite 6 von 86

Test Report No.

Page 6 of 86



Site no.	: 3m Chamber	Data no.	: 828
Dis. / Ant.	: 3m 27137	Ant. pol.	: VERTICAL
Limit	: ICES-003		
Env. / Ins.	: Temp:25.6';Humi:56%;Press:101.52kPa		
Engineer	: Tony		
EUT	: Bluetooth Speaker		
Power	: DC 15V From Adapter Input AC 120V/60Hz		
M/N	: BeoPlay A2		
Test Mode	: GFSK TX 2402MHz		

	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	48.43	8.37	2.30	22.04	32.71	40.00	7.29	QP
2	58.13	4.91	2.54	21.47	28.92	40.00	11.08	QP
3	106.63	10.15	3.15	16.04	29.34	43.50	14.16	QP
4	114.39	10.85	3.26	18.99	33.10	43.50	10.40	QP
5	145.43	11.22	3.73	6.38	21.33	43.50	22.17	QP
6	196.84	7.72	4.26	8.47	20.45	43.50	23.05	QP


Prüfbericht - Nr.:

16060205 001

Seite 7 von 86

Test Report No.

Page 7 of 86



Site no.	: 3m Chamber	Data no.	: 830
Dis. / Ant.	: 3m 27137	Ant. pol.	: HORIZONTAL
Limit	: ICES-003		
Env. / Ins.	: Temp:25.6';Humi:56%;Press:101.52kPa		
Engineer	: Tony		
EUT	: Bluetooth Speaker		
Power	: DC 15V From Adapter Input AC 120V/60Hz		
M/N	: BeoPlay A2		
Test Mode	: GFSK TX 2441MHz		

	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	114.39	10.85	3.26	12.72	26.83	43.50	16.67	QP
2	196.84	7.72	4.26	13.50	25.48	43.50	18.02	QP
3	334.58	13.99	5.52	14.95	34.46	46.00	11.54	QP
4	358.83	14.45	5.73	17.52	37.70	46.00	8.30	QP
5	363.68	14.61	5.72	16.31	36.64	46.00	9.36	QP
6	371.44	14.89	5.77	11.68	32.34	46.00	13.66	QP


Prüfbericht - Nr.:

16060205 001

Seite 8 von 86

Test Report No.

Page 8 of 86



Site no.	: 3m Chamber	Data no.	: 831
Dis. / Ant.	: 3m 27137	Ant. pol.	: VERTICAL
Limit	: ICES-003		
Env. / Ins.	: Temp:25.6';Humi:56%;Press:101.52kPa		
Engineer	: Tony		
EUT	: Bluetooth Speaker		
Power	: DC 15V From Adapter Input AC 120V/60Hz		
M/N	: BeoPlay A2		
Test Mode	: GFSK TX 2441MHz		

	Freq.	Ant.	Cable	Emission				
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	48.43	8.37	2.30	21.58	32.25	40.00	7.75	QP
2	114.39	10.85	3.26	17.90	32.01	43.50	11.49	QP
3	196.84	7.72	4.26	10.08	22.06	43.50	21.44	QP
4	371.44	14.89	5.77	7.72	28.38	46.00	17.62	QP
5	555.74	19.61	7.08	7.49	34.18	46.00	11.82	QP
6	615.88	19.97	7.47	6.97	34.41	46.00	11.59	QP


Prüfbericht - Nr.:

16060205 001

Seite 9 von 86

Test Report No.

Page 9 of 86



Site no. : 3m Chamber Data no. : 833
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : ICES-003
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	111.48	10.60	3.22	10.46	24.28	43.50	19.22	QP
2	196.84	7.72	4.26	15.07	27.05	43.50	16.45	QP
3	334.58	13.99	5.52	15.00	34.51	46.00	11.49	QP
4	344.28	14.28	5.63	14.62	34.53	46.00	11.47	QP
5	352.04	14.47	5.69	16.28	36.44	46.00	9.56	QP
6	363.68	14.61	5.72	15.42	35.75	46.00	10.25	QP


Prüfbericht - Nr.:

16060205 001

Seite 10 von 86

Test Report No.

Page 10 of 86



Site no. : 3m Chamber Data no. : 832
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : ICES-003
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2480MHz

		Ant.	Cable		Emission			
Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	48.43	8.37	2.30	21.34	32.01	40.00	7.99	QP
2	106.63	10.15	3.15	16.46	29.76	43.50	13.74	QP
3	114.39	10.85	3.26	20.29	34.40	43.50	9.10	QP
4	363.68	14.61	5.72	8.55	28.88	46.00	17.12	QP
5	555.74	19.61	7.08	7.92	34.61	46.00	11.39	QP
6	618.79	20.02	7.49	6.57	34.08	46.00	11.92	QP


Prüfbericht - Nr.:

16060205 001

Seite 11 von 86

Test Report No.

Page 11 of 86



Site no. : 3m Chamber Data no. : 834
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : ICES-003
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2402MHz

		Ant.	Cable		Emission			
	Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	114.39	10.85	3.26	13.60	27.71	43.50	15.79	QP
2	196.84	7.72	4.26	13.88	25.86	43.50	17.64	QP
3	334.58	13.99	5.52	15.02	34.53	46.00	11.47	QP
4	344.28	14.28	5.63	14.61	34.52	46.00	11.48	QP
5	352.04	14.47	5.69	15.75	35.91	46.00	10.09	QP
6	363.68	14.61	5.72	16.10	36.43	46.00	9.57	QP


Prüfbericht - Nr.:

16060205 001

Seite 12 von 86

Test Report No.

Page 12 of 86



Site no.	: 3m Chamber	Data no.	: 835
Dis. / Ant.	: 3m 27137	Ant. pol.	: VERTICAL
Limit	: ICES-003		
Env. / Ins.	: Temp:25.6';Humi:56%;Press:101.52kPa		
Engineer	: Tony		
EUT	: Bluetooth Speaker		
Power	: DC 15V From Adapter Input AC 120V/60Hz		
M/N	: BeoPlay A2		
Test Mode	: 8-DPSK TX 2402MHz		

	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	48.43	8.37	2.30	21.63	32.30	40.00	7.70	QP
2	114.39	10.85	3.26	17.83	31.94	43.50	11.56	QP
3	363.68	14.61	5.72	7.34	27.67	46.00	18.33	QP
4	555.74	19.61	7.08	7.55	34.24	46.00	11.76	QP
5	606.18	19.77	7.41	7.66	34.84	46.00	11.16	QP
6	623.64	20.08	7.53	6.16	33.77	46.00	12.23	QP


Prüfbericht - Nr.:

16060205 001

Seite 13 von 86

Test Report No.

Page 13 of 86



Site no.	: 3m Chamber	Data no.	: 837
Dis. / Ant.	: 3m 27137	Ant. pol.	: HORIZONTAL
Limit	: ICES-003		
Env. / Ins.	: Temp:25.6°;Humi:56%;Press:101.52kPa		
Engineer	: Tony		
EUT	: Bluetooth Speaker		
Power	: DC 15V From Adapter Input AC 120V/60Hz		
M/N	: BeoPlay A2		
Test Mode	: 8-DPSK TX 2441MHz		

	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	111.48	10.60	3.22	9.40	23.22	43.50	20.28	QP
2	196.84	7.72	4.26	15.72	27.70	43.50	15.80	QP
3	334.58	13.99	5.52	15.17	34.68	46.00	11.32	QP
4	352.04	14.47	5.69	15.47	35.63	46.00	10.37	QP
5	363.68	14.61	5.72	14.61	34.94	46.00	11.06	QP
6	383.08	15.18	5.81	6.94	27.93	46.00	18.07	QP


Prüfbericht - Nr.:

16060205 001

Seite 14 von 86

Test Report No.

Page 14 of 86



Site no.	: 3m Chamber	Data no.	: 836
Dis. / Ant.	: 3m 27137	Ant. pol.	: VERTICAL
Limit	: ICES-003		
Env. / Ins.	: Temp:25.6';Humi:56%;Press:101.52kPa		
Engineer	: Tony		
EUT	: Bluetooth Speaker		
Power	: DC 15V From Adapter Input AC 120V/60Hz		
M/N	: BeoPlay A2		
Test Mode	: 8-DPSK TX 2441MHz		

	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	48.43	8.37	2.30	20.75	31.42	40.00	8.58	QP
2	101.78	9.65	3.07	15.65	28.37	43.50	15.13	QP
3	114.39	10.85	3.26	18.63	32.74	43.50	10.76	QP
4	145.43	11.22	3.73	6.93	21.88	43.50	21.62	QP
5	363.68	14.61	5.72	8.63	28.96	46.00	17.04	QP
6	616.85	19.99	7.49	6.53	34.01	46.00	11.99	QP


Prüfbericht - Nr.:

16060205 001

Seite 15 von 86

Test Report No.

Page 15 of 86



Site no.	: 3m Chamber	Data no.	: 838
Dis. / Ant.	: 3m 27137	Ant. pol.	: HORIZONTAL
Limit	: ICES-003		
Env. / Ins.	: Temp:25.6';Humi:56%;Press:101.52kPa		
Engineer	: Tony		
EUT	: Bluetooth Speaker		
Power	: DC 15V From Adapter Input AC 120V/60Hz		
M/N	: BeoPlay A2		
Test Mode	: 8-DPSK TX 2480MHz		

	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	111.48	10.60	3.22	10.18	24.00	43.50	19.50	QP
2	196.84	7.72	4.26	14.55	26.53	43.50	16.97	QP
3	320.03	13.57	5.37	11.03	29.97	46.00	16.03	QP
4	334.58	13.99	5.52	14.27	33.78	46.00	12.22	QP
5	352.04	14.47	5.69	15.44	35.60	46.00	10.40	QP
6	363.68	14.61	5.72	15.51	35.84	46.00	10.16	QP


Prüfbericht - Nr.:

16060205 001

Seite 16 von 86

Test Report No.

Page 16 of 86



Site no. : 3m Chamber Data no. : 839
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : ICES-003
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2480MHz

		Ant.	Cable		Emission			
Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	50.37	7.43	2.35	21.98	31.76	40.00	8.24	QP
2	114.39	10.85	3.26	19.87	33.98	43.50	9.52	QP
3	378.23	14.98	5.78	8.56	29.32	46.00	16.68	QP
4	499.48	17.87	6.72	6.74	31.33	46.00	14.67	QP
5	555.74	19.61	7.08	8.37	35.06	46.00	10.94	QP
6	628.49	20.14	7.56	6.54	34.24	46.00	11.76	QP


Prüfbericht - Nr.:

16060205 001

Seite 17 von 86

Test Report No.

Page 17 of 86



Site no. : 3m Chamber Data no. : 840
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL
 Limit : ICES-003
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : RX Mode

	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	80.44	7.07	1.25	20.78	29.10	40.00	10.90	QP
2	111.48	10.60	1.44	16.92	28.96	43.50	14.54	QP
3	133.79	11.36	1.56	20.05	32.97	43.50	10.53	QP
4	145.43	11.22	1.53	18.93	31.68	43.50	11.82	QP
5	167.74	9.43	1.71	19.93	31.07	43.50	12.43	QP
6	216.24	8.80	1.95	18.22	28.97	46.00	17.03	QP


Prüfbericht - Nr.:

16060205 001

Seite 18 von 86

Test Report No.

Page 18 of 86



Site no. : 3m Chamber Data no. : 841
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL
 Limit : ICES-003
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : RX Mode

		Ant.	Cable		Emission			
	Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	33.88	16.11	0.70	18.64	35.45	40.00	4.55	QP
2	48.43	8.37	0.98	17.59	26.94	40.00	13.06	QP
3	77.53	6.80	1.20	14.40	22.40	40.00	17.60	QP
4	143.49	11.29	1.55	18.06	30.90	43.50	12.60	QP
5	216.24	8.80	1.95	22.02	32.77	46.00	13.23	QP
6	271.53	12.49	2.29	9.83	24.61	46.00	21.39	QP

Prüfbericht - Nr.:


16060205 001

Seite 19 von 86

Test Report No.

Page 19 of 86

3. RADIATED EMISSIONS (1GHz-18GHz)



Site no. : 3m Chamber Data no. : 769
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2402MHz

	Freq.	Ant.	Cable	Amp	Emission		Limits	Margin	Remark
	(MHz)	Factor	Loss	Factor	Reading	Level	(dBuV/m)	(dB)	
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)			
1	2402.00	27.61	6.62	34.18	101.41	101.46	74.00	-27.46	Peak
2	4804.00	31.25	11.77	31.81	48.58	59.79	74.00	14.21	Peak
3	4804.00	31.25	11.77	0.00	5.28	48.30	54.00	5.70	Average
4	8038.00	36.95	11.40	31.28	34.59	51.66	74.00	22.34	Peak
5	10044.00	38.18	11.56	31.85	34.63	52.52	74.00	21.48	Peak
6	14294.00	41.71	10.92	33.08	33.24	52.79	74.00	21.21	Peak
7	17133.00	40.26	10.94	33.03	29.03	47.20	74.00	26.80	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 20 von 86

Test Report No.

Page 20 of 86



Site no. : 3m Chamber Data no. : 768
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2402MHz

		Ant.	Cable	Amp	Emission				
	Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2402.00	27.61	6.62	34.18	102.64	102.69	74.00	-28.69	Peak
2	4804.00	31.25	11.77	31.81	42.69	53.90	74.00	20.10	Peak
3	8633.00	37.24	11.45	32.31	34.51	50.89	74.00	23.11	Peak
4	11064.00	39.48	11.24	33.78	33.58	50.52	74.00	23.48	Peak
5	14413.00	41.80	10.92	32.78	32.95	52.89	74.00	21.11	Peak
6	17116.00	40.19	10.95	32.92	30.15	48.37	74.00	25.63	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 21 von 86

Test Report No.

Page 21 of 86



Site no. : 3m Chamber Data no. : 773
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2441MHz

	Freq.	Ant.	Cable	Amp	Emission		Limits	Margin	Remark
	(MHz)	Factor	Loss	Factor	Reading	Level	(dBuV/m)	(dB)	
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)			
1	2441.00	27.60	6.67	34.12	100.38	100.53	74.00	-26.53	Peak
2	4859.00	31.34	11.99	31.88	40.40	51.85	74.00	22.15	Peak
3	7324.00	36.55	11.57	31.99	35.41	51.54	74.00	22.46	Peak
4	9500.00	37.99	11.71	31.92	32.39	50.17	74.00	23.83	Peak
5	10724.00	39.22	11.30	33.14	33.49	50.87	74.00	23.13	Peak
6	14498.00	41.88	10.93	33.08	32.32	52.05	74.00	21.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 22 von 86

Test Report No.

Page 22 of 86



Site no. : 3m Chamber Data no. : 772
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2441MHz

		Ant.	Cable	Amp	Emission				
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	2441.00	27.60	6.67	34.12	102.65	102.80	74.00	-28.80	Peak
2	4882.00	31.37	12.07	31.90	37.40	48.94	74.00	25.06	Peak
3	8004.00	37.01	11.40	31.22	34.76	51.95	74.00	22.05	Peak
4	9993.00	38.12	11.59	31.78	33.47	51.40	74.00	22.60	Peak
5	14498.00	41.88	10.93	33.08	33.62	53.35	74.00	20.65	Peak
6	17133.00	40.26	10.94	33.03	30.24	48.41	74.00	25.59	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 23 von 86

Test Report No.

Page 23 of 86



Site no. : 3m Chamber Data no. : 774
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2480MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
				Reading (dBuV)	Level (dBuV/m)			
1	27.58	6.71	34.03	99.91	100.17	74.00	-26.17	Peak
2	31.49	12.44	31.97	42.54	54.50	74.00	19.50	Peak
3	31.49	12.44	0.00	2.32	46.25	54.00	7.75	Average
4	36.58	11.60	31.97	34.63	50.84	74.00	23.16	Peak
5	38.24	11.54	31.92	33.90	51.76	74.00	22.24	Peak
6	41.71	10.92	33.08	32.85	52.40	74.00	21.60	Peak
7	40.78	10.89	33.87	29.94	47.74	74.00	26.26	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 24 von 86

Test Report No.

Page 24 of 86



Site no. : 3m Chamber Data no. : 775
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2480MHz

	Freq.	Ant.	Cable	Amp	Reading	Emission	Limits	Margin	Remark
	(MHz)	Factor	Loss	Factor	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
		(dB/m)	(dB)	(dB)					
1	2480.00	27.58	6.71	34.03	96.66	96.92	74.00	-22.92	Peak
2	4960.00	31.49	12.44	31.97	41.99	53.95	74.00	20.05	Peak
3	4960.00	31.49	12.44	0.00	1.07	45.00	54.00	9.00	Average
4	8684.00	37.32	11.45	32.43	34.19	50.53	74.00	23.47	Peak
5	10588.00	39.07	11.31	32.88	32.88	50.38	74.00	23.62	Peak
6	14498.00	41.88	10.93	33.08	33.32	53.05	74.00	20.95	Peak
7	17184.00	40.45	10.92	33.34	30.12	48.15	74.00	25.85	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 25 von 86

Test Report No.

Page 25 of 86



Site no. : 3m Chamber Data no. : 778
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2402MHz

		Ant.	Cable	Amp	Emission				
	Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2402.00	27.61	6.62	34.18	100.15	100.20	74.00	-26.20	Peak
2	4804.00	31.25	11.77	31.81	45.66	56.87	74.00	17.13	Peak
3	4804.00	31.25	11.77	0.00	1.83	44.85	54.00	9.15	Average
4	8208.00	36.66	11.42	31.46	34.33	50.95	74.00	23.05	Peak
5	10163.00	38.39	11.50	32.08	33.90	51.71	74.00	22.29	Peak
6	14294.00	41.71	10.92	33.08	33.39	52.94	74.00	21.06	Peak
7	16045.00	37.13	10.65	32.79	31.34	46.33	74.00	27.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 26 von 86

Test Report No.

Page 26 of 86



Site no. : 3m Chamber Data no. : 779
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2402MHz

	Ant.	Cable	Amp	Emission					
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	2402.00	27.61	6.62	34.18	106.08	106.13	74.00	-32.13	Peak
2	4804.00	31.25	11.77	31.81	42.81	54.02	74.00	19.98	Peak
3	4804.00	31.25	11.77	0.00	1.19	44.21	54.00	9.79	Average
4	7324.00	36.55	11.57	31.99	34.01	50.14	74.00	23.86	Peak
5	9959.00	38.13	11.60	31.77	33.23	51.19	74.00	22.81	Peak
6	14481.00	41.86	10.93	33.02	31.70	51.47	74.00	22.53	Peak
7	17048.00	39.93	10.97	33.09	29.38	47.19	74.00	26.81	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 27 von 86

Test Report No.

Page 27 of 86



Site no. : 3m Chamber Data no. : 782
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2441MHz

	Freq.	Ant.	Cable	Amp		Emission			
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2441.00	27.60	6.67	34.12	99.61	99.76	74.00	-25.76	Peak
2	4882.00	31.37	12.07	31.90	40.90	52.44	74.00	21.56	Peak
3	7834.00	36.68	11.47	31.40	34.39	51.14	74.00	22.86	Peak
4	10078.00	38.24	11.54	31.92	33.18	51.04	74.00	22.96	Peak
5	14294.00	41.71	10.92	33.08	32.19	51.74	74.00	22.26	Peak
6	17014.00	39.80	10.98	33.17	29.66	47.27	74.00	26.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 28 von 86

Test Report No.

Page 28 of 86



Site no. : 3m Chamber Data no. : 783
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2441MHz

	Freq.	Ant.	Cable	Amp		Emission			
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2441.00	27.60	6.67	34.12	105.31	105.46	74.00	-31.46	Peak
2	4882.00	31.37	12.07	31.90	39.19	50.73	74.00	23.27	Peak
3	7273.00	36.54	11.56	32.04	33.89	49.95	74.00	24.05	Peak
4	10129.00	38.33	11.52	32.01	33.54	51.38	74.00	22.62	Peak
5	14413.00	41.80	10.92	32.78	32.07	52.01	74.00	21.99	Peak
6	17133.00	40.26	10.94	33.03	28.35	46.52	74.00	27.48	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 29 von 86

Test Report No.

Page 29 of 86



Site no. : 3m Chamber Data no. : 785
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2480MHz

	Freq.	Ant.	Cable	Amp		Emission			
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2480.00	27.58	6.71	34.03	99.68	99.94	74.00	-25.94	Peak
2	4960.00	31.49	12.44	31.97	41.71	53.67	74.00	20.33	Peak
3	7953.00	36.91	11.42	31.26	32.59	49.66	74.00	24.34	Peak
4	9908.00	38.14	11.61	31.76	33.53	51.52	74.00	22.48	Peak
5	14073.00	41.52	10.90	33.75	32.72	51.39	74.00	22.61	Peak
6	15858.00	37.30	10.79	33.47	31.62	46.24	74.00	27.76	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 30 von 86

Test Report No.

Page 30 of 86



Site no. : 3m Chamber Data no. : 784
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6°;Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2480MHz

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2480.00	27.58	6.71	34.03	102.25	102.51	74.00	-28.51	Peak
2	4960.00	31.49	12.44	31.97	42.62	54.58	74.00	19.42	Peak
3	4960.00	31.49	12.44	0.00	-0.28	43.65	54.00	10.35	Average
4	8684.00	37.32	11.45	32.43	35.42	51.76	74.00	22.24	Peak
5	10758.00	39.26	11.30	33.20	33.31	50.67	74.00	23.33	Peak
6	14328.00	41.74	10.92	32.98	31.96	51.64	74.00	22.36	Peak
7	17167.00	40.39	10.93	33.24	28.93	47.01	74.00	26.99	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 31 von 86

Test Report No.

Page 31 of 86



Site no. : 3m Chamber Data no. : 825
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : RX Mode

		Ant.	Cable	Amp	Emission				
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	5063.00	31.58	12.51	32.11	37.57	49.55	74.00	24.45	Peak
2	6253.00	33.42	12.17	31.96	37.42	51.05	74.00	22.95	Peak
3	8038.00	36.95	11.40	31.28	33.91	50.98	74.00	23.02	Peak
4	10044.00	38.18	11.56	31.85	33.39	51.28	74.00	22.72	Peak
5	14549.00	41.77	10.92	33.26	31.17	50.60	74.00	23.40	Peak
6	17099.00	40.13	10.95	32.96	29.11	47.23	74.00	26.77	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 32 von 86

Test Report No.

Page 32 of 86



Site no. : 3m Chamber Data no. : 824
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : RX Mode

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
					Reading	Level			
					(dBuV)	(dBuV/m)			
1	4808.00	31.25	11.77	31.81	39.47	50.68	74.00	23.32	Peak
2	7783.00	36.59	11.50	31.45	35.65	52.29	74.00	21.71	Peak
3	10163.00	38.39	11.50	32.08	33.54	51.35	74.00	22.65	Peak
4	11064.00	39.48	11.24	33.78	32.88	49.82	74.00	24.18	Peak
5	14243.00	41.67	10.91	33.24	31.29	50.63	74.00	23.37	Peak
6	17184.00	40.45	10.92	33.34	27.40	45.43	74.00	28.57	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Prüfbericht - Nr.:


16060205 001

Seite 33 von 86

Test Report No.

Page 33 of 86

4. RADIATED EMISSIONS (18GHz-25GHz)



Site no. : 3m Chamber Data no. : 796
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2402MHz

	Ant.	Cable	Amp		Emission				
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	21024.00	46.29	20.14	35.78	16.46	47.11	74.00	26.89	Peak
2	22389.00	45.78	20.79	34.48	16.29	48.38	74.00	25.62	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 34 von 86

Test Report No.

Page 34 of 86



Site no. : 3m Chamber Data no. : 797
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2402MHz

		Ant.	Cable	Amp	Emission				
	Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	18784.00	45.20	18.28	35.66	17.60	45.42	74.00	28.58	Peak
2	20926.00	46.26	20.10	35.87	16.25	46.74	74.00	27.26	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 35 von 86

Test Report No.

Page 35 of 86



Site no. : 3m Chamber Data no. : 799
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2441MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
				Reading (dBuV)	Level (dBuV/m)			
1 20709.00	46.12	20.00	36.07	15.64	45.69	74.00	28.31	Peak
2 21927.00	45.75	20.53	34.97	15.30	46.61	74.00	27.39	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 36 von 86

Test Report No.

Page 36 of 86



Site no. : 3m Chamber Data no. : 798
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2441MHz

	Freq.	Ant.	Cable	Amp		Emission			
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	21143.00	46.21	20.19	35.67	19.04	49.77	74.00	24.23	Peak
2	24818.00	45.96	22.49	34.08	19.32	53.69	74.00	20.31	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 37 von 86

Test Report No.

Page 37 of 86



Site no. : 3m Chamber Data no. : 800
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2480MHz

		Ant.	Cable	Amp		Emission			
	Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	20709.00	46.12	20.00	36.07	19.25	49.30	74.00	24.70	Peak
2	23663.00	45.67	21.74	33.14	18.07	52.34	74.00	21.66	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 38 von 86

Test Report No.

Page 38 of 86



Site no. : 3m Chamber Data no. : 801
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2480MHz

	Ant.	Cable	Amp		Emission				
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 20163.00	46.07	19.75	36.54	13.81	43.09	74.00	30.91	Peak	
2 21584.00	45.95	20.38	35.28	14.43	45.48	74.00	28.52	Peak	

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 39 von 86

Test Report No.

Page 39 of 86



Site no. : 3m Chamber Data no. : 802
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2402MHz

	Freq.	Ant.	Cable	Amp	Reading	Emission	Limits	Margin	Remark
	(MHz)	Factor	Loss	Factor	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
		(dB/m)	(dB)	(dB)					
1	19876.00	46.05	19.54	36.59	14.48	43.48	74.00	30.52	Peak
2	22501.00	45.80	20.85	34.38	14.68	46.95	74.00	27.05	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 40 von 86

Test Report No.

Page 40 of 86



Site no. : 3m Chamber Data no. : 803
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2402MHz

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	19414.00	45.81	19.01	36.21	13.56	42.17	74.00	31.83	Peak
2	21304.00	46.12	20.26	35.53	13.56	44.41	74.00	29.59	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 41 von 86

Test Report No.

Page 41 of 86



Site no. : 3m Chamber Data no. : 805
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2441MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
					Level				
1	20625.00	46.07	19.96	36.14	13.63	43.52	74.00	30.48	Peak
2	23152.00	45.63	21.28	33.69	12.97	46.19	74.00	27.81	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 42 von 86

Test Report No.

Page 42 of 86



Site no. : 3m Chamber Data no. : 804
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2441MHz

	Freq.	Ant.	Cable	Amp		Emission			
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	20282.00	46.04	19.81	36.45	13.87	43.27	74.00	30.73	Peak
2	23082.00	45.62	21.22	33.77	14.15	47.22	74.00	26.78	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 43 von 86

Test Report No.

Page 43 of 86



Site no. : 3m Chamber Data no. : 806
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : S-DPSK TX 2480MHz

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	20975.00	46.29	20.12	35.82	13.94	44.53	74.00	29.47	Peak
2	22543.00	45.79	20.88	34.32	13.74	46.09	74.00	27.91	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 44 von 86

Test Report No.

Page 44 of 86



Site no. : 3m Chamber Data no. : 807
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2480MHz

		Ant.	Cable	Amp	Emission				
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	19792.00	46.01	19.44	36.53	12.69	41.61	74.00	32.39	Peak
2	21367.00	46.08	20.29	35.46	14.10	45.01	74.00	28.99	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 45 von 86

Test Report No.

Page 45 of 86



Site no. : 3m Chamber Data no. : 826
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : RX Mode

	Ant.	Cable	Amp		Emission				
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 19820.00	46.03	19.47	36.55	14.75	43.70	74.00	30.30	Peak	
2 22228.00	45.74	20.70	34.66	15.16	46.94	74.00	27.06	Peak	

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 46 von 86

Test Report No.

Page 46 of 86



Site no. : 3m Chamber Data no. : 827
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : RX Mode

	Ant.	Cable	Amp		Emission				
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 18861.00	45.26	18.38	35.72	14.85	42.77	74.00	31.23	Peak	
2 23341.00	45.67	21.45	33.48	14.52	48.16	74.00	25.84	Peak	

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Prüfbericht - Nr.:

16060205 001


Seite 47 von 86

Test Report No.


Page 47 of 86

5. MAXIMUM PEAK OUTPUT POWER

GFSK 2402 MHz




GFSK 2441 MHz




Prüfbericht - Nr.: 16060205 001
Test Report No.

Seite 48 von 86
Page 48 of 86

GFSK 2480 MHz




8-DPSK 2402 MHz




Prüfbericht - Nr.: 16060205 001
Test Report No.

Seite 49 von 86
Page 49 of 86

8-DPSK 2441 MHz



8-DPSK 2480 MHz




Prüfbericht - Nr.:
Test Report No.

16060205 001


Seite 50 von 86
Page 50 of 86

6. 20 dB BANDWIDTH

GFSK 2402MHz



GFSK 2441MHz



Prüfbericht - Nr.:


16060205 001

Seite 51 von 86


Test Report No.

Page 51 of 86

GFSK 2480MHz



8-DPSK 2402MHz



Prüfbericht - Nr.:


16060205 001

Seite 52 von 86


Test Report No.

Page 52 of 86

8-DPSK 2441MHz



8-DPSK 2480MHz



Prüfbericht - Nr.:



16060205 001

Seite 53 von 86

Test Report No.

Page 53 of 86

7. CARRIER FREQUENCY SEPARATION





Prüfbericht - Nr.:

16060205 001

Seite 54 von 86

Test Report No.

Page 54 of 86



Prüfbericht - Nr.:


16060205 001

Seite 55 von 86


Test Report No.

Page 55 of 86

Mid Channel



High Channel



Prüfbericht - Nr.:

16060205 001


Seite 56 von 86

Test Report No.

Page 56 of 86

8. NUMBER OF HOPPING CHANNEL

GFSK



Prüfbericht - Nr.:


16060205 001

Seite 57 von 86

Test Report No.

Page 57 of 86

8-DPSK



Prüfbericht - Nr.:

16060205 001



Seite 58 von 86

Test Report No.

Page 58 of 86

9. DWELL TIME

$$\text{GFSK DH1 : } 50\text{hop}/5\text{s} * 0.4 * 79 * 0.50\text{ms} = 158.00$$



Prüfbericht - Nr.:



16060205 001

Seite 59 von 86

Test Report No.

Page 59 of 86



GFSK DH3 : $25\text{hop}/5\text{s} * 0.4 * 79 * 1.71\text{ms} = 270.18$



Prüfbericht - Nr.: 16060205 001
Test Report No.

Seite 60 von 86
Page 60 of 86

GSFK DH5 : $17\text{hop}/5\text{s} * 0.4 * 79 * 2.99\text{ms} = 321.25$



Prüfbericht - Nr.:



16060205 001

Seite 61 von 86

Test Report No.

Page 61 of 86

8-DPSK DH1 : $50\text{hop}/5\text{s} * 0.4 * 79 * 0.45\text{ms} = 142.20$



Prüfbericht - Nr.:



16060205 001

Seite 62 von 86

Test Report No.

Page 62 of 86

8-DPSK DH3 : $25\text{hop}/5\text{s} * 0.4 * 79 * 1.71\text{ms} = 270.18$



Prüfbericht - Nr.:



16060205 001

Seite 63 von 86

Test Report No.

Page 63 of 86

8-DPSK DH5 : $17\text{hop}/5\text{s} * 0.4 * 79 * 2.97\text{ms} = 319.10$



Prüfbericht - Nr.:


16060205 001

Seite 64 von 86

Test Report No.

Page 64 of 86

10. BAND-EDGE COMPLIANCE



Site no. : 3m Chamber Data no. : 770
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2402MHz (No Hopping)

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2337.07	27.73	6.56	34.23	41.78	41.84	74.00	32.16	Peak
2	2388.77	27.64	6.62	34.19	45.48	45.55	74.00	28.45	Peak
3	2390.00	27.64	6.62	34.19	44.40	44.47	74.00	29.53	Peak
4	2401.86	27.61	6.62	34.18	101.88	101.93	74.00	-27.93	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 65 von 86

Test Report No.

Page 65 of 86



Site no. : 3m Chamber Data no. : 771
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2402MHz (No Hopping)

	Freq.	Ant.	Cable	Amp	Reading	Emission	Limits	Margin	Remark
	(MHz)	Factor	Loss	Factor	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
		(dB/m)	(dB)	(dB)					
1	2375.02	27.64	6.60	34.19	45.95	46.00	74.00	28.00	Peak
2	2388.77	27.64	6.62	34.19	44.53	44.60	74.00	29.40	Peak
3	2390.00	27.64	6.62	34.19	43.66	43.73	74.00	30.27	Peak
4	2401.97	27.61	6.62	34.18	104.50	104.55	74.00	-30.55	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 66 von 86

Test Report No.

Page 66 of 86



Site no. : 3m Chamber Data no. : 777
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.93	27.58	6.71	34.03	102.05	102.31	74.00	-28.31	Peak
2	2483.50	27.58	6.71	34.03	41.09	41.35	74.00	32.65	Peak
3	2493.05	27.58	6.73	34.03	46.77	47.05	74.00	26.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 67 von 86

Test Report No.

Page 67 of 86



Site no. : 3m Chamber Data no. : 776
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : GFSK TX 2480MHz (No Hopping)

	Freq.	Ant.	Cable	Amp		Emission			
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2480.05	27.58	6.71	34.03	105.49	105.75	74.00	-31.75	Peak
2	2483.50	27.58	6.71	34.03	44.19	44.45	74.00	29.55	Peak
3	2494.80	27.57	6.73	34.00	48.00	48.30	74.00	25.70	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 68 von 86

Test Report No.

Page 68 of 86



Site no. : 3m Chamber Data no. : 781
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2402MHz (No Hopping)

		Ant.	Cable	Amp	Emission				
	Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2375.02	27.64	6.60	34.19	43.33	43.38	74.00	30.62	Peak
2	2388.99	27.64	6.62	34.19	47.05	47.12	74.00	26.88	Peak
3	2390.00	27.64	6.62	34.19	44.28	44.35	74.00	29.65	Peak
4	2401.64	27.61	6.62	34.18	99.99	100.04	74.00	-26.04	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 69 von 86

Test Report No.

Page 69 of 86



Site no.	: 3m Chamber	Data no.	: 780
Dis. / Ant.	: 3m ANT 1-18G	Ant. pol.	: VERTICAL
Limit	: RSS-210 PEAK		
Env. / Ins.	: Temp:25.6';Humi:56%;Press:101.52kPa		
Engineer	: Tony		
EUT	: Bluetooth Speaker		
Power	: DC 15V From Adapter Input AC 120V/60Hz		
M/N	: BeoPlay A2		
Test Mode	: 8-DPSK TX 2402MHz (No Hopping)		

	Ant.	Cable	Amp	Emission					
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	2327.39	27.73	6.54	34.23	42.07	42.11	74.00	31.89	Peak
2	2375.02	27.64	6.60	34.19	45.76	45.81	74.00	28.19	Peak
3	2390.00	27.64	6.62	34.19	43.47	43.54	74.00	30.46	Peak
4	2401.64	27.61	6.62	34.18	109.31	109.36	74.00	-35.36	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 70 von 86

Test Report No.

Page 70 of 86



Site no. : 3m Chamber Data no. : 786
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2480MHz (No Hopping)

	Freq.	Ant.	Cable	Amp	Reading	Emission	Limits	Margin	Remark
	(MHz)	Factor	Loss	Factor	(dBuV)	Level	(dBuV/m)	(dB)	
		(dB/m)	(dB)	(dB)					
1	2479.73	27.58	6.71	34.03	98.12	98.38	74.00	-24.38	Peak
2	2483.50	27.58	6.71	34.03	42.56	42.82	74.00	31.18	Peak
3	2492.18	27.58	6.73	34.03	44.96	45.24	74.00	28.76	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.


Prüfbericht - Nr.:

16060205 001

Seite 71 von 86

Test Report No.

Page 71 of 86



Site no. : 3m Chamber Data no. : 787
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL
 Limit : RSS-210 PEAK
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa
 Engineer : Tony
 EUT : Bluetooth Speaker
 Power : DC 15V From Adapter Input AC 120V/60Hz
 M/N : BeoPlay A2
 Test Mode : 8-DPSK TX 2480MHz (No Hopping)

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.73	27.58	6.71	34.03	104.92	105.18	74.00	-31.18	Peak
2	2483.50	27.58	6.71	34.03	45.09	45.35	74.00	28.65	Peak
3	2491.18	27.58	6.73	34.03	47.63	47.91	74.00	26.09	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. The emission levels that are 20dB below the official limit are not reported.

Prüfbericht - Nr.:

16060205 001



Seite 72 von 86

Test Report No.

Page 72 of 86

11. Out-of-Band Emission (Conducted spurious emission)

Test Mode: GFSK 2402MHz





Prüfbericht - Nr.:

16060205 001

Seite 73 von 86



Test Report No.


Page 73 of 86



Prüfbericht - Nr.: 16060205 001
Test Report No.

Seite 74 von 86
Page 74 of 86





Prüfbericht - Nr.:



16060205 001

Seite 76 von 86

Test Report No.

Page 76 of 86

Test Mode: GFSK 2480MHz





Prüfbericht - Nr.:

16060205 001

Seite 77 von 86

Test Report No.

Page 77 of 86



Prüfbericht - Nr.:



16060205 001

Seite 78 von 86

Test Report No.

Page 78 of 86

Test Mode: 8-DPSK 2402MHz





Prüfbericht - Nr.:

16060205 001

Seite 79 von 86

Test Report No.



Page 79 of 86



Prüfbericht - Nr.: 16060205 001
Test Report No.


Seite 80 von 86
Page 80 of 86

Test Mode: 8-DPSK 2441MHz



Prüfbericht - Nr.: 16060205 001
Test Report No.

Seite 81 von 86
Page 81 of 86



Prüfbericht - Nr.:



16060205 001

Seite 82 von 86

Test Report No.

Page 82 of 86

Test Mode: 8-DPSK 2480MHz





Prüfbericht - Nr.:

16060205 001

Seite 83 von 86

Test Report No.

Page 83 of 86




Prüfbericht - Nr.:
Test Report No.

16060205 001


Seite 84 von 86
Page 84 of 86

12. 99% BANDWIDTH

GFSK 2402MHz



GFSK 2441MHz




Prüfbericht - Nr.:
Test Report No.


16060205 001

Seite 85 von 86
Page 85 of 86

GFSK 2480MHz



8-DPSK 2402MHz



Prüfbericht - Nr.:


16060205 001

Seite 86 von 86

Test Report No.

Page 86 of 86

8-DPSK 2441MHz



8-DPSK 2480MHz

