





RF Exposure Evaluation Report

FCC ID TTUBEOPLAYH4G2 **Bluetooth Headphone Equipment**

Bang & Olufsen **Brand Name**

Beoplay H4 2nd Gen **Model Name** Bang & Olufsen A/S Applicant/

Bang og Olufsen Allé 1, 7600 Struer, Denmark Manufacturer

Standard 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Aug. 07, 2019, and testing was started from Aug. 12, 2019 and completed on Aug. 26, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Allen Lin

FCC ID: TTUBEOPLAYH4G2

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 5

FAX: 886-3-327-0973 Issued Date : Sep. 05, 2019

Report Template No.: HE1-A3 Ver2.1 Report Version

: 01



Table of Contents

HI	STORY OF THIS TEST REPORT				
1.	GENERAL DESCRIPTION	4			
	1.1. EUT General Information	4			
	1.2. Testing Location Information	4			
		_			
2.	. RF EXPOSURE EVALUATION	5			
	2.1. Applicable Standard	5			
	2.2. SAR evaluation	5			

Photographs of EUT V01

TEL: 886-3-327-3456 Page Number : 2 of 5 FAX: 886-3-327-0973 Issued Date : Sep. 0

Report Template No.: HE1-A3 Ver2.1 FCC ID: TTUBEOPLAYH4G2

Issued Date : Sep. 05, 2019
Report Version : 01



HISTORY OF THIS TEST REPORT

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA971118	01	Initial issue of report	Sep. 05, 2019

Reviewed by: Sam Tsai

Report Producer: Kate Lo

TEL: 886-3-327-3456 Page Number : 3 of 5
FAX: 886-3-327-0973 Issued Date : Sep. 05, 2019

Report Template No.: HE1-A3 Ver2.1 Report Version : 01 FCC ID: TTUBEOPLAYH4G2



1. GENERAL DESCRIPTION

1.1. EUT General Information

RF General Information					
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type		
Bluetooth	etooth 2400-2483.5 2402-2480		BR / EDR: FHSS (GFSK / π/4-DQPSK / 8DPSK) LE: DSSS (GFSK)		

1.2. Testing Location Information

Testing Location					
\boxtimes	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)			
		TEL: 886-3-327-3456 FAX: 886-3-327-0973			
Test site Designation No. TW1190 with FCC.					
	JHUBEI	BEI ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)			
		TEL: 886-3-656-9065 FAX: 886-3-656-9085			
Test site Designation No. TW0006 with FCC.					

TEL: 886-3-327-3456 Page Number : 4 of 5
FAX: 886-3-327-0973 Issued Date : Sep. 05, 2019

Report Template No.: HE1-A3 Ver2.1 Report Version : 01 FCC ID: TTUBEOPLAYH4G2



2. RF EXPOSURE EVALUATION

2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. SAR evaluation

1. Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]•

 $[\sqrt{f}_{(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f_(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Max. Power	Gain	Tolerance	Tune-up Max. Power		Test Distance	Frequency	Exclusion
(dBm)	(dBi)	(dB)	(dBm)	(mW)	(mm)	(GHz)	Thresholds
3.30	0.69	0.00	3.99	2.51	5	2.402	0.78

Note: The transmissions are sporadic and the duty cycle within a 100ms observation time is 3.8%.

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is 0.78 < 3, RF exposure evaluation is not required.

——THE END——

TEL: 886-3-327-3456 Page Number : 5 of 5
FAX: 886-3-327-0973 Issued Date : Sep. 05, 2019

Report Template No.: HE1-A3 Ver2.1 Report Version : 01 FCC ID: TTUBEOPLAYH4G2