**RF** Exposure Calculations

Mikrotik	Model: RB912UAG-5HPnD	-OUT-US Test Number:			170405		
MPE Calculator	MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in			ed to the antenna gain in dBi.			
	dBi = dB gain compared to a		Ī.				
	S = power density in mW/cm^2						
						Antenna Gain (dBi)	3
		Output Power			dBd + 2.17 = dBi	dBi to dBd	2
x Frequency (MHz)	5785	Maximum (Watts)		0.550405		Antenna Gain (dBd)	32.8
•							
Cable Loss (dB)	0.0	(dBm)		27.4		Antenna minus cable (dBi)	35.0
	Calculated ERP (mw)	1056045.342			EIRP = Po(dBM) + Gain (dB)		
	Calculated EIRP (mw)	1740534.217				Radiated (EIRP) dBm	62.4
		Power density (S)			ERP = EIRP - 2.17 dB		
						Radiated (ERP) dBm	60.2
		EIRP					
		= mW/cr	m^2				
		4 p r^2					
		EIRP (mW), r (cm)					
	0 " ""	,, 1 (em)	FCC	1. 6. 1	F > 1.1210		
	Occupational Limit			dio frequency radiation exposure			
5		Frequency (MHz)	Occi	npational Limit (mW/cm <sup>2</sup> )	Public Limit (mW/cm <sup>2</sup> )		
50		300-1,500		f/300	f/1500		
	General Public Limit	1,500-10,000		5	1		
1	mW/cm <sup>2</sup>						
10	$W/m^2$						
	Occupational Limit	IC radio frequency radiation exposure lin		nits per RSS-102			
$0.6455 f^{0.5}$	W/m <sup>2</sup>	Frequency (MHz)	Oc	cupational Limit (W/m²)	Public Limit (W/m <sup>2</sup> )		
49.09621		100-6,000		$0.6455f^{0.5}$	, , ,		
	General Public Limit	6,000-15,000		50			
$0.02619 f^{0.6834}$		48-300			1.291		
9.75649		300-6,000			$0.02619f^{0.6834}$		
	W/m <sup>2</sup>	6,000-15,000		50	10		
		0,000-13,000		30	10		
EIRP	S	S		Distance	Distance	Distance	Distance
milliwatts	mW/cm <sup>2</sup>	W/m <sup>2</sup>		cm	meter	inches	Feet
1740534.217	0.86567	8.657	400.00		4.00	157.48	13.12
1740534.217	0.96937	9.694	378.00		3.78	148.82	12.40
1740534.217	0.98494	9.849		375.00	3.75	147.64	12.30
1740534.217	1.13067	11.307	350.00		3.50	137.80	11.48
1740534.217	1.53897	15.390		300.00	3.00	118.11	9.84
1740534.217	1.83150	18.315		275.00	2.75	108.27	9.02
1740534.217	2.21612	22.161	250.00		2.50	98.43	8.20
1740534.217	2.73595	27.359	225.00		2.25	88.58	7.38
1740534.217	3.46268	34.627	200.00		2.00	78.74	6.56
1740534.217	4.52269	45.227		175.00	1.75	68.90	5.74
1740534.217	4.79264	47.926		170.00	1.700	66.93	5.58
1740534.217	4.90743	49.074	168.00		1.680	66.14	5.51
1740534.217	4.96638	49.664	167.00		1.670	65.75	5.48
1740534.217	5.08750	50.875	165.00		1.650	64.96	5.41
1740534.217	5.41044	54.104		160.00	1.600	62.99	5.25
1740534.217	6.15588	61.559		150.00	1.500	59.06	4.92
1740534.217	7.06670	70.667		140.00	1.400	55.12	4.59
		Frequency (MHz)	Occupat	ional Limit minimum Distance (meters)	Public Limit minimum distance (meters)		
		47CED 1 1210			2.75		
		47CFR 1.1310 RSS-102		1.67 1.68	3.75 3.78		
		KSS-102		1.08	5.78		

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA Model: RB912UAG-5HPnD-US

Model: RB912UAG-5HPnD-US Test #: 170405

Test to: 47CFR, 15.407, RSS-247 I File: RB912UAG-5HPnD-US RFExp

S/N: 6814011B01E3

FCC ID: TV7RB912G-5HPNDM

IC: 7442A-912G5HPNDM

Date: May 25, 2017 ap Page 1 of 1