RF Exposure Calculations

RF Exposure	Calculations						
Mikrotik	Model: RB SXT HG5 ac				170511		
	MPE uses EIRP for calculate	E uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi.					
	dBi = dB gain compared to an isotropic radiator.						
	S = power density in mW/cm^2						
						Antenna Gain (dBi)	2
		Output Power			dBd + 2.17 = dBi	dBi to dBd	2
x Frequency (MHz)	5825	Maximum (Watts)		0.055065	<mark>5</mark>	Antenna Gain (dBd)	17.8
Cable Loss (dB)	0.0	(dBm)		17.4	1	Antenna minus cable (dBi)	20.0
	Calculated ERP (mw)	3340.998			EIRP = Po(dBM) + Gain (dB)		
	Calculated EIRP (mw)	5506.506				Radiated (EIRP) dBm	37.4
		Power density (S)			ERP = EIRP - 2.17 dB		
						Radiated (ERP) dBm	35.2
		EIRP					
		= mW/c	m^2				
		4 p r^2	-				
		EIRP (mW), r (cm)	-				
	0 4 171 5			1. 6 1. 7	F : 1 1210		
	Occupational Limit	F 257		radio frequency radiation exposure			
5		Frequency (MHz)	0	ccupational Limit (mW/cm²)	Public Limit (mW/cm²)		
50		300-1,500		f/300	f/1500		
	General Public Limit	1,500-10,000		5	1		
1	mW/cm ²						
10	W/m^2						
	Occupational Limit	IC radio frequency radiation exposure		dio frequency radiation exposure li	mits per RSS-102		
$0.6455 f^{0.5}$	W/m^2	Frequency (MHz)		Occupational Limit (W/m²)	Public Limit (W/m ²)		
49.26565		100-6,000		$0.6455f^{0.5}$	` ,		
	General Public Limit	6,000-15,000		50			
$0.02619 f^{0.6834}$		48-300			1.291		
9.80254		300-6,000			$0.02619f^{0.6834}$		
	W/m ²	·		50			
		6,000-15,000		50	10		
EIRP	S	S		Distance	Distance	Distance	Distance
milliwatts		W/m ²				inches	Feet
	mW/cm ²			cm	meter		
5506.506	0.01095	0.110		200.00	2.00	78.74	6.56
5506.506	0.04382	0.438		100.00	1.00 0.90	39.37	3.28
5506.506	0.05410 0.06847	0.541		90.00 80.00	0.90	35.43	2.95 2.62
5506.506 5506.506	0.08943	0.685 0.894	1	70.00	0.80	31.50 27.56	2.62
5506.506	0.12172	1.217	 	60.00	0.60	23.62	1.97
5506.506	0.17528	1.753	 	50.00	0.50	19.69	1.64
5506.506	0.27387	2.739		40.00	0.40	15.75	1.31
5506.506	0.48688	4.869		30.00	0.30	11.81	0.98
5506.506	0.70111	7.011		25.00	0.25	9.84	0.82
5506.506	0.90536	9.054		22.00	0.220	8.66	0.72
5506.506	1.94753	19.475		15.00	0.150	5.91	0.49
5506.506	2.59286	25.929	1	13.00	0.130	5.12	0.43
5506.506	4.38194	43.819	1	10.00	0.100	3.94	0.33
5506.506	4.85533	48.553		9.50	0.095	3.74	0.31
5506.506	6.84678	68.468		8.00	0.080	3.15	0.26
5506.506	8.94273	89.427		7.00	0.070	2.76	0.23
		Fraguancy (MIIa)	Occu	pational Limit minimum Distance	Public Limit minimum distance (mat)		
		Frequency (MHz)		(meters)	Public Limit minimum distance (meters)		
		47CFR 1.1310		0.095	0.22 0.22		
		RSS-102		0.095	0.22		

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA S/N: 667D05D31C4E/608, 667D0509FA1b/549

Model: RBSXTG-5HPacD FCC ID: TV7SXTG-5HACD Test #: 170511 IC: 7442A-SXTG5HACD

Date: June 9, 2017 Test to: 47CFR, 15.407, RSS-247

File: SXTG5HACD MPE Page 1 of 1