

# RF Exposure Evaluation Report

**Equipment** : 802.11a/b/g/n/ac RTL8821CE Combo module  
**Brand Name** : REALTEK  
**Model No.** : RTL8821CE  
**FCC ID** : TX2-RTL8821CE  
**Standard** : 47 CFR Part 2.1091  
**Applicant** : Realtek Semiconductor Corp.  
No. 2, Innovation Road II, Hsinchu Science Park,  
Hsinchu 300, Taiwan  
**Manufacturer** : Realtek Semiconductor Corp.  
No. 2, Innovation Road II, Hsinchu Science Park,  
Hsinchu 300, Taiwan

The product sample received on Sep. 30, 2016 and completely tested on Nov. 29, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

  
Sam Chen  
SPORTON INTERNATIONAL INC.





## **TABLE OF CONTENTS**

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>4</b>
1.1	EUT General Information .....	4
1.2	Testing Location .....	4
1.3	Antenna Information .....	5
<b>2</b>	<b>MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>6</b>
2.1	Limit of Maximum Permissible Exposure .....	6
2.2	MPE Calculation Method .....	6
2.3	Calculated Result and Limit .....	7
<b>APPENDIX A. ANTENNA LIST</b>		

## REVISION HISTORY

[illegible]

# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2472	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5720 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: DSSS (GFSK)

## 1.2 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

### 1.3 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
					2.4GHz	5GHz
1	LYNwave	ALA110-222050-300011	PIFA Antenna	IPEX MHF4	3.5	5
2	PSA	RFDPA171320EMLB301	Dipole Antenna	IPEX MHF4	3.14	5

Note: 1. The EUT has two types of antenna and there are above only records higher gain of same type antenna.

2. For more information, refer to Appendix A. Antenna List.

3. There are four configurations for EUT.

4. Chain 1: Connect to Ant. 1 or Ant. 2, Chain 2: Connect to Ant. 1 or Ant. 2

EUT	Configuration	Antenna Chain	Description
EUT 1	Config.1 Diversity	2 chains	<p>The EUT supports the antenna with TX/RX diversity function for WLAN and Bluetooth. (Ex. Assume chain 1 was selected to conduct transmitting function in WLAN, so chain 2 was selected in Bluetooth Mode. Vice versa.) WLAN 2.4GHz and Bluetooth will be transmitting from the different chains; WLAN 5GHz and Bluetooth will be transmitting from the same chain.</p> <p><b>WLAN function (1TX, 1RX) / Bluetooth function (1TX, 1RX)</b></p> <p>The EUT supports 1TX/1RX function, and it supports TX/RX diversity function.</p> <p>Both chain 1 and chain 2 could be used as transmitting/receiving antenna, but only one of them could transmit/receive at the same time.</p>
EUT 2	Config.2 Fixed	2 chains	<p><b>WLAN function (1TX, 1RX) / Bluetooth function (1TX, 1RX)</b></p> <p>Chain 2 is designated for WLAN (2.4GHz), Chain 1 is designated for WLAN (5GHz) and Bluetooth.</p>
EUT 3	Config.3 Single	1 chain	<p><b>WLAN function (1TX, 1RX) / Bluetooth function (1TX, 1RX)</b></p> <p>WLAN and BT share a common chain, where WLAN (2.4GHz) and BT couldn't transmit/receive at the same time, but WLAN (5GHz) and BT could transmit/receive at the same time.</p>
EUT 4	Config.4 Single	1 chain	<p><b>WLAN function (1TX, 1RX) / Bluetooth function (1TX, 1RX)</b></p> <p>WLAN and BT share a common chain, where WLAN (2.4GHz) and BT couldn't transmit/receive at the same time, but WLAN (5GHz) and BT could transmit/receive at the same time.</p>

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



## 2.3 Calculated Result and Limit

### Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
2.4G;D1D	3.50	18.97	22.47	0.17660	20	0.03515	1	0.03515
2.4G;BT-LE	3.50	5.53	9.03	0.00800	20	0.00159	1	0.00159
							Sum Ratio	0.03674
							Ratio Limit	1

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
5.3G;D1D	5.00	18.23	23.23	0.21038	20	0.04187	1	0.04187
2.4G;BT-LE	3.50	5.53	9.03	0.00800	20	0.00159	1	0.00159
							Sum Ratio	0.04346
							Ratio Limit	1