#01_WLAN2.4GHz_802.11b 1Mbps_Bottom Face_0mm_Ch13;Ant 2

Communication System:　802.11b ; Frequency: 2472 MHz;Duty Cycle: 1:1
Medium: HSL_2450_200213 Medium parameters used: f = 2472 MHz; σ = 1.885 S/m; ε_r = 38.944; ρ = 1000 kg/m^3
Ambient Temperature：23.7 ℃; Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: ES3DV3 - SN3270; ConvF(4.57, 4.57, 4.57); Calibrated: 2019/9/25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2019/5/21
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1227
- Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

Area Scan (51x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 1.65 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 28.15 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 2.87 W/kg
SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.538 W/kg
Maximum value of SAR (measured) = 1.70 W/kg

0 dB = 1.65 W/kg = 2.17 dBW/kg

#02_WLAN5GHz_802.11a 1Mbps_Bottom Face_0mm_Ch64;Ant 1

Communication System: 802.11a; Frequency: 5320 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200213 Medium parameters used: f = 5320 MHz; σ = 4.861 S/m; ε_r = 37.102; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3925;ConvF(5.49, 5.49, 5.49); Calibrated: 2019/9/20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1311; Calibrated: 2019/8/27
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7373)

Area Scan (61x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.82 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 20.76 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 2.97 W/kg
SAR(1 g) = 0.719 W/kg; SAR(10 g) = 0.203 W/kg
Maximum value of SAR (measured) = 1.79 W/kg

0 dB = 1.79 W/kg = 2.53 dBW/kg

#03_WLAN5GHz_802.11a 1Mbps_Bottom Face_0mm_Ch100;Ant 2

Communication System: 802.11a; Frequency: 5500 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200213 Medium parameters used: f = 5500 MHz; σ = 5.038 S/m; ε_r = 36.862; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：22.3 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3925;ConvF(4.89, 4.89, 4.89); Calibrated: 2019/9/20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1311; Calibrated: 2019/8/27
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7373)

Area Scan (61x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 2.22 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 21.53 V/m; Power Drift = -0.09 dB
Peak SAR (extrapolated) = 4.40 W/kg
SAR(1 g) = 0.991 W/kg; SAR(10 g) = 0.315 W/kg
Maximum value of SAR (measured) = 2.39 W/kg

0 dB = 2.39 W/kg = 3.78 dBW/kg

#04_WLAN5GHz_802.11a 1Mbps_Bottom Face_0mm_Ch165;Ant 1

Communication System: 802.11a; Frequency: 5825 MHz;Duty Cycle: 1:1
Medium: HSL_5G_200213 Medium parameters used: f = 5825 MHz; σ = 5.385 S/m; ε_r = 36.434; ρ = 1000 kg/m^3
Ambient Temperature：23.3 ℃; Liquid Temperature：22.3 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3925;ConvF(5.22, 5.22, 5.22); Calibrated: 2019/9/20;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1311; Calibrated: 2019/8/27
- Phantom: ELI v4.0; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7373)

Area Scan (81x121x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 1.15 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 7.341 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 2.46 W/kg
SAR(1 g) = 0.402 W/kg; SAR(10 g) = 0.071 W/kg
Maximum value of SAR (measured) = 1.45 W/kg

0 dB = 1.45 W/kg = 1.61 dBW/kg

#05_Bluetooth_LE_1Mbps_Bottom Face_0mm_Ch39;Ant 2

Communication System: Bluetooth_LE; Frequency: 2480 MHz;Duty Cycle: 1:1.576

Medium: HSL_2450_200217 Medium parameters used: f = 2480 MHz; σ = 1.831 S/m; ε_r = 38.603; ρ = 1000 kg/m^3

Ambient Temperature：23.7 ℃; Liquid Temperature：22.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN7306;ConvF(7.48, 7.48, 7.48); Calibrated: 2019/7/22;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn577; Calibrated: 2019/9/17
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1238
- Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7373)

Area Scan (51x101x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 0.0737 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.862 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 0.0560 W/kg
SAR(1 g) = 0.029 W/kg; SAR(10 g) = 0.012 W/kg
Maximum value of SAR (measured) = 0.0396 W/kg

0 dB = 0.0396 W/kg = -14.02 dBW/kg