

**#01\_WLAN2.4GHz\_802.11b 1Mbps\_Bottom of Laptop\_0mm\_Ch6\_Main Ant**

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_170416 Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.964$  S/m;  $\epsilon_r = 54.071$ ;

$\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.4 °C

**DASY5 Configuration**

- Probe: EX3DV4 - SN3976; ConvF(7.93, 7.93, 7.93); Calibrated: 2017/2/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1424; Calibrated: 2017/2/16
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1227
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

**Area Scan (71x161x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.541 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.32 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 0.777 W/kg

**SAR(1 g) = 0.356 W/kg; SAR(10 g) = 0.163 W/kg**

Maximum value of SAR (measured) = 0.587 W/kg



0 dB = 0.587 W/kg = -2.31 dBW/kg

**#02\_WLAN5GHz\_802.11n-HT40 MCS0\_Bottom of Laptop\_0mm\_Ch54\_Main Ant**

Communication System: 802.11n ; Frequency: 5270 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_170510 Medium parameters used:  $f = 5270$  MHz;  $\sigma = 5.563$  S/m;  $\epsilon_r = 46.954$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3976; ConvF(4.87, 4.87, 4.87); Calibrated: 2017/2/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1424; Calibrated: 2017/2/16
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1227
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

**Area Scan (61x121x1):** Interpolated grid:  $dx=1.000$  mm,  $dy=1.000$  mm

Maximum value of SAR (interpolated) = 1.42 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4$ mm,  $dy=4$ mm,  $dz=1.4$ mm

Reference Value = 18.50 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 2.86 W/kg

**SAR(1 g) = 0.731 W/kg; SAR(10 g) = 0.267 W/kg**

Maximum value of SAR (measured) = 1.67 W/kg



0 dB = 1.67 W/kg = 2.23 dBW/kg

**#03\_WLAN5GHz\_802.11n-HT40 MCS0\_Bottom of Laptop\_0mm\_Ch134\_Aux Ant**

Communication System: 802.11n ; Frequency: 5670 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_170510 Medium parameters used:  $f = 5670$  MHz;  $\sigma = 6.085$  S/m;  $\epsilon_r = 46.297$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3976; ConvF(4.03, 4.03, 4.03); Calibrated: 2017/2/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1424; Calibrated: 2017/2/16
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1227
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

**Area Scan (61x121x1):** Interpolated grid:  $dx=1.000$  mm,  $dy=1.000$  mm

Maximum value of SAR (interpolated) = 1.95 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4$ mm,  $dy=4$ mm,  $dz=1.4$ mm

Reference Value = 14.96 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 4.19 W/kg

**SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.369 W/kg**

Maximum value of SAR (measured) = 2.47 W/kg



0 dB = 2.47 W/kg = 3.93 dBW/kg

**#04\_WLAN5GHz\_802.11ac-VHT80 MCS0\_Bottom of Laptop\_0mm\_Ch155\_Aux Ant**

Communication System: 802.11ac ; Frequency: 5775 MHz;Duty Cycle: 1:1

Medium: MSL\_5G\_170510 Medium parameters used:  $f = 5775$  MHz;  $\sigma = 6.229$  S/m;  $\epsilon_r = 46.13$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3976; ConvF(4.33, 4.33, 4.33); Calibrated: 2017/2/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1424; Calibrated: 2017/2/16
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1227
- Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7373)

**Area Scan (61x121x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.11 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 16.06 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 4.34 W/kg

**SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.363 W/kg**

Maximum value of SAR (measured) = 2.58 W/kg



0 dB = 2.58 W/kg = 4.12 dBW/kg