



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

| | |
|------------------------|--|
| Applicant's company | Realtek Semiconductor Corp. |
| Applicant Address | No. 2, Innovation Road II, Hsinchu Science Park, Hsinchu 300, Taiwan |
| FCC ID | TX2RTL8192EEBT |
| Manufacturer's company | Realtek Semiconductor Corp. |
| Manufacturer Address | No. 2, Innovation Road II, Hsinchu Science Park, Hsinchu 300, Taiwan |

| | |
|------------------|---------------------------------------|
| Product Name | 802.11b/g/n RTL8192EE Combo module |
| Brand Name | REALTEK |
| Model No. | RTL8192EEBT |
| Test Rule | 47 CFR FCC Part 15 Subpart C § 15.247 |
| Test Freq. Range | 2400 ~ 2483.5MHz |
| Received Date | Mar. 06, 2013 |
| Final Test Date | Apr. 14, 2013 |
| Submission Type | Original Equipment |
| Multiple Listing | Please refer to section 3.7 |

Statement

Test result included is only for the Bluetooth part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

| | |
|--|----------------|
| 1. CERTIFICATE OF COMPLIANCE | 1 |
| 2. SUMMARY OF THE TEST RESULT | 2 |
| 3. GENERAL INFORMATION | 3 |
| 3.1. Product Details..... | 3 |
| 3.2. Accessories..... | 3 |
| 3.3. Table for Filed Antenna..... | 3 |
| 3.4. Table for Carrier Frequencies | 4 |
| 3.5. Table for Test Modes | 4 |
| 3.6. Table for Testing Locations..... | 6 |
| 3.7. Table for Multiple List..... | 6 |
| 3.8. Table for Supporting Units | 7 |
| 3.9. Table for Parameters of Test Software Setting | 8 |
| 3.10. EUT Operation during Test | 8 |
| 3.11. Test Configurations | 9 |
| 4. TEST RESULT | 12 |
| 4.1. AC Power Line Conducted Emissions Measurement..... | 12 |
| 4.2. Maximum Conducted Output Power Measurement..... | 16 |
| 4.3. Hopping Channel Separation Measurement | 18 |
| 4.4. Number of Hopping Frequency Measurement..... | 29 |
| 4.5. Dwell Time Measurement..... | 31 |
| 4.6. Radiated Emissions Measurement | 38 |
| 4.7. Emissions Measurement | 56 |
| 4.8. Antenna Requirements | 72 |
| 5. LIST OF MEASURING EQUIPMENTS | 73 |
| 6. TEST LOCATION..... | 75 |
| APPENDIX A. TEST PHOTOS | A1 ~ A7 |
| APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE | B1 ~ B3 |
| APPENDIX C. CO-LOCATION REPORT..... | C1 ~ C9 |
| APPENDIX D. Antenna List..... | D1 ~ D4 |


History of This Test Report

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|------------|---------|-------------------------|--------------|
| FR332724AB | Rev. 01 | Initial issue of report | May 08, 2013 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

1. CERTIFICATE OF COMPLIANCE

Product Name : 802.11b/g/n RTL8192EE Combo module
Brand Name : REALTEK
Model No. : RTL8192EEBT
Applicant : Realtek Semiconductor Corp.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Mar. 06, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

| Applied Standard: 47 CFR FCC Part 15 Subpart C | | | | |
|--|--------------|-----------------------------------|----------|-------------|
| Part | Rule Section | Description of Test | Result | Under Limit |
| 4.1 | 15.207 | AC Power Line Conducted Emissions | Complies | 14.35 dB |
| 4.2 | 15.247(b)(1) | Maximum Conducted Output Power | Complies | 23.32 dB |
| 4.3 | 15.247(a)(1) | Hopping Channel Separation | Complies | - |
| 4.4 | 15.247(b)(1) | Number of Hopping Frequency | Complies | - |
| 4.5 | 15.247(a)(1) | Dwell Time | Complies | - |
| 4.6 | 15.247(d) | Radiated Emissions | Complies | 7.50 dB |
| 4.7 | 15.247(d) | Band Edge Emissions | Complies | 0.56 dB |
| 4.8 | 15.203 | Antenna Requirements | Complies | - |

| Test Items | Uncertainty | Remark |
|---|-----------------------|--------------------------|
| AC Power Line Conducted Emissions | ±2.3dB | Confidence levels of 95% |
| Maximum Conducted Output Power | ±0.8dB | Confidence levels of 95% |
| Hopping Channel Separation | ±8.5×10 ⁻⁸ | Confidence levels of 95% |
| Radiated Emissions (9kHz~30MHz) | ±0.8dB | Confidence levels of 95% |
| Radiated Emissions (30MHz~1000MHz) | ±1.9dB | Confidence levels of 95% |
| Radiated / Band Edge Emissions (1GHz~18GHz) | ±1.9dB | Confidence levels of 95% |
| Radiated Emissions (18GHz~40GHz) | ±1.9dB | Confidence levels of 95% |
| Temperature | ±0.7°C | Confidence levels of 95% |
| Humidity | ±3.2% | Confidence levels of 95% |
| DC / AC Power Source | ±1.4% | Confidence levels of 95% |

3. GENERAL INFORMATION

3.1. Product Details

| Items | Description |
|--------------------------------|--|
| Power Type | From host system |
| Modulation | FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) |
| Data Rate (Mbps) | GFSK: 1 ; $\pi/4$ -DQPSK: 2 ; 8DPSK: 3 |
| Frequency Range | 2400 ~ 2483.5MHz |
| Channel Number | 79 |
| Channel Band Width (99%) | For Bluetooth 1.0 : 0.9200 MHz For Bluetooth 2.0 : 1.1920 MHz For Bluetooth 2.1 + EDR : 1.2320 MHz |
| Maximum Conducted Output Power | For Bluetooth 1.0 : 6.68 dBm For Bluetooth 2.0 : 5.31 dBm For Bluetooth 2.1 + EDR : 5.82 dBm |
| Carrier Frequencies | Please refer to section 3.4 |
| Antenna | Please refer to section 3.3 |

3.2. Accessories

N/A

3.3. Table for Filed Antenna

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) | Remark |
|------|---------|----------------------|----------------|------------|------------|--------|
| 1 | LYNwave | ALA110-222050-300011 | PIFA Antenna | I-PEX MHF4 | 3.5 | TX/RX |
| 2 | LYNwave | ALA110-222050-300010 | PIFA Antenna | I-PEX | 3.5 | TX/RX |
| 3 | JOYMAX | TWF-614XMPXX-500 | Dipole Antenna | I-PEX | 3.0 | TX/RX |


Note: There are two configurations of EUT. The more information is listed as below table.

| Configuration | Type | Power Type | Type of Antenna |
|---------------|------|-----------------|--------------------------------|
| 1 | HMC | PCI-E (WLAN) | PIFA with I-PEX connector |
| | | USB (Bluetooth) | Dipole with I-PEX connector |
| 2 | NGFF | PCI-E (WLAN) | PIFA with I-PEX MHF4 connector |
| | | USB (Bluetooth) | |

The EUT supports the diversity function for WLAN and Bluetooth, and it only works in chain 2.

For Bluetooth (1TX, 1RX) mode:

Only Chain 2 can be use as transmit and receive antenna.



3.4. Table for Carrier Frequencies

| Frequency Band | Channel No. | Frequency | Channel No. | Frequency |
|----------------|-------------|-----------|-------------|-----------|
| 2400~2483.5MHz | 0 | 2402 MHz | 40 | 2442 MHz |
| | 1 | 2403 MHz | : | : |
| | : | : | 77 | 2479 MHz |
| | 38 | 2440 MHz | 78 | 2480 MHz |
| | 39 | 2441 MHz | - | - |

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

For Bluetooth 1.0:

| Test Items | Mode | Data Rate | Channel | Chain |
|--------------------------------|-------------|-----------|-----------------|-------|
| AC Power Conducted Emissions | Normal Link | - | - | - |
| Maximum Conducted Output Power | GFSK | 1 Mbps | 0/39/78 | 2 |
| Hopping Channel Separation | GFSK | 1 Mbps | 0~1/39~40/77~78 | 2 |
| Number of Hopping Frequency | GFSK | 1 Mbps | 0~78 | 2 |
| Dwell Time | DH1/DH3/DH5 | 1 Mbps | 0/39/78 | 2 |
| Radiated Emissions Below 1GHz | Normal Link | - | - | - |
| Radiated Emissions Above 1GHz | GFSK | 1 Mbps | 0/39/78 | 2 |
| Band Edge Emissions | GFSK | 1 Mbps | 0/78 | 2 |

For Bluetooth 2.0:

| Test Items | Mode | Data Rate | Channel | Chain |
|--------------------------------|-------------|-----------|-----------------|-------|
| AC Power Conducted Emissions | Normal Link | - | - | - |
| Maximum Conducted Output Power | 4-DQPSK | 2 Mbps | 0/39/78 | 2 |
| Hopping Channel Separation | 4-DQPSK | 2 Mbps | 0~1/39~40/77~78 | 2 |
| Number of Hopping Frequency | 4-DQPSK | 2 Mbps | 0~78 | 2 |
| Dwell Time | DH1/DH3/DH5 | 2 Mbps | 0/39/78 | 2 |
| Radiated Emissions Below 1GHz | Normal Link | - | - | - |
| Radiated Emissions Above 1GHz | 4-DQPSK | 2 Mbps | 0/39/78 | 2 |
| Band Edge Emissions | 4-DQPSK | 2 Mbps | 0/78 | 2 |

For Bluetooth 2.1 + EDR:

| Test Items | Mode | Data Rate | Channel | Chain |
|--------------------------------|-------------|-----------|-----------------|-------|
| AC Power Conducted Emissions | Normal Link | - | - | - |
| Maximum Conducted Output Power | 8DPSK | 3 Mbps | 0/39/78 | 2 |
| Hopping Channel Separation | 8DPSK | 3 Mbps | 0~1/39~40/77~78 | 2 |
| Number of Hopping Frequency | 8DPSK | 3 Mbps | 0~78 | 2 |
| Dwell Time | DH1/DH3/DH5 | 3 Mbps | 0/39/78 | 2 |
| Radiated Emissions Below 1GHz | Normal Link | - | - | - |
| Radiated Emissions Above 1GHz | 8DPSK | 3 Mbps | 0/39/78 | 2 |
| Band Edge Emissions | 8DPSK | 3 Mbps | 0/78 | 2 |

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. HMC + PIFA with I-PEX connector

Mode 2. HMC + Dipole with I-PEX connector

Mode 3. NGFF + PIFA with I-PEX MHF4 connector

Mode 3 generated the worst test result, so it was recorded in this report.

For Radiated Emission test below 1GHz:

Mode 1. HMC + PIFA with I-PEX connector

Mode 2. HMC + Dipole with I-PEX connector

Mode 3. NGFF + PIFA with I-PEX MHF4 connector

Mode 1 generated the worst test result, so it was recorded in this report.

For Radiated Emission test above 1GHz:

Mode 1. HMC + PIFA with I-PEX connector

Mode 2. NGFF + PIFA with I-PEX MHF4 connector

Mode 3. HMC + Dipole with I-PEX connector

Mode 1 and Mode 3 generated the worst test result, so they were recorded in the report.

For Co-location Test:

The device supports WLAN and Bluetooth functions, and both of them could transmit and receive signal simultaneously through SPDT switch.

Therefore, it is evaluated co-location and MPE tests.

Mode 1. HMC+PIFA with I-PEX connector:11n 20MHz 2437MHz+Bluetooth 2480MHz (WLAN Path Chain 2)

Mode 2. HMC+PIFA with I-PEX connector:11n 20MHz 2437MHz+Bluetooth 2480MHz(Bluetooth Path Chain 2)

Mode 3. HMC+Dipole with I-PEX connector:11n 20MHz 2437MHz+Bluetooth 2480MHz(Bluetooth Path Chain 2)

Mode 4. HMC+Dipole with I-PEX connector:11n 20MHz 2437MHz+Bluetooth 2480MHz(WLAN Path Chain 2)

Mode 5. HMC+PIFA with I-PEX connector:11b Chain1 2437MHz+Bluetooth 2480MHz (WLAN Path Chain 2)

Mode 6. HMC+PIFA with I-PEX connector: 11b Chain1 2437MHz+Bluetooth 2480MHz (Bluetooth Path Chain 2)

Mode 7. HMC+Dipole with I-PEX connector: 11b Chain2 2437MHz+Bluetooth 2480MHz (WLAN Path Chain 2)

Mode 8. HMC+Dipole with I-PEX connector: 11b Chain2 2437MHz+Bluetooth 2480MHz (Bluetooth Path Chain 2)

Mode 2, Mode 3, Mode 5 and Mode 8 generated the worst test result, so they were recorded in the report.

<For MPE and Co-location Test>:

The EUT could be applied with 2.4GHz WLAN function and Bluetooth function; therefore Maximum Permissible Exposure (Please refer to Appendix B) and Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and Bluetooth function.

3.6. Table for Testing Locations

| Test Site No. | Site Category | Location | FCC Reg. No. | IC File No. | VCCI Reg. No |
|---------------|---------------|----------|--------------|-------------|--------------|
| 03CH01-CB | SAC | Hsin Chu | 262045 | IC 4086D | - |
| CO01-CB | Conduction | Hsin Chu | 262045 | IC 4086D | - |
| TH01-CB | OVEN Room | Hsin Chu | - | - | - |

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC) Please refer section 6 for Test Site Address.

3.7. Table for Multiple List

The brand/model names in the following table are all refer to the identical product.

| Model No. | | Combination of interface and board type | | Antenna Variety | Type of antenna | |
|-------------|------|---|-----------|------------------------|-----------------|--------|
| | | WLAN | Bluetooth | | PIFA | Dipole |
| RTL8192EEBT | HMC | PCI-E | USB | Dual antenna Diversity | V | V |
| | NGFF | | | | V | - |

3.8. Table for Supporting Units

Test Site No: CO01-CB

| Support Unit | Brand | Model | FCC ID |
|------------------------------------|------------|--------------|----------------|
| Wireless AP | Planex | GW-AP54SGX | N/A |
| Notebook | DELL | E6430 | QDS-BRCM1049LE |
| Notebook | DELL | E6220 | QDS-BRCM1049LE |
| Mouse | Logitech | M-U0026 | DoC |
| Earphone | SHYARO CHI | MIC-04 | N/A |
| 802.11b/g/n RTL8192EE Combo module | REALTEK | RTL8192EEBT | TX2RTL8192EEBT |
| The test fixture | REALTEK | PCIE Adapter | N/A |

Test Site No: 03CH01-CB

| Support Unit | Brand | Model | FCC ID |
|------------------------------------|------------|--------------|----------------|
| Notebook | DELL | E6220 | N/A |
| Mouse | Logitech | M-U0026 | DoC |
| Earphone | SHYARO CHI | MIC-04 | N/A |
| Notebook | DELL | E6430 | QDS-BRCM1049 |
| Wireless AP | Planex | GW-AP54SGX | N/A |
| 802.11b/g/n RTL8192EE Combo module | REALTEK | RTL8192EEBT | TX2RTL8192EEBT |
| The test fixture | REALTEK | PCIE Adapter | N/A |

Test Site No: TH01-CB

| Support Unit | Brand | Model | FCC ID |
|------------------|---------|--------------|--------|
| Notebook | DELL | E6220 | N/A |
| The test fixture | REALTEK | PCIE Adapter | N/A |

3.9. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For Bluetooth 1.0:

| Test Software Version | Realtek Bluetooth MP v2.86 --- RTL8761 | | |
|-----------------------|--|----------|----------|
| Frequency | 2402 MHz | 2441 MHz | 2480 MHz |
| Power Parameters | Default | Default | Default |

For Bluetooth 2.0:

| Test Software Version | Realtek Bluetooth MP v2.86 --- RTL8761 | | |
|-----------------------|--|----------|----------|
| Frequency | 2402 MHz | 2441 MHz | 2480 MHz |
| Power Parameters | Default | Default | Default |

For Bluetooth 2.1 +EDR:


| Test Software Version | Realtek Bluetooth MP v2.86 --- RTL8761 | | |
|-----------------------|--|----------|----------|
| Frequency | 2402 MHz | 2441 MHz | 2480 MHz |
| Power Parameters | Default | Default | Default |

3.10. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test Configuration



| Item | Connection | Shield | Length |
|------|-------------|--------|--------|
| 1 | Power cable | No | 2.6m |
| 2 | ANT cable | Yes | 0.2m |
| 3 | ANT cable | Yes | 0.2m |
| 4 | ANT cable | Yes | 0.2m |
| 5 | ANT cable | Yes | 0.2m |
| 6 | USB cable | No | 1.8m |
| 7 | Audio cable | No | 1.1m |


3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



| Item | Connection | Shield | Length |
|------|-------------|--------|--------|
| 1 | Power cable | No | 2.6m |
| 2 | ANT cable | Yes | 0.2m |
| 3 | ANT cable | Yes | 0.2m |
| 4 | ANT cable | Yes | 0.2m |
| 5 | ANT cable | Yes | 0.2m |
| 6 | USB cable | No | 1.8m |
| 7 | Audio cable | No | 1.1m |

Test Configuration: above 1GHz



| Item | Connection | Shield | Length |
|------|-------------|--------|--------|
| 1 | Power cable | No | 2.6m |
| 2 | ANT cable | Yes | 0.2m |
| 3 | ANT cable | Yes | 0.2m |

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For a Low-power Radio-frequency Device which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

| Frequency (MHz) | QP Limit (dBuV) | AV Limit (dBuV) |
|-----------------|-----------------|-----------------|
| 0.15~0.5 | 66~56 | 56~46 |
| 0.5~5 | 56 | 46 |
| 5~30 | 60 | 50 |

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

| Receiver Parameters | Setting |
|---------------------|----------|
| Attenuation | 10 dB |
| Start Frequency | 0.15 MHz |
| Stop Frequency | 30 MHz |
| IF Bandwidth | 9 KHz |

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

| | | | |
|---------------|-------------|-----------|--------|
| Temperature | 25°C | Humidity | 60% |
| Test Engineer | Parody Lin | Phase | Line |
| Configuration | Normal Link | Test Mode | Mode 3 |



| | Freq | Level | Over Limit | Limit Line | Read Level | LISN Factor | Cable Loss | Remark |
|----|---------|-------|------------|------------|------------|-------------|------------|---------|
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.16944 | 50.64 | -14.35 | 64.99 | 50.29 | 0.16 | 0.19 | QP |
| 2 | 0.16944 | 37.43 | -17.56 | 54.99 | 37.08 | 0.16 | 0.19 | AVERAGE |
| 3 | 0.18346 | 41.43 | -22.89 | 64.33 | 41.09 | 0.15 | 0.19 | QP |
| 4 | 0.18346 | 22.65 | -31.67 | 54.33 | 22.31 | 0.15 | 0.19 | AVERAGE |
| 5 | 0.54934 | 20.00 | -36.01 | 56.00 | 19.64 | 0.16 | 0.20 | QP |
| 6 | 0.54934 | 9.93 | -36.08 | 46.00 | 9.57 | 0.16 | 0.20 | AVERAGE |
| 7 | 3.623 | 37.83 | -18.17 | 56.00 | 37.33 | 0.21 | 0.28 | QP |
| 8 | 3.623 | 29.60 | -16.40 | 46.00 | 29.10 | 0.21 | 0.28 | AVERAGE |
| 9 | 3.820 | 29.02 | -16.98 | 46.00 | 28.51 | 0.22 | 0.29 | AVERAGE |
| 10 | 3.820 | 37.01 | -18.99 | 56.00 | 36.50 | 0.22 | 0.29 | QP |
| 11 | 20.924 | 28.12 | -31.88 | 60.00 | 27.12 | 0.50 | 0.50 | QP |
| 12 | 20.924 | 22.00 | -28.00 | 50.00 | 21.00 | 0.50 | 0.50 | AVERAGE |

| | | | |
|---------------|-------------|-----------|---------|
| Temperature | 25°C | Humidity | 60% |
| Test Engineer | Parody Lin | Phase | Neutral |
| Configuration | Normal Link | Test Mode | Mode 3 |



| | Freq | Level | Over | Limit | Read | LISN | Cable | |
|----|---------|-------|--------|-------|-------|--------|-------|---------|
| | MHz | dBuV | Limit | Line | Level | Factor | Loss | Remark |
| | MHz | dBuV | dB | dBuV | dBuV | dB | dB | |
| 1 | 0.15240 | 49.78 | -16.09 | 65.87 | 49.52 | 0.08 | 0.18 | QP |
| 2 | 0.15240 | 33.04 | -22.83 | 55.87 | 32.78 | 0.08 | 0.18 | AVERAGE |
| 3 | 0.17215 | 46.03 | -18.83 | 64.86 | 45.76 | 0.08 | 0.19 | QP |
| 4 | 0.17215 | 31.95 | -22.91 | 54.86 | 31.68 | 0.08 | 0.19 | AVERAGE |
| 5 | 0.20396 | 43.54 | -19.91 | 63.45 | 43.26 | 0.08 | 0.20 | QP |
| 6 | 0.20396 | 25.37 | -28.08 | 53.45 | 25.09 | 0.08 | 0.20 | AVERAGE |
| 7 | 0.54934 | 7.67 | -38.33 | 46.00 | 7.39 | 0.08 | 0.20 | AVERAGE |
| 8 | 0.54934 | 19.64 | -36.36 | 56.00 | 19.36 | 0.08 | 0.20 | QP |
| 9 | 3.661 | 37.17 | -18.83 | 56.00 | 36.76 | 0.13 | 0.28 | QP |
| 10 | 3.661 | 29.61 | -16.39 | 46.00 | 29.20 | 0.13 | 0.28 | AVERAGE |
| 11 | 20.056 | 27.35 | -32.65 | 60.00 | 26.46 | 0.39 | 0.50 | QP |
| 12 | 20.056 | 19.80 | -30.20 | 50.00 | 18.91 | 0.39 | 0.50 | AVERAGE |

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, the limit for peak output power is 1Watt (30dBm). For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts (21dBm). The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

| Power Meter Parameter | Setting |
|-----------------------|--|
| Bandwidth | 50MHz bandwidth is greater than the EUT emission bandwidth |
| Detector | Average |

4.2.3. Test Procedures

This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

| | | | |
|---------------|---------------|----------------|------------------|
| Temperature | 23°C | Humidity | 63% |
| Test Engineer | Benson Peng | Configurations | GFSK/DQPSK/8DPSK |
| Test Date | Mar. 26, 2013 | | |

For Bluetooth 1.0:

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|------------------|----------|
| 0 | 2402 MHz | 5.60 | 30.00 | Complies |
| 39 | 2441 MHz | 6.36 | 30.00 | Complies |
| 78 | 2480 MHz | 6.68 | 30.00 | Complies |

For Bluetooth 2.0:

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|------------------|----------|
| 0 | 2402 MHz | 4.30 | 30.00 | Complies |
| 39 | 2441 MHz | 5.03 | 30.00 | Complies |
| 78 | 2480 MHz | 5.31 | 30.00 | Complies |

For Bluetooth 2.1 +EDR:

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|------------------|----------|
| 0 | 2402 MHz | 4.50 | 30.00 | Complies |
| 39 | 2441 MHz | 5.44 | 30.00 | Complies |
| 78 | 2480 MHz | 5.82 | 30.00 | Complies |

4.3. Hopping Channel Separation Measurement

4.3.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

| Spectrum Parameter | Setting |
|--------------------|---|
| Attenuation | Auto |
| Span Frequency | > Measurement Bandwidth or Channel Separation |
| RB | 30 kHz (20dB Bandwidth) / 100 kHz (Channel Separation) |
| VB | 100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation) |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | Auto |

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilized for 20 dB bandwidth measurement.
3. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were utilized for channel separation measurement.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Hopping Channel Separation

| | | | |
|---------------|-------------|----------------|------------------|
| Temperature | 23°C | Humidity | 63% |
| Test Engineer | Benson Peng | Configurations | GFSK/DQPSK/8DPSK |

For Bluetooth 1.0:

| Frequency | Ch. Separation (MHz) | 20dB Bandwidth (MHz) | Two-Thirds of 20dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Result |
|-----------|----------------------|----------------------|------------------------------------|------------------------------|----------|
| 2402 MHz | 1.00 | 1.0400 | 0.693 | 0.9200 | Complies |
| 2441 MHz | 1.00 | 1.0360 | 0.691 | 0.9160 | Complies |
| 2480 MHz | 1.00 | 1.0400 | 0.693 | 0.9160 | Complies |

Ch. Separation Limits: >20dB bandwidth or > Two-Thirds of 20dB bandwidth

For Bluetooth 2.0:

| Frequency | Ch. Separation (MHz) | 20dB Bandwidth (MHz) | Two-Thirds of 20dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Result |
|-----------|----------------------|----------------------|------------------------------------|------------------------------|----------|
| 2402 MHz | 1.00 | 1.3440 | 0.896 | 1.1920 | Complies |
| 2441 MHz | 1.00 | 1.3400 | 0.893 | 1.1920 | Complies |
| 2480 MHz | 1.00 | 1.3400 | 0.893 | 1.1920 | Complies |

Ch. Separation Limits: >20dB bandwidth or > Two-Thirds of 20dB bandwidth


For Bluetooth 2.1+EDR:

| Frequency | Ch. Separation (MHz) | 20dB Bandwidth (MHz) | Two-Thirds of 20dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Result |
|-----------|----------------------|----------------------|------------------------------------|------------------------------|----------|
| 2402 MHz | 1.00 | 1.3600 | 0.907 | 1.2320 | Complies |
| 2441 MHz | 1.00 | 1.3600 | 0.907 | 1.2320 | Complies |
| 2480 MHz | 1.00 | 1.3640 | 0.909 | 1.2320 | Complies |

Ch. Separation Limits: >20dB bandwidth or > Two-Thirds of 20dB bandwidth

For Bluetooth 1.0:


20 dB Bandwidth Plot on Channel 0 / 2402 MHz




20 dB Bandwidth Plot on Channel 39 / 2441 MHz




20 dB Bandwidth Plot on Channel 78 / 2480 MHz



Channel Separation Plot on Channel 0~1 / 2402 MHz ~ 2403 MHz




Channel Separation Plot on Channel 39~40 / 2441 MHz ~ 2442 MHz



Date: 26.MAR.2013 10:53:59


Channel Separation Plot on Channel 77~78 / 2479 MHz ~ 2480 MHz




Date: 26.MAR.2013 10:54:31




20 dB Bandwidth Plot on Channel 0 / 2402 MHz




20 dB Bandwidth Plot on Channel 78 / 2480 MHz



Channel Separation Plot on Channel 0~1 / 2402 MHz ~ 2403 MHz




Channel Separation Plot on Channel 39~40 / 2441 MHz ~ 2442 MHz



Date: 26.MAR.2013 10:51:52


Channel Separation Plot on Channel 77~78 / 2479 MHz ~ 2480 MHz



Date: 26.MAR.2013 10:51:16

For Bluetooth 2.1 +EDR:


20 dB Bandwidth Plot on Channel 0 / 2402 MHz




20 dB Bandwidth Plot on Channel 39 / 2441 MHz




20 dB Bandwidth Plot on Channel 78 / 2480 MHz



Channel Separation Plot on Channel 0~1 / 2402 MHz ~ 2403 MHz




Channel Separation Plot on Channel 39~40 / 2441 MHz ~ 2442 MHz



Date: 26.MAR.2013 10:49:00

Channel Separation Plot on Channel 77~78 / 2479 MHz ~ 2480 MHz



Date: 26.MAR.2013 10:49:46

4.4. Number of Hopping Frequency Measurement

4.4.1. Limit

At least 15 hopping frequencies, and should be equally spaced.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

| Spectrum Parameters | Setting |
|---------------------|-----------------------------|
| Attenuation | Auto |
| Span Frequency | > Operating Frequency Range |
| RB | 1000 kHz |
| VB | 1000 kHz |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | Auto |

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 1000 kHz and the video bandwidth of 1000 kHz were utilized.
3. Observe frequency hopping in 2400MHz~2483.5MHz, there are at least 75 non-overlapping channels.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Number of Hopping Frequency


| | | | |
|---------------|-------------|----------------|------------------|
| Temperature | 23°C | Humidity | 63% |
| Test Engineer | Benson Peng | Configurations | GFSK/DQPSK/8DPSK |

For Bluetooth 1.0 / Bluetooth 2.0 / Bluetooth 2.1+EDR:

| Modulation Type | Channel No. | Frequency (MHz) | Hopping Ch. (Channels) | Min. Limit (Channels) | Test Result |
|------------------|-------------|-----------------|------------------------|-----------------------|-------------|
| GFSK/DQPSK/8DPSK | 0 ~ 78 | 2402 ~ 2480 | 79 | 15 | Complies |

For Bluetooth 1.0 / Bluetooth 2.0 / Bluetooth 2.1+EDR :

Number of Hopping Channel Plot on Channel 0~78 / 2402 MHz ~ 2480 MHz



4.5. Dwell Time Measurement

4.5.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.5.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

| Spectrum Parameter | Setting |
|--------------------|----------------|
| Attenuation | Auto |
| Span Frequency | 0 MHz |
| RB | 1000 kHz |
| VB | 1000 kHz |
| Detector | Peak |
| Trace | Single Trigger |

4.5.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer
2. Set RBW of spectrum analyzer to 1000kHz and VBW to 1000kHz.
3. Use a video trigger with the trigger level set to enable triggering only on full pulses.
4. Sweep Time is more than once pulse time.
5. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
6. Measure the maximum time duration of one single pulse.
7. Set the EUT for 3DH5, 3DH3 and 3DH1 packet transmitting.
8. Measure the maximum time duration of one single pulse.

4.5.4. Test Setup Layout



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Test Result of Dwell Time

For Bluetooth 1.0 / Bluetooth 2.0 / Bluetooth 2.1 +EDR:

| | | | |
|---------------|-------------|----------------|---------------------------------------|
| Temperature | 23°C | Humidity | 63% |
| Test Engineer | Benson Peng | Configurations | GFSK / DQPSK / 8DPSK DH1, DH3, DH5 |

| Data Packet | Frequency (MHz) | Pulse Duration (ms) | Dwell Time (s) | Limits (s) | Test Result |
|-------------|-----------------|---------------------|----------------|------------|-------------|
| DH5 | 2402 MHz | 2.9000 | 0.3093 | 0.4000 | Complies |
| DH3 | 2402 MHz | 1.6400 | 0.2624 | 0.4000 | Complies |
| DH1 | 2402 MHz | 0.3800 | 0.1216 | 0.4000 | Complies |
| DH5 | 2441 MHz | 2.9000 | 0.3093 | 0.4000 | Complies |
| DH3 | 2441 MHz | 1.6400 | 0.2624 | 0.4000 | Complies |
| DH1 | 2441 MHz | 0.3800 | 0.1216 | 0.4000 | Complies |
| DH5 | 2480 MHz | 2.9000 | 0.3093 | 0.4000 | Complies |
| DH3 | 2480 MHz | 1.6400 | 0.2624 | 0.4000 | Complies |
| DH1 | 2480 MHz | 0.3800 | 0.1216 | 0.4000 | Complies |

Note: Pulse Duration * Number of Pulses*(Dwell time / measure time)

Remark:


Dwell Time= 79(channels) x 0.4(s) x average hopping channel x package transfer time (us)

79 channels come from the Hopping Channel number.

Average Hopping Channel = hops / sweep time


For Bluetooth 1.0 / Bluetooth 2.0 / Bluetooth 2.1+EDR:

Dwell Time Plot on Channel 0 / DH1 / 2402 MHz




Date: 26.MAR.2013 08:09:40

Dwell Time Plot on Channel 39 / DH1 / 2441 MHz




Date: 26.MAR.2013 08:10:29

Dwell Time Plot on Channel 78 / DH1 / 2480 MHz




Date: 26.MAR.2013 08:13:51

Dwell Time Plot on Channel 0 / DH3 / 2402 MHz




Date: 26.MAR.2013 08:08:55

Dwell Time Plot on Channel 39 / DH3 / 2441 MHz




Date: 26.MAR.2013 08:11:01

Dwell Time Plot on Channel 78 / DH3 / 2480 MHz




Date: 26.MAR.2013 08:13:25

Dwell Time Plot on Channel 0 / DH5 / 2402 MHz




Date: 26.MAR.2013 08:07:53

Dwell Time Plot on Channel 39 / DH5 / 2441 MHz



Date: 26.MAR.2013 08:12:10

Dwell Time Plot on Channel 78 / DH5 / 2480 MHz



Date: 26.MAR.2013 08:12:54

4.6. Radiated Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---|--|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10th carrier harmonic |
| RB / VB (Emission in restricted band) | 1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 100kHz / 300kHz for peak |


| Receiver Parameter | Setting |
|------------------------|----------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |

4.6.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.6.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Results of Radiated Emissions (9kHz~30MHz)

| | | | |
|---------------|---------------|----------------|-------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Normal Link |
| Test Date | Apr. 08, 2013 | Test Mode | Mode 1 |

| Freq. (MHz) | Level (dBuV) | Over Limit (dB) | Limit Line (dBuV) | Remark |
|----------------|-----------------|--------------------|----------------------|----------|
| - | - | - | - | See Note |

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.6.8. Results of Radiated Emissions (30MHz~1GHz)


| | | | |
|---------------|---------|----------------|-------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Normal Link |
| Test Mode | Mode 1 | | |

Horizontal



| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|--------|--------|--------|--------|-------|--------------|--------|-------|-------|-----------|-----------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 163.86 | 31.07 | 43.50 | -12.43 | 51.61 | 1.55 | 9.46 | 31.55 | 300 | 2 | HORIZONTAL Peak |
| 2 | 206.54 | 31.63 | 43.50 | -11.87 | 52.65 | 1.75 | 8.68 | 31.45 | 125 | 360 | HORIZONTAL Peak |
| 3 | 270.56 | 23.21 | 46.00 | -22.79 | 40.40 | 1.99 | 12.37 | 31.55 | 125 | 355 | HORIZONTAL Peak |
| 4 | 399.57 | 30.13 | 46.00 | -15.87 | 43.24 | 2.49 | 15.86 | 31.46 | 100 | 0 | HORIZONTAL Peak |
| 5 | 480.08 | 27.70 | 46.00 | -18.30 | 39.37 | 2.72 | 16.81 | 31.20 | 200 | 92 | HORIZONTAL Peak |
| 6 | 531.49 | 27.35 | 46.00 | -18.65 | 38.24 | 2.89 | 17.60 | 31.38 | 300 | 300 | HORIZONTAL Peak |

Vertical



| | Freq | Level | Limit | Over | Read | Cable | Antenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|--------|--------|--------|--------|-------|-------|---------|--------|-------|-------|-----------|--------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 39.70 | 29.22 | 40.00 | -10.78 | 47.93 | 0.74 | 12.43 | 31.88 | 400 | 240 | VERTICAL | Peak |
| 2 | 61.04 | 32.50 | 40.00 | -7.50 | 58.52 | 0.90 | 4.87 | 31.79 | 150 | 121 | VERTICAL | Peak |
| 3 | 80.44 | 31.62 | 40.00 | -8.38 | 55.47 | 1.04 | 6.83 | 31.72 | 100 | 339 | VERTICAL | Peak |
| 4 | 163.86 | 26.61 | 43.50 | -16.89 | 47.15 | 1.55 | 9.46 | 31.55 | 300 | 63 | VERTICAL | Peak |
| 5 | 298.69 | 38.40 | 46.00 | -7.60 | 54.73 | 2.12 | 12.98 | 31.43 | 150 | 95 | VERTICAL | Peak |
| 6 | 398.60 | 27.50 | 46.00 | -18.50 | 40.66 | 2.49 | 15.81 | 31.46 | 150 | 4 | VERTICAL | Peak |

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6.9. Results for Radiated Emissions (1GHz~10th Harmonic)

For Bluetooth 1.0:

| | | | |
|---------------|---------------|----------------|-----------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 0 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 1 |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 pk | 4803.80 | 48.93 | 74.00 | -25.07 | 45.82 | 5.66 | 32.74 | 35.29 | 104 | 133 | HORIZONTAL | Peak |
| 2 pp | 4803.99 | 39.34 | 54.00 | -14.66 | 36.23 | 5.66 | 32.74 | 35.29 | 104 | 133 | HORIZONTAL | Average |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 pk | 4803.58 | 49.81 | 74.00 | -24.19 | 46.70 | 5.66 | 32.74 | 35.29 | 112 | 103 | VERTICAL | Peak |
| 2 pp | 4803.96 | 41.68 | 54.00 | -12.32 | 38.57 | 5.66 | 32.74 | 35.29 | 112 | 103 | VERTICAL | Average |

| | | | |
|---------------|---------------|----------------|------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 39 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 1 |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4881.91 | 47.85 | 74.00 | -26.15 | 44.60 | 5.76 | 32.81 | 35.32 | 100 | 59 | HORIZONTAL | Peak |
| 2 | 4882.02 | 36.98 | 54.00 | -17.02 | 33.73 | 5.76 | 32.81 | 35.32 | 100 | 59 | HORIZONTAL | Average |
| 3 pk | 7322.08 | 52.40 | 74.00 | -21.60 | 43.56 | 7.06 | 37.13 | 35.35 | 100 | 85 | HORIZONTAL | Peak |
| 4 pp | 7322.84 | 39.96 | 54.00 | -14.04 | 31.12 | 7.06 | 37.13 | 35.35 | 100 | 85 | HORIZONTAL | Average |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4881.98 | 38.51 | 54.00 | -15.49 | 35.26 | 5.76 | 32.81 | 35.32 | 122 | 277 | VERTICAL | Average |
| 2 | 4882.54 | 48.56 | 74.00 | -25.44 | 45.31 | 5.76 | 32.81 | 35.32 | 122 | 277 | VERTICAL | Peak |
| 3 pk | 7324.04 | 51.94 | 74.00 | -22.06 | 43.10 | 7.06 | 37.13 | 35.35 | 100 | 163 | VERTICAL | Peak |
| 4 pp | 7325.20 | 39.82 | 54.00 | -14.18 | 30.98 | 7.06 | 37.13 | 35.35 | 100 | 163 | VERTICAL | Average |

| | | | |
|---------------|---------------|----------------|------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 78 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 1 |

Horizontal

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|--------------|--------|--------|-------|-----------|--------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | Loss | Factor | Factor | cm | deg | |
| 1 | 4959.77 | 36.98 | 54.00 | -17.02 | 33.61 | 5.85 | 32.87 | 35.35 | 100 | 317 | HORIZONTAL Average |
| 2 | 4960.72 | 46.53 | 74.00 | -27.47 | 43.16 | 5.85 | 32.87 | 35.35 | 100 | 317 | HORIZONTAL Peak |
| 3 pp | 7441.13 | 40.24 | 54.00 | -13.76 | 31.24 | 7.11 | 37.17 | 35.28 | 104 | 234 | HORIZONTAL Average |
| 4 pk | 7442.05 | 53.75 | 74.00 | -20.25 | 44.75 | 7.11 | 37.17 | 35.28 | 104 | 234 | HORIZONTAL Peak |

Vertical

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|--------------|--------|--------|-------|-----------|------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | Loss | Factor | Factor | cm | deg | |
| 1 | 4959.37 | 47.15 | 74.00 | -26.85 | 43.78 | 5.85 | 32.87 | 35.35 | 100 | 26 | VERTICAL Peak |
| 2 | 4960.01 | 35.64 | 54.00 | -18.36 | 32.27 | 5.85 | 32.87 | 35.35 | 100 | 26 | VERTICAL Average |
| 3 pk | 7438.28 | 53.44 | 74.00 | -20.56 | 44.45 | 7.11 | 37.17 | 35.29 | 100 | 116 | VERTICAL Peak |
| 4 pp | 7438.62 | 40.17 | 54.00 | -13.83 | 31.18 | 7.11 | 37.17 | 35.29 | 100 | 116 | VERTICAL Average |

For Bluetooth 2.1 +EDR:

| | | | |
|---------------|---------------|----------------|-----------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 0 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 1 |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 pk | 4803.82 | 47.23 | 74.00 | -26.77 | 44.12 | 5.66 | 32.74 | 35.29 | 100 | 131 | HORIZONTAL | Peak |
| 2 pp | 4804.13 | 38.66 | 54.00 | -15.34 | 35.55 | 5.66 | 32.74 | 35.29 | 100 | 131 | HORIZONTAL | Average |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 pk | 4803.47 | 50.73 | 74.00 | -23.27 | 47.62 | 5.66 | 32.74 | 35.29 | 111 | 90 | VERTICAL | Peak |
| 2 pp | 4804.02 | 41.43 | 54.00 | -12.57 | 38.32 | 5.66 | 32.74 | 35.29 | 111 | 90 | VERTICAL | Average |

| | | | |
|---------------|---------------|----------------|------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 39 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 1 |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4881.43 | 46.92 | 74.00 | -27.08 | 43.67 | 5.76 | 32.81 | 35.32 | 104 | 120 | HORIZONTAL | Peak |
| 2 | 4882.19 | 34.98 | 54.00 | -19.02 | 31.73 | 5.76 | 32.81 | 35.32 | 104 | 120 | HORIZONTAL | Average |
| 3 pk | 7323.38 | 51.29 | 74.00 | -22.71 | 42.45 | 7.06 | 37.13 | 35.35 | 100 | 215 | HORIZONTAL | Peak |
| 4 pp | 7323.61 | 39.06 | 54.00 | -14.94 | 30.22 | 7.06 | 37.13 | 35.35 | 100 | 215 | HORIZONTAL | Average |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4881.49 | 50.14 | 74.00 | -23.86 | 46.89 | 5.76 | 32.81 | 35.32 | 125 | 82 | VERTICAL | Peak |
| 2 pp | 4881.95 | 39.05 | 54.00 | -14.95 | 35.80 | 5.76 | 32.81 | 35.32 | 125 | 82 | VERTICAL | Average |
| 3 | 7322.11 | 39.04 | 54.00 | -14.96 | 30.20 | 7.06 | 37.13 | 35.35 | 100 | 139 | VERTICAL | Average |
| 4 pk | 7323.33 | 51.38 | 74.00 | -22.62 | 42.54 | 7.06 | 37.13 | 35.35 | 100 | 139 | VERTICAL | Peak |

| | | | |
|---------------|---------------|----------------|------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 78 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 1 |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4959.22 | 49.97 | 74.00 | -24.03 | 46.60 | 5.85 | 32.87 | 35.35 | 131 | 142 | HORIZONTAL | Peak |
| 2 | 4959.57 | 37.92 | 54.00 | -16.08 | 34.55 | 5.85 | 32.87 | 35.35 | 131 | 142 | HORIZONTAL | Average |
| 3 pk | 7440.06 | 51.56 | 74.00 | -22.44 | 42.56 | 7.11 | 37.17 | 35.28 | 100 | 242 | HORIZONTAL | Peak |
| 4 pp | 7440.69 | 39.52 | 54.00 | -14.48 | 30.52 | 7.11 | 37.17 | 35.28 | 100 | 242 | HORIZONTAL | Average |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4959.43 | 48.73 | 74.00 | -25.27 | 45.36 | 5.85 | 32.87 | 35.35 | 147 | 110 | VERTICAL | Peak |
| 2 | 4959.53 | 37.45 | 54.00 | -16.55 | 34.08 | 5.85 | 32.87 | 35.35 | 147 | 110 | VERTICAL | Average |
| 3 pp | 7440.38 | 39.44 | 54.00 | -14.56 | 30.44 | 7.11 | 37.17 | 35.28 | 100 | 261 | VERTICAL | Average |
| 4 pk | 7440.59 | 52.23 | 74.00 | -21.77 | 43.23 | 7.11 | 37.17 | 35.28 | 100 | 261 | VERTICAL | Peak |

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Bluetooth 1.0:

| | | | |
|---------------|---------------|----------------|-----------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 0 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 3 |

Horizontal

| | Freq | Level | Limit | Over | Read | Cable | Antenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|-------|---------|--------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | Loss | Factor | Factor | cm | deg | | |
| 1 pp | 4803.72 | 35.96 | 54.00 | -18.04 | 32.85 | 5.66 | 32.74 | 35.29 | 100 | 322 | HORIZONTAL | Average |
| 2 pk | 4804.28 | 46.72 | 74.00 | -27.28 | 43.61 | 5.66 | 32.74 | 35.29 | 100 | 322 | HORIZONTAL | Peak |

Vertical

| | Freq | Level | Limit | Over | Read | Cable | Antenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|-------|---------|--------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | Loss | Factor | Factor | cm | deg | | |
| 1 pp | 4804.00 | 39.20 | 54.00 | -14.80 | 36.09 | 5.66 | 32.74 | 35.29 | 100 | 263 | VERTICAL | Average |
| 2 pk | 4804.08 | 49.97 | 74.00 | -24.03 | 46.86 | 5.66 | 32.74 | 35.29 | 100 | 263 | VERTICAL | Peak |

| | | | |
|---------------|---------------|----------------|------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 39 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 3 |

Horizontal

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|--------------|--------|--------|-------|-----------|--------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | Loss | Factor | Factor | cm | deg | |
| 1 | 4881.25 | 47.34 | 74.00 | -26.66 | 44.09 | 5.76 | 32.81 | 35.32 | 100 | 177 | HORIZONTAL Peak |
| 2 | 4881.74 | 35.36 | 54.00 | -18.64 | 32.11 | 5.76 | 32.81 | 35.32 | 100 | 177 | HORIZONTAL Average |
| 3 pk | 7322.73 | 51.76 | 74.00 | -22.24 | 42.92 | 7.06 | 37.13 | 35.35 | 100 | 230 | HORIZONTAL Peak |
| 4 pp | 7323.69 | 39.85 | 54.00 | -14.15 | 31.01 | 7.06 | 37.13 | 35.35 | 100 | 230 | HORIZONTAL Average |

Vertical

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|--------------|--------|--------|-------|-----------|------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | Loss | Factor | Factor | cm | deg | |
| 1 pp | 4881.98 | 40.92 | 54.00 | -13.08 | 37.67 | 5.76 | 32.81 | 35.32 | 101 | 101 | VERTICAL Average |
| 2 | 4882.22 | 50.93 | 74.00 | -23.07 | 47.68 | 5.76 | 32.81 | 35.32 | 101 | 101 | VERTICAL Peak |
| 3 | 7323.10 | 39.82 | 54.00 | -14.18 | 30.98 | 7.06 | 37.13 | 35.35 | 100 | 250 | VERTICAL Average |
| 4 pk | 7323.83 | 52.61 | 74.00 | -21.39 | 43.77 | 7.06 | 37.13 | 35.35 | 100 | 250 | VERTICAL Peak |

| | | | |
|---------------|---------------|----------------|------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 78 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 3 |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4959.06 | 38.13 | 54.00 | -15.87 | 34.76 | 5.85 | 32.87 | 35.35 | 100 | 153 | HORIZONTAL | Average |
| 2 | 4960.66 | 47.03 | 74.00 | -26.97 | 43.66 | 5.85 | 32.87 | 35.35 | 100 | 153 | HORIZONTAL | Peak |
| 3 pk | 7440.23 | 51.94 | 74.00 | -22.06 | 42.94 | 7.11 | 37.17 | 35.28 | 106 | 21 | HORIZONTAL | Peak |
| 4 pp | 7440.38 | 40.01 | 54.00 | -13.99 | 31.01 | 7.11 | 37.17 | 35.28 | 106 | 21 | HORIZONTAL | Average |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4959.74 | 48.95 | 74.00 | -25.05 | 45.58 | 5.85 | 32.87 | 35.35 | 123 | 220 | VERTICAL | Peak |
| 2 pp | 4960.07 | 41.53 | 54.00 | -12.47 | 38.16 | 5.85 | 32.87 | 35.35 | 123 | 220 | VERTICAL | Average |
| 3 pk | 7440.76 | 52.25 | 74.00 | -21.75 | 43.25 | 7.11 | 37.17 | 35.28 | 100 | 214 | VERTICAL | Peak |
| 4 | 7440.90 | 40.07 | 54.00 | -13.93 | 31.07 | 7.11 | 37.17 | 35.28 | 100 | 214 | VERTICAL | Average |

For Bluetooth 2.1 +EDR:

| | | | |
|---------------|---------------|----------------|-----------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 0 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 3 |

Horizontal

| | Freq | Level | Limit | Over | Read | Cable | Antenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|-------|---------|--------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | Loss | Factor | Factor | cm | deg | | |
| 1 pk | 4803.50 | 49.78 | 74.00 | -24.22 | 46.67 | 5.66 | 32.74 | 35.29 | 100 | 90 | HORIZONTAL | Peak |
| 2 pp | 4803.80 | 36.65 | 54.00 | -17.35 | 33.54 | 5.66 | 32.74 | 35.29 | 100 | 90 | HORIZONTAL | Average |

Vertical

| | Freq | Level | Limit | Over | Read | Cable | Antenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|-------|---------|--------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | Loss | Factor | Factor | cm | deg | | |
| 1 pp | 4803.96 | 40.00 | 54.00 | -14.00 | 36.89 | 5.66 | 32.74 | 35.29 | 111 | 274 | VERTICAL | Average |
| 2 pk | 4804.44 | 48.73 | 74.00 | -25.27 | 45.62 | 5.66 | 32.74 | 35.29 | 111 | 274 | VERTICAL | Peak |

| | | | |
|---------------|---------------|----------------|------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 39 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 3 |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4879.77 | 37.30 | 54.00 | -16.70 | 34.07 | 5.75 | 32.80 | 35.32 | 100 | 226 | HORIZONTAL | Average |
| 2 | 4880.34 | 47.77 | 74.00 | -26.23 | 44.53 | 5.76 | 32.80 | 35.32 | 100 | 226 | HORIZONTAL | Peak |
| 3 pp | 7324.97 | 39.61 | 54.00 | -14.39 | 30.77 | 7.06 | 37.13 | 35.35 | 100 | 183 | HORIZONTAL | Average |
| 4 pk | 7324.99 | 52.71 | 74.00 | -21.29 | 43.87 | 7.06 | 37.13 | 35.35 | 100 | 183 | HORIZONTAL | Peak |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4881.73 | 49.33 | 74.00 | -24.67 | 46.08 | 5.76 | 32.81 | 35.32 | 100 | 281 | VERTICAL | Peak |
| 2 | 4882.04 | 39.22 | 54.00 | -14.78 | 35.97 | 5.76 | 32.81 | 35.32 | 100 | 281 | VERTICAL | Average |
| 3 pk | 7322.92 | 51.69 | 74.00 | -22.31 | 42.85 | 7.06 | 37.13 | 35.35 | 100 | 140 | VERTICAL | Peak |
| 4 pp | 7323.81 | 39.34 | 54.00 | -14.66 | 30.50 | 7.06 | 37.13 | 35.35 | 100 | 140 | VERTICAL | Average |

| | | | |
|---------------|---------------|----------------|------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 78 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 3 |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4958.79 | 49.08 | 74.00 | -24.92 | 45.71 | 5.85 | 32.87 | 35.35 | 100 | 234 | HORIZONTAL | Peak |
| 2 | 4959.93 | 38.13 | 54.00 | -15.87 | 34.76 | 5.85 | 32.87 | 35.35 | 100 | 234 | HORIZONTAL | Average |
| 3 pp | 7439.10 | 40.17 | 54.00 | -13.83 | 31.18 | 7.11 | 37.17 | 35.29 | 100 | 129 | HORIZONTAL | Average |
| 4 pk | 7440.04 | 51.21 | 74.00 | -22.79 | 42.21 | 7.11 | 37.17 | 35.28 | 100 | 129 | HORIZONTAL | Peak |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | Cable Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 4959.98 | 40.20 | 54.00 | -13.80 | 36.83 | 5.85 | 32.87 | 35.35 | 110 | 220 | VERTICAL | Average |
| 2 | 4960.38 | 48.44 | 74.00 | -25.56 | 45.07 | 5.85 | 32.87 | 35.35 | 110 | 220 | VERTICAL | Peak |
| 3 pk | 7437.57 | 51.75 | 74.00 | -22.25 | 42.76 | 7.11 | 37.17 | 35.29 | 100 | 162 | VERTICAL | Peak |
| 4 pp | 7439.57 | 40.39 | 54.00 | -13.61 | 31.40 | 7.11 | 37.17 | 35.29 | 100 | 162 | VERTICAL | Average |

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.7. Emissions Measurement

4.7.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

4.7.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting |
|---|--|
| Attenuation | Auto |
| Span Frequency | 100 MHz |
| RB / VB (Emission in restricted band) | 1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 100 kHz /100 kHz for Peak |

4.7.3. Test Procedures

For Radiated band edges Measurement:

- The test procedure is the same as section 4.6.3, only the frequency range investigated is limited to 100MHz around band edges.

For Conducted Out of Band Emission Measurement:

- The conducted emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit.
Only worst data of each operating mode is presented.

4.7.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.6.4.

For Conducted Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.7.7. Test Result of Band Edge and Fundamental Emissions

For Bluetooth 1.0:

| | | | |
|---------------|---------------|----------------|-------------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 0, 39, 78 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 1 |

Channel 0

| | Freq | Level | Limit | Over | Read | Cable | Antenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|-------|---------|--------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 2367.20 | 46.86 | 54.00 | -7.14 | 15.29 | 3.67 | 27.90 | 0.00 | 148 | 274 | HORIZONTAL | Average |
| 2 | 2374.10 | 59.23 | 74.00 | -14.77 | 27.66 | 3.67 | 27.90 | 0.00 | 148 | 274 | HORIZONTAL | Peak |
| 3 pk | 2401.90 | 105.90 | | | 74.31 | 3.69 | 27.90 | 0.00 | 148 | 274 | HORIZONTAL | Peak |
| 4 pp | 2402.00 | 105.42 | | | 73.83 | 3.69 | 27.90 | 0.00 | 148 | 274 | HORIZONTAL | Average |

Item 3, 4 are the fundamental frequency at 2402 MHz.

Channel 39

| | Freq | Level | Limit | Over | Read | Cable | Antenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|-------|---------|--------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 2360.80 | 46.81 | 54.00 | -7.19 | 15.25 | 3.66 | 27.90 | 0.00 | 146 | 84 | HORIZONTAL | Average |
| 2 | 2361.00 | 57.52 | 74.00 | -16.48 | 25.96 | 3.66 | 27.90 | 0.00 | 146 | 84 | HORIZONTAL | Peak |
| 3 pp | 2441.00 | 103.66 | | | 72.05 | 3.71 | 27.90 | 0.00 | 146 | 84 | HORIZONTAL | Average |
| 4 pk | 2441.00 | 104.21 | | | 72.60 | 3.71 | 27.90 | 0.00 | 146 | 84 | HORIZONTAL | Peak |
| 5 | 2483.50 | 58.97 | 74.00 | -15.03 | 27.34 | 3.73 | 27.90 | 0.00 | 146 | 84 | HORIZONTAL | Peak |
| 6 | 2483.60 | 45.31 | 54.00 | -8.69 | 13.68 | 3.73 | 27.90 | 0.00 | 146 | 84 | HORIZONTAL | Average |

Item 3, 4 are the fundamental frequency at 2441 MHz.

Channel 78

| | Freq | Level | Limit | Over | Read | Cable | Antenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|-------|---------|--------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 pk | 2479.80 | 105.55 | | | 73.92 | 3.73 | 27.90 | 0.00 | 144 | 82 | HORIZONTAL | Peak |
| 2 pp | 2480.00 | 104.42 | | | 72.79 | 3.73 | 27.90 | 0.00 | 144 | 82 | HORIZONTAL | Average |
| 3 | 2493.20 | 59.44 | 74.00 | -14.56 | 27.80 | 3.74 | 27.90 | 0.00 | 144 | 82 | HORIZONTAL | Peak |
| 4 ! | 2493.40 | 53.44 | 54.00 | -0.56 | 21.80 | 3.74 | 27.90 | 0.00 | 144 | 82 | HORIZONTAL | Average |

Item 1, 2 are the fundamental frequency at 2480 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Bluetooth 2.1 +EDR:

| | | | |
|---------------|---------------|----------------|-------------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 0, 39, 78 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 1 |

Channel 0

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|--------------|--------|-------|-------|---------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 2365.00 | 55.18 | 74.00 | -18.82 | 23.61 | 3.67 | 27.90 | 0.00 | 148 | 86 HORIZONTAL | Peak |
| 2 | 2367.11 | 44.77 | 54.00 | -9.23 | 13.20 | 3.67 | 27.90 | 0.00 | 148 | 86 HORIZONTAL | Average |
| 3 pk | 2401.80 | 104.75 | | | 73.16 | 3.69 | 27.90 | 0.00 | 148 | 86 HORIZONTAL | Peak |
| 4 pp | 2402.00 | 100.37 | | | 68.78 | 3.69 | 27.90 | 0.00 | 148 | 86 HORIZONTAL | Average |

Item 3, 4 are the fundamental frequency at 2402 MHz.

Channel 39

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|--------------|--------|-------|-------|---------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 2360.80 | 44.61 | 54.00 | -9.39 | 13.05 | 3.66 | 27.90 | 0.00 | 145 | 88 HORIZONTAL | Average |
| 2 | 2360.80 | 54.92 | 74.00 | -19.08 | 23.36 | 3.66 | 27.90 | 0.00 | 145 | 88 HORIZONTAL | Peak |
| 3 pp | 2441.00 | 99.70 | | | 68.09 | 3.71 | 27.90 | 0.00 | 145 | 88 HORIZONTAL | Average |
| 4 pk | 2441.00 | 104.04 | | | 72.43 | 3.71 | 27.90 | 0.00 | 145 | 88 HORIZONTAL | Peak |
| 5 | 2483.50 | 42.93 | 54.00 | -11.07 | 11.30 | 3.73 | 27.90 | 0.00 | 145 | 88 HORIZONTAL | Average |
| 6 | 2496.70 | 54.57 | 74.00 | -19.43 | 22.93 | 3.74 | 27.90 | 0.00 | 145 | 88 HORIZONTAL | Peak |

Item 3, 4 are the fundamental frequency at 2441 MHz.

Channel 78

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|--------------|--------|-------|-------|---------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 pp | 2480.00 | 99.52 | | | 67.89 | 3.73 | 27.90 | 0.00 | 145 | 70 HORIZONTAL | Average |
| 2 pk | 2480.20 | 103.82 | | | 72.19 | 3.73 | 27.90 | 0.00 | 145 | 70 HORIZONTAL | Peak |
| 3 | 2492.90 | 57.71 | 74.00 | -16.29 | 26.07 | 3.74 | 27.90 | 0.00 | 145 | 70 HORIZONTAL | Peak |
| 4 ! | 2493.30 | 48.72 | 54.00 | -5.28 | 17.08 | 3.74 | 27.90 | 0.00 | 145 | 70 HORIZONTAL | Average |

Item 1, 2 are the fundamental frequency at 2480 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Bluetooth 1.0:

| | | | |
|---------------|---------------|----------------|-------------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 0, 39, 78 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 3 |

Channel 0

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|---------------|-------|-------|-------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 2367.30 | 45.21 | 54.00 | -8.79 | 13.64 | 3.67 | 27.90 | 0.00 | 100 | 90 VERTICAL | Average |
| 2 | 2369.20 | 58.92 | 74.00 | -15.08 | 27.35 | 3.67 | 27.90 | 0.00 | 100 | 90 VERTICAL | Peak |
| 3 pp | 2402.00 | 102.89 | | | 71.30 | 3.69 | 27.90 | 0.00 | 100 | 90 VERTICAL | Average |
| 4 pk | 2402.00 | 103.36 | | | 71.77 | 3.69 | 27.90 | 0.00 | 100 | 90 VERTICAL | Peak |

Item 3, 4 are the fundamental frequency at 2402 MHz.

Channel 39

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|---------------|-------|-------|--------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 2361.00 | 47.24 | 54.00 | -6.76 | 15.68 | 3.66 | 27.90 | 0.00 | 100 | 202 VERTICAL | Average |
| 2 | 2376.40 | 58.87 | 74.00 | -15.13 | 27.30 | 3.67 | 27.90 | 0.00 | 100 | 202 VERTICAL | Peak |
| 3 pp | 2441.00 | 104.13 | | | 72.52 | 3.71 | 27.90 | 0.00 | 100 | 202 VERTICAL | Average |
| 4 pk | 2441.00 | 104.67 | | | 73.06 | 3.71 | 27.90 | 0.00 | 100 | 202 VERTICAL | Peak |
| 5 | 2483.40 | 45.06 | 54.00 | -8.94 | 13.43 | 3.73 | 27.90 | 0.00 | 100 | 202 VERTICAL | Average |
| 6 | 2483.40 | 57.15 | 74.00 | -16.85 | 25.52 | 3.73 | 27.90 | 0.00 | 100 | 202 VERTICAL | Peak |

Item 3, 4 are the fundamental frequency at 2441 MHz.

Channel 78

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|------------|------------|------------|-------------------|---------------|-------|-------|--------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 pk | 2479.80 | 102.72 | | | 71.09 | 3.73 | 27.90 | 0.00 | 100 | 282 VERTICAL | Peak |
| 2 pp | 2480.00 | 102.15 | | | 70.52 | 3.73 | 27.90 | 0.00 | 100 | 282 VERTICAL | Average |
| 3 | 2492.80 | 60.33 | 74.00 | -13.67 | 28.69 | 3.74 | 27.90 | 0.00 | 100 | 282 VERTICAL | Peak |
| 4 ! | 2493.30 | 49.58 | 54.00 | -4.42 | 17.94 | 3.74 | 27.90 | 0.00 | 100 | 282 VERTICAL | Average |

Item 1, 2 are the fundamental frequency at 2480 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Bluetooth 2.1 +EDR:

| | | | |
|---------------|---------------|----------------|-------------------|
| Temperature | 24°C | Humidity | 60% |
| Test Engineer | Sean Ku | Configurations | Channel 0, 39, 78 |
| Test Date | Mar. 07, 2013 | Test Mode | Mode 3 |

Channel 0

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|--------------|--------|-------|-------|--------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 2367.40 | 45.33 | 54.00 | -8.67 | 13.76 | 3.67 | 27.90 | 0.00 | 100 | 159 VERTICAL | Average |
| 2 | 2367.70 | 56.54 | 74.00 | -17.46 | 24.97 | 3.67 | 27.90 | 0.00 | 100 | 159 VERTICAL | Peak |
| 3 pp | 2402.00 | 100.55 | | | 68.96 | 3.69 | 27.90 | 0.00 | 100 | 159 VERTICAL | Average |
| 4 pk | 2402.20 | 104.46 | | | 72.87 | 3.69 | 27.90 | 0.00 | 100 | 159 VERTICAL | Peak |

Item 3, 4 are the fundamental frequency at 2402 MHz.

Channel 39

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|--------------|--------|-------|-------|--------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 2360.80 | 58.28 | 74.00 | -15.72 | 26.72 | 3.66 | 27.90 | 0.00 | 100 | 204 VERTICAL | Peak |
| 2 | 2361.20 | 46.06 | 54.00 | -7.94 | 14.50 | 3.66 | 27.90 | 0.00 | 100 | 204 VERTICAL | Average |
| 3 pp | 2441.00 | 101.55 | | | 69.94 | 3.71 | 27.90 | 0.00 | 100 | 204 VERTICAL | Average |
| 4 pk | 2441.20 | 105.42 | | | 73.81 | 3.71 | 27.90 | 0.00 | 100 | 204 VERTICAL | Peak |
| 5 | 2483.50 | 45.05 | 54.00 | -8.95 | 13.42 | 3.73 | 27.90 | 0.00 | 100 | 204 VERTICAL | Average |
| 6 | 2489.70 | 57.45 | 74.00 | -16.55 | 25.82 | 3.73 | 27.90 | 0.00 | 100 | 204 VERTICAL | Peak |

Item 3, 4 are the fundamental frequency at 2441 MHz.

Channel 78

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|------|---------|--------|--------|--------|-------|--------------|--------|-------|-------|--------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 pp | 2480.00 | 100.00 | | | 68.37 | 3.73 | 27.90 | 0.00 | 100 | 282 VERTICAL | Average |
| 2 pk | 2480.20 | 103.83 | | | 72.20 | 3.73 | 27.90 | 0.00 | 100 | 282 VERTICAL | Peak |
| 3 ! | 2493.40 | 48.43 | 54.00 | -5.57 | 16.79 | 3.74 | 27.90 | 0.00 | 100 | 282 VERTICAL | Average |
| 4 | 2493.40 | 59.67 | 74.00 | -14.33 | 28.03 | 3.74 | 27.90 | 0.00 | 100 | 282 VERTICAL | Peak |

Item 1, 2 are the fundamental frequency at 2480 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Bluetooth 1.0:


Plot on Configuration For Bluetooth 1.0 / Channel 0 / Reference Level



Plot on Configuration For Bluetooth 1.0 / Channel 0 / 30MHz~2400MHz (down 30dBc)




Plot on Configuration For Bluetooth 1.0 / Channel 0 / 2500MHz~26500MHz (down 30dBc)




Date: 14.APR.2013 15:30:10

Plot on Configuration For Bluetooth 1.0 / Channel 78 / Reference Level




Date: 12.APR.2013 21:43:14

Plot on Configuration For Bluetooth 1.0 / Channel 78 / 30MHz~2400MHz (down 30dBc)




Date: 14.APR.2013 15:31:17

Plot on Configuration For Bluetooth 1.0 / Channel 78 / 2500MHz~26500MHz (down 30dBc)




Date: 12.APR.2013 21:44:24

Plot on Configuration For Bluetooth 1.0 / Hopping / Reference Level




Date: 12.APR.2013 21:48:07

Plot on Configuration For Bluetooth 1.0 / Hopping / 30MHz~2400MHz (down 30dBc)



Date: 12.APR.2013 21:48:54


Plot on Configuration For Bluetooth 1.0 / Hopping / 2500MHz~26500MHz (down 30dBc)



Date: 12.APR.2013 21:49:34


For Bluetooth 2.1 +EDR:

Plot on Configuration For Bluetooth 2.1 +EDR / Channel 0 / Reference Level




Date: 12.APR.2013 21:51:19

Plot on Configuration For Bluetooth 2.1 +EDR / Channel 0 / 30MHz~2400MHz (down 30dBc)




Date: 12.APR.2013 21:52:05

Plot on Configuration For Bluetooth 2.1 + EDR / Channel 0 / 2500MHz~26500MHz (down 30dBc)




Date: 14.APR.2013 15:26:30

Plot on Configuration For Bluetooth 2.1 + EDR / Channel 78 / Reference Level




Date: 12.APR.2013 21:53:13

Plot on Configuration For Bluetooth 2.1 + EDR / Channel 78 / 30MHz~2400MHz (down 30dBc)




Date: 14.APR.2013 15:27:45

Plot on Configuration For Bluetooth 2.1 + EDR / Channel 78 / 2500MHz~26500MHz (down 30dBc)




Date: 12.APR.2013 21:53:46

Plot on Configuration For Bluetooth 2.1 + EDR / Hopping / Reference Level




Date: 12.APR.2013 21:55:26

Plot on Configuration For Bluetooth 2.1 + EDR / Hopping / 30MHz~2400MHz (down 30dBc)



Date: 12.APR.2013 21:56:42

Plot on Configuration For Bluetooth 2.1 + EDR / Hopping / 2500MHz~26500MHz (down 30dBc)



Date: 12.APR.2013 21:57:29

4.8. Antenna Requirements

4.8.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.8.2. Antenna Connector Construction

Please refer to section 3.3 in this test report, antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Remark |
|----------------------------------|---------------|------------------|-------------|------------------|------------------|-----------------------|
| EMI Test Receiver | R&S | ESCS 30 | 100377 | 9kHz ~ 2.75GHz | Oct. 23, 2012 | Conduction (CO01-CB) |
| LISN | F.C.C. | FCC-LISN-50-16-2 | 04083 | 150kHz ~ 100MHz | Nov. 26, 2012 | Conduction (CO01-CB) |
| V- LISN | Schwarzbeck | NSLK 8127 | 8127-478 | 9kHz ~ 30MHz | Jun. 22, 2012 | Conduction (CO01-CB) |
| Impulsbegrenzer Pulse Limiter | Rohde&Schwarz | ESH3-Z2 | 100430 | 9kHz~30MHz | Feb. 21, 2013 | Conduction (CO01-CB) |
| COND Cable | Woken | Cable | 01 | 0.15MHz~30MHz | Dec. 04, 2012 | Conduction (CO01-CB) |
| Software | Audix | E3 | 5.410e | - | - | Conduction (CO01-CB) |
| BILOG ANTENNA | Schaffner | CBL6112D | 22021 | 20MHz ~ 2GHz | Jan. 11, 2013 | Radiation (03CH01-CB) |
| Loop Antenna | Teseq | HLA 6120 | 24155 | 9 kHz - 30 MHz | Nov. 05, 2012* | Radiation (03CH01-CB) |
| Horn Antenna | EMCO | 3115 | 00075790 | 750MHz~18GHz | Nov. 27, 2012 | Radiation (03CH01-CB) |
| Horn Antenna | SCHWARZBEAK | BBHA 9170 | BBHA9170252 | 15GHz ~ 40GHz | Nov. 23, 2012 | Radiation (03CH01-CB) |
| Pre-Amplifier | Agilent | 8447D | 2944A10991 | 0.1MHz ~ 1.3GHz | Nov. 27, 2012 | Radiation (03CH01-CB) |
| Pre-Amplifier | Agilent | 8449B | 3008A02310 | 1GHz ~ 26.5GHz | Nov. 23, 2012 | Radiation (03CH01-CB) |
| Pre-Amplifier | WM | TF-130N-R1 | 923365 | 26.5GHz ~ 40GHz | Jul. 31, 2012 | Radiation (03CH01-CB) |
| Spectrum analyzer | R&S | FSP40 | 100056 | 9KHz~40GHz | Nov. 16, 2012 | Radiation (03CH01-CB) |
| EMI Test Receiver | R&S | ESCS 30 | 100355 | 9KHz ~ 2.75GHz | Mar. 20, 2013 | Radiation (03CH01-CB) |
| Turn Table | INN CO | CO 2000 | N/A | 0 ~ 360 degree | N.C.R | Radiation (03CH01-CB) |
| Antenna Mast | INN CO | CO2000 | N/A | 1 m - 4 m | N.C.R | Radiation (03CH01-CB) |
| RF Cable-low | Woken | Low Cable-1 | N/A | 30 MHz - 1 GHz | Nov. 18, 2012 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-1 | N/A | 1 GHz – 26.5 GHz | Nov. 18, 2012 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-2 | N/A | 1 GHz – 26.5 GHz | Nov. 18, 2012 | Radiation (03CH01-CB) |

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Remark |
|----------------------------|--------------|---------------|----------------|------------------|------------------|-----------------------|
| RF Cable-high | Woken | High Cable-3 | N/A | 1 GHz - 40 GHz | Nov. 18, 2012 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-4 | N/A | 1 GHz - 40 GHz | Nov. 18, 2012 | Radiation (03CH01-CB) |
| Signal analyzer | R&S | FSV40 | 100979 | 9KHz~40GHz | Oct. 08, 2012 | Conducted (TH01-CB) |
| Temp. and Humidity Chamber | Ten Billion | TTH-D3SP | TBN-931011 | -30~100 degree | Jun. 05, 2012 | Conducted (TH01-CB) |
| RF Power Divider | Woken | 2 Way | 0120A02056002D | 2GHz ~ 18GHz | Nov. 18, 2012 | Conducted (TH01-CB) |
| RF Power Divider | Woken | 3 Way | MDC2366 | 2GHz ~ 18GHz | Nov. 18, 2012 | Conducted (TH01-CB) |
| RF Power Divider | Woken | 4 Way | 0120A04056002D | 2GHz ~ 18GHz | Nov. 18, 2012 | Conducted (TH01-CB) |
| RF Cable-high | Woken | High Cable-7 | - | 1 GHz – 26.5 GHz | Nov. 19, 2012 | Conducted (TH01-CB) |
| RF Cable-high | Woken | High Cable-8 | - | 1 GHz – 26.5 GHz | Nov. 19, 2012 | Conducted (TH01-CB) |
| RF Cable-high | Woken | High Cable-9 | - | 1 GHz – 26.5 GHz | Nov. 19, 2012 | Conducted (TH01-CB) |
| RF Cable-high | Woken | High Cable-10 | - | 1 GHz – 26.5 GHz | Nov. 19, 2012 | Conducted (TH01-CB) |
| RF Cable-high | Woken | High Cable-11 | - | 1 GHz – 26.5 GHz | Nov. 19, 2012 | Conducted (TH01-CB) |
| Power Sensor | Anritsu | MA2411B | 0917223 | 300MHz~40GHz | Nov. 28, 2012 | Conducted (TH01-CB) |
| Power Meter | Anritsu | ML2495A | 1035008 | 300MHz~40GHz | Nov. 27, 2012 | Conducted (TH01-CB) |

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. TEST LOCATION

| | |
|--------|--|
| SHIJR | ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255 |
| HWA YA | ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055 |
| LINKOU | ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695 |
| DUNGHU | ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740 |
| JUNGHE | ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626 |
| NEIHU | ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777 |
| JHUBEI | ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085 |