

ATTACHMENT O – SAR TEST PLOTS (2 of 3)

Test Laboratory: HCT

Company : CASIO HITACHI Mobile Communication Co.,Ltd

Mode : PCS1900 /Channel : 25

Liquid Temperature : 21.6℃

Date Tested : October 17, 2006

DUT: G'zOne TYPE-S; Type: Folder; Serial: TYKNX9210-20061000001

Communication System: PCS 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1851.25 \text{ MHz}$; $\sigma = 1.42 \text{ mho/m}$; $\epsilon_r = 40.3$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section ;Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(5.6, 5.6, 5.6); Calibrated: 2006-08-25

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn446; Calibrated: 2006-03-17

- Phantom: SAM 1800/1900 MHz; Type: SAM

Left touch 25/Area Scan (51x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 1.13 mW/g

Left touch 25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$


Reference Value = 23.8 V/m; Power Drift = 0.015 dB

Peak SAR (extrapolated) = 1.73 W/kg

SAR(1 g) = 1.09 mW/g; SAR(10 g) = 0.653 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 1.21 mW/g



Test Laboratory: HCT

Company: CASIO HITACHI Mobile Communication Co., Ltd
Mode: PCS1900 /Channel: 600
Liquid Temperature: 21.6 °C
Date Tested: October 17, 2006

DUT: G'zOne TYPE-S; Type: Folder; Serial: TYKNX9210-20061000001


Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³
Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(5.6, 5.6, 5.6); Calibrated: 2006-08-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2006-03-17
- Phantom: SAM 1800/1900 MHz; Type: SAM

Left touch 600/Area Scan (51x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (interpolated) = 0.895 mW/g

Left touch 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm
Reference Value = 20.3 V/m; Power Drift = -0.012 dB
Peak SAR (extrapolated) = 1.36 W/kg
SAR(1 g) = 0.849 mW/g; SAR(10 g) = 0.504 mW/g
Maximum value of SAR (measured) = 0.945 mW/g



0 dB = 0.945mW/g

Test Laboratory: HCT

Company : CASIO HITACHI Mobile Communication Co.,Ltd
Mode : PCS1900 /Channel : 1175
Liquid Temperature : 21.6°C
Date Tested : October 17, 2006

DUT: G'zOne TYPE-S; Type: Folder; Serial: TYKNX9210-20061000001

Communication System: PCS 1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1908.75$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³

Phantom section: Left Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(5.6, 5.6, 5.6); Calibrated: 2006-08-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2006-03-17
- Phantom: SAM 1800/1900 MHz; Type: SAM

Left touch 1175/Area Scan (51x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.830 mW/g

Left touch 1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm


Reference Value = 19.0 V/m; Power Drift = -0.055 dB

Peak SAR (extrapolated) = 1.28 W/kg

SAR(1 g) = 0.783 mW/g; SAR(10 g) = 0.453 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.874 mW/g



0 dB = 0.874mW/g

Test Laboratory: HCT

Company : CASIO HITACHI Mobile Communication Co.,Ltd
Mode : PCS1900 /Channel : 25
Liquid Temperature : 21.6℃
Date Tested : October 17, 2006

DUT: G'zOne TYPE-S; Type: Folder; Serial: TYKNX9210-20061000001

Communication System: PCS 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 1851.25 \text{ MHz}$; $\sigma = 1.42 \text{ mho/m}$; $\epsilon_r = 40.3$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(5.6, 5.6, 5.6); Calibrated: 2006-08-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2006-03-17
- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 25/Area Scan (51x111x1): Measurement grid: $\Delta x = 15\text{mm}$, $\Delta y = 15\text{mm}$

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (interpolated) = 1.42 mW/g


Right touch 25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8\text{mm}$, $\Delta y = 8\text{mm}$, $\Delta z = 5\text{mm}$

Reference Value = 28.3 V/m; Power Drift = -0.028 dB

Peak SAR (extrapolated) = 2.20 W/kg

SAR(1 g) = 1.34 mW/g; SAR(10 g) = 0.742 mW/g

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 1.52 mW/g



Test Laboratory: HCT

Company : CASIO HITACHI Mobile Communication Co.,Ltd
Mode : PCS1900 /Channel : 25(Bluetooth)
Liquid Temperature : 21.6°C
Date Tested : October 17, 2006

DUT: G'zOne TYPE-S; Type: Folder; Serial: TYKNX9210-20061000001

Communication System: PCS 1900; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1851.25 \text{ MHz}$; $\sigma = 1.42 \text{ mho/m}$; $\epsilon_r = 40.3$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section ;Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(5.6, 5.6, 5.6); Calibrated: 2006-08-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2006-03-17
- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 25/Area Scan (51x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (interpolated) = 1.38 mW/g


Right touch 25/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.9 V/m; Power Drift = 0.173 dB

Peak SAR (extrapolated) = 2.13 W/kg

SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.729 mW/g

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 1.48 mW/g



Test Laboratory: HCT

Company : CASIO HITACHI Mobile Communication Co.,Ltd
Mode : PCS1900 /Channel : 600
Liquid Temperature : 21.6℃
Date Tested : October 17, 2006

DUT: G'zOne TYPE-S; Type: Folder; Serial: TYKNX9210-20061000001

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.44 \text{ mho/m}$; $\epsilon_r = 40.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(5.6, 5.6, 5.6); Calibrated: 2006-08-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2006-03-17
- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 600/Area Scan (51x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.956 mW/g


Right touch 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.2 V/m; Power Drift = -0.168 dB

Peak SAR (extrapolated) = 1.47 W/kg

SAR(1 g) = 0.887 mW/g; SAR(10 g) = 0.493 mW/g

Maximum value of SAR (measured) = 1.00 mW/g



Test Laboratory: HCT

Company : CASIO HITACHI Mobile Communication Co.,Ltd
Mode : PCS1900 /Channel : 1175
Liquid Temperature : 21.6℃
Date Tested : October 17, 2006

DUT: G'zOne TYPE-S; Type: Folder; Serial: TYKNX9210-20061000001

Communication System: PCS 1900; Frequency: 1908.75 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 1908.75$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 40$; $\rho = 1000$ kg/m³

Phantom section: Right Section ; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(5.6, 5.6, 5.6); Calibrated: 2006-08-25
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2006-03-17
- Phantom: SAM 1800/1900 MHz; Type: SAM

Right touch 1175/Area Scan (51x111x1): Measurement grid: $\Delta x = 15$ mm, $\Delta y = 15$ mm

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (interpolated) = 0.928 mW/g

Right touch 1175/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $\Delta x = 8$ mm, $\Delta y = 8$ mm, $\Delta z = 5$ mm


Reference Value = 22.7 V/m; Power Drift = -0.109 dB

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 0.875 mW/g; SAR(10 g) = 0.480 mW/g

Info: Interpolated medium parameters used for SAR evaluation.

Maximum value of SAR (measured) = 0.988 mW/g



Test Laboratory: HCT

Company : CASIO HITACHI Mobile Communication Co.,Ltd

Mode : PCS1900 /Channel : 600

Liquid Temperature : 21.6℃

Date Tested : October 17, 2006

DUT: G'zOne TYPE-S; Type: Folder; Serial: TYKNX9210-20061000001

Communication System: PCS 1900; Frequency: 1880 MHz;Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section ;Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(5.6, 5.6, 5.6); Calibrated: 2006-08-25

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn446; Calibrated: 2006-03-17

- Phantom: SAM 1800/1900 MHz; Type: SAM

Left tilt 600/Area Scan (51x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.514 mW/g


Left tilt 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 6.99 V/m; Power Drift = 0.001 dB

Peak SAR (extrapolated) = 0.680 W/kg

SAR(1 g) = 0.448 mW/g; SAR(10 g) = 0.280 mW/g

Maximum value of SAR (measured) = 0.487 mW/g



Test Laboratory: HCT

Company: CASIO HITACHI Mobile Communication Co., Ltd

Mode: PCS1900 /Channel: 600

Liquid Temperature: 21.6°C

Date Tested: October 17, 2006

DUT: G'zOne TYPE-S; Type: Folder; Serial: TYKNX9210-20061000001

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section; Measurement SW: DASY4, V4.7 Build 44

DASY4 Configuration:

- Probe: ET3DV6 - SN1798; ConvF(5.6, 5.6, 5.6); Calibrated: 2006-08-25

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn446; Calibrated: 2006-03-17

- Phantom: SAM 1800/1900 MHz; Type: SAM

Right tilt 600/Area Scan (51x111x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.422 mW/g

Right tilt 600/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 8.82 V/m; Power Drift = -0.175 dB

Peak SAR (extrapolated) = 0.518 W/kg

SAR(1 g) = 0.370 mW/g; SAR(10 g) = 0.245 mW/g

Maximum value of SAR (measured) = 0.398 mW/g

