

TEST REPORT

For

Mobile Phone

In conformity with

FCC Part22H (01 Oct, 2008)

Model : CDMA CA003

FCC ID : TYKNX6520

Test Item : Mobile Phone

Report No : RY0907P09R1

Issue Date : 09 July, 2009

Prepared for

Casio Hitachi Mobile Communications Co., Ltd.
2-229-1, Sakuragaoka, Higashiyamato-shi, Tokyo,
207-8501, Japan

Prepared by

RF Technologies Ltd.
472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan
Telephone: +81+(0)45- 534-0645
FAX: +81+(0)45- 534-0646

This report shall not be reproduced, except in full, without the written permission of RF Technologies Ltd. The test results in this report apply only to the sample(s) tested. RF Technologies Ltd. is managed to ISO17025 and has the necessary knowledge and test facilities for testing according to the referenced standards.

Table of Contents

1	General information	3
1.1	Product description	3
1.2	Test(s) performed/ Summary of test result	3
1.3	Test facility	4
1.4	Measurement uncertainty	4
1.5	Description of essential requirements and test results.....	5
1.5.1	Transmitter requirements	5
1.5.2	Receiver requirements.....	5
1.5.3	AC Power Line Parameters.....	5
1.5.4	Normal test conditions	5
1.5.5	Extreme test conditions	5
1.6	Setup of equipment under test (EUT)	6
1.6.1	Test configuration of EUT	6
1.6.2	Operating condition:	6
1.6.3	Setup diagram of tested system:.....	7
1.7	Equipment modifications	7
1.8	Deviation from the standard.....	7
2	Test procedure and result.....	8
2.1	Transmitter requirements	8
2.1.1	Carrier Output Power (Conducted)	8
2.1.2	Carrier Output Power (Radiated)	10
2.1.3	Frequency Stability (Temperature)	13
2.1.4	Frequency Stability (Voltage)	15
2.1.5	Occupied Bandwidth.....	17
2.1.6	Transmitter Out of Band Spurious Emissions (Conducted).....	22
2.1.7	Transmitter Out of Band Spurious Emissions (Radiated).....	28
2.1.8	Band Edge Emissions.....	32
2.1.9	Transmitter AC Power Line Emission requirement.....	35
2.2	Receiver requirement	37
2.2.1	Receiver Spurious Emissions (Radiated).....	37
2.2.2	Receiver AC Power Line Emission requirement	39
3	Test setup photographs.....	42
4	List of utilized test equipment/ calibration	44

History

Report No.	Issue Date	Revisions	Issued by
RY0907P09R1	09 July, 2009	Initial Issue	T.Kato

1 General information

1.1 Product description

Test item : Mobile phone
Manufacturer : Casio Hitachi Mobile Communications Co., Ltd.
Address : 2-229-1, Sakuragaoka, Higashiyamato-shi, Tokyo, 207-8501, Japan
Model : CDMA CA003
FCC ID : TYKNX6520
Operating frequency range : TX 824.70 - 848.31 MHz (CDMA850)
: RX 869.70 - 893.31 MHz (CDMA850)
Type of Modulation : QPSK
Receipt date of EUT : 01 July, 2009
Nominal power voltages : 3.7VDC (Lithium-ion battery)
Antenna Type : integral antenna
Serial numbers : SCADU000125 (for Radiated test)
: SCADU000126 (for Conducted test)


1.2 Test(s) performed/ Summary of test result

Applicable Standard(s) : FCC Part22 Subpart H (01 Oct ,2008)
Test(s) started : 03 July, 2009
Test(s) completed : 08 July, 2009
Purpose of test(s) : Grant for Certification of FCC

Summary of test result : Complied

Note: The above judgment is only based on the measurement data and it does not include the measurement uncertainty. Accordingly, the statement below is applied to the test result. The EUT complies with the limit required in the standard in case that the margin is not less than the measurement uncertainty in the Laboratory. Compliance of the EUT is more probable than non-compliance is case that the margin is less than the measurement uncertainty in the Laboratory.

Test engineer

: 
T. Kato (Engineer, EMC Testing Department)

Reviewer

: 
K. Ohnishi (Manager, EMC Testing Department)

1.3 Test facility

The Federal Communications Commission has reviewed the technical characteristics of the test facilities at RF Technologies Ltd., located in 472, Nippa-cho, Kohoku-ku, Yokohama, 223-0057, Japan, and has found these test facilities to be in compliance with the requirements of 47 CFR Part 15, section 2.948, per October 01, 2007.

The description of the test facilities has been filed under registration number 319924 at the Office of the Federal Communications Commission. The facility has been added to the list of laboratories performing these test services for the public on a fee basis.

The list of all public test facilities is available on the Internet at <http://www.fcc.gov>.

Registered by Voluntary Control Council for Interference by Information Technology Equipment (VCCI).

Each registered facility number is as follows;

Test site (Semi-anechoic chamber 3m) R-2393

Test site (Shielded room) C-2617

Registered by Industry Canada (IC). The registered facility number is as follows;

Test site No.1(Semi-anechoic chamber 3m) : 6974A-1

Accredited by **National Voluntary Laboratory Accreditation Program** (NVLAP) for the emission tests stated in the scope of the certificate under Certificate Number 200780-0

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB CODE 200780-0

1.4 Measurement uncertainty

The treatment of uncertainty is based on the general matters on the definition of uncertainty in “Guide to the expression of uncertainty in measurement (GUM)” published by ISO. The Lab’s uncertainty is determined by referring UKAS Publication LAB34: 2002 “The Expression of Uncertainty in EMC Testing” and CISPR16-4-2: 2003 “Uncertainty in EMC Measurements”.

The uncertainty of the measurement result in the level of confidence of approximately 95% (k=2) is as follows;

RF frequency : $\pm 1 \times 10^{-7}$

RF conducted level : ± 1.0 dB

AC Power line emission : ± 1.9 dB

Radiated emission (30MHz - 1000MHz) : ± 5.7 dB

Radiated emission (above 1000MHz) : ± 5.8 dB

Temperature : ± 1 degree

Humidity : ± 5 %

1.5 Description of essential requirements and test results

An overview of radio requirements, as laid out in FCC Part22 are given below.

1.5.1 Transmitter requirements

Test Description	Section in this report	Applicable	Result
22.913 Carrier Output Power (Conducted)	2.1.1	Yes	Passed
22.913 Carrier Output Power (Radiated)	2.1.2	Yes	Passed
22.355 Frequency Stability (Temperature Variation)	2.1.3	Yes	Passed
22.355 Frequency Stability (Voltage Variation)	2.1.4	Yes	Passed
2.1049 Occupied Bandwidth	2.1.5	Yes	Passed
22.917 Out of Band Emissions (Conducted)	2.1.6	Yes	Passed
22.917 Out of Band Emissions (Radiated)	2.1.7	Yes	Passed
22.917 Band Edge Emissions	2.1.8	Yes	Passed

1.5.2 Receiver requirements

Test Description	Section in this report	Applicable	Result
15.109 Radiated Spurious Emissions	2.2.1	Yes	Passed

1.5.3 AC Power Line Parameters

Test Description	Section in this report	Applicable	Result
15.107 AC line Spurious Emissions (Idle mode)	2.3.1	Yes	Passed
15.207 AC line Spurious Emissions (Traffic mode)	2.3.2	Yes	Passed

1.5.4 Normal test conditions

Temperature(*) : +15 degC to +35 degC
Relative humidity(*) : 20 % to 75 %
Supply voltage : 3.7 VDC (Nominal)
Measurement Frequency : 824.70 MHz(1013ch), 836.52 MHz(384ch), 848.31 MHz(777ch)

* When it is impracticable to carry out tests under these conditions, a note to this effect, stating the ambient temperature and relative humidity during the tests, must be stated separately.

1.5.5 Extreme test conditions

Temperature : -30 °C (min) to +50 °C (max)
Supply voltage : 3.4 VDC (min) to 4.2 VDC (max)
The equipment has a function that it is automatically turned off when min. battery voltage (3.4 V) is detected.

1.6 Setup of equipment under test (EUT)

1.6.1 Test configuration of EUT

Equipment(s) under test:

	Item	Manufacturer	Model No.	Serial No.	FCC ID No.
A	Mobile phone	Cashio Hitachi Mobile Communications Co., Ltd.	CDMA CA003	SCADU000125	TYKNX6520
B	Mobile phone	Cashio Hitachi Mobile Communications Co., Ltd.	CDMA CA003 (RF cable is attached instead of integral antenna)	SCADU000126	TYKNX6520
C	Battery pack	CASIO	CA003UAA	None	N/A
D	AC Adaptor	MITSUMI ELECTRIC	0203PQA	None	N/A

Connected cable(s):


No.	Item	Identification (Manu.e.t.c)	Shielded YES / NO	Ferrite Core YES / NO	Connector Type Shielded YES / NO	Length (m)
1	DC power cable	-	No	No	No	1.5

1.6.2 Operating condition:

- Traffic mode : EUT is connected with RF tester in Max power level.
RC3/SO55 with Power Control Bit "ALL UP" was worst condition in all test items.
These conditions were set for all transmitter tests in this report.
- Idle mode : EUT is under idle mode, no output power is transmitted.

1.6.3 Setup diagram of tested system:

[Configuration I]



[Configuration II]



1.7 Equipment modifications

No modifications have been made to the equipment in order to achieve compliance with the applicable standards described in clause 1.2.

1.8 Deviation from the standard

No deviations from the standards described in clause 1.2.

2 Test procedure and result

2.1 *Transmitter requirements*

2.1.1 Carrier Output Power (Conducted)

Reference Standard

FCC : Part22.913, 2.0146

Test Conditions

Date: 06 July, 2009
Ambient Temperature: 24 degC
Relative humidity: 59 %
Test Voltage: 3.7 V

Test Sample

Configuration II

Test Method

- a) EUT is connected to RF tester with pseudo random data modulation and set to maximum output power level.
- b) The output power is measured with RF tester.

Test Setup



Test Results

Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Result
Bottom (1013ch)	824.70	23.9	38.4	Pass
Middle (384ch)	836.52	24.1	38.4	Pass
Top (777ch)	848.31	23.9	38.4	Pass

Test Equipment Used

Equipment name	RFT ID No.
RF tester	RC02

Final Result

The EUT met the requirements of the standard for this test.

2.1.2 Carrier Output Power (Radiated)

Reference Standard

FCC : Part22.913, 2.0146

Test Conditions

Date: 07 July, 2009
Ambient Temperature: 18 degC
Relative humidity: 60 %
Test Voltage: 3.7 V

Test Sample

Configuration I

Test Method

Substitution method is used for this test.

- a) EUT is set on non-conducting turntable and the output power is set to the maximum level.
- b) As a receive antenna, Horn antenna is used for high frequency range (above 1GHz), and Bilogical antenna is used for low frequency range (30MHz to 1GHz).
- c) Maximum power is measured by a spectrum analyzer(SA) in below conditions.

Turntable is rotated 360 degrees.

The height of receive antenna is changed from 1m to 4m.

Receive antenna polarization is set to vertical and horizontal.

This maximum power is recorded.


During this measurement, receive antenna is adjusted the direction to keep the EUT within the beamwidth of receive antenna.

- d) Reference antenna is replaced with EUT, and connected with signal generator(SG).
SG output power is adjusted to get same level as the recorded maximum radiated EUT power by SA.
- e) Radiated output power (Pout) is calculated with adjusted SG output (Psg) [dBm], reference antenna gain (Gref) [dBd] and cable loss between SG and reference antenna (Lcab) [dB].


$$P_{out} [\text{dBm e.r.p}] = P_{sg} + G_{ref} + L_{cab}$$

Test Setup

[Measurement]



[Substitution]



Test Results

Channel	Frequency (MHz)	Output Power (dBm e.r.p)	Limit (dBm e.r.p)	Result
Bottom (1013ch)	824.70	21.5	38.4	Pass
Middle (384ch)	836.52	22.1	38.4	Pass
Top (777ch)	848.31	21.8	38.4	Pass

Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06
Receive Antenna	DH02
Reference Antenna	LA02
Signal Generator	SG05
Power Meter	PM03
RF tester	RC02

Final Result

The EUT met the requirements of the standard for this test.

2.1.3 Frequency Stability (Temperature)

Reference Standard

FCC : Part22.355, 2.1055

Test Conditions

Date: 03 July, 2009
Ambient Temperature: 23 degC
Relative humidity: 69 %
Test Voltage: 3.7 V

Test Sample


Configuration II

Test Method

To measure the carrier frequency, "Frequency error measurement" function of RF tester is used.

- a) EUT is hold about 30 minutes under measurement temperature condition.
 - b) EUT is powered on with nominal voltage.
 - c) EUT is connected to RF tester with Max transmit power level.
 - d) Frequency error is measured by RF tester.
- Process b) to d) must be finished within 2 minutes to prevent EUT warming.
- e) Process a) to d) is repeated at 10deg increments from -30 to +50degC.

Test Setup



Test Results**Worst condition (Middle Channel 384ch, Nominal Freq.:836.52MHz)**

Temperature (deg C)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Result
-30	-33	- 0.04	± 2.5	Passed
-20	+16	0.02	± 2.5	Passed
-10	-13	- 0.02	± 2.5	Passed
0	+13	0.02	± 2.5	Passed
10	+11	0.01	± 2.5	Passed
20	-11	- 0.01	± 2.5	Passed
30	-15	- 0.02	± 2.5	Passed
40	-11	- 0.01	± 2.5	Passed
50	-12	- 0.01	± 2.5	Passed

Test Equipment Used

Equipment name	RFT ID No.
RF tester	RC02
Temp Chamber	TC01

Final Result

The EUT met the requirements of the standard for this test

2.1.4 Frequency Stability (Voltage)

Reference Standard

FCC : Part22.355, 2.1055

Test Conditions

Date: 03 July, 2009
Ambient Temperature: 23 degC
Relative humidity: 69 %
Test Voltage: 3.4 V to 4.2 V

Test Sample


Configuration II

Test Method

To measure the carrier frequency, “Frequency error measurement” function of RF tester is used.

- EUT is powered on with nominal voltage. Temperature is 20degC.
- EUT is connected to RF tester with Max transmitter power level.
- Frequency error is measured by RF tester.
- Process a) to c) is repeated at minimum and maximum voltage condition.

Test Setup



Test Results**Worst condition (Middle Channel 383ch, Nominal Freq.:836.49MHz)**

Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Result
3.40	-10	- 0.01	± 2.5	Passed
3.70	-11	- 0.01	± 2.5	Passed
4.20	-11	- 0.01	± 2.5	Passed

Test Equipment Used

Equipment name	RFT ID No.
RF tester	RC02
Temp chamber	TC01

Final Result

The EUT met the requirements of the standard for this test

2.1.5 Occupied Bandwidth

Reference Standard

FCC : Part2.1049

Test Conditions

Date: 06 July, 2009
Ambient Temperature: 24 degC
Relative humidity: 59 %
Test Voltage: 3.7 V


Test Sample

Configuration II

Test Method

- EUT is connected to RF tester with Max transmitter power level.
- 26dB bandwidth is measured by Spectrum Analyzer.
- 99% occupied bandwidth of transmitter spectrum is measured by Spectrum Analyzer.
RBW is changed to 1% of 26dB bandwidth.

Test Setup



Test Results


Occupied Bandwidth (99%)

Channel	Frequency (MHz)	RBW (kHz)	VBW (kHz)	Occupied Bandwidth (MHz)
Bottom (1013ch)	824.70	20kHz	50kHz	1.280
Middle (384ch)	836.52	20kHz	50kHz	1.280
Top (777ch)	848.31	20kHz	50kHz	1.280


26dB Bandwidth

Channel	Frequency (MHz)	RBW (kHz)	VBW (kHz)	26dB Bandwidth (MHz)
Bottom (1013ch)	824.70	10kHz	30kHz	1.427
Middle (384ch)	836.52	10kHz	30kHz	1.426
Top (777ch)	848.31	10kHz	30kHz	1.426


Graphical Data




1013ch Occupied Bandwidth




384ch Occupied Bandwidth




777ch Occupied Bandwidth



1013ch 26dB Bandwidth



384ch 26dB Bandwidth



777ch 26dB Bandwidth

Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06
RF tester	RC02

2.1.6 Transmitter Out of Band Spurious Emissions (Conducted)

Reference Standard

FCC : Part22.917

Test Conditions

Date: 06 July, 2009
Ambient Temperature: 24 degC
Relative humidity: 59 %
Test Voltage: 3.7 V

Test Sample


Configuration II

Test Method


- EUT is connected to RF tester with Max transmitter power level.
- Out of band Spurious is measured by Spectrum Analyzer.
- Resolution band width of spectrum analyzer is set to 1MHz (above 1GHz) or 100kHz (below 1GHz).

Test Setup

30MHz to 1500MHz



above 1500MHz



Test Results

Bottom Channel (1013ch, Nominal Freq.:824.70MHz)

Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level (dBm)	Limit (dBm)	Result Pass/Fail
1649.40	1	-39.5	-13.0	Pass
2474.10	1	-50.5	-13.0	Pass
3298.80	1	-56.0	-13.0	Pass
4123.50	1	< -60	-13.0	Pass
4948.20	1	< -60	-13.0	Pass
5772.90	1	-56.2	-13.0	Pass
6597.60	1	< -60	-13.0	Pass
7422.30	1	< -60	-13.0	Pass
8247.00	1	-56.8	-13.0	Pass
others		none	-13.0	Pass


Middle Channel (384ch, Nominal Freq.:836.52MHz)



Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level (dBm)	Limit (dBm)	Result Pass/Fail
1673.04	1	-39.1	-13.0	Pass
2509.56	1	-51.2	-13.0	Pass
3346.08	1	-55.4	-13.0	Pass
4182.60	1	-59.3	-13.0	Pass
5019.12	1	< -60	-13.0	Pass
5855.64	1	-53.7	-13.0	Pass
6692.16	1	< -60	-13.0	Pass
7528.68	1	< -60	-13.0	Pass
8365.20	1	-53.4	-13.0	Pass
others		none	-13.0	Pass


Top Channel (777ch, Nominal Freq.:848.31MHz)


Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level (dBm)	Limit (dBm)	Result Pass/Fail
1696.62	1	-41.0	-13.0	Pass
2544.93	1	-51.4	-13.0	Pass
3393.24	1	-56.4	-13.0	Pass
4241.55	1	-58.1	-13.0	Pass
5089.86	1	< -60	-13.0	Pass
5938.17	1	-54.2	-13.0	Pass
6786.48	1	< -60	-13.0	Pass
7634.79	1	-57.4	-13.0	Pass
8483.10	1	-50.8	-13.0	Pass
others		none	-13.0	Pass

Graphical Data (384ch)









Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06
RF tester	RC02

Final Result

The EUT met the requirements of the standard for this test.

2.1.7 Transmitter Out of Band Spurious Emissions (Radiated)

Reference Standard

FCC : Part22.917

Test Conditions

Date: 07 July, 2009 (above 1000MHz), 08 July, 2009 (below 1000MHz)
Ambient Temperature: 18 degC (07 Jul), 18 degC (08 Jul)
Relative humidity: 60 % (07 Jul), 59 % (08 Jul)
Test Voltage: 3.7 V

Test Sample

Configuration I

Test Method

Substitution method is used for this test.

- a) EUT is set on non-conducting turntable and the output power is set to the maximum level.
- b) As a receive antenna, Horn antenna is used for high frequency range (above 1GHz), and Bilogical antenna is used for low frequency range (30MHz to 1GHz).
- c) The maximum level of each spurious emission is measured by a spectrum analyzer(SA) in below conditions.

Turntable is rotated 360 degrees.

The height of receive antenna is changed from 1m to 4m.

Receive antenna polarization is set to vertical and horizontal.

EUT was placed at three different orientations (X, Y and Z axis) in order to find the worst orientation.

This emission level is recorded.


During this measurement, receive antenna is adjusted the direction to keep the EUT within the beamwidth of receive antenna.

- d) Reference antenna is replaced with EUT, and connected with signal generator(SG).
SG output power is adjusted to get same level as the recorded maximum radiated EUT power by SA.
- e) Radiated output power (Pout) is calculated with adjusted SG output (Psg) [dBm], reference antenna gain (Gref) [dBd] and cable loss between SG and reference antenna (Lcab) [dB].


$$P_{out} [\text{dBm e.r.p}] = P_{sg} + G_{ref} + L_{cab}$$

Test Setup

[Measurement]



[Substitution]



Test Results

Bottom Channel (1013ch, Nominal Freq.:824.70MHz)

Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level(dBm)		Limit (dBm)	Result Pass/Fail
		Vertical	Horizontal		
1649.40	1	-35.9	-32.6	-13.0	Pass
2474.10	1	-24.8	-23.5	-13.0	Pass
3298.80	1	-27.4	-27.2	-13.0	Pass
4123.50	1	-38.7	-38.6	-13.0	Pass
4948.20	1	-38.9	-39.0	-13.0	Pass
5772.90	1	-43.4	-39.4	-13.0	Pass
6597.60	1	-34.8	-33.4	-13.0	Pass
7422.30	1	-36.6	-38.3	-13.0	Pass
8247.00	1	-41.7	-43.2	-13.0	Pass
3478.80	1	-46.8	-46.2	-13.0	Pass

Middle Channel (384ch, Nominal Freq.:836.52MHz)

Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level(dBm)		Limit (dBm)	Result Pass/Fail
		Vertical	Horizontal		
1673.04	1	-32.5	-28.7	-13.0	Pass
2509.56	1	-23.1	-22.5	-13.0	Pass
3346.08	1	-24.5	-23.0	-13.0	Pass
4182.60	1	-34.3	-34.5	-13.0	Pass
5019.12	1	-35.1	-32.4	-13.0	Pass
5855.64	1	-38.6	-34.8	-13.0	Pass
6692.16	1	-33.0	-31.1	-13.0	Pass
7528.68	1	-30.9	-32.4	-13.0	Pass
8365.20	1	-36.5	-38.8	-13.0	Pass
3526.08	1	-48.8	-45.3	-13.0	Pass

Top Channel (777ch, Nominal Freq.:848.31MHz)

Measurement Frequency (MHz)	Measurement Bandwidth (MHz)	Emission Level(dBm)		Limit (dBm)	Result Pass/Fail
		Vertical	Horizontal		
1696.62	1	-30.6	-27.1	-13.0	Pass
2544.93	1	-20.9	-19.8	-13.0	Pass
3393.24	1	-21.5	-24.5	-13.0	Pass
4241.55	1	-33.6	-32.2	-13.0	Pass
5089.86	1	-33.8	-27.6	-13.0	Pass
5938.17	1	-35.7	-32.8	-13.0	Pass
6786.48	1	-31.2	-28.6	-13.0	Pass
7634.79	1	-26.4	-27.0	-13.0	Pass
8483.10	1	-32.3	-34.4	-13.0	Pass
3573.24	1	-45.7	-47.6	-13.0	Pass

Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06
Receive Antenna	DH02
Reference Antenna	DH01
Pre AMP	PR12
Filter	BRF3, HPF2
Signal Generator	SG05
Power Meter	PM03
RF tester	RC02

Final Result

The EUT met the requirements of the standard for this test.

2.1.8 Band Edge Emissions

Reference Standard

FCC : Part22.917

Test Conditions

Date: 06 July, 2009
Ambient Temperature: 24 degC
Relative humidity: 59 %
Test Voltage: 3.7 V


Test Sample

Configuration II

Test Method

- EUT is connected to RF tester with Max transmitter power level.
- Lower band edge level is measured in bottom channel transmission.
- Higher band edge level is measured in top channel transmission.
- 1% of band width is used for resolution band width for spectrum analyzer.

Test Setup



Test Results


Bottom Band Edge

Measured Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Result
824.0	-14.9	-13.0	Passed


Top Band Edge

Measured Frequency (MHz)	Peak Level	Limit	Result
849.0	-13.4	-13.0	Passed

Graphical Data



Bottom band edge



Top band edge

Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR06
RF tester	RC02

Final Result

The EUT met the requirements of the standard for this test.

2.1.9 Transmitter AC Power Line Emission requirement

Reference Standard

FCC : Part15.207

Test Conditions

Date: 08 July, 2009
Ambient Temperature: 18 degC
Relative humidity: 59 %
Test Voltage: 3.7 V


Test Sample

Configuration I

Test Method

- EUT is connected to RF tester with Max transmitter power level.
- AC power is supplied to AC charger through LISN.
- AC charger is connected to EUT.
- AC Power Line emission is measured by EMI receiver.
Both Live/Neutral is measured emission level.

Test Setup



Limit


Frequency (MHz)	Limit QP (dBuV)	Limit AV (dBuV)
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

Test Results

Worst condition (Middle Channel 383ch, Nominal Freq.:836.49MHz)

Frequency [MHz]	Reading dB [QP]	Reading dB [AV]	C.Fac [dB]	Result dB μ V [QP]	Result dB μ V [AV]	Limit dB μ V [QP]	Limit dB μ V [AV]	Margin dB [QP]	Margin dB [AV]	Line	
0.214	38.2	22.5	0.2	38.4	22.7	63.0	53.0	24.6	30.3	Va	Pass
1.945	35.5	16.4	0.5	36.0	16.9	56.0	46.0	20.0	29.1	Va	Pass
0.214	40.7	25.8	0.2	40.9	26.0	63.0	53.0	22.1	27.0	Vb	Pass
1.880	28.6	8.8	0.5	29.1	9.3	56.0	46.0	26.9	36.7	Vb	Pass
1.985	28.2	10.5	0.5	28.7	11.0	56.0	46.0	27.3	35.0	Vb	Pass

Graphical Data



Test Equipment Used

Equipment name	RFT ID No.
EMI Receiver	TR04
LISN	LN06
RF tester	RC02

Final Result

The EUT met the requirements of the standard for this test

2.2 Receiver requirement

2.2.1 Receiver Spurious Emissions (Radiated)

Reference Standard

FCC : Part15.109

Test Conditions

Date: 07 July, 2009 (above 1000MHz), 08 July, 2009 (below 1000MHz)
Ambient Temperature: 18 degC (07 Jul), 18 degC (08 Jul)
Relative humidity: 60 % (07 Jul), 59 % (08 Jul)
Test Voltage: 3.7 V


Test Sample

Configuration I

Test Method

- EUT is connected to RF tester with idle mode.
- Radiated receiver spurious emission is received by receive antenna.
- Turn table is rotated 360deg.
- Maximum level of each spurious is measured by spectrum analyzer.
- RBW of spectrum analyzer is set to 100kHz for 30 - 1000MHz, 1MHz for above 1GHz.
- Level is measured with QP detect for 30 - 1000MHz, Average detect for above 1GHz.
- EUT was placed at three different orientations (X, Y and Z axis) in order to find the worst orientation.

Test Setup



Limit

Frequency (MHz)	Distance (m)	Field strength (uV/m)	Field strength (dBuV/m)
30 - 88	3	100	40.0
88 - 216	3	150	43.5
216 - 960	3	200	46.0
above 960	3	500	53.9

Test Results

Worst condition (Middle Channel 383ch)

Frequency (MHz)	Antenna	Field strength (dBuV/m)	Limit (dBuV/m)	Result
42.91	Vert	26.4	40.0	Passed
3526.08	Hori	52.0	53.9	Passed

Test Equipment Used

Equipment name	RFT ID No.
Spectrum Analyzer	TR04, TR06
Receive Antenna	BA04, DH01
Pre-AMP	PR03, PR12
RF tester	RC02

Final Result

The EUT met the requirements of the standard for this test.

2.2.2 Receiver AC Power Line Emission requirement

Reference Standard

FCC : Part15.107

Test Conditions

Date: 08 July, 2009
Ambient Temperature: 18 degC
Relative humidity: 59 %
Test Voltage: 3.7 V


Test Sample

Configuration I

Test Method

- EUT is connected to RF tester with idle mode.
- AC power is supplied to AC charger through LISN.
- AC charger is connected to EUT.
- AC Power Line emission is measured by EMI receiver.
Both Live/Neutral is measured emission level.

Test Setup



Limit


Frequency (MHz)	Limit QP (dBuV)	Limit AV (dBuV)
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

Test Results

The EUT could not achieved continuous receiving mode, therefore the measurement was carried out under receiving ready condition of the EUT. The EUT is registered to the RF tester.

Frequency [MHz]	Reading dB [QP]	Reading dB [AV]	C.Fac [dB]	Result dB μ V [QP]	Result dB μ V [AV]	Limit dB μ V [QP]	Limit dB μ V [AV]	Margin dB [QP]	Margin dB [AV]	Line	
0.154	43.7	30.1	0.3	44.0	30.4	65.8	55.8	21.8	25.4	Va	Pass
0.169	47.3	31.8	0.3	47.6	32.1	65.0	55.0	17.4	22.9	Va	Pass
2.259	31.3	19.2	0.5	31.8	19.7	56.0	46.0	24.2	26.3	Va	Pass
2.627	30.0	15.2	0.5	30.5	15.7	56.0	46.0	25.5	30.3	Va	Pass
2.893	29.8	16.0	0.5	30.3	16.5	56.0	46.0	25.7	29.5	Va	Pass
0.154	42.4	27.6	0.3	42.7	27.9	65.8	55.8	23.1	27.9	Vb	Pass
0.167	49.5	37.5	0.3	49.8	37.8	65.1	55.1	15.3	17.3	Vb	Pass
1.982	28.1	13.1	0.5	28.6	13.6	56.0	46.0	27.4	32.4	Vb	Pass
2.865	28.0	12.8	0.5	28.5	13.3	56.0	46.0	27.5	32.7	Vb	Pass

Graphical Data



Test Equipment Used

Equipment name	RFT ID No.
EMI Receiver	TR04
LISN	LN06
RF tester	RC02

Final Result

The EUT met the requirements of the standard for this test

4 List of utilized test equipment/ calibration

RFT ID No.	Kind of Equipment and Precision	Manufacturer	Model No.	Serial Number	Calibration Date	Calibrated until
AC01	Anechoic Chamber (1st test room)	JSE	203397C	-	2008/7/4	2009/7/31
BA04	Biological Antenna	SCHAFFNER	CA2855	2903	2009/1/6	2010/1/31
BRF4	Band Reject Filter (WCDMA850)	M-City	BRF0835-01	RF0004	2009/4/8	2010/4/30
CL11	Antenna Cable for RE	RFT	-	-	2009/4/13	2010/4/30
CL23	RF Cable 0.5m	SUCOFLEX	SF104PE	48773/4PE	2009/6/25	2010/6/30
CL24	RF Cable 5.0m	SUCOFLEX	SF104PE	48775/4PE	2009/6/25	2010/6/30
CL26	RF Cable 2.0m	SUCOFLEX	SF104	274754/4	2009/6/25	2010/6/30
CL27	RF Cable 0.5m	SUCOFLEX	SF104	230286/4	2009/6/29	2010/6/30
DC01	Directional Coupler	KRYTAR	1850	77202	2009/5/18	2010/5/31
HPF2	High Pass Filter (1500MHz)	M-City	HPF0900-01	RF0003-01	2009/6/25	2010/6/30
LN06	LISN	Kyoritsu	KNW-407	8-1773-3	2009/5/26	2010/5/31
PM03	Power Meter	Anritsu	ML2438A	99070001	2008/7/24	2009/7/31
PR03	Pre. Amplifier	Anritsu	MH648A	M41984	2009/5/26	2010/5/31
PR12	Pre. Amplifier (1-26G)	Agilent Technologies	8449B	3008A02513	2009/1/13	2010/1/31
PU03	Power Sensor	Anritsu	MA2472A	990103	2008/7/24	2009/7/31
TR04	Test Receiver (F/W : 3.82 SP1)	Rohde & Schwarz	ESCI	100447	2008/9/16	2009/9/30
TR06	Test Receiver (F/W : 3.93 SP2)	Rohde & Schwarz	ESU26	100002	2008/9/2	2009/9/30
DH01	DRG Horn Antenna	A.H. Systems	SAS-571	785	2008/1/31	2010/1/31
DH02	DRG Horn Antenna	A.H. Systems	SAS-200/571	239	2009/4/13	2011/4/30
RC02	Radio communication tester (F/W : V5.00)	Rohde & Schwarz	CMU200	105097	2008/9/17	2009/9/30
SG05	Signal Generator	Rohde & Schwarz	SMR20	100905	2009/6/18	2010/6/30
TC01	Temperature Chamber	ESPEC	SH-641	92000964	2008/11/17	2009/11/30

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.