

# FCC CERTIFICATION TEST REPORT

**FCC ID: TZ8-COOLER445**

Report Reference No..... : 16FBS09029 11

FCC 2.948 No..... : 923232

Date of issue..... : 2016-09-20

Testing Laboratory..... : ATT Product Service Co., Ltd.

Address..... : No. 3, ChangLianShan Industrial Park, ChangAn Town,  
DongGuan City, GuangDong, China.

Applicant's name ..... : Evervictory Electronic Company Limited

Address..... : Chu-Chi Management District, Hu-men Town, Dong Guan  
City, Guang Dong Province, P.R.China

Manufacturer..... : Evervictory Electronic Company Limited

Test specification:

Test item description..... : Cooler Amplified BT speaker System


Trade Mark ..... : N/A

Model/Type reference ..... : COOLER-445

Serial Model ..... : N/A


Ratings..... : I/P: 12Vdc

Responsible Engineer :



Mary Ye

Authorized Signatory:



King Wang

## TABLE OF CONTENTS

1.	Summary of test results .....	5
2.	General test information.....	6
2.1.	Description of EUT .....	6
2.2.	Accessories of EUT .....	6
2.3.	Assistant equipment used for test .....	6
2.4.	Block diagram of EUT configuration for test .....	7
2.5.	Test environment conditions .....	8
2.6.	Measurement uncertainty .....	8
3.	20dB Bandwidth .....	9
3.1.	Test equipment.....	9
3.2.	Block diagram of test setup .....	9
3.3.	Limits.....	9
3.4.	Test Procedure .....	9
3.5.	Test Result .....	10
3.6.	Original test data .....	10
4.	CARRIER FREQUENCY SEPARATION TEST .....	15
4.1.	Test equipment.....	15
4.2.	The Requirement For Section 15.247(a)(1) .....	15
4.3.	EUT Configuration on Measurement.....	15
4.4.	Operating Condition of EUT .....	15
4.5.	Test Procedure .....	15
4.6.	Test Result .....	16
5.	NUMBER OF HOPPING FREQUENCY TEST .....	22
5.1.	Test equipment.....	22
5.2.	The Requirement For Section 15.247(a)(1)(iii).....	22
5.3.	EUT Configuration on Measurement.....	22
5.4.	Operating Condition of EUT .....	22
5.5.	Test Procedure .....	22
5.6.	Test Result .....	23
6.	DWELL TIME TEST.....	24
6.1.	Test equipment.....	24
6.2.	The Requirement For Section 15.247(a)(1)(iii).....	24
6.3.	EUT Configuration on Measurement.....	24
6.4.	Operating Condition of EUT .....	24
6.5.	Test Procedure .....	24

6.6.	Test Result .....	25
7.	Maxmum Output Power .....	31
7.1.	Test equipment.....	31
7.2.	Block diagram of test setup .....	31
7.3.	Limits.....	31
7.4.	Test Procedure .....	32
7.5.	Test Result .....	32
7.6.	Original test data .....	33
8.	CONDUCTED EMISSION MEASUREMENT .....	38
8.1.	POWER LINE CONDUCTED EMISSION .....	38
8.2.	MEASUREMENT INSTRUMENTS LIST .....	38
8.3.	TEST PROCEDURE .....	39
8.4.	DEVIATION FROM TEST STANDARD.....	39
8.5.	TEST SETUP.....	39
8.6.	EUT OPERATING CONDITIONS.....	39
8.7.	TEST RESULT .....	40
9.	Spurious Emission .....	42
9.1.	Test equipment.....	42
9.2.	Block diagram of test setup .....	42
9.3.	Limit.....	44
9.4.	Test Procedure .....	45
9.5.	Test result(Below 30MHz) .....	47
10.	100 kHz BANDWIDTH OF FREQUENCY BAND EDGE .....	52
10.1.	Test Equipment .....	52
10.2.	Limit.....	52
10.3.	Test Procedure .....	52
10.4.	Test result.....	53
11.	Antenna Requirements.....	60
11.1.	Limit.....	60
11.2.	EUT ANTENNA.....	60

## TEST REPORT DECLARE

<b>Applicant</b>	:	Evervictory Electronic Company Limited
<b>Address</b>	:	Chu-Chi Management District, Hu-men Town, Dong Guan City, Guang Dong Province, P.R.China
<b>Equipment under Test</b>	:	Cooler Amplified BT speaker System
<b>Test Model No</b>	:	COOLER-445
<b>Serial Model</b>	:	N/A
<b>FCC ID</b>	:	TZ8-COOLER445
<b>Manufacturer</b>	:	Evervictory Electronic Company Limited
<b>Address</b>	:	Chu Chi Management District, Hu Men Town, Dong-Guan City, Guang-Dong Province, P.R.China

**Test Standard Used:** FCC Rules and Regulations Part 15 Subpart C: 2016.

**Test procedure used:** ANSI C63.10-2013 , DA 00-705, ANSI C63.4-2014

**We Declare:**

The equipment described above is tested by ATT Product Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and ATT Product Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

**After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.**

<b>Report No:</b>	16FBS09029 11		
<b>Date of Test:</b>	2016-09-09 To 2016-09-20	<b>Date of Report:</b>	2016/09/20

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of ATT Product Service Co., Ltd.

## 1. SUMMARY OF TEST RESULTS

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
20dB Bandwidth	FCC Part 15: 15.247(a)( 1)	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)( 1)	PASS
Number Of Hopping Frequency	FCC Part 15: 15.247(a)( 1) (iii)	PASS
Dwell Time Test	FCC Part 15: 15.247(a)( 1) (iii)	PASS
Maximum Output Power	FCC Part 15: 15.247(b)(1)	PASS
Radiated Spurious Emissions	FCC Part 15.247(c)	PASS
Band Edge Emission	FCC Part 15.205	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
Conducted Emission	FCC Part 15.207	PASS

## 2. GENERAL TEST INFORMATION

### 2.1. DESCRIPTION OF EUT

EUT* Name	:	Cooler Amplified BT speaker System
Model Number	:	COOLER-445
Serial Model	:	N/A
Model Difference	:	N/A
EUT function description	:	Please reference user manual of this device
Power supply	:	12Vdc
Operation frequency	:	2402-2480MHz
Modulation	:	GFSK, $\pi/4$ DQPSK,8DPSK
Antenna Type	:	PCB antenna, maximum PK gain: 0 dBi
Date of Receipt	:	2016/09/09
Sample Type	:	Single production

### 2.2. ACCESSORIES OF EUT


Description of Accessories	Manufacturer	Model number	SN
Rechargeable batteries	Ao Neng	6-DZM-10	/
Speaker 1	TRACER	TRG-495	/
Speaker 2	Enjoy	PS-101	/
Iphone 6S	Apple	A1688	/
DC source	LONG WEI	TRP-3010D	020215651

### 2.3. ASSISTANT EQUIPMENT USED FOR TEST


Description of Assistant equipment	Manufacturer	Model number or Type	EMC Compliance	SN
Notebook	acer	Aspire E1-472G	FCC DoC	/

## 2.4. BLOCK DIAGRAM OF EUT CONFIGURATION FOR TEST

### Radiated Spurious Emission Test



### Conducted Emission Test



EUT was connected to control to a special test jig provided by manufacturer which has a Micro USB connector to connect to Notebook, and the Notebook will run a special test software to control EUT work in Continuous TX mode, and select test channel, wireless mode and data rate.

Remark: GFSK,8DPSK, $\pi/4$ DQPSK all these modulation all have been tested , GFSK is found as worst case and only reported for radiated emission.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
GFSK	1	Low :CH0	2402
	1	Middle: CH39	2441
	1	High: CH78	2480
$\pi/4$ DQPSK	2	Low :CH0	2402
	2	Middle: CH39	2441
	2	High: CH78	2480
8DPSK	3	Low :CH0	2402
	3	Middle: CH39	2441
	3	High: CH78	2480

Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

## 2.5. TEST ENVIRONMENT CONDITIONS

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

## 2.6. MEASUREMENT UNCERTAINTY

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.44dB
Uncertainty for Radiation Emission test (9KHz-30MHz)	3.21dB
Uncertainty for Radiation Emission test (30MHz-200MHz)	3.42 dB (Polarize: V)
	3.52 dB (Polarize: H)
Uncertainty for Radiation Emission test (200MHz-1GHz)	3.52 dB (Polarize: V)
	3.54 dB (Polarize: H)
Uncertainty for Radiation Emission test (1GHz to 25GHz)	4.20 dB (Polarize: V)
	4.20 dB (Polarize: H)
Uncertainty for radio frequency	1×10-9
Uncertainty for conducted RF Power	0.65dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.




### 3. 20dB BANDWIDTH

#### 3.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2017/05/05	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2016/12/19	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2016/12/19	1 Year

#### 3.2. BLOCK DIAGRAM OF TEST SETUP



#### 3.3. LIMITS

No limit requirement.

#### 3.4. TEST PROCEDURE

- (1) Configure EUT and assistant system according clause 2.4 and 3.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) Set the spectrum analyzer as follows:

RBW:	30KHz
VBW:	100KHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode:	Max hold


- (5) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.



## 3.5. TEST RESULT

Mode	Frequency (MHz)	20dB Bandwidth (MHz)	Result
GFSK	2402	1.029	Pass
	2441	1.027	Pass
	2480	1.024	Pass
$\pi/4$ -DQPSK	2402	1.308	Pass
	2441	1.332	Pass
	2480	1.332	Pass
8DPSK	2402	1.297	Pass
	2441	1.299	Pass
	2480	1.300	Pass



## 3.6. ORIGINAL TEST DATA


### GFSK








## $\pi/4$ -DQPSK





8DPSK





## 4. CARRIER FREQUENCY SEPARATION TEST

### 4.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2017/05/05	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2016/12/19	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2016/12/19	1 Year

### 4.2. THE REQUIREMENT FOR SECTION 15.247(A)(1)

Section 15.247(a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### 4.3. EUT CONFIGURATION ON MEASUREMENT

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 4.4. OPERATING CONDITION OF EUT

- (1) Setup the EUT and simulator as shown as Section 6.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz.  
We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

### 4.5. TEST PROCEDURE

- (1) The transmitter output was connected to the spectrum analyzer through a low loss cable.
- (2) .Set RBW of spectrum analyzer to 30 kHz and VBW to 100 kHz. Adjust Span to 2.5 MHz.
- (3) Set the adjacent channel of the EUT maxhold another trace.
- (4) Measurement the channel separation

**4.6. TEST RESULT****GFSK**

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	0.995	>( 2/3*20dB Bandwidth)	PASS
Middle	2441	0.998	>(2/3*20dB Bandwidth)	PASS
High	2479	1.003	>(2/3*20dB Bandwidth)	PASS

 **$\pi/4$ DQPSK**

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.003	>( 2/3*20dB Bandwidth)	PASS
Middle	2441	0.995	>(2/3*20dB Bandwidth)	PASS
High	2479	0.995	>(2/3*20dB Bandwidth)	PASS

**8DPSK**

Channel	Frequency (MHz)	Channel Separation(MHz)	Limit (MHz)	Result
Low	2402	1.003	>( 2/3*20dB Bandwidth)	PASS
Middle	2441	1.003	>(2/3*20dB Bandwidth)	PASS
High	2479	1.000	>(2/3*20dB Bandwidth)	PASS

The spectrum analyzer plots are attached as below.





## GFSK






$\pi/4$ -DQPSK





## 8DPSK





## 5. NUMBER OF HOPPING FREQUENCY TEST

### 5.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2017/05/05	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2016/12/19	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2016/12/19	1 Year

### 5.2. THE REQUIREMENT FOR SECTION 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 5.3. EUT CONFIGURATION ON MEASUREMENT

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 5.4. OPERATING CONDITION OF EUT

- (1) Setup the EUT and simulator as shown as Section 7.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in TX (Hopping on) modes measure it.

### 5.5. TEST PROCEDURE


- (1) The transmitter output was connected to the spectrum analyzer through a low loss cable.
- (2) Set the spectrum analyzer as Span=83.5MHz, RBW=100 kHz, VBW=300 kHz.
- (3) Max hold, view and count how many channel in the band.

## 5.6. TEST RESULT

Total number of hopping channel	Measurement result(CH)	Limit(CH)
	79	≥15

The spectrum analyzer plots are attached as below

Number of hopping channels



Channle information

CH	Frequency	CH	Frequency	CH	Frequency	CH	Frequency	CH	Frequency
0	2402	16	2418	32	2434	48	2450	64	2466
1	2403	17	2419	33	2435	49	2451	65	2467
2	2404	18	2420	34	2436	50	2452	66	2468
3	2405	19	2421	35	2437	51	2453	67	2469
4	2406	20	2422	36	2438	52	2454	68	2470
5	2407	21	2423	37	2439	53	2455	69	2471
6	2408	22	2424	38	2440	54	2456	70	2472
7	2409	23	2425	39	2441	55	2457	71	2473
8	2410	24	2426	40	2442	56	2458	72	2474
9	2411	25	2427	41	2443	57	2459	73	2475
10	2412	26	2428	42	2444	58	2460	74	2476
11	2413	27	2429	43	2445	59	2461	75	2477
12	2414	28	2430	44	2446	60	2462	76	2478
13	2415	29	2431	45	2447	61	2463	77	2479
14	2416	30	2432	46	2448	62	2464	78	2480
15	2417	31	2433	47	2449	63	2465	-	-

## 6. DWELL TIME TEST

### 6.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2017/05/05	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2016/12/19	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2016/12/19	1 Year

### 6.2. THE REQUIREMENT FOR SECTION 15.247(a)(1)(iii)

Section 15.247(a)(1)(iii): Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 6.3. EUT CONFIGURATION ON MEASUREMENT

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 6.4. OPERATING CONDITION OF EUT

- (1) Setup the EUT and simulator as shown as Section 8.1.
- (2) Turn on the power of all equipment.
- (3) Let the EUT work in TX (Hopping on) modes measure it. The transmit frequency are 2402-2480MHz.  
We select 2402MHz, 2441MHz, and 2480MHz TX frequency to transmit.

### 6.5. TEST PROCEDURE

- (1) The transmitter output was connected to the spectrum analyzer through a low loss cable.
- (2) Set center frequency of spectrum analyzer = operating frequency.
- (3) Set the spectrum analyzer as RBW=1MHz, VBW=3MHz, Span=0Hz.
- (4) A Period Time = (channel number)\*0.4  
 DH1 Time Slot: Reading \* (1600/2)\*31.6/(channel number)  
 DH3 Time Slot: Reading \* (1600/4)\*31.6/(channel number)  
 DH5 Time Slot: Reading \* (1600/6)\*31.6/(channel number)



**6.6. TEST RESULT****GFSK Mode**

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.46	147	400
DH3	2441	1.74	278	400
DH5	2441	2.94	314	400

**Π/4-DQPSK Mode**

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.45	144	400
DH3	2441	1.71	274	400
DH5	2441	2.97	317	400


**8DPSK Mode**

Mode	Channel Frequency (MHz)	Pulse Time (ms)	Dwell Time (ms)	Limit (ms)
DH1	2441	0.46	147	400
DH3	2441	1.69	270	400
DH5	2441	2.99	319	400


The spectrum analyzer plots are attached as below:

## GFSK Mode


DH1



DH3



## DH5



## $\pi/4$ -DQPSK Mode

## DH1



## DH3




## DH5



## 8DPSK Mode


### DH1



### DH3



## DH5



## 7. MAXMUM OUTPUT POWER

### 7.1. TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2017/05/05	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2016/12/19	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2016/12/19	1 Year

### 7.2. BLOCK DIAGRAM OF TEST SETUP

Same with 3.2

### 7.3. LIMITS

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz bands: 0.125 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

## 7.4. TEST PROCEDURE

- (1) Configure EUT and assistant system according clause 2.4 and 3.2
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) Set the spectrum analyzer as follows:

GFSK	RBW:	3MHz
	VBW:	3MHz
Span		>1.5x 20dB bandwidth
Detector Mode:		Peak
Sweep time:		auto
Trace mode		Max hold

- (5) Allow the trace to stabilize, Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges measure out the Average and PK output power.



## 7.5. TEST RESULT


EUT Set Mode	Data Rate (Mbps)	Frequency (MHz)	Result(dBm)	Limit (dBm)	Verdict
			Peak		
GFSK	1	2402	4.605	30	PASS
		2441	4.096	30	PASS
		2480	3.764	30	PASS
$\pi/4$ DQPSK	2	2402	3.950	21	PASS
		2441	3.426	21	PASS
		2480	3.086	21	PASS
8DPSK	3	2402	3.895	21	PASS
		2441	3.390	21	PASS
		2480	3.081	21	PASS




## 7.6. ORIGINAL TEST DATA



### GFSK








$\pi/4$ DQPSK





## 8DPSK





## 8. CONDUCTED EMISSION MEASUREMENT

### 8.1. POWER LINE CONDUCTED EMISSION

(Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

### 8.2. MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.
1	Pulse Limiter	MTS-systemtechnik	MTS-IMP-136	261115-010-0024	12/19/2016
2	EMI Test Receiver	R&S	ESCI	101308	12/19/2016
3	LISN	AFJ	LS16	16011103219	12/19/2016
4.	LISN	Schwarzbeck	NSLK 8127	8127-432	12/19/2016


### 8.3. TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal reference ground plane and 0.4 meters from vertical reference ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 8.4. DEVIATION FROM TEST STANDARD

No deviation

### 8.5. TEST SETUP




### 8.6. EUT OPERATING CONDITIONS

The EUT exercise program used during radiated and/or conducted emission measurement was designed to exercise the various system components in a manner similar to a typical use.

## 8.7. TEST RESULT

EUT:	Cooler Amplified BT speaker System	Model No.:	COOLER-445
Temperature:	24	Relative Humidity:	55%
Probe:	L	Test Power:	12Vdc
Test Mode:	TX	Test Result:	Pass




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	39.21	11.47	50.68	65.99	-15.31	QP
2	0.1500	30.51	11.47	41.98	55.99	-14.01	AVG
3	0.1700	35.04	11.33	46.37	64.96	-18.59	QP
4	0.1700	26.08	11.33	37.41	54.96	-17.55	AVG
5	0.5899	17.97	10.15	28.12	56.00	-27.88	QP
6	0.5899	16.65	10.15	26.80	46.00	-19.20	AVG
7	1.2260	16.94	10.10	27.04	56.00	-28.96	QP
8	1.2260	14.42	10.10	24.52	46.00	-21.48	AVG
9	3.9860	16.00	10.14	26.14	56.00	-29.86	QP
10	3.9860	12.51	10.14	22.65	46.00	-23.35	AVG
11	15.4660	39.99	10.17	50.16	60.00	-9.84	QP
12	15.4660	35.56	10.17	45.73	50.00	-4.27	AVG

Measurement result=Reading + Correct;Margin=Result-Limit.



EUT:	Cooler Amplified BT speaker System	Model No.:	COOLER-445
Temperature:	24	Relative Humidity:	55%
Probe:	N	Test Power:	12Vdc
Test Mode:	TX	Test Result:	Pass



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	36.86	11.47	48.33	65.99	-17.66	QP
2	0.1500	27.85	11.47	39.32	55.99	-16.67	AVG
3	0.1712	33.36	11.32	44.68	64.90	-20.22	QP
4	0.1712	27.46	11.32	38.78	54.90	-16.12	AVG
5	0.5899	19.34	10.15	29.49	56.00	-26.51	QP
6	0.5899	18.34	10.15	28.49	46.00	-17.51	AVG
7	1.2980	13.57	10.10	23.67	56.00	-32.33	QP
8	1.2980	12.26	10.10	22.36	46.00	-23.64	AVG
9	3.9620	17.27	10.14	27.41	56.00	-28.59	QP
10	3.9620	12.09	10.14	22.23	46.00	-23.77	AVG
11	15.4540	40.01	10.17	50.18	60.00	-9.82	QP
12	15.4540	36.77	10.17	46.94	50.00	-3.06	AVG

Measurement result=Reading + Correct;Margin=Result-Limit.


## 9. SPURIOUS EMISSION

### 9.1. Test equipment


Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	EMI Test Receiver	R&S	ESU8	100316	2016/12/19	1 Year
2	Spectrum analyzer	R&S	FSU	1166.1660.26	2016/12/19	1 Year
3	Loop antenna	TESEQ	HLA6120	20129	2016/12/19	1 Year
4	Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	2016/12/19	1 Year
5	Double Ridged Horn Antenna	Schwarzbeck	BBHA9120D	9120D 1065	2016/12/19	1 Year
6	Horn Antenna	Schwarzbeck	BBHA 9170	9170 1248	2016/12/19	1 Year
7	Pre-amplifier	A.H.	PAM-1840VH	562	2016/12/19	1 Year
8	Pre-amplifier	R&S	AFS33-18002 650-30-8P-44	SEL0080	2016/12/19	1 Year
9	Pre-Amplifier	HP	8449B	3274A06298	2016/12/19	1 Year
10	RF Cable	R&S	R01	10403	2016/12/19	1 Year
11	RF Cable	R&S	R02	10512	2016/12/19	1 Year

### 9.2. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

### 9.3. Limit

#### 9.3.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

#### 9.3.2. FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(KHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(KHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer then that specified, and the limit at closer measurement distance can be extrapolated by below formula:  

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

### 9.3.3. Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 30dB below the fundamental emissions, or comply with 15.209 limits.

## 9.4. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and assistant system according clause 2.4 and 7.2
- (3) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used
9KHz-30MHz	Active Loop antenna
30MHz-1GHz	Trilog Broadband Antenna
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)
18GHz-40GHz	Horn Antenna(18GHz-40GHz)

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (4) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 25GHz:
  - (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)
  - (b) Change work frequency or channel of device if practicable.
  - (c) Change modulation type of device if practicable.
  - (d) new battery is used during testing
  - (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9KHz to 18GHz.

- (5) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.
- (6) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz, 110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.
- (7) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

- (8) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure(according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure). Peak detector is used for Peak and AV measurement both.

**9.5. Test result(Below 30MHz)**

<b>EUT:</b>	Cooler Amplified BT speaker System	<b>Model No.:</b>	COOLER-445
<b>Temperature:</b>	24℃	<b>Relative Humidity:</b>	55%
<b>Distance:</b>	3m	<b>Test Power:</b>	12Vdc
<b>Polarization:</b>	Horizontal	<b>Test Result:</b>	Pass
<b>Test Mode:</b>	Keeping TX mode	<b>Test By:</b>	Mary

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

**Note:**


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $20 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

**TEST RESULTS (Between 30M – 1000 MHz)**

<b>EUT:</b>	Cooler Amplified BT speaker System	<b>Model No.:</b>	COOLER-445
<b>Temperature:</b>	24℃	<b>Relative Humidity:</b>	55%
<b>Distance:</b>	3m	<b>Test Power:</b>	12Vdc
<b>Polarization:</b>	Horizontal	<b>Test Result:</b>	Pass
<b>Test Mode:</b>	Keeping TX mode	<b>Test By:</b>	Mary




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	39.8541	44.81	-13.23	31.58	40.00	-8.42	QP
2	63.5356	44.72	-11.09	33.63	40.00	-6.37	QP
3	121.9753	42.06	-11.51	30.55	43.50	-12.95	QP
4	180.0165	37.43	-8.46	28.97	43.50	-14.53	QP
5	468.8761	32.09	-2.01	30.08	46.00	-15.92	QP
6	601.4265	30.49	-0.54	29.95	46.00	-16.05	QP

Measurement result=Reading + Correct;Margin=Result-Limit.



EUT:	Cooler Amplified BT speaker System	Model No.:	COOLER-445
Temperature:	24℃	Relative Humidity:	55%
Distance:	3m	Test Power:	12Vdc
Polarization:	Vertical	Test Result:	Pass
Test Mode:	Keeping TX mode	Test By:	Mary



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	39.0245	43.63	-13.42	30.21	40.00	-9.79	QP
2	69.8448	46.18	-14.43	31.75	40.00	-8.25	QP
3	89.9047	54.57	-18.80	35.77	43.50	-7.73	QP
4	102.0014	49.38	-16.93	32.45	43.50	-11.05	QP
5	201.3930	42.07	-12.94	29.13	43.50	-14.37	QP
6	426.5210	34.30	-3.52	30.78	46.00	-15.22	QP

Measurement result=Reading + Correct;Margin=Result-Limit.

Note: Mode 1Mbps(Mid CH) is the worst mode.

### TEST RESULTS ( 1000~25000 MHz)

<b>EUT</b>	: Cooler Amplified BT speaker System	<b>Tested By</b>	: Mary
<b>Power Supply</b>	: 12Vdc	<b>Model Number</b>	: COOLER-445
<b>Condition</b>	: Temp:24.5'C,Humi:55%, Press:100.1kPa	<b>Test Mode</b>	: Keeping TX mode
<b>Note</b>	: GFSK(worst case)		

Frequency	Receiver	Factor	Emission Level	Limit	Margin	Detector Type	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Low Channel (2402)							
4804	48.27	6.43	54.7	74	-19.3	PK	H
4804	26.35	6.43	32.78	54	-21.22	AV	H
4804	47.45	6.43	53.88	74	-20.12	PK	V
4804	28.26	6.43	34.69	54	-19.31	AV	V
7206	43.57	11.67	55.24	74	-18.76	PK	H
7206	20.69	11.67	32.36	54	-21.64	AV	H
7206	30.89	11.67	42.56	74	-31.44	PK	V
7206	21.65	11.67	33.32	54	-20.68	AV	V
Low Channel (2441)							
4882	45.77	7.46	53.23	74	-20.77	PK	H
4882	28.29	7.46	35.75	54	-18.25	AV	H
4882	48.29	7.46	55.75	74	-18.25	PK	V
4882	32.07	7.46	39.53	54	-14.47	AV	V
7323	31.58	12.85	44.43	74	-29.57	PK	H
7323	22.89	12.85	35.74	54	-18.26	AV	H
7323	33.48	12.85	46.33	74	-27.67	PK	V
7323	24.35	12.85	37.2	54	-16.80	AV	V
Low Channel (2480)							
4960	45.44	7.71	53.15	74	-20.85	PK	H
4960	28.27	7.71	35.98	54	-18.02	AV	H
4960	43.55	7.71	51.26	74	-22.74	PK	V
4960	25.47	7.71	33.18	54	-20.82	AV	V
7440	31.08	13.00	44.08	74	-29.92	PK	H
7440	20.18	13.00	33.18	54	-20.82	AV	H
7440	33.59	13.00	46.59	74	-27.41	PK	V
7440	20.46	13.00	33.46	54	-20.54	AV	V

Note: Emission Level = ReadingLevel+ Factor, Margin= Emission Level - Limit

## Radiated band edge:

Frequency	Receiver	Factor	Emission Level	Limit	Margin	Detector Type	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Lowest Channel (GFSK)							
2390	24.68	31.37	56.05	74	-17.95	PK	Horizontal
2390	11.33	31.37	42.7	54	-11.3	AV	Horizontal
2390	25.48	31.37	56.85	74	-17.15	PK	Vertical
2390	12.75	31.37	44.12	54	-9.88	AV	Vertical
Highest Channel (GFSK)							
2483.5	22.64	32.42	55.06	74	-18.94	PK	Horizontal
2483.5	12.48	32.42	44.9	54	-9.1	AV	Horizontal
2483.5	25.63	32.42	58.05	74	-15.95	PK	Vertical
2483.5	12.86	32.42	45.28	54	-8.72	AV	Vertical
Lowest Channel (π/4DQPSK)							
2390	21.68	31.37	53.05	74	-20.95	PK	Horizontal
2390	11.53	31.37	42.9	54	-11.1	AV	Horizontal
2390	20.68	31.37	52.05	74	-21.95	PK	Vertical
2390	12.36	31.37	43.73	54	-10.27	AV	Vertical
Highest Channel (π/4DQPSK)							
2483.5	22.75	32.42	55.17	74	-18.83	PK	Horizontal
2483.5	13.22	32.42	45.64	54	-8.36	AV	Horizontal
2483.5	22.65	32.42	55.07	74	-18.93	PK	Vertical
2483.5	12.58	32.42	45	54	-9	AV	Vertical
Lowest Channel (8DBSK)							
2390	25.64	31.37	57.01	74	-16.99	PK	Horizontal
2390	14.51	31.37	45.88	54	-8.12	AV	Horizontal
2390	23.61	31.37	54.98	74	-19.02	PK	Vertical
2390	12.54	31.37	43.91	54	-10.09	AV	Vertical
Highest Channel (8DBSK)							
2483.5	22.85	32.42	55.27	74	-18.73	PK	Horizontal
2483.5	12.46	32.42	44.88	54	-9.12	AV	Horizontal
2483.5	24.03	32.42	56.45	74	-17.55	PK	Vertical
2483.5	12.53	32.42	44.95	54	-9.05	AV	Vertical

Note: 1. Emission Level = ReadingLevel+ Factor, Margin= Emission Level - Limit

2. After test and evaluation hopping off mode and hopping on mode, will record worst case (hopping off mode) in this report.

## 10. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

### 10.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Due.	Cal. Interval
1	Spectrum analyzer	KEYSIGHT	N9010A	MY55150427	2017/05/05	1 Year
2	Attenuator	Mini-Circuits	BW-S10W2	101109	2016/12/19	1 Year
3	RF Cable	Micable	C10-01-01-1	100309	2016/12/19	1 Year

### 10.2. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 10.3. Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.



#### 10.4. Test result

**PASS (See below detailed test result.)**



Frequency Band	Delta Peak to band emission (dBc)	>Limit (dBc)	Result
1Mbps Non-hopping			
2400	32.30	20	Pass
2483.5	48.16	20	Pass
2Mbps Non-hopping			
2400	33.06	20	Pass
2483.5	46.76	20	Pass
3Mbps Non-hopping			
2400	32.25	20	Pass
2483.5	40.12	20	Pass

Frequency Band	Delta Peak to band emission (dBc)	>Limit (dBc)	Result
1Mbps hopping			
2400	29.88	20	Pass
2483.5	48.76	20	Pass
2Mbps hopping			
2400	31.07	20	Pass
2483.5	42.58	20	Pass
3Mbps hopping			
2400	33.83	20	Pass
2483.5	43.85	20	Pass



## GFSK



## $\pi/4$ DQPSK




## 8DPSK







## GFSK 2402MHz



## GFSK 2480MHz




## $\pi/4$ DQPSK 2402MHz




## $\pi/4$ DQPSK 2480MHz



## 8DPSK 2402MHz



## 8DPSK 2480MHz



## 11. ANTENNA REQUIREMENTS

### 11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 11.2. EUT ANTENNA

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

**END OF REPORT**