## **Limited Modular Approval Request FCC** (KDB 996369 D01 & Part 15.212)

## FCC ID: U280MSTREAMER

	ns to be covered by Limited Single modular transmitters.	Answer from applicant
1.	The modular transmitter must have its own RF shielding.	No. It complies to all requirements without shielding
2.	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part 15 requirements under conditions of excessive data rates or over-modulation.	All modulation is digital. It can't be changed by a too high level signal.
3.	The modular transmitter must have its own power supply regulation.	The component number is IC5: TLV 320AIC3204
4.	The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204(b)(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable).	There are two antenna Connectors are J10 and J11 for 3.84MHz. Two unique loop antennas are delivered as part of the product, and the module has been tested with these antennas. The BT antenna is internal.
5.	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed.	This modular is tested inside a host: Oticon Streamer Pro XM. The host does not provide any shielding.
6.	The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number in accordance with $15.212~(a)(1)(vi)(A)$ / (B).	The modular transmitter is labeled with its own FCC ID number. Please refer to label sample and label location.
7.	The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.	The modular complies with this requirement. Please refer to user manual.
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 1.1310, 2.1091, 2.1093, and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance. Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.	The device complies with this requirement. Please refer to RF exposure report.

2019-02-25

Asif Muhammad

\_\_\_\_\_\_

Asif Muhammad / Head of Regulatory Affairs, QARA

Oticon A/S

Phone: +45 3913 7100