

No.198 Kezhu Road, Science Town Economic& Technology Development

District Guangzhou, China 510663

Telephone: +86 (0) 20 8215 5555 Report No.: SZEMO080603019TXF (R)

Fax: +86 (0) 20 8207 5059 Page: 1 of 11

Email: sgs_internet_operations@sgs.com FCC ID: U2F30040801R4

FCC Test Report

Application No.: SZEMO080603019TX **Applicant**: RIDEMAKERZ LLC.

Equipment Under Test (EUT):

EUT Name: RC car Item No.: 3004

FCC ID: U2F30040801R4

Standards: FCC PART15 SUBPART B:2007

Date of Receipt: 30 June 2008

Date of Test: 30 June to 22 July 2008

Date of Issue: 23 July 2008

Test Result : PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at http://www.sqs.com/terms and conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law." Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of the Company.



Report No.: SZEMO080603019TXF (R)

Page: 2 of 7

Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Radiated Emission (30MHz to 1GHz)	FCC PART 15, SUBPART B: 2007	ANSI C63.4:2003	Class B	PASS

Remark:

New batteries were installed in the EUT during all tests.

The three channels of the EUT has the same carried frequency 49.860MHz, with only different of the modulation signal code.



Report No.: SZEMO080603019TXF (R)

Page: 3 of 7

Contents

			Page
1	COV	/ER PAGE	1
2	TES.	T SUMMARY	2
3		ITENTS	
4	GEN	IERAL INFORMATION	4
	4.2 4.3 4.4 4.5 4.6 4.7	CLIENT INFORMATION	
5		IIPMENTS USED DURING TEST	
6	TES	T RESULTS	6
	6.1.1	RADIATED EMISSIONS, 30MHz TO 1GHz 1 E.U.T. Operation 2 Measurement Data	6



Report No.: SZEMO080603019TXF (R)

Page: 4 of 7

4 General Information

4.1 Client Information

Applicant: RIDEMAKERZ LLC.

Address of Applicant: 1930 INNERBELT BUSINESS CENTER DR. ST. LOUIS, MISSOURI 63114.

4.2 Details of E.U.T.

Power Supply: 6.0V DC (4* 1.5 " AA" Size Batteries) for Rx.

4.3 Description of Support Units

The EUT has been tested as an independent unit.

4.4 Standards Applicable for Testing

The customer requested FCC tests for a receiver for a 49MHz transmitter.

The standard used was FCC PART 15, SUBPART B, CLASS B (2007)

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663

Tel: +86 20 8215 5555 Fax: +86 20 8207 5059

No tests were sub-contracted.

4.6 Deviation from Standards

None.

4.7 Abnormalities from Standard Conditions

None.



Report No.: SZEMO080603019TXF (R)

Page: 5 of 7

Equipments Used during Test 5

R8	R&TTE RE in Chamber								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)			
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2007	15-06-2009			
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	12-12-2007	11-12-2008			
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A			
4	4 Coaxial cable SGS		N/A	SEL0028	01-06-2008	31-05-2009			
5	Coaxial cable	SGS	N/A	SEL0027	01-06-2008	31-05-2009			
6	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0014	12-08-2007	11-08-2008			
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	27-06-2007	26-06-2008			
8	Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	15-06-2007	14-06-2008			



Report No.: SZEMO080603019TXF (R)

Page: 6 of 7

6 Test Results

6.1 Radiated Emissions, 30MHz to 1GHz

Test Requirement: FCC Part15 B
Test Method: ANSI C63.4
Frequency Range: 30MHz to 1GHz

Measurement Distance: 3m Class: Class B

Limit: $40.0 \text{ dB}\mu\text{V/m}$ between 30MHz & 88MHz

 $43.5~dB\mu V/m$ between 88MHz~&~216MHz $46.0~dB\mu V/m$ between 216MHz~&~960MHz

 $54.0 \text{ dB}\mu\text{V/m}$ above 960MHz

Detector: Peak for pre-scan (120kHz resolution bandwidth)

Quasi-Peak if maximised peak within 6dB of limit

6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C Humidity: 52 % RH Atmospheric Pressure: 1015 mbar

EUT Operation: Test the EUT in On Mode.

6.1.2 Measurement Data

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. The EUT was measured by Bilog antenna with 2 orthogonal polarities and peak emissions from the EUT were detected within 6dB of the class B limit line.



Report No.: SZEMO080603019TXF (R)

7 of 7 Page:

Vertical:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
320.03	1.97	14.63	26.88	48.63	38.35	46.00	-7.65
339.43	2.03	15.16	27.02	52.44	42.61	46.00	-3.39
442.25	2.38	16.74	27.54	51.20	42.78	46.00	-3.22
488.81	2.56	17.80	27.68	46.93	39.61	46.00	-6.39
696.39	2.89	21.58	27.29	33.32	30.50	46.00	-15.50

Horizontal:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
324.88	1.98	14.80	26.92	51.39	41.25	46.00	-4.75
364.65	2.11	15.78	27.19	51.40	42.10	46.00	-3.90
403.45	2.21	16.31	27.42	50.52	41.62	46.00	-4.38
463.59	2.46	17.41	27.60	38.94	31.21	46.00	-14.79
727.43	2.98	21.61	27.18	37.60	35.01	46.00	-10.99