
onectado el receptor. Consultar al distribuidor o a un técnico con experiencia en radio/televisión para

FCC: U2ZBT3001 | [C: 6924A-BT3001 | Jasco Products Company | Model: BT3001 / 13870 CAN ICES-3|B) / NMB-3|B|

MADE IN CHINA/FABRIQLÉ EN CHINE/HECHO EN CHIN GE IS ATTAMORMARK OF GENERAL ELECTRIC COMPA AND IS UNIDER LICENSE BY JASCO PRODUCTS COMPANY LLC, 10 E. MEMORIAL RD, OKLAHOMA CITY, OK 73114.



MANUAL • MANUEL • MANUAL

In-wall Wireless **Smart Dimmer**

Montage mural Intelligent Gradateur sans fil

Interruptor de pared reductor inalámbrico de luz inteligente

Bluetooth® Certified Wireless Lighting Control Certifié Bluetooth Commande d'éclairage sans fil Control inalámbrico para iluminación certificado por Bluetooth



(9,0)

DO NOT RETURN THIS PRODUCT TO THE STORE NE RETOURNEZ PAS CE PRODUIT AU MAGASIN STOP NO DEVUELVA ESTE PRDUCTO A LA TIENDA

z des problèmes ou des questions, communiquez avec notre équipe de nnique au 1-800-654-8483, option 1, du lundi au vendredi, de 8 h à 17 h

WARNING

ONTROLLING APPLIANCES

AVERTISSEMENT

SQUE D'INCENDIE SQUE DE CHOC ÉLECTRIQUE SOUF DE BRÛLURFS

ADVERTENCIA

NE PAS UTILISER AVEC UN ÉQUIPEMENT MÉDICAL OU DE SURVIE


JASCO Products Company, Building B 10 E Memorial Rd. Oklahoma City, OK 73114


BT3001 Power 120 VMC, 60 Hz.
Power 120 VMC, 60 Hz.
Max 150W CFL/LED, 2-gaing 125W or 3-gains 100W CFL/LED,
Was 150W CFL/LED, 2-gains (125W or 3-gains 100W CFL/LED,
Range Up to 100 feet time of sight between the Winders Controller and the closed Bluetooth recoller manage. Operating Temperature Range: 32-77°F (0-25°C)
For indoor use only.

BT001 120 WC, 60 Hz.

Soft Birthard Control (120 WC, 60 Hz.)

Soft Birthard Control (1





Getting To Know Your New Bluetooth Device

- strang in Know Your New Blueboth Device

 Tim ONDFF and object drin levels manually or remalely via the Blueboth controller.


 Can be included in multiple circups and Scenes.

 3-way or 4-way wiening configurations.

 Compatible with all inconsiscent and most dimmable CFULED bulbs interchangeable Padde switch—White S light olimoral paddle in package.

 Uses a standard, decorative-size wall plate for single gang installations (well plate for single gang installations).

- Blue LED indicates switch location in a dark room
- oth Certified for simple pairing and integrated home auto




B. Bottom Rocker - //

Single, Dual And Triple Gang Boxes








WARNING — SHOCK HAZARD

OF THE power to the branch circuit for the switch and lighting fixture at territor panel. All wiring connections must be made with the POWER OFF or word personal injury and/or drange to the switch. device is intended for installation in accordance with the National Electric and local regulations in the United States, or the Canadian Electrical end local regulations in Canada. If you are ursure or without the Complete Company of the States of the Canadian Electrical medical regulations in Canada. If you are ursure or without the County Portraining this residiation consult or qualified electricion.

IMPORTANT! Verify power is OFF to switch box before continuing.

Remove wall plate.
 Remove the switch mounting screws,
 Grefully remove the switch from the switch box, DO NOT disconnect the wires.



Match these screw terminals to the wires connected to the existing switch.

6. Disconnect the wires from the existing switch. Be careful to label wires according to the provious terminal connection.

copper wire.

Wire Gauge Requirements

**Lea-1.4 AWIG or larger wires suitable for at least 80° C for supplying Line (HOT), Load

**Lea-1.4 AWIG or larger wires suitable for at least 80° C for supplying Line (HOT), Load

Wire strip length:
For ottachment to sow terminals Strip insulation 1º (25mm)
For ottachment to sow terminals Strip insulation 1º (25mm)
For ottachment using the enclosure's holes Strip insulation 5/8° (16mm)
Ut specifies that the fightening forque for the screws is 14 Mg/G-m 1/2 16-fml.
7. Connect the green or bore copper ground wire to the GROUND terminal.
8. Connect the black wire that goes to the light to the terminal market LOAD
9. Connect the black wire that comes from the electrical service parel Broth
9. Connect the black wire that comes from the electrical service parel Broth
9. Connect the black wire that comes from the electrical service parel Broth



Remotery writer a
 Manual Control
 The Front Panel Rocker Dimmer allows the user to:
 AM/OFF the connected fixture.







OFF and adjust dim levels according to groups, scenes, schedules and interactive automations prograi



To Change Color Of The Paddle

Once this step has been completed ple return to section 3.

NOTE: Actual performance of any CFL or LED will vary from bulb type to bulb type and among different manufacturers. It is important to note that only bulbs that have been designed as dimmoble should be used on a dimmobl. Find out if your bulb is dimmoble, please check the package, the bulb itself, or call the bulb manufacturer directly.

products from Jasco, please vist www.jascoproducts.com/Bluetooth

The GE Add-on switch is required for Multi-Switch 3-way or 4-way installations