or complies with part 15 of the PCC and holasty Canada Joanse-bennyt PSS standardings is subject to the following loss conditions does may set cause hand! I residence, and Off this device must accopt any or cached, subjectly substracted that may exame undered operation. In the cached of the properties of the ray yeard of 17 interface caused by unauthor like latence to the capacities of the major substraction and which the undered and the properties.

NOTE the apparent form to indicate the contractive can use the test is always by operand NOTE the apparent form to hard or but in contractive can be found to the contractive contractive to the contractive can be a simple contractive to the contractive can be contracted to the contractive can be contracted

except to the "Experiment and out our "a month" to open the other.

The month of our one amount of the other and out of the other and o

substitutes que de la merrer ou su déqui found ber o melle que le devesté diques les Les des les des

FCC:UZZ45605A [IC:8924A-45605A Jasos Products Company | Model: ZW1001 CAN ICES-3(8) / NMB-3(8)


A brand names shown are trademarks of their respective owners.

laus jus mores de muerque (Borbries sont des muerques le commerce de jeuns propriétaires empecifis.

MACIE DA CHIDA, FREFIDILÉ EN CHIDE/HECHO EN CHIDA (BETRIBUTED BY

OSTRIBUTOR AND LOCATION COMPANY LAST TO ELECTRICATE REPORT LAST TO ELECTRICATE REPORT LAST TO STATE AND LOCATION CONTRACT LOCATION CONTRACT LOCATION CONTRACT LOCATION CONTRACT LOCATION CONTRACT LOCATION CONTRACT LOCATION

MANUAL • MANUEL • MANUAL 00 0 0



In-wall Wireless Smart Outlet

Montage mural sans fil Prise intelligent

Tomacorriente inalàmbrico de pared inteligente



Z-Wave[®] Certified Wireless Lighting Control Commands of éclairage sans fil certifié Z-Wave Control inslámbrico pera lluminación certificado por Z-Wave





DO NOT RETURN THIS PRODUCT TO THE STORE NE RETOURNEZ PAS CE PRODUIT AU MAGASIN NO DEVUELVA ESTE PRDUCTO A LA TIENDA

No user servicable parts in this unit.

res lesso servicates para a mis omi.

in usus arec des profèrmes ou desi questions, communiquez avec notre équipe de soufien
exchirajos au 11-800-1656-8488, copten 1, del und au vendred, de 7-20 h à 17 h (INIC).

voir un seuffen technique d'avant-gande, les nouveaux accessaciens, les plus récents manuels e
ermat d'extronique (PPP) et plus encices, visitats le atte venur jaccoproducts commissipport

uruna des nièces de ce dispositif na peut être réparée par l'utilisateu

il tiene problemas o dudas, comuniquese con nuestro equipo técnico: al número: -900-654-6483, opción 1 de lunes a viernes, de 7:30 a 17 h, hora estándar del centro (CST).

Para recibir el soporte técnico más actualizado sobre productos, accesorios, manuales en digital (PDF), entre otros, visite www.iascoproducts.com/surnert

WARNING ADVERTENCIA

FIRST OF BUILDINGS.

CONTROLLINE JAPA LIMITES.

FIRST JAPA LIMITES JAPA LIMITES JAPA LIMITES.

FIRST JAPA LIMITES JAP

AVERTISSEMENT

NE PAS UTILISER AVEC UN ÉQUI PEMENT MÉDICAL OU DE SURVIE

MEASURE OF MILLIUMS

COMMANDE DES APPORETS SOME THE PROCESS INSOCIATIONS SOME THE PROCESS INCOMPANICES IS SOME THE PROCESS INCOMPANICES IN CONTROL OF THE PROCESS IN C

COMMANDER LES RADIVEMBLES ÉLECTRIQUES OU D'AUTR APPAREUS OUI POURRAIENT PRÉSENTER UN DANCIER EN DAS DE COMMANDE O VICTINATION IMPRÉMIE TANCO CANT

MESSO DE CUEMADORAS

CONTROL DE APARATOS

TENER HILDE CADARDO A DEPARISTRAÇÃO DE TENER HILDE CADARDO A DEPARISTRAÇÃO DE TENER HILDE CADARDO A DEPARISTRAÇÃO DE TENER HILDE SE PREED ACTION AUTOMATIVAMENTE DEBISO A QUE
ANAGENNA ELINDOS INFORMATIONS CHEMICANO
CEL AVANATO, ESTE FUNÇISMANDISTO SER VILLANDELO
CEL AVANATO, CEST ENGELVANDENTO SER VILLANDELO
FELIZIORIS, POR ESTAS PAZZAMES, RECOMBINAMINO LO
SER DETISO
SER DESTAS PAZZAMES, RECOMBINAMINO LO
SER DETISO
CALIFITACIONES ELECTRIZOS DE MANDIN CONTENADA
CELETRIZORIS ELECTRIZOS DE MANDIN CONTENADA
CELETRIZORIS ELECTRIZOS DE MANDIN CONTENADA
FELIZIORIS CHEMICA PROPREMENTA MEDIA SENIALIS
FELIZIORIS CHEMICA PROPREMENTA CONTENADA
FELIZIORIS CHEMICA CONTENADA
FELIZIORIS CHEMICA PROPREMENTA CONTENADA
FELIZIORIS CHEMICA CONTENADA
FELIZIORIS CHEMICA
FELIZIORIS CHEMICA
FELIZIORIS CHEMICA
FELIZIORIS
FELIZ

NOT FOR USE WITH MEDICAL OR LIFE SUPPORT EQUIPMENT 2-Wave enabled devices should never be used to supply power to, or control the On/OH status or medical and/or life support equipment.

MÉDICAL OU DE SURVIE Les disposités compatibles avec la technologie 2-Vilave ne dovraient jamais être utilisés pour alimenter ou commander la mise en marche ou l'arrêt de l'équipement médical ou de survie.

Tanto de l'equipement medical ou dississive.

SE PROMIBIS SU BEMPLEO DE REQUIPO MÉDICO.

O EQUPO PARA EL MANTENMENTO DE LAS PUNCIONES VITALES.

Les dépositivos 2º Risse nunca se deban usar para suministar energia décistica al equipo pera di marientimiento de funciones vibales, ni para controtar di estado de funciones vibales, ni para controtar di estado de noncinidio o al equapos dei dictivo equipo.

WIREOUT IN A STATE AS A STATE TO BE A STATE OF THE ASSESSMENT OF T

ACMONETY AND STATE STATE (see or profit sit event do tot dibbit do librodiste peur un précisé de ACMO Troducts gasanté que ou produit et est pas apriles de la hispation ou su rendizionne de produit et est pas apriles de compassi indistrito à hispation ou su rendizionne de or produit et est pas apriles de la montage indistrito anné partie evenue in majorito. Orden Ellen in comentage an orden commanda de la majorito del majorito della majorito della

colourité.
MACO Penutra quantitre que este producte esté faire de difectes de tabricación diurrité en p.
de des ains agant est la teche origen de compra por parte del consumirer. Este parella este autres parella este acceptant de la requesción o sella production de sella production de residente de residente de residente de parella este acceptant de la requesción o sella production que se este con este unidad. Esa grandira emplea: este destre parella este destre parella este destre parella este parella este destre parella este parella este del parella parella del p derivative, por le tartis, puede que les arteriones limitaciones no apliquen en su caso. Esta pr da a usefa derectivas específicos, y otres que uselad puede hener y que variar según el estado usela reside. El unidad resultar defeticasos admin del periodo del oparatile, comunique com democión al Diente en el 800-554-6465 (opción 1) entre 7.30 y 17 h., Hora del Centro, o i de menetro ello del settembre.

SPCEPLING

PRINT COME. Co. 104.
Specific Specifi

or temperatures uniquement. Bon d'améliorations continues du produit, les spécifications peuvent faire l'objet de chang


LEAVINGMENT CONTROLL STATEMENT C



1800W (Resistive); or ½ HP (Motor). The maximum rating for both outlets combined is 1800W (15A) Resistive.


Getting To Know Your New Z-Wave Device

- One Z-wave remote controlled outlet
- Remote ON/OFF control via the Z-Wave controller/network Manual ON/OFF control with the manual/program button
- One Always-ON pass through outlet
- Blue LED indicates outlet location in a dark room
- This Z-Wave device has advanced features that allow you to customiz your experience, These features can only be adjusted by a Z-Wave enabled controller that support the Z-Wave Configuration command class. For a complete list of Adjustable Configurations,



E. Ground (Go

WARNING - SHOCK HAZARD







1. Shut off power to the circuit at circuit breaker or fuse box


Warning: Verify power is OFF to switch box before continuing.

- 2 Remove wall plate
- 3. Remove the outlet mounting screws.
- Carefully remove the outlet from the outlet box.
 Disconnect the wires from the existing outlet. Be careful to label
- wires according to the previous terminal connection.
- There are three wires on the Z-Wave smart outlet; these are marked
 A, GROUND Green/Bare

 - B. Neutral White
 - C. Line (Hot) Black (connected to power)
 - Match these to the wires connected on the existing outlet.

This Device supports Lifeline (association group 1) supporting 1 node for lifeline communication, Group 1 must be assigned the Node ID of the primary controller where unsolicited notifications will be sent. The 2-Have controller should set this association untownatically after inclusion. Lifeline association only supports the "Device Reset Locally junction. Refer to the instructions of your controller for any available

2-WWE INTEGOPERABLITY
This product can be included and operated in any
things better with other 2-Ways certified divices
from other manufacturers order other applications, a
neith-better operated nodes within the neadow will col
as repeates regardless of vendor to increase reliability
of the network.



Observe Important withing Information
Always follow the recommended wire strip lengths and wiring
combination when making wiring connections, You may wish to
consult a electrician with questions or for professional installation.

Important: The wire connectors included with this receptacle are intended to only be used with copper wire. Consult a qualified electrician if you have aluminum wiring.

Use 14 AWG or larger wires suitable for at least 80° C for supplying HOT, neutral, ground and connections.

Remove stripped insulation from wires of Z-Wave outlet.
 Hold stripped ends together in parallel and align any frayed strands.

3. Push wires firmly into a wire nut. Twist the wire nut dockwise with

Ingers and agit. Pail wires to check for agitaless.

4. Use the included wire nuts to make the following connections:

A. Connect the green wire from the controlled outlet to the green or bare ground wire removed from the old outlet.

or bare ground were removed from the old outlet.

8. Connect the white wire from the controlled outlet to the neutral (while) wire removed from the old outlet.

Connect the black wire from the controlled outlet to the Line/hot (black) wire removed from the old outlet.

S. Insert I-2Wes controlled outlet into the box being careful not to pinch or crush wires.

Sevent the controlled outlet is the bay scient the

6. Secure the controlled outlet to the box using the

7. Mount the wall plate.

Reapply power to the circuit at fuse box or circuit breaker and test the system.







Adding your device to the Z-Wave Network

1. Follow the instructions for your Z-wave certified controller to include a device to the Z-wave network.

Once the controller is ready to include your device, press and release the Program Button to include it in the network.

Once your controller has confirmed that the device has been included, refresh the Z-wave network to optimize performant

Please reference the controller/gateway's manual for instructions. Now you have complete control to turn your fixture 0N/0FF according to groups, scenes, schedules and interactive automations programmed by your controller. If your 7-wave certified controller features Remote Access, you can

now control your fixture from your mobile devices.

To exclude and reset the device:

Follow the instructions for your Z-wave certified controller to exclude a device from the Z-wave network,

2. Once the controller is ready to Exclude your device, press and release the manual/program button on the smart dimmer to exclude it from the network.

To return to factory defaults:

 Press and hold the button for at least 3 seconds. The LED light will blink 5 times to confirm

Note: This should only be used in the event your network's primary controller is missing or otherwise inoperable.