exception for the opener requirement and resident in standards to complete the observafield and control and exception for the owner's or a collegate as the control and opened and opened and the control and opened and o

exposed required as 6° et a poural service feet de reflexion à silière e deputif.

Se allembration qui les la françaissement quarter la la la manufacture de putification de la companie de la manufacture de la manufacture de la companie del companie del companie de la companie del companie

FCC:U2ZZW4002A | IC:6924A-ZW4002A

tive owners . is noms de manque illustrés cont des es de commerce de jeurs propriétaires

respectini. Todas las marcas que aperecen aquí sen marcas consistrados de nos comos tiens desilvos

MICE N CHAUGERFOLE DI CHAERECH DETREUTED BY LYSCO PRODUCTS COMPANY LLC, 10 E. MENORINL RD, OKLAHOMA CITY, DK 73114.





In-wall Wireless **Smart Fan Control** 

Montage mural Intelligent

Commande de

Interruptor de pared inteligente para el control inalámbrico de ventiladores

ventilateur sans fil

Z-Wave<sup>®</sup> Certified Wireless Lighting Centrol Certifié Z-Wave Commande d'éclairage sans fil Control insjámbrico para iljuminación certificado por Z-Wave<sup>®</sup>



DO NOT RETURN THIS PRODUCT TO THE STORE NE RETOURNEZ PAS CE PRODUIT AU MAGASIN NO DEVUELVA ESTE PRDUCTO A LA TIENDA

For the most up-to-date product support, accessories, electronic (PDF) format manuals and more, visit www.jascoproducts.com/support

No user servicable parts in this unit.

Si vous avez des problèmes ou des questions, communiquez avec notre équipe de souti-technique au 1-800-864-8483, option 1, du land au vended, de 7:30 h à 17 h (#VC). Pour un soutien technique d'avant-gonde, les nouveaux accessoires, les plus récents ma en format déchardaque (\*PU) et plus encore, visitez le site view jescoproducés zonniagon.

Aucune des pièces de ce dispositif pe peut être pérsorée par l'utilisateur

Si tiene problemas o dudies, comuniquese con nuestro equipo técnico al número: 1-900-654 8483, opción 1 de junes a viemes, de 7:30 a 17, hora estándar del contro (CST).

· Esta unidad no contiene piezas que el usuario queda reparar.

### WARNING

THE OF SHEET AND APPLIANCES.

DOTTED LING APPLIANCES.

DOTTED CONTROL CUITON MENT HAD A PARKE CONTROL

DOTTED CONTROL CUITON MENT HAD THE PRESENCE FOR MENT HAD THE PRESENCE FOR MENT HAD THE PRESENCE FOR HAD THE PRESENCE

## AVERTISSEMENT

# ADVERTENCIA

CHECK OF CHEMICALS CONTROL OF

COMMANDER LES PACANTILIES ÉLECTROLIS CU D'AUTRES PERRIELS CUI POLIFIMENT PRÉSENTES UN CARGES EN JAS DE COMMANDE D'ACTIVITION ENPRÉAUE, ENCLOSTRES SU AUTOMATIQUE.

NOT FOR USE WITH MEDICAL OR LIFE SUPPORT EQUIPMENT 2-Wase enabled divides should never be used to supply power to, or control the On/Off status of medical and/or life support equipment.

us medical aneire life support equipment.

ME PAS UTLISER AUTO UN ÉQUIPMENT

MEDICAL OU DE SURVIE

Les dispositifs compatibles avec la technologia

2-Wave ne domande la prande être utilisés pour
adimenter ou commandre la missi en mercho a

l'arrêt de l'équipement médical ou de survie.

SE PROHIBE SU EMPLEO EN EQUIPO MÉDICO O EQUIPO PARA EL MANTENIMENTO DE LAS PRINCIONES NATALES Los dispositives 7.2 Ware nursea se deben usar para suministrar energia eléctrica al ecupio módico o al equipo para el mantenimiento de fundenes Walles, ri para contributar el estado de concesido o pagade de eláctros estajos.

WARRANT AND A STATE AND A STAT

JASCO Products Company, Building B 10 E Memorial Rd. Oklahoma City. OK 73114

veser 100 W.C. 60 Int. 1 Signal Preparation 5 006.4 / 916 Met.
Maximum Loade: 1.54 file more from two liverance of mis this pasts. Not to exceed 1.5 Amp resistive
load. CONTRACT SNM NUTUR CONET, for one of with all to question which plan in more.

Outside plan of the contract of the contract of the depart 2-files on occasion receive residue.

Outside plan preparation for page 1.5 164 F (F-47 C)

For Indices was the contract of the contract of the depart 2-files on occasion receives the contract of the con


ly. iect to change willhout notice due to continuing product improvemen

Table 11.

Table 12.

Table 13.

Table 14.






identical fans to the smart switch. Not to exceed 1.5 Amp VTROLS FAN MOTOR ONLY. For use only with split ed pole ceiling fan motors.

### Getting To Know Your New 7-Wave Device


- Tium ON/OFF and adjust fan speed levels manually or remotely via the Z-Wave controller Can be Included in multiple Groups and Scenes May be used in single pole institution or with up to two Jasoo Add-on switches in 3-way or

- May be used in night pole inhalbation or with go the subsect Advisor motives in New ye 4-way wing configuration. I while A light densed patide in package telestrow upod a horder sealor— mile a few or gold page in self-ation of self-ation not school and the self-ation of the self-ation of the self-ation of the self-ation of self-ation not school and the self-ation of 2-dates confident for simple paring self-inspired terms automation. Self-ation of the self-ation of the self-ation of the self-ation of Goods. These have view required to \$2-sep or \$2-sep institution. These features can not be self-ation of the se










MANUAL • MANUEL • MANUAL

### WARNING — SHOCK HAZARD


IMPORTANT! Verify power is OFF to switch box before continuing



## To exclude and reset the device: 1. Follow the instructions for your 2-wave certified controller to exclude a dev

Poton the manuscram may you a more common common and release the top or bottom the controller is ready to Exclude your device, press and release the top or bottom the wireless arrant switch (rocker) to exclude it from the network.

To return your switch to factory defaults:



Note: The Transfer forminal is only used for 3 way or 4-way writing and should installed if the Fair Control is being installed in a 2-way system (see switch if II.) Insert Fair Control in the seath to being certain for it must be run. 12. Secure the Fair Control to the box using the supplied screen. 13. Moret the varial plats. 14. Reapply some to the circuit at fixee box or circuit treater and lest the sy

Adjust fan speed
To decrease fan rejsse in en ooker.
Adjust fan speed: Press and hald lawer rocker.
To increase fan speed: Press and hald lawer rocker.
To increase fan speed: Press and hald lawer rocker.
The LED wild berk cerey 2 executes fan 's 0 executes'.
MCH — LED will blink every teath execute fan 's 0 executes'.
MCH — LED will blink every taf execute fan '10 executes'.



The Jasco Add-on switch is required for Multi-Switch 3-way or 4-way installations. Connecting the traveler terminal of this switch to a standard, see-Jasco and/or Mill Gause damage or result in improper function. If this switch is a get or it also work to standards installation, on information the base wine or apply governed to the switch as an occurrent principle of or more information on 3-May or 4-May relations, were manufactured explication principle on consensation provided in addition.

This Device supports Lifeline (association group 1) supporting 1 node for lifeline communication. Group 1 must be assigned the folder ID of the primary controller where unsoleteled notifications will be sent. The Z-Marc controller should set this association automatically with chalcius. Lifeline association only supports the "Device Reset Locally function. Befor to the instructions of your controller for any available defauls on how this can be set.

