el equipo, se aconsejo al susurior que intente umo a más de los siguentes medidos concretivos:

- Rescriberto por la composição de la consigiente com el distributor o besupe o justa com un tentrico experte en rodo y televisión.

- Puede que este dispositiva no couse interferencia.

- Puede que este dispositiva no couse interferencia.

- Este dispositivo deve compositiva ferencia puede generor una operación de la compositiva del compositiva de la compositiva de la compositiva del compositiva del compositiva de la compositiva del compositivo del compositivo

MADE IN CHINA/TABRIQUÉ EN CHINE/HECHO EN CHI GEIS ATRADEMARK OF GENERAL ELECTRIC COMRI AND IS UNIDER LUCENSE BY JASCO PRODUCTS COMPANY LLC, 10 E. MEMORIAL RD., OKLAHOMA CITY, OK 73.114.



Plug-in Wireless Smart Dimmer

Module gradateur intelligent enfichable

enchufable inalàmbrico Reductor de luz inteligente

Control inalámbrico para iluminación certificado por Blue



(ge)



DO NOT RETURN THIS PRODUCT TO THE STORE NE RETOURNEZ PAS CE PRODUIT AU MAGASIN NO DEVUELVA ESTE PRDUCTO A LA TIENDA.

No user servicable parts in this unit.

Si vous avez des problèmes ou des questions, communiquez avec notre équipe de soutien technique au 1-800-654-8483, option 1, du lundi au vendredi, de 7 h 30 à 17 h IHMC).

• Aucune des pièces de ce dispositif ne peut être réparée par l'utilisateur. Si tiene problemas o dudas, comuníquese con nuestro equipo técnico al número 1-800-654-8483, opción 1 de lunes a viernes, de 7:30 a 5 p.m., hora estándar del

WARNING

AVERTISSEMENT

SQUE DE CHOC ÉLECTRIQUE SQUE DE BRÛLURES

PhotoBurlet COUINS—
Burlet Couins—

ADVERTENCIA

RIESGO DE INCENDIO RIESGO DE DESCARGA ELÉCTRICA RIESGO DE QUEMADURAS

NE PAS UTILISER AVEC UN ÉQUIPEMENT MÉDICAL OU DE SURVIE

De l'egiperient intendicion de suive-se PROHIBES SI EMPLEO EN EQUIPO MÉDICO O EQUIPO PARA EL HANTENMIENTO DE LAS FUNCIONES VITALES Los dispositivos Buleatorin funca se deben usor poro sumistror energia elèctrica ol egippo médico a ol equipo poro el montenimiento de funciones vitoles, ni poro corritdor el estodo de encendido o apagado de dichos equipo

JASCO Products Company, Building B 10 E Memorial Rd. Oklahoma City, OK 73114

Mosmum load for the Bustanth controlled outlet 2.54 3.00M (narrodnessert or 100M (mmobile CPL/IED Blustanth controlled outlet is fused 69 54. This fuse is nat user s Range (Ip to 100 feet line of sight between the smart device and the dosest Bluetooth receiver module. Operating Temperature Ranger 32-77F (0.45°C) For Indoor use on 100 feet in 100 feet line of sight line of the For Indoor use on 100 feet line of sight line of the For Indoor use on 100 feet line of sight line of the For Indoor use on 100 feet line of the For Indoor use on 100 feet line of the For Indoor use of the Foreign Section 100 feet line of Foreign Section 100 feet

. ect to change without notice due to continuing product improvement

SPÉCIFICATIONS

Section 2010 Section 2010 Fee who can tracte do to do not making product in provenient in SECTION 2010 SECTI


Septicifications. Energial 22 VCA, 60 Hz
Seffol (Fireculancia) 2.6 GHz
Seffol (Fireculancia) 2.6 GHz
Carga midwine partie to from Billuscothor 2.5A 300W incondescente 100W CFL y LED attenua
La toma Billuscoth està protegida con fusible de 5A. El usuario no puede reparar este
fisible.

Getting To Know Your New Bluetooth Device

Maximum load for the Bluetooth controlled outlet: 2.5A; 300W Incandescent or 100W Dimmable CFL/LED

- . One Bluetooth controlled AC outlet for standard incandescent lighting or
- One Billietroot Controlled No Objects of States and States of States of
- Space efficient design
 Does not block the lower outlet when plugged in to the upper outlet of a duplex wall receptacle. (This assumes that the duplex receptacle is mounted with the ground
- pin down). Plugs and cords for connected devices route to the side allowing close placement
- of furniture

 Grounded 3-wire power connection for safety




A. Bluetooth controlled outlet

This outlet can remotely turn On/Off and Dim the connected lamp

B. Manual control button

Single press — turn the lamp On/Off Press and hold — Dim/Brighten the lamp



Plug the smart dimmer directly into an available grounded outlet (Top outlet recommend if possible).

NOTE: Plug directly into outlet. Do not use with extension cords

Add new picture for top button

4.

The manual control button on the dimmer allows the user to:

1. Manually turn the connected lamp ON or OFF (press and release).

2. Adjust the brightness level of the connected lighting by pressing and holding the button. Release the button when the desired level is attained.



1. Follow the instructions for your Bluetooth certified smart device to include the smart dimmer to the Bluetooth network

Please reference the application instructions.

Note: Your dimmer may need to be within 10 feet of the controller to be included. If so, include the dimme to the network within 10 feet of the controller and relocate it to the desired position in your home. Be sure to refresh the network if the dimmer is included



2. Once your smart device has confirmed that the smart dimmer has been included, you now have complete control to turn your lamp ON/OFF or set Dim levels according to groups, scenes, schedules and interactive automations programmed by your device

Note: To exclude and reset the device, follow the instructions provided by your Bluetooth device.

NOTE: Actual performance of any CFL or LED will vary from bulb type to bulb type and among different manufacturers. It is important to note that only bulbs that have been designed as dimmoble shall be used on a dimmer. To find out if your bulb is dimmoble, please check the package, the bulb itself, or call the bulb manufacturer directly.

For a complete list of recommended CFL/LED bulbsfor this and other Bluetooth products from Jasco, please vist www.jascoproducts.com/Bluetooth