less with part 15 of the FCO and industry Canada bonsto-exempt FRSS sits of to the Althoring last considerate.

In the Set of the Althoring last considerate of the device must account any set, industry interference that may cause underself operation.

Annualization in an incorposable for any application of Villinterference caused to efficiations to this egulpment. Such modifications could work the seem's as

with the equipment.

Et the equipment in the three prices and the equipment in the limits for a Class B digital device and to their 15 of the 1000 Rules. These first in an adaptive to previous reconstitution and to the contraction of a function on an endough selection and contraction a

miscleds. Creatil the dealer or an experienced radio/TV technician for help creatil the dealer or an experienced radio/TV technician for help creating neither to comply with the EVCRP exposure complance requirements, no change to the man or the device is permitted. Any change to the antenna or the device could result in the device extent to RP requirementationsmitted and value of an attribute to industry the device.

exceeding bits of proportion agreements and volumes a facility to separate the oriess.

All proportions are proportionally assumed to the account of the proportion of the pro

composed for sequent and the of power at most level of the other but there is deposed.

The deposed many one of the contract and the deposed of the other but the other is an extract on a first product of the other power and th

roms de marque Bustrés sont des de commerce de leurs organitaires

MADE NO MANMANDAÉ EN OPREMEIO DES CO GE EA TRADOMEN (OF GERERAL ELECTRIC DO 15 UNIDER LICENSE BY JASZO PRODUCTS COMPANY LLC, 10 E. MERIOPELL IRL, OKLAHOMA (TTY, CK 73114.

JASCO[®]

MANUAL • MANUEL •

ANUAL

Plug-in Wireless Outdoor Smart Switch

enfichable sans fil Interrupteur extérieur

Inteligente Interruptor inalámbrico enchufable para exteriores

Z-Wave® Certified Wireless Lighting Control Commande d'éclairage sans fil certifié Z-Wave Control inalámbrico para lluminación certificado por Z-Wave^o

MANE!





DO NOT RETURN THIS PRODUCT TO THE STORE NE RETOURNEZ PAS CE PRODUIT AU MAGASIN NO DEVUELVA ESTE PRDUCTO A LA TIENDA

xu. 1-xu-1xu-1xu-1xux, open 1 Menday-Pridgy, 7:30-5 pm CST
 for the most up-to-daile product support, accessories, electronic (PDF) former manuals and more, visit www.jasooproducts.com/support
 No user servicable parts in this unit.

Si yous avez des problèmes ou des questions, communiquez avec notre équipe de soutien technique au 1-900-654-9483, option 1, du lundi au vendredi, de 7 h 30 à 17 h (HNC).

Pour un soutien technique d'avecades, opinion ; ou inter au renareur, per in ale plus récents manuels en termat électronique (PBP) et plus encres, visitez le site wirwi, siscoproducts, comésupont « Aucune des pièces de ce dispositif ne peut être réperée par l'utilisateur.

Si tiene problemas o dudas, comuniquese con nuestro equipo técnico al número: 1-800-854-8483, opción 1 de luxes a viernes, de 7:30 a 17 h, hora estándar del centro (CST). oless, quotini dei timbe a viennes, de 2 de a 17 in, final estamata dei denno (cis). Para recibir a seporte técnico más actualizado sobre productos, accescrios, manueles en formato digital (PDP), entre etros, visite views, jascoproducts com/support Esta unidad no contiene piezas que el usuario pueda repara;

WARNING

TORSING LINE REPORTED COUNTS ON TO WARE THE
FOUR THAN THE PROPER COUNTS ON TO WARE THE
FOUR THAN THE PROPERTY OF THE
FOUR THAN THE
F

IN A HAZHROUS CONTINUE OF THESE RESEARCH WE RECOMMEND THE FOLLOWING DO MOT 1852 AND CONTINUE CHECKING WE HAZHROUS ON ANY OTHER WAY UNKNOWN THE PROSINT A HAZHROUS CONTINUE ON THE PROPERTY OF THE UNKNOWN CONTINUE ON ANY OWNER POWER ON COMMENT.

AVERTISSEMENT

PROVIDED BIOLOGISTS

OF PRODUCT COMPAND AS CHOCK SECTIONS:
OF PRODUCT COMPAND AS CHOCK SECTIONS:
OF PRODUCT COMPAND AS CHOCK SECTION AS A THEFE
CONTINE FOR MEMBER PRODUCT MEMBER ALL TERMS
OF THE FLOW AS PRODUCT SECTION AS A THEFE
CONTINUED AS CHOCK SECTION AS A THEFE
CONTINUED AS CHOCK SECTION AS A THEFE
CONTINUED AS CHOCK SECTION AS A THEFE
THE INSERT SECTION AS A THEFE
THE MEMBER COMPANDATION AS THE FOR THE
ORDER COMPANDATION AS CHOCK SECTION
AS A SECTION AS A THEFE
THE ORDER COMPANDATION AS CHOCK SECTION
AS A SECTION AS CHOCK SECTION
AS

ANGIONES DE CONNECT POR LA PRISE DE CONSCIONA COMMISSION DE CONNECT POR LA PRISE DE CONSCIONA SOCIA DE CONTROLLA CONCETA DE LA SIS-SOCIA DE LA CONTROLLA CONCETA DE LA SIS-SOCIA DE PRISE DE CONTROLLA SI SI DICE. SOCIA DE PRISE DE CONTROLLA SI SI DICE. SOCIA DE PRISE DE CONTROLLA SI SI DICE. SOCIA DE CONTROLLA SI SI DICE. SOCIA DE CONTROLLA SI SI DICE. SOCIA DE CONTROLLA DE LA CONTROLLA DE LA CONTROLLA DE CONTROLLA DEL CONTROLLA DE LA CONTROLLA DE SI DICE. SOCIA DEL CONTROLLA DE LA CONTROLLA DE SI DICE. SOCIA DEL CONTROLLA DE SI DICE. SI DICE. SOCIA DEL CONTROLLA DE SI DICE. SI DI SI DICE. SI DICE. SI DICE. SI DICE. SI DICE. SI DICE. SI

ADVERTENCIA

RESON DE RECEIVE LE CITE LA CONTRE LE CITE LA CONTRE LE CITE LA CONTRE LE CITE LA CONTRE LA CONT

ELECTRICA DE LA PLOCA PARAMENTA ALCA TIDAS ENTRE LA CAPILLA COMPINA, EL REGITA DEL CAPILLA COMPINADA PARAMENTA ALCA COMPINADA EL SE CIPITADA COMPINADA PARAMENTA PAR

MOT FOR USE WITH MEDICAL OR LIFE SUPPORT EQUIPMENT Z-Wave enabled devices should never be to supply power to, or control the Child's status of medical and/or life support on intervals.

NE PAS UTILISER AVEC UN ÉQUIPEMENT MÉDICAL OU DE SURVIE MEDICAL OU DE SURME

Les dispositifs compatibles avec la technologie
Z-Wave ne devraient jamais être utilisés pour
alimenter ou commander la mise en merche o
[ambt de] équipement médical ou de survie.

SE PROHÍBE SU EMPLEO EN EQUIPO MÉDICO O EQUIPO PARA EL MANTENIMIENTO DE LAS FUNCIONES VITALES

COMMITTED

ACTION THE COMMITTED AND ACTION THE COMMITTED ACTION THE COMM

SCHAMING. AND ADDRESS AND ADDR

JASCO Products Company, Building B 10 F Mamorial Brt. Didahoma City, DK 73114

SPECIFICATIONS Private 120/AC, 60Hz

Power 12004C, CRVA: Syrum Fronzerry 1908 A / 016 Milez Mainram Hood for both outleb 13 Anna, 1 1000M Residue Mainram Hood for bettime controlled outlet: CRVAII Handwood, 1 HP Motor or 1500M Residue Range (b) to 100 bet in ord sight between the Wireless Controller and the classes 2-Wilese receive Controller Residue in Pages (25 Pol F I) — MP C) Solidate for couldows on in drong (sections).

Specialization safeth in target referrance between the bordinary product improvement FORMATIONS
Alternation 1.10 (Au., 60), 60.

Alternation 1.10 (Au., 60), 60.

Congressional special profits of the special section of the spec

Printer Committee Committe

Getting To Know Your New 7-Wave Device

Maximum load for the Z-Wave controlled outlet:

600W Incandescent; 1800W (15A) Resistive or 1/2 HP Motor

- One Z-wave controlled grounded outlet for lighting & small appliances Remote ON/OFF control via the Z-Wave controller
- . Manual ON/OFF control with the manual/program button
- · Grounded 3-wire power connection for safety
- . Weather and impact resistant housing: suitable for outdoors in a wet or damp conditions
- . Integrated outlet cover keeps dirt and debris out when the smart switch is not in
- . This Z-Wave device has advanced features that allow you to customize your experience. These features can only be adjusted by a Z-Wave enabled controller that support the Z-Wave Configuration command class. For a complete list of Adjustable Configurations, visit: www.jascoproducts.com/z-waveconfig


INSTANTANTAL SUITABLE for outdoor use in damp locations. Do not expose to rain or immerise in water, Install at least 3ft, above ground level with the receptacle pointed down. When used outdoors you should upig the unit into a GFCI recep-tacle with a receptacle cover rated for outdoor use





- 1. A mounting tab with screw key-hole is located at the top of this unit. Install the included screw in the desired location leaving 3/16" of the screw exposed.
- 2. Align the mounting tab with the screw head, slide the tab over the screw and let the unit drop down to lock it in place.


6



ote: Plug switch directly into outlet. Do not use with extension cords,

The manual/program button on the outdoor switch allows the user to:

Turn the connected lamp ON or OFF. If the outdoor switch is OFF, press and release the button once to turn it ON and vice versa to turn OFF.



Add your device to the Z-Wave network

1. Follow the instructions for your Z-Wave certified controller to include the smart switch to the Z-Wave network. 2. Once the controller is ready to include your outdoor smart

switch, single press and release the manual/program button on the smart switch to include it in the network. Once your controller has confirmed that the smart switch
has been included, refresh the Z-Wave network to

Now you have complete control to turn your device ON/OFF according to groups, scenes, schedules and interactive automations programmed by your controller.

If your Z-wave certified controller features Remote Access, you can now control your lighting from your mobile devices.



1. Follow the instructions for your Z-wave certified controller to

exclude a device from the Z-wave network. 2. Once the controller is ready to Exclude your device, press and release the manual/program button on the smart switch to exclude

it from the network, To return to factory defaults:

1. If plugged in, unplug the Switch from the receptacle.

2. Press and hold the top button for at least 3 seconds while you plug

Note: This should only be used in the event your network primary controller is missing or otherwise inoperable.

is Device supports Lifeline (association group 1) supporting 1 note for lifeline minimization, Group 1 must be assigned the Mod D of the primary controller here unschliched notifications will be sent. The 2-Make controller should set this sociation automatically after inclusion, Lifeline association only supports the beside Reseal Locally* Inaction. Refer to the instructions of your controller for ya available distals on how this can be set.



Z-WAVE INTEROPERABILITY
This product can be included and operated in any Z-Wave network with other Z-Wave certified devices from other manufacturers and/or other applications. All more-before operation drose within the network will act as repeaters regardless of vendor to increase reliability of the network.