

# MET Laboratories, Inc. Safety Certification - EMI - Telecom Environmental Simulation 3162 BELICK STREET • SANTA CLARA, CA 95054 • PHONE (408) 748-3585 • FAX (510) 489-6372

# **Electromagnetic Compatibility MPE Calculation**

For the

Arch Rock Corporation FCC ID: U3SRMB3000R1

Tested under

Title 47 of the Code of Federal Regulations (CFR), Part 15 Subpart C

**MET Report: EMCS80832-MPE** 

June 23, 2008

Prepared For:

Arch Rock Corporation 501 2<sup>nd</sup> Street, Suite 410 San Francisco, CA 94107

Prepared By: MET Laboratories, Inc. 3162 Belick Street Santa Clara, CA 95054



#### Electromagnetic Compatibility MPE Calculation

For the

Arch Rock Corporation FCC ID: U3SRMB3000R1

Tested under

Title 47 of the Code of Federal Regulations (CFR), Part 15 Subpart C

**MET Report: EMCS80832-MPE** 

made, the equipment tested is capable of operation in accordance with the requirements of Title 47 of the CFR, Part 15, Subpart C under

Shawn McMillen
Manager, Electromagnetic Compatibility Lab

**Engineering Statement:** The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the applicable limits. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements

normal use and maintenance.



#### **Electromagnetic Compatibility Criteria for Intentional Radiators**

#### § 15.249 Peak Power Output and RF Exposure

**Test Purpose:** Co-location of two modules, Arch Rock Corporation, FCC ID:

U3SRMB3000R1 (3.3dBi) and Compex, Inc., FCC ID: MK8CPX-05-

WLM54G (2dBi).

RF Exposure Requirements: §1.1307(b)(1) and §1.1307(b)(2): Systems operating under the provisions

of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's

guidelines.

**RF Radiation Exposure Limit:** §1.1310: As specified in this section, the Maximum Permissible Exposure

(MPE) Limit shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Sec. 1.1307(b), except in the case of portable devices which shall be evaluated according to

the provisions of Sec. 2.1093 of this chapter.



## MPE Calculation – Arch Rock Corporation Module: 2405 - 2480 MHz (FCC ID: U3SRMB3000R1)

Equation from page 18 of OET 65, Edition 97-01

 $S = PG / 4\pi R^2$  or  $R = \int PG / 4\pi S$ 

MPE Limit Calculation: EUT's operating frequencies @  $\underline{2405 - 2480 MHz}$ ; highest conducted power = 0dBm (peak) therefore, Limit for Uncontrolled exposure: 1 mW/cm<sup>2</sup> or  $10 \text{ W/m}^2$ 

EUT maximum antenna gain = 3.3 dBi.

where,  $S = Power Density (mW/cm^2)$ 

P = Power Input to antenna (1mW)

G = Antenna Gain (2.137 numeric)

 $S = (1*2.137/4*3.14*20.0^2) = (2.137/5024) = 0.000426 \text{mW/cm}^2$  @ 20cm separation



# MPE Calculation – Compex, Inc. Module: 2412 - 2462MHz (FCC ID: MK8CPX-05-WLM54G)

Equation from page 18 of OET 65, Edition 97-01

 $S = PG / 4\pi R^2$  or  $R = \int PG / 4\pi S$ 

MPE Limit Calculation: EUT's operating frequencies @  $\underline{2412 - 2462MHz}$ ; highest conducted power = 16.02dBm (peak) therefore, Limit for Uncontrolled exposure:  $1 \text{ mW/cm}^2$  or  $10 \text{ W/m}^2$ 

EUT maximum antenna gain = 2 dBi.

where,  $S = Power Density (mW/cm^2)$ 

P = Power Input to antenna (39.99mW)

G = Antenna Gain (1.58 numeric)

 $S = (39.99*1.58/4*3.14*20.0^2) = (63.38697/5024) = 0.0126 \text{mW/cm}^2$  @ 20cm separation



# MPE Calculation – Co-Location of Wistron Module, FCC ID: NKRCM9 & Novatel Module, FCC ID: PKRNVWV620 &

#### **MPE Summary:**

Frequency Range (MHz)	MPE Result (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2405 - 2480	0.000426	1
2412 – 2462	0.0126	1

**Test Requirements:** [MPE(f1) + MPE(f2) / limit(f1) + / limit(f2)] < 1

#### **Test Results:**

MPE(f1)	MPE(f2)	Calculation	MPE Result
Frequency (MHz)	Frequency (MHz)	[MPE(f1) + MPE(f2) / limit(f1) + / limit(f2)]	$(mW/cm^2)$
2405 - 2480	2412 – 2462	0.000426/1 + 0.0126/1 = (0.000426 + 0.0126)	0.013