

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-18O-RWD-008

AGR No. : A188A-406

Applicant : BLUECOM Co., Ltd.

Address : 116, Venture-ro, Yeonsu-gu, Incheon, Korea

Manufacturer : BLUECOM Co., Ltd.

Address : 116, Venture-ro, Yeonsu-gu, Incheon, Korea

Type of Equipment : Bluetooth Headset

FCC ID. : U3WBCS200

Model Name : BCS-200

Multiple Model Name : BCS-100

Serial number : N/A

Total page of Report : 7 pages (including this page)

Date of Incoming : August 28, 2018

Date of issue : October 04, 2018

SUMMARY

The equipment complies with the regulation; FCC PART 15 SUBPART C Section 15.247

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:

Jae-Ho Lee / Chief Engineer ONETECH Corp.

Approved by:

Keun-Young, Choi / Vice President


Report No.: OT-18O-RWD-008

ONETECH Corp.



CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION	
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT	5
3. EUT MODIFICATIONS	5
4. MAXIMUM PERMISSIBLE EXPOSURE	6
4.1 EUT DESCRIPTION	6
4.3 CALCULATED MPE SAFE DISTANCE	7





Revision History

Rev. No.	Issue Report No.	ue Report No.		Section Affected
0	OT-18O-RWD-008	October 04, 2018	Initial Issue	All



Report No.: OT-18O-RWD-008



1. VERIFICATION OF COMPLIANCE

Applicant : BLUECOM Co., Ltd.

Address : 116, Venture-ro, Yeonsu-gu, Incheon, Korea

Contact Person: Ki-eok Park / Principal Engineer

Telephone No. : 82-32-8100-582
FCC ID : U3WBCS200
Model Name : BCS-200

Brand Name : Serial Number : N/A

Date : October 04, 2018

EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER
E.U.T. DESCRIPTION	Bluetooth Headset
KIND OD EQUIPMENT	Modular Transmitter
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

^{-.} The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

Report No.: OT-18O-RWD-008



2. GENERAL INFORMATION

2.1 Product Description

The BLUECOM Co., Ltd., Model BCS-200 (referred to as the EUT in this report) is a Bluetooth Headset. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	Bluetooth Headset		
Operating Frequency	2 402 MHz ~ 2 480 MHz		
RF Output Power	1 Mbps	5.84 dBm	
	2 Mbps	5.66 dBm	
	3 Mbps	5.85 dBm	
Number of Channel	79 Channels		
Modulation Type	GFSK for 1 Mbps, π/4-DQPSK for 2 Mbps, 8-DPSK for 3Mbps		
Antenna Type	FPCB Antenna		
Antenna Gain	5.07 dBi		
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	16 MHz		
Rated Supply Voltage	DC 3.7 V		

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None



4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 EUT Description

Kind of EUT	Bluetooth Headset			
Operating Frequency Band	 □ Wireless Microphone: 494.000 MHz ~ 501.000 MHz and 498.200 MHz ~ 505.200 MHz □ WLAN: 2 412 MHz ~ 2 462 MHz □ WLAN: 5 180 MHz ~ 5 240 MHz □ WLAN: 5 745 MHz ~ 5 825 MHz ■ Bluetooth: 2 402 MHz ~ 2 480 MHz □ Bluetooth BLE: 2 402 MHz ~ 2 480 MHz 			
MAX. RF OUTPUT POWER	1 Mbps 5.84 dBm 2 Mbps 5.66 dBm 3 Mbps 5.85 dBm			
Antenna Gain	5.07 dBi			
Exposure Evaluation Applied	□ MPE □ SAR ■ N/A			

Report No.: OT-18O-RWD-008

4.3 Calculated MPE Safe Distance

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is [(Max. Power of channel, including tune-up tolerance, mW)/(Mim. test separation distance, mm)] X [$\sqrt{f(GHz)}$] < 3 = (3.85/5) X $\sqrt{2.441}$ = 1.20

Conclusion: The SAR test exclusion threshold is less than 3, so the device meets the RF Exposure Requirement and are excluded from SAR Test.

	Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
1 Mbps	2 441	5.34 ± 0.5	5.84	3.84	5	1.20
2 Mbps	2 441	5.16 ± 0.5	5.66	3.68	5	1.15
3 Mbps	2 441	5.35 ± 0.5	5.85	3.85	5	1.20

Tested by: Ju Yun Park / Assistant Manager