

# FCC RF Test Report

APPLICANT : Teleepoch Ltd.  
EQUIPMENT : CDMA1X handset  
BRAND NAME : PCD  
MODEL NAME : CDM2070PM  
FCC ID : U46-CDM2070  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Apr. 26, 2012 and completely tested on Jul. 17, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



---

Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.**

## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Feature of Equipment Under Test.....	5
1.4 Testing Site.....	6
1.5 Applied Standards .....	6
1.6 Ancillary Equipment List .....	6
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>7</b>
2.1 RF Output Power.....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 RF Utility .....	9
<b>3 TEST RESULT .....</b>	<b>10</b>
3.1 Number of Channel Measurement .....	10
3.2 Hopping Channel Separation Measurement .....	12
3.3 Dwell Time Measurement.....	15
3.4 20dB and 99% Bandwidth Measurement.....	17
3.5 Peak Output Power Measurement .....	30
3.6 Conducted Band Edges Measurement .....	33
3.7 Conducted Spurious Emission Measurement .....	35
3.8 Radiated Band Edges Measurement.....	39
3.9 Radiated Spurious Emission Measurement .....	49
3.10 AC Conducted Emission Measurement.....	59
3.11 Antenna Requirements.....	63
<b>4 LIST OF MEASURING EQUIPMENT.....</b>	<b>64</b>
<b>5 UNCERTAINTY OF EVALUATION.....</b>	<b>65</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT</b>	
<b>APPENDIX B. SETUP PHOTOGRAPHS</b>	

## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR242601	Rev. 01	Initial issue of report	Jul. 18, 2012
FR242601	Rev. 02	Update report for revising photograph of EUT	Jul. 26, 2012

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	A8.4(2)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	A8.1(b)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	A8.1(d)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	A8.1(a)	20dB Bandwidth	NA	Pass	-
3.4	-	Gen 4.6.1	99% Bandwidth	-	Pass	-
3.5	15.247(b)(1)	A8.1(b)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	A8.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	A8.5	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	A8.5	Radiated Band Edges	15.209(a) & 15.247(d)	Pass	-
3.9	15.247(d)	A8.5	Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.37 dB at 71.710 MHz
3.10	15.207	Gen 7.2.4	AC Conducted Emission	15.207(a)	Pass	Under limit 16.61 dB at 3.440 MHz
3.11	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

# 1 General Description

## 1.1 Applicant

**Teleepoch Ltd.**

5A, B1 building, Digital tech zone, Hi-Tech industry park, Nanshan District Shenzhen, 518057, China

## 1.2 Manufacturer

**Teleepoch Ltd.**

5A, B1 building, Digital tech zone, Hi-Tech industry park, Nanshan District Shenzhen, 518057, China

## 1.3 Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	CDMA1X handset
<b>Brand Name</b>	PCD
<b>Model Name</b>	CDM2070PM
<b>FCC ID</b>	U46-CDM2070
<b>EUT supports Radios application</b>	CDMA / Bluetooth
<b>HW Version</b>	C5630_Main_V1.0
<b>SW Version</b>	C5630_01.01.11I
<b>EUT Stage</b>	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Product Specification subjective to this standard	
<b>Tx/Rx Frequency Range</b>	2402 MHz ~ 2480 MHz
<b>Number of Channels</b>	79
<b>Carrier Frequency of Each Channel</b>	2402+n*1 MHz; n=0~78
<b>Maximum Output Power to Antenna</b>	Bluetooth (1Mbps) : 3.68 dBm (0.0023 W) Bluetooth EDR (2Mbps) : 2.98 dBm (0.0020 W) Bluetooth EDR (3Mbps) : 1.65 dBm (0.0015 W)
<b>99% Occupied Bandwidth</b>	Bluetooth (1Mbps) : 0.916MHz Bluetooth EDR (2Mbps) : 1.180MHz Bluetooth EDR (3Mbps) : 1.188MHz
<b>Antenna Type</b>	PCB Antenna with gain 0.56 dBi
<b>Type of Modulation</b>	Bluetooth (1Mbps) : GFSK Bluetooth 2.1 EDR (2Mbps) : $\pi$ /4-DQPSK Bluetooth 2.1 EDR (3Mbps) : 8-DPSK

## 1.4 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.			
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
<b>Test Site No.</b>	<b>Sporton Site No.</b>			<b>FCC/IC Registration No.</b>
	TH01-KS	CO01-KS	03CH01-KS	149928/4086E-1

## 1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.4-2003 and ANSI C63.10-2009
- ♦ IC RSS-210 Issue 8
- ♦ IC RSS-Gen Issue 3

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
3.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-106	QTLBH-106	N/A	N/A

## 2 Test Configuration of Equipment Under Test

### 2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Band	Bluetooth RF Output Power		
Channel	00	39	78
Frequency	2402	2441	2480
Peak Power	1.77	2.18	3.68

**Remark:**

1. All the test data for each data rate were verified, but only the worst case was reported.
2. The data rate was set in 1Mbps for all the test items due to the highest RF output power.
3. The EUT is programmed to transmit signals continuously for all testing.

## 2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and ANSI C63.10-2009 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 KHz to 30 MHz), radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Pre-scanned tests, X, Y, Z in three orthogonal panels, were conducted to determine the final configuration from all possible combinations.


The following tables are showing the test modes as the worst cases (X plane) and recorded in this report.

Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	N/A	N/A
AC Conducted Emission	Mode 1 :CDMA2000 BC0 Idle + Bluetooth Idle + USB Cable (Charging from Adapter) + Earphone + Camera		
Remark:  For radiated TCs, the data rate was set in 1Mbps due to the highest RF output power; only the data of these modes was reported.			




## 2.3 Connection Diagram of Test System

### <Bluetooth Tx Mode>



### <AC Conducted Emission Mode>



## 2.4 RF Utility

For Bluetooth function, key in “\*01763\*918#” on the EUT directly. Then, the EUT will get into the engineering modes to contact with Bluetooth base station for continuous transmitting and receiving signals.

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedure


1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation;  $RBW \geq 1\%$  of the span;  $VBW \geq RBW$ ; Sweep = auto; Detector function = peak; Trace = max hold.

4. The number of hopping frequency used is defined as the device has the numbers of total channel.


##### 3.1.4 Test Setup




### 3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	1Mbps	Temperature :	23~24℃
Test Engineer :	Lizy Li	Relative Humidity :	47~48%
Number of Hopping Channels (Channel)		Limits (Channel)	Pass/Fail
79		> 15	Pass

**Number of Hopping Channel Plot on Channel 00 - 78**



Date: 22.JUN.2012 00:06:05



Date: 22.JUN.2012 00:09:51

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  $RBW \geq 1\%$  of the span;  
VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

### 3.2.4 Test Setup




### 3.2.5 Test Result of Hopping Channel Separation


Test Mode :	1Mbps	Temperature :	23~24℃
Test Engineer :	Lizy Li	Relative Humidity :	47~48%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.6560	Pass
39	2441	1.002	0.6533	Pass
78	2480	1.002	0.6347	Pass


**Channel Separation Plot on Channel 00 - 01**



Date: 21.JUN.2012 23:38:28

**Channel Separation Plot on Channel 39 - 40**


Date: 21.JUN.2012 23:39:08

**Channel Separation Plot on Channel 77 - 78**


Date: 21.JUN.2012 23:39:47

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:  
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

#### 3.3.4 Test Setup



#### 3.3.5 Test Result of Dwell Time


<b>Test Mode :</b>	DH5	<b>Temperature :</b>	23~24℃
<b>Test Engineer :</b>	Lizy Li	<b>Relative Humidity :</b>	47~48%


Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
DH5	3.30	2962.00	0.31	0.4	Pass

**Remark:**

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. T: Package Transfer Time(us)

**DH5 Dwell Time (One Pulse) Plot on Channel 39**


Date: 21.JUN.2012 15:58:27

**DH5 Dwell Time (Count Pulses) Plot on Channel 39**


Date: 21.JUN.2012 16:03:15



### 3.4 20dB and 99% Bandwidth Measurement

#### 3.4.1 Limit of 20dB Bandwidth

N/A


#### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:  
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

#### 3.4.4 Test Setup




### 3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	23~24℃
Test Engineer :	Lizy Li	Relative Humidity :	47~48%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.984
39	2441	0.980
78	2480	0.952


**20 dB Bandwidth Plot on Channel 00**



Date: 21.JUN.2012 23:46:03




### 20 dB Bandwidth Plot on Channel 39



Date: 21.JUN.2012 23:46:12

### 20 dB Bandwidth Plot on Channel 78




Date: 21.JUN.2012 23:46:21




Test Mode :	2Mbps	Temperature :	23~24℃
Test Engineer :	Lizy Li	Relative Humidity :	47~48%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.278
39	2441	1.284
78	2480	1.284

**20 dB Bandwidth Plot on Channel 00**

Date: 21.JUN.2012 23:46:35

**20 dB Bandwidth Plot on Channel 39**


Date: 21.JUN.2012 23:46:46

**20 dB Bandwidth Plot on Channel 78**



Date: 21.JUN.2012 23:46:55



Test Mode :	3Mbps	Temperature :	23~24°C
Test Engineer :	Lizy Li	Relative Humidity :	47~48%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.308
39	2441	1.308
78	2480	1.302

20 dB Bandwidth Plot on Channel 00




Date: 21.JUN.2012 23:47:02

### 20 dB Bandwidth Plot on Channel 39



Date: 21.JUN.2012 23:47:10

### 20 dB Bandwidth Plot on Channel 78




Date: 21.JUN.2012 23:47:16

### 3.4.6 Test Result of 99% Occupied Bandwidth

Test Mode :	1Mbps	Temperature :	23~24℃
Test Engineer :	Lizy Li	Relative Humidity :	47~48%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.892
39	2441	0.912
78	2480	0.916

**99% Bandwidth Plot on Channel 00**




Date: 21.JUN.2012 23:53:39






### 99% Occupied Bandwidth Plot on Channel 39



Date: 21.JUN.2012 23:54:15


### 99% Occupied Bandwidth Plot on Channel 78




Date: 22.JUN.2012 00:37:12

<b>Test Mode :</b>	2Mbps	<b>Temperature :</b>	23~24℃
<b>Test Engineer :</b>	Lizy Li	<b>Relative Humidity :</b>	47~48%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.172
39	2441	1.180
78	2480	1.180

**99% Bandwidth Plot on Channel 00**


Date: 21.JUN.2012 23:55:28

**99% Occupied Bandwidth Plot on Channel 39**



Date: 21.JUN.2012 23:56:04

**99% Occupied Bandwidth Plot on Channel 78**


Date: 21.JUN.2012 23:56:40


<b>Test Mode :</b>	3Mbps	<b>Temperature :</b>	23~24℃
<b>Test Engineer :</b>	Lizy Li	<b>Relative Humidity :</b>	47~48%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.180
39	2441	1.188
78	2480	1.184

**99% Bandwidth Plot on Channel 00**



Date: 21.JUN.2012 23:57:16

## 99% Occupied Bandwidth Plot on Channel 39



Date: 21.JUN.2012 23:57:52

## 99% Occupied Bandwidth Plot on Channel 78



Date: 21.JUN.2012 23:58:28

### 3.5 Peak Output Power Measurement

#### 3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps is 1watt, and for 2Mbps, and 3Mbps are 0.125 watts.


#### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.

#### 3.5.4 Test Setup




#### 3.5.5 Test Result of Peak Output Power

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	23~24°C
<b>Test Engineer :</b>	Lizy Li	<b>Relative Humidity :</b>	47~48%


Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	1.77	30.00	Pass
39	2441	2.18	30.00	Pass
78	2480	3.68	30.00	Pass

## Peak Output Power Plot on Channel 00



Date: 21.JUN.2012 15:14:39


## Peak Output Power Plot on Channel 39



Date: 21.JUN.2012 15:15:54



Peak Output Power Plot on Channel 78



Date: 21.JUN.2012 15:17:10



### 3.6 Conducted Band Edges Measurement

#### 3.6.1 Limit of Band Edges

In any 100 KHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


#### 3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.6.3 Test Procedures

1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.
2. Set RBW = 300KHz ( $\geq 1\%$  span=30MHz ), VBW = 300KHz ( $\geq$  RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300k Hz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.


#### 3.6.4 Test Setup



### 1.6.5 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	23~24℃
Test Channel :	00 and 78	Relative Humidity :	47~48%
		Test Engineer :	Lizy Li

#### Low Band Edge Plot on Channel 00



Date: 21.JUN.2012 23:48:10

#### High Band Edge Plot on Channel 78



Date: 21.JUN.2012 23:49:13

### 3.7 Conducted Spurious Emission Measurement

#### 3.7.1 Limit of Spurious Emission Measurement

In any 100 KHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


#### 3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.7.3 Test Procedure

1. The testing follows the guidelines in Spurious RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines
2. The transmitter output was connected to the spectrum analyzer via a low lose cable.
3. Set RBW = 100 KHz, VBW = 300KHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 KHz RBW.


#### 3.7.4 Test Setup



### 3.7.5 Test Result


Test Mode :	1Mbps	Temperature :	23~24℃
Test Channel :	00	Relative Humidity :	47~48%
		Test Engineer :	Lizy Li

#### Conducted Spurious Emission Plot between 30MHz ~ 3 GHz




Date: 17.JUL.2012 09:46:41

#### Conducted Spurious Emission Plot between 2 GHz ~ 25 GHz




Date: 17.JUL.2012 09:47:31

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	23~24°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	47~48%
		<b>Test Engineer :</b>	Lizy Li

**Conducted Spurious Emission Plot between 30MHz ~ 3 GHz**



Date: 17.JUL.2012 09:49:19

**Conducted Spurious Emission Plot between 2 GHz ~ 25 GHz**



Date: 17.JUL.2012 09:48:37



Test Mode :	1Mbps	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	47~48%
		Test Engineer :	Lizy Li

**Conducted Spurious Emission Plot between 30MHz ~ 3 GHz**

Date: 17.JUL.2012 09:50:33

**Conducted Spurious Emission Plot between 2 GHz ~ 25 GHz**

Date: 17.JUL.2012 09:51:11

### 3.8 Radiated Band Edges Measurement

#### 3.8.1 Limit of Radiated Band Edges

In any 100 KHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3


#### 3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.8.3 Test Procedures

1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines and fulfills ANSI C63.4-2003 and the guidelines in ANSI C63.10-2009 test site requirement.
2. Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
3. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

### 3.8.4 Test Setup





**3.8.5 Test Result of Radiated Band Edges**

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	41~42%
		<b>Test Engineer :</b>	Jack Li

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2332.23	44.78	-29.22	74	42.65	32.76	3.27	33.9	100	186	Peak
2332.23	30.72	-23.28	54	28.59	32.76	3.27	33.9	100	186	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2311.33	45.43	-28.57	74	43.34	32.73	3.22	33.86	100	360	Peak
2311.33	31.03	-22.97	54	28.94	32.73	3.22	33.86	100	360	Average

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~42%
		<b>Test Engineer :</b>	Jack Li

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2484.35	48.37	-25.63	74	45.88	33.01	3.68	34.2	198	360	Peak
2484.35	34.83	-19.17	54	32.34	33.01	3.68	34.2	198	360	Average

**Summary results of marker-delta method:**

Test mode	Maximum field strength of the fundamental emission (dBμV/m)	Delta Result (dB)	Average Result (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)	Result
Single Carrier Mode	85.88	53.19	32.69	54	-21.31	Pass
Hopping Mode	85.88	51.05	34.83	54	-19.17	Pass

**Note:** Average result = Maximum field strength – Delta result


ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2484.71	44.84	-29.16	74	42.35	33.01	3.68	34.2	120	12	Peak
2484.71	33.62	-20.38	54	31.13	33.01	3.68	34.2	120	12	Average

**Summary results of marker-delta method:**

Test mode	Maximum field strength of the fundamental emission (dBμV/m)	Delta Result (dB)	Average Result (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)	Result
Single Carrier Mode	80.42	47.17	33.25	54	-20.75	Pass
Hopping Mode	80.42	46.8	33.62	54	-20.38	Pass

**Note:** Average result = Maximum field strength – Delta result

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal




Site : 03CH01-KS  
 Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL  
 Project : (FR) 242601

: DH5

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 X	2480.00	99.92	25.92	74.00	97.43	33.01	3.68	34.20	176	360 Peak
2 X	2480.00	85.88	31.88	54.00	83.39	33.01	3.68	34.20	176	360 Average

\* Maximum field strength of the fundamental emission

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal




Site : 03CH01-KS  
 Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL  
 Project : (FR) 242601

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 X	2480.00	99.78	25.78	74.00	97.29	33.01	3.68	34.20	177	358 Peak
2	2483.58	46.59	-27.41	74.00	44.10	33.01	3.68	34.20	200	360 Peak

\* Marker-Delta Method (RBW/VBW=100KHz): 53.19 dB , single carrier Mode

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal




Site : 03CH01-KS  
Condition: FCC PART 15C 3m HF ANT-100803 HORIZONTAL  
Project : (FR) 242601

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 X	2480.00	99.42	25.42	74.00	96.93	33.01	3.68	34.20	176	359 Peak
2	2484.35	48.37	-25.63	74.00	45.88	33.01	3.68	34.20	198	360 Peak

\* Marker-Delta Method (RBW/VBW=100KHz): 51.05 dB , Hopping Mode

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical




Site : 03CH01-KS  
Condition: FCC PART 15C 3m HF ANI-100803 VERTICAL  
Project : (FR) 242601

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 X	2480.00	92.63	18.63	74.00	90.14	33.01	3.68	34.20	175	3	Peak
2 X	2480.00	80.42	26.42	54.00	77.93	33.01	3.68	34.20	175	3	Average

\* Maximum field strength of the fundamental emission

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical




Site : 03CH01-KS  
 Condition: FCC PART 15C 3m HF ANT-100803 VERTICAL  
 Project : (FR) 242601

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	
	MHz	dBuV/m	dB	dBuV/m	Level	Loss	Factor	Pos	Pos	Remark
					dBuV	dB		cm	deg	
1 X	2480.00	91.95	17.95	74.00	89.46	33.01	3.68	34.20	177	0 Peak
2	2484.54	44.78	-29.22	74.00	42.29	33.01	3.68	34.20	125	210 Peak

\* Marker-Delta Method (RBW/VBW=100KHz): 47.17 dB , single carrier Mode

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical



Site : 03CH01-KS  
Condition: FCC PART 15C 3m HF ANT-100803 VERTICAL  
Project : (FR) 242601

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preampl	Ant	Table	
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	Remark
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 X	2480.00	91.64	17.64	74.00	89.15	33.01	3.68	34.20	176	2 Peak
2	2484.71	44.84	-29.16	74.00	42.35	33.01	3.68	34.20	120	12 Peak

\* Marker-Delta Method (RBW/VBW=100KHz): 46.8 dB , Hopping Mode



### 3.9 Radiated Spurious Emission Measurement

#### 3.9.1 Limit of Radiated Emission

In any 100 KHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.9.2 Measuring Instruments


See list of measuring instruments of this test report.

### **3.9.3 Test Procedures**


1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines and fulfills ANSI C63.4-2003 and the guidelines in ANSI C63.10-2009 test site requirement.
2. Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
3. Follow the guidelines in ANSI C63.4-2003 and ANSI C63.10-2009 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.
4. Measured average value if the peak value is greater than 54 dBuV/m

### 3.9.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.9.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

**3.9.6 Test Result of Radiated Emission (30 MHz ~ 10<sup>th</sup> Harmonic)**

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2402 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
34.85	35.99	-4.01	40	50.75	15.1	0.23	30.09	125	342	Peak
74.62	34.48	-5.52	40	58.4	5.8	0.34	30.06	-	-	Peak
191.99	33.02	-10.48	43.5	53.81	8.59	0.58	29.96	-	-	Peak
288.02	37.56	-8.44	46	53.98	12.82	0.71	29.95	-	-	Peak
307.42	34.96	-11.04	46	51.01	13.17	0.73	29.95	-	-	Peak
432.55	28.77	-17.23	46	41.48	16.21	0.88	29.8	-	-	Peak
2332.23	30.72	-23.28	54	28.59	32.76	3.27	33.9	100	186	Average
2332.23	44.78	-29.22	74	42.65	32.76	3.27	33.9	100	186	Peak
2402	97.97	-	-	95.69	32.86	3.47	34.05	100	170	Average
2402	98.47	-	-	96.19	32.86	3.47	34.05	100	170	Peak
2494.11	31.85	-22.15	54	29.31	33.05	3.72	34.23	125	69	Average
2494.11	47.99	-26.01	74	45.45	33.05	3.72	34.23	125	69	Peak
4804	41.94	-12.06	54	34.07	35.17	4.97	32.27	145	245	Average
4804	51.28	-22.72	74	43.41	35.17	4.97	32.27	145	245	Peak

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	00	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2402 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
40.67	31.7	-8.3	40	49.86	11.64	0.25	30.05	128	273	Peak
74.62	30.15	-9.85	40	54.07	5.8	0.34	30.06	-	-	Peak
345.25	30.92	-15.08	46	45.65	14.4	0.81	29.94	-	-	Peak
432.55	29.4	-16.6	46	42.11	16.21	0.88	29.8	-	-	Peak
480.08	33.82	-12.18	46	45.76	16.87	0.94	29.75	-	-	Peak
576.11	31.01	-14.99	46	41.07	18.55	1.04	29.65	-	-	Peak
2311.33	31.03	-22.97	54	28.94	32.73	3.22	33.86	100	360	Average
2311.33	45.43	-28.57	74	43.34	32.73	3.22	33.86	100	360	Peak
2402	94.53	-	-	92.25	32.86	3.47	34.05	100	360	Average
2402	94.72	-	-	92.44	32.86	3.47	34.05	100	360	Peak
2493.73	31.73	-22.27	54	29.19	33.05	3.72	34.23	108	256	Average
2493.73	46.19	-27.81	74	43.65	33.05	3.72	34.23	108	256	Peak
4804	45.58	-8.42	54	37.71	35.17	4.97	32.27	100	360	Average
4804	54.36	-19.64	74	46.49	35.17	4.97	32.27	100	360	Peak

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2441 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
34.85	34.95	-5.05	40	49.71	15.1	0.23	30.09	-	-	Peak
71.71	36.63	-3.37	40	60.9	5.46	0.34	30.07	125	92	Peak
122.15	39.61	-3.89	43.5	57.35	11.78	0.45	29.97	-	-	Peak
288.02	36.1	-9.9	46	52.52	12.82	0.71	29.95	-	-	Peak
307.42	34.56	-11.44	46	50.61	13.17	0.73	29.95	-	-	Peak
675.05	29.53	-16.47	46	39.01	19.1	1.11	29.69	-	-	Peak
2374	33	-21	54	30.76	32.83	3.42	34.01	127	89	Average
2374	44.91	-29.09	74	42.67	32.83	3.42	34.01	127	89	Peak
2441	97.76	-	-	95.36	32.95	3.6	34.15	100	177	Average
2441	99.56	-	-	97.16	32.95	3.6	34.15	100	177	Peak
2492.59	32.6	-21.4	54	30.06	33.05	3.72	34.23	125	24	Average
2492.59	47.88	-26.12	74	45.34	33.05	3.72	34.23	125	24	Peak
4882	40.63	-13.37	54	32.74	35.18	4.98	32.27	100	360	Average
4882	50.84	-23.16	74	42.95	35.18	4.98	32.27	100	360	Peak

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	39	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2441 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
36.79	28.79	-11.21	40	44.43	14.19	0.24	30.07	-	-	Peak
73.65	30.09	-9.91	40	54.13	5.68	0.34	30.06	138	245	Peak
345.25	32.19	-13.81	46	46.92	14.4	0.81	29.94	-	-	Peak
480.08	32.96	-13.04	46	44.9	16.87	0.94	29.75	-	-	Peak
578.05	28.3	-17.7	46	38.34	18.56	1.04	29.64	-	-	Peak
720.64	28.83	-17.17	46	37.81	19.53	1.15	29.66	-	-	Peak
2313.8	31.17	-22.83	54	29.08	32.73	3.22	33.86	110	45	Average
2313.8	44.69	-29.31	74	42.6	32.73	3.22	33.86	110	45	Peak
2441	94.58	-	-	92.18	32.95	3.6	34.15	108	0	Average
2441	94.84	-	-	92.44	32.95	3.6	34.15	108	0	Peak
2497.34	31.29	-22.71	54	28.75	33.05	3.72	34.23	108	25	Average
2497.34	47.78	-26.22	74	45.24	33.05	3.72	34.23	108	25	Peak
4881	45.92	-8.08	54	38.03	35.18	4.98	32.27	100	254	Average
4881	52.53	-21.47	74	44.64	35.18	4.98	32.27	100	254	Peak



<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	2480 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
36.79	32.78	-7.22	40	48.42	14.19	0.24	30.07	-	-	Peak
74.62	35.61	-4.39	40	59.53	5.8	0.34	30.06	145	239	Peak
137.67	31.82	-11.68	43.5	50.28	11.05	0.49	30	-	-	Peak
191.99	32.74	-10.76	43.5	53.53	8.59	0.58	29.96	-	-	Peak
288.02	36.26	-9.74	46	52.68	12.82	0.71	29.95	-	-	Peak
307.42	32.83	-13.17	46	48.88	13.17	0.73	29.95	-	-	Peak
2318	36.1	-17.9	54	33.97	32.76	3.27	33.9	108	342	Average
2318	49.34	-24.66	74	47.21	32.76	3.27	33.9	108	342	Peak
2480	99.92	-	-	97.43	33.01	3.68	34.2	176	360	Peak
2480	85.88	-	-	83.39	33.01	3.68	34.2	176	360	Average
2484.35	48.37	-25.63	74	45.88	33.01	3.68	34.2	198	360	Peak
2484.35	34.83	-19.17	54	32.34	33.01	3.68	34.2	198	360	Average

<b>Test Mode :</b>	1Mbps	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	78	<b>Relative Humidity :</b>	41~42%
<b>Test Engineer :</b>	Jack Li	<b>Polarization :</b>	Vertical
<b>Remark :</b>	2480 MHz is fundamental signal which can be ignored.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
35.82	34.06	-5.94	40	49.26	14.65	0.23	30.08	104	245	Peak
73.65	31.77	-8.23	40	55.81	5.68	0.34	30.06	-	-	Peak
345.25	31.21	-14.79	46	45.94	14.4	0.81	29.94	-	-	Peak
480.08	34.94	-11.06	46	46.88	16.87	0.94	29.75	-	-	Peak
576.11	31.79	-14.21	46	41.85	18.55	1.04	29.65	-	-	Peak
719.67	29.48	-16.52	46	38.47	19.52	1.15	29.66	-	-	Peak
2326	48.71	-25.29	74	46.58	32.76	3.27	33.9	100	256	Peak
2326	35.95	-18.05	54	33.82	32.76	3.27	33.9	100	256	Average
2480	92.63	-	-	90.14	33.01	3.68	34.2	175	3	Peak
2480	80.42	-	-	77.93	33.01	3.68	34.2	175	3	Average
2484.71	44.84	-29.16	74	42.35	33.01	3.68	34.2	120	12	Peak
2484.71	33.62	-20.38	54	31.13	33.01	3.68	34.2	120	12	Average

### 3.10 AC Conducted Emission Measurement

#### 3.10.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.10.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.10.3 Test Procedures


1. Please follow the guidelines in ANSI C63.4-2003 and ANSI C63.10-2009 test site requirement.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 KHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

### 3.10.4 Test Setup



### 3.10.5 Test Result of AC Conducted Emission


<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	19~20℃
<b>Test Engineer :</b>	Tom Wang	<b>Relative Humidity :</b>	39~40%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Line
<b>Function Type :</b>	CDMA2000 BC0 Idle + Bluetooth Idle + USB Cable (Charging from Adapter) + Earphone + Camera		
<b>Remark :</b>	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS  
 Condition: FCC PART15C LISN-111230 LINE  
 Project : (FR) 242601  
 mode : Mode 1  
 IMEI : 0x801579BA

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	2.38	27.41	-18.59	46.00	16.80	-0.11	10.72	Average
2	2.38	35.11	-20.89	56.00	24.50	-0.11	10.72	QP
3	2.58	35.32	-20.68	56.00	24.69	-0.11	10.74	QP
4	2.58	27.72	-18.28	46.00	17.09	-0.11	10.74	Average
5	2.72	28.34	-17.66	46.00	17.71	-0.12	10.75	Average
6	2.72	35.24	-20.76	56.00	24.61	-0.12	10.75	QP
7	3.19	28.28	-17.72	46.00	17.60	-0.12	10.80	Average
8	3.19	35.58	-20.42	56.00	24.90	-0.12	10.80	QP
9	3.55	27.59	-18.41	46.00	16.89	-0.12	10.82	Average
10	3.55	35.29	-20.71	56.00	24.59	-0.12	10.82	QP
11	3.78	27.20	-18.80	46.00	16.51	-0.13	10.82	Average
12	3.78	34.50	-21.50	56.00	23.81	-0.13	10.82	QP

<b>Test Mode :</b>	Mode 1	<b>Temperature :</b>	19~20℃
<b>Test Engineer :</b>	Tom Wang	<b>Relative Humidity :</b>	39~40%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Neutral
<b>Function Type :</b>	CDMA2000 BC0 Idle + Bluetooth Idle + USB Cable (Charging from Adapter) + Earphone + Camera		
<b>Remark :</b>	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : C001-KS  
 Condition: FCC PART15C LISN-111230 NEUTRAL  
 Project : (FR) 242601  
 mode : Mode 1  
 IMEI : 0x801579BA

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	2.84	28.95	-17.05	46.00	18.30	-0.12	10.77	Average
2	2.84	36.35	-19.65	56.00	25.70	-0.12	10.77	QP
3	2.95	36.56	-19.44	56.00	25.90	-0.12	10.78	QP
4	2.95	28.86	-17.14	46.00	18.20	-0.12	10.78	Average
5	3.06	36.37	-19.63	56.00	25.70	-0.12	10.79	QP
6	3.06	29.07	-16.93	46.00	18.40	-0.12	10.79	Average
7	3.21	29.18	-16.82	46.00	18.50	-0.12	10.80	Average
8	3.21	36.58	-19.42	56.00	25.90	-0.12	10.80	QP
9	3.44	29.39	-16.61	46.00	18.70	-0.12	10.81	Average
10	3.44	36.19	-19.81	56.00	25.50	-0.12	10.81	QP
11	3.64	29.19	-16.81	46.00	18.49	-0.12	10.82	Average
12	3.64	35.99	-20.01	56.00	25.29	-0.12	10.82	QP

## 3.11 Antenna Requirements

### 3.11.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### 3.11.2 Antenna Connected Construction

Non-standard connector used.

### 3.11.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Jun. 21, 2012~ Jul. 17, 2012	Dec. 29, 2012	Conducted (TH01-KS)
Power Meter	Agilent	E4416A	MY451015 55	N/A	Aug. 23, 2011	Jun. 21, 2012~ Jul. 17, 2012	Aug. 22, 2012	Conducted (TH01-KS)
Power Sensor	Agilent	E9327A	MY444211 98	N/A	Aug. 23, 2011	Jun. 21, 2012~ Jul. 17, 2012	Aug. 22, 2012	Conducted (TH01-KS)
DC Power Supply	GWINSTEK	GPS-3030D	E1884515	N/A	Aug. 23, 2011	Jun. 21, 2012~ Jul. 17, 2012	Aug. 22, 2012	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-9605 02	N/A	Dec. 30, 2011	Jun. 21, 2012~ Jul. 17, 2012	Dec. 29, 2012	Conducted (TH01-KS)
Bluetooth Base Station	R&S	CBT	100783	N/A	Aug. 18, 2011	Jun. 21, 2012~ Jul. 17, 2012	Aug. 17, 2012	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 09, 2011	Jul. 16, 2012	Nov. 08, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Jul. 16, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 08, 2011	Jul. 16, 2012	Dec. 07, 2012	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/00	9 kHz~30 MHz	Jul. 28, 2011	Jul. 16, 2012	Jul. 27, 2012	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2012	Jul. 16, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 30, 2011	Jul. 16, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A023 70	1GHz~26.5GHz	Dec. 30, 2011	Jul. 16, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701023	1GHz~18GHz	Nov. 07, 2011	Jul. 16, 2012	Nov. 06, 2012	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Oct. 11, 2011	Jul. 16, 2012	Oct.10, 2012	Radiation (03CH01-KS)
Bluetooth Base Station	R&S	CBT	100783	N/A	Aug. 18, 2011	Jul. 16, 2012	Aug. 17, 2012	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz	Jun. 01, 2012	Jun. 21, 2012	May 31, 2013	Conduction (CO01-KS)
LISN	MessTec	AN3016	60103	9kHz~30MHz	Dec. 30, 2011	Jun. 21, 2012	Dec. 29, 2012	Conduction (CO01-KS)
LISN	MessTec	AN3016	60105	9kHz~30MHz	Dec. 30, 2011	Jun. 21, 2012	Dec. 29, 2012	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	N/A	Nov. 16, 2011	Jun. 21, 2012	Nov. 15, 2012	Conduction (CO01-KS)
System Simulator	R&S	CMU200	837587/06 6	2G Full-Band	Dec. 30, 2011	Jun. 21, 2012	Dec. 29, 2012	Conduction (CO01-KS)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	2.26
--	------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	2.54
--	------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	4.72
--	------



## **Appendix A. Photographs of EUT**

Please refer to Sporton report number EP242601 as below.