## #01 CDMA2000 BC0_RC3 SO55_Right Cheek_Ch1013

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: HSL_835_101228 Medium parameters used: f = 824.7 MHz; $\sigma$ = 0.893 mho/m; $\varepsilon_r$ = 40.8; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：21.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM1; Type: SAM; Serial: TP-1477
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (41x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.08 mW/g

**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 30.1 V/m; Power Drift = -0.103 dB
Peak SAR (extrapolated) = 1.28 W/kg
**SAR(1 g) = 0.974 mW/g; SAR(10 g) = 0.697 mW/g**
Maximum value of SAR (measured) = 1.03 mW/g




0 dB = 1.03mW/g

## #02 CDMA2000 BC0_RC3 SO55_Right Tilted_Ch1013

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: HSL_835_101228 Medium parameters used: f = 824.7 MHz; $\sigma$ = 0.893 mho/m; $\varepsilon_r$ = 40.8; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：21.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM1; Type: SAM; Serial: TP-1477
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (41x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.729 mW/g

**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 27.7 V/m; Power Drift = 0.107 dB
Peak SAR (extrapolated) = 0.945 W/kg
**SAR(1 g) = 0.654 mW/g; SAR(10 g) = 0.477 mW/g**
Maximum value of SAR (measured) = 0.693 mW/g




0 dB = 0.693mW/g

## #03 CDMA2000 BC0_RC3 SO55_Left Cheek_Ch1013

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: HSL_835_101228 Medium parameters used: f = 824.7 MHz; $\sigma$ = 0.893 mho/m; $\varepsilon_r$ = 40.8; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：21.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM1; Type: SAM; Serial: TP-1477
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (41x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.28 mW/g

**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 32.6 V/m; Power Drift = -0.104 dB
Peak SAR (extrapolated) = 1.49 W/kg
**SAR(1 g) = 1.14 mW/g; SAR(10 g) = 0.810 mW/g**
Maximum value of SAR (measured) = 1.19 mW/g




0 dB = 1.19mW/g

## #03 CDMA2000 BC0_RC3 SO55_Left Cheek_Ch1013_2D

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: HSL_835_101228 Medium parameters used: f = 824.7 MHz; $\sigma$ = 0.893 mho/m; $\varepsilon_r$ = 40.8; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：21.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM1; Type: SAM; Serial: TP-1477
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (41x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.28 mW/g

**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 32.6 V/m; Power Drift = -0.104 dB
Peak SAR (extrapolated) = 1.49 W/kg
**SAR(1 g) = 1.14 mW/g; SAR(10 g) = 0.810 mW/g**
Maximum value of SAR (measured) = 1.19 mW/g


1g/10g Averaged SAR
SAR; Zoom Scan:Value Along Z, X=2, Y=2
Markers
mW/g
1.2
1.1
1.0
0.9
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0.0
0.005
0.010
0.015
0.020
0.025
0.030
0.035
m

## #04 CDMA2000 BC0_RC3 SO55_Left Tilted_Ch1013

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: HSL_835_101228 Medium parameters used: f = 824.7 MHz; $\sigma$ = 0.893 mho/m; $\varepsilon_r$ = 40.8; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：21.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.67, 8.67, 8.67); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM1; Type: SAM; Serial: TP-1477
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (41x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.801 mW/g

**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 28.1 V/m; Power Drift = 0.090 dB
Peak SAR (extrapolated) = 1.06 W/kg
**SAR(1 g) = 0.708 mW/g; SAR(10 g) = 0.497 mW/g**
Maximum value of SAR (measured) = 0.743 mW/g




0 dB = 0.743mW/g

## #09 CDMA2000 BC1_RC3 SO55_Right Cheek_Ch600

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: HSL_1900_101229 Medium parameters used: f = 1880 MHz; $\sigma$ = 1.43 mho/m; $\varepsilon_r$ = 39.8; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.39, 7.39, 7.39); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM2; Type: SAM; Serial: TP-1479
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch600/Area Scan (41x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.832 mW/g

**Ch600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.7 V/m; Power Drift = 0.043 dB
Peak SAR (extrapolated) = 1.49 W/kg
**SAR(1 g) = 0.784 mW/g; SAR(10 g) = 0.428 mW/g**
Maximum value of SAR (measured) = 0.838 mW/g

**Ch600/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.7 V/m; Power Drift = 0.043 dB
Peak SAR (extrapolated) = 1.04 W/kg
**SAR(1 g) = 0.555 mW/g; SAR(10 g) = 0.321 mW/g**
Maximum value of SAR (measured) = 0.701 mW/g




0 dB = 0.701mW/g

## #14 CDMA2000 BC1_RC3 SO55_Right Tilted_Ch1175

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 1908.75 MHz;Duty Cycle: 1:1
Medium: HSL_1900_101229 Medium parameters used: f = 1909 MHz; $\sigma$ = 1.45 mho/m; $\varepsilon_r$ = 39.6; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.39, 7.39, 7.39); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM2; Type: SAM; Serial: TP-1479
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1175/Area Scan (41x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.43 mW/g

**Ch1175/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 26.6 V/m; Power Drift = -0.112 dB
Peak SAR (extrapolated) = 2.43 W/kg
**SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.669 mW/g**
Maximum value of SAR (measured) = 1.41 mW/g




0 dB = 1.41mW/g

## #16 CDMA2000 BC1_RC3 SO55_Left Cheek_Ch1175

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 1908.75 MHz;Duty Cycle: 1:1
Medium: HSL_1900_101229 Medium parameters used: f = 1909 MHz; $\sigma$ = 1.45 mho/m; $\varepsilon_r$ = 39.6; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.39, 7.39, 7.39); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM2; Type: SAM; Serial: TP-1479
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1175/Area Scan (41x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.28 mW/g

**Ch1175/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 20.5 V/m; Power Drift = 0.040 dB
Peak SAR (extrapolated) = 2.43 W/kg
**SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.584 mW/g**
Maximum value of SAR (measured) = 1.26 mW/g




0 dB = 1.26mW/g

## #18 CDMA2000 BC1_RC3 SO55_Left Tilted_Ch1175

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 1908.75 MHz;Duty Cycle: 1:1
Medium: HSL_1900_101229 Medium parameters used: f = 1909 MHz; $\sigma$ = 1.45 mho/m; $\varepsilon_r$ = 39.6; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.39, 7.39, 7.39); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM2; Type: SAM; Serial: TP-1479
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1175/Area Scan (41x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.62 mW/g

**Ch1175/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.4 V/m; Power Drift = 0.020 dB
Peak SAR (extrapolated) = 2.92 W/kg
**SAR(1 g) = 1.42 mW/g; SAR(10 g) = 0.710 mW/g**
Maximum value of SAR (measured) = 1.49 mW/g




0 dB = 1.49mW/g

## #18 CDMA2000 BC1_RC3 SO55_Left Tilted_Ch1175_2D

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 1908.75 MHz;Duty Cycle: 1:1
Medium: HSL_1900_101229 Medium parameters used: f = 1909 MHz; $\sigma$ = 1.45 mho/m; $\varepsilon_r$ = 39.6; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.2 ℃; Liquid Temperature：21.7 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.39, 7.39, 7.39); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM2; Type: SAM; Serial: TP-1479
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1175/Area Scan (41x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 1.62 mW/g

**Ch1175/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.4 V/m; Power Drift = 0.020 dB
Peak SAR (extrapolated) = 2.92 W/kg
**SAR(1 g) = 1.42 mW/g; SAR(10 g) = 0.710 mW/g**
Maximum value of SAR (measured) = 1.49 mW/g


1g/10g Averaged SAR
SAR; Zoom Scan:Value Along Z, X=2, Y=2
Markers
mW/g
1.4
1.2
1.0
0.8
0.6
0.4
0.2
0.0
0.005
0.010
0.015
0.020
0.025
0.030
0.035
m

## #19 CDMA2000 BC0_RC3 SO32_Bottom_1.5cm_Ch1013

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: MSL_835_101229 Medium parameters used: f = 825 MHz; $\sigma$ = 0.961 mho/m; $\varepsilon_r$ = 56.4; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.1 ℃； Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM1; Type: SAM; Serial: TP-1477
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.796 mW/g

**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 17.4 V/m; Power Drift = 0.105 dB
Peak SAR (extrapolated) = 0.974 W/kg
**SAR(1 g) = 0.737 mW/g; SAR(10 g) = 0.524 mW/g**
Maximum value of SAR (measured) = 0.779 mW/g




0 dB = 0.779mW/g

## #19 CDMA2000 BC0_RC3 SO32_Bottom_1.5cm_Ch1013_2D

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: MSL_835_101229 Medium parameters used: f = 825 MHz; $\sigma$ = 0.961 mho/m; $\varepsilon_r$ = 56.4; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.1 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM1; Type: SAM; Serial: TP-1477
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.796 mW/g

**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 17.4 V/m; Power Drift = 0.105 dB
Peak SAR (extrapolated) = 0.974 W/kg
**SAR(1 g) = 0.737 mW/g; SAR(10 g) = 0.524 mW/g**
Maximum value of SAR (measured) = 0.779 mW/g


1g/10g Averaged SAR
SAR; Zoom Scan:Value Along Z, X=2, Y=1
Markers
0.8
0.7
0.6
0.5
0.4
0.3
0.2
0.1
0.0
mW/g
0.005
0.010
0.015
0.020
0.025
0.030
0.035
m

## #20 CDMA2000 BC0_RC3 SO32_Face_1.5cm_Ch1013

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 824.7 MHz;Duty Cycle: 1:1
Medium: MSL_835_101229 Medium parameters used: f = 825 MHz; $\sigma$ = 0.961 mho/m; $\varepsilon_r$ = 56.4; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.1 ℃; Liquid Temperature：21.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(8.65, 8.65, 8.65); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM1; Type: SAM; Serial: TP-1477
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch1013/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.353 mW/g

**Ch1013/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 13.7 V/m; Power Drift = 0.048 dB
Peak SAR (extrapolated) = 0.438 W/kg
**SAR(1 g) = 0.324 mW/g; SAR(10 g) = 0.231 mW/g**
Maximum value of SAR (measured) = 0.345 mW/g




0 dB = 0.345mW/g

## #21 CDMA2000 BC1_RC3 SO32_Bottom_1.5cm_Ch600

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL_1900_101229 Medium parameters used: f = 1880 MHz; $\sigma$ = 1.51 mho/m; $\varepsilon_r$ = 54.6; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：21.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.26, 7.26, 7.26); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM2; Type: SAM; Serial: TP-1479
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch600/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.362 mW/g

**Ch600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.5 V/m; Power Drift = 0.085 dB
Peak SAR (extrapolated) = 0.621 W/kg
**SAR(1 g) = 0.369 mW/g; SAR(10 g) = 0.209 mW/g**
Maximum value of SAR (measured) = 0.392 mW/g

**Ch600/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.5 V/m; Power Drift = 0.085 dB
Peak SAR (extrapolated) = 0.503 W/kg
**SAR(1 g) = 0.317 mW/g; SAR(10 g) = 0.191 mW/g**
Maximum value of SAR (measured) = 0.346 mW/g




0 dB = 0.346mW/g

## #21 CDMA2000 BC1_RC3 SO32_Bottom_1.5cm_Ch600_2D

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL_1900_101229 Medium parameters used: f = 1880 MHz; $\sigma$ = 1.51 mho/m; $\varepsilon_r$ = 54.6; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：21.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.26, 7.26, 7.26); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM2; Type: SAM; Serial: TP-1479
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch600/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.362 mW/g

**Ch600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.5 V/m; Power Drift = 0.085 dB
Peak SAR (extrapolated) = 0.621 W/kg
**SAR(1 g) = 0.369 mW/g; SAR(10 g) = 0.209 mW/g**
Maximum value of SAR (measured) = 0.392 mW/g

**Ch600/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 10.5 V/m; Power Drift = 0.085 dB
Peak SAR (extrapolated) = 0.503 W/kg
**SAR(1 g) = 0.317 mW/g; SAR(10 g) = 0.191 mW/g**
Maximum value of SAR (measured) = 0.346 mW/g


1g/10g Averaged SAR
SAR; Zoom Scan:Value Along Z, X=2, Y=1
Markers
0.40
0.35
0.30
0.25
0.20
0.15
0.10
0.05
0.00
mW/g
0.005
0.010
0.015
0.020
0.025
0.030
0.035
m

## #22 CDMA2000 BC1_RC3 SO32_Face_1.5cm_Ch600

**DUT: 0D0306**

Communication System: CDMA2000; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: MSL_1900_101229 Medium parameters used: f = 1880 MHz; $\sigma$ = 1.51 mho/m; $\varepsilon_r$ = 54.6; $\rho$ = 1000 kg/$m^3$
Ambient Temperature：23.3 ℃; Liquid Temperature：21.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3697; ConvF(7.26, 7.26, 7.26); Calibrated: 2010/11/23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2010/11/18
- Phantom: SAM2; Type: SAM; Serial: TP-1479
- Measurement SW : DASY5, V5.2 Build 162; SEMCAD X Version 14.0 Build 57

**Ch600/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 0.254 mW/g

**Ch600/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.59 V/m; Power Drift = 0.115 dB
Peak SAR (extrapolated) = 0.429 W/kg
**SAR(1 g) = 0.249 mW/g; SAR(10 g) = 0.138 mW/g**
Maximum value of SAR (measured) = 0.266 mW/g

**Ch600/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 9.59 V/m; Power Drift = 0.115 dB
Peak SAR (extrapolated) = 0.233 W/kg
**SAR(1 g) = 0.159 mW/g; SAR(10 g) = 0.095 mW/g**
Maximum value of SAR (measured) = 0.175 mW/g




0 dB = 0.175mW/g