

FCC PART 22H, PART 24E

TEST REPORT

For

Teleepoch Limited

5A, B1 Building, Digital Tech Zone, High-Tech Park (south), Nanshan district,
Shenzhen, Guangdong Province, China

FCC ID: U46-C5620

Report Type: Original Report	Product Type: Mobile Phone
Test Engineer: Brown Lu	<i>Brown Lu</i>
Report Number: RSZ120109001-00	
Report Date: 2012-04-01	
Reviewed By: Alvin Huang EMC Engineer	<i>Alvin Huang</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST METHODOLOGY	3
TEST FACILITY	3
SYSTEM TEST CONFIGURATION.....	3
DESCRIPTION OF TEST CONFIGURATION	3
EQUIPMENT MODIFICATIONS	3
SUPPORT EQUIPMENT LIST AND DETAILS	3
CONFIGURATION OF TEST SETUP	3
BLOCK DIAGRAM OF TEST SETUP	3
SUMMARY OF TEST RESULTS.....	3
FCC §1.1307 & §2.1093 - RF EXPOSURE.....	3
APPLICABLE STANDARD	3
TEST RESULT	3
FCC §2.1047 - MODULATION CHARACTERISTIC.....	3
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....	3
APPLICABLE STANDARD	3
TEST PROCEDURE	3
TEST EQUIPMENT LIST AND DETAILS.....	3
TEST DATA	3
FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH.....	3
APPLICABLE STANDARD	3
TEST PROCEDURE	3
TEST EQUIPMENT LIST AND DETAILS.....	3
TEST DATA	3
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	3
APPLICABLE STANDARD	3
TEST PROCEDURE	3
TEST EQUIPMENT LIST AND DETAILS.....	3
TEST DATA	3
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS	3
APPLICABLE STANDARD	3
TEST PROCEDURE	3
TEST EQUIPMENT LIST AND DETAILS.....	3
TEST DATA	3
FCC §22.917(A) & §24.238(A) - BAND EDGES.....	3
APPLICABLE STANDARD	3
TEST PROCEDURE	3
TEST EQUIPMENT LIST AND DETAILS.....	3
TEST DATA	3
FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY.....	3

APPLICABLE STANDARD3

TEST PROCEDURE3

TEST EQUIPMENT LIST AND DETAILS.....3

TEST DATA3

DECLARATION LETTER.....3

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Teleepoch Limited*'s product, model number: C5620 (FCC ID: U46-C5620) or the "EUT" in this report was a *Mobile Phone*, which was measured approximately: 99 mm (L) x 4.86 mm (W) x 16.8 mm (H), rated input voltage: DC 3.7 V battery

Frequency Range:

CDMA Cellular Band: 824-849 MHz (TX), 869-893 MHz (RX)
US-PCS Band: 1850-1910 MHz (TX), 1930-1990 MHz (RX)
BLOCK-G Band: 1850-1915 MHz (TX), 1930-1995 MHz (RX)
Bluetooth: 2402-2480 MHz (TX/RX)

Modulation Mode:

QPSK (cellular-CDMA Downlink, US-PCS Downlink, BLOCK-G Downlink),
BPSK (cellular-CDMA Uplink, US-PCS Uplink, BLOCK-G Uplink)
GFSK, $\pi/4$ -DQPSK, 8DPSK (Bluetooth)

Transmitter Output Power:

CDMA Cellular Band: 24.76 dBm (Conducted output power)
US-PCS Band: 23.79 dBm (Conducted output power)
BLOCK-G Band: 23.72 dBm (Conducted output power)
Bluetooth: 9.12 dBm (Conducted output power)

Note: The series product, model C5620, FLIP and MXC-628 are electrically identical, they have the same PCB layout and schematic, we select C5620 for fully testing, which was explained in the attached declaration letter.

** All measurement and test data in this report was gathered from production sample serial number: W920447135000092 (Assigned by BACL, Shenzhen). The EUT was received on 2012-02-10.*

Objective

This test report is prepared on behalf of *Teleepoch Limited* in accordance with Part 2-Subpart J, Part 22 Subpart H, and Part 24 Subpart E of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, band edge and radiated margin.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS and Part 15B JBP submission with FCC ID: U46-C5620

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D, ANSI C63.4-2009.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-C.

The final qualification was performed with the EUT operating at testing mode.


Equipment Modifications

No modifications were made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
R & S	Universal Radio Communication Tester	CMU200	109038

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	26 dB Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: * Please refer to SAR report released by BACL, report number: R12022110-SAR

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1307 and §2.1093.

Test Result

Compliance, please refer to the SAR report: R12022110-SAR

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standard


According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

TIA 603-C section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04
HP	Signal Generator	HP8657A	2849U00982	2011-10-28	2012-10-27
HP	Synthesized Sweeper	8341B	2624A00116	2011-11-07	2012-11-06
COM POWER	Dipole Antenna	AD-100	041000	2011-09-25	2012-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2011-05-17	2012-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Brown Lu on 2012-02-15

Conducted Output Power**Cellular Band (Part 22H)**

Cellular Band: BC0

Mode	#	Test Case		Conducted Output Power (dBm)		
		FWD RC/TAP	REV RC/TAP	CH 1013	CH 384	CH 777
1xRTT	1	RC1	RC1 (SO2)	24.76	24.29	24.35
	2	RC1	RC1 (SO3)	24.33	23.73	23.85
	3	RC2	RC2 (SO9)	24.30	23.74	23.83
	4	RC3	RC3 (SO32)	23.84	23.26	23.39
	5	RC3	RC3 (SO3)	23.85	23.33	23.44

PCS Band (Part 24E)

US-PCS: BC1

Mode	#	Test Case		Conducted Output Power (dBm)		
		FWD RC/TAP	REV RC/TAP	CH 25	CH 600	CH 1175
1xRTT	1	RC1	RC1 (SO2)	23.20	23.65	23.48
	2	RC1	RC1 (SO3)	23.49	23.62	23.39
	3	RC2	RC2 (SO9)	23.74	23.75	23.53
	4	RC3	RC3 (SO32)	23.31	23.79	23.58
	5	RC3	RC3 (SO3)	23.77	23.79	23.55

PCS Band (Part 24E)

BLOCK-G: BC14

Mode	#	Test Case		Conducted Output Power (dBm)		
		FWD RC/TAP	REV RC/TAP	CH 25	CH 650	CH 1275
1xRTT	1	RC1	RC1 (SO2)	23.41	23.69	23.23
	2	RC1	RC1 (SO3)	23.26	23.59	23.32
	3	RC2	RC2 (SO9)	23.50	23.72	23.54
	4	RC3	RC3 (SO32)	23.32	23.60	23.34
	5	RC3	RC3 (SO3)	23.32	23.57	23.30

ERP & EIRP**ERP for Cellular Band (Part 22H)**

Cellular Band: BC0

Indicated		Table Angle Degree	Test Antenna		Substituted			Antenna Gain Correction (dBd)	Cable Loss (dB)	Absolute Level (dBm)	Part 22H Limit (dBm)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)				
Low Channel											
824.7	113.99	140	1.8	V	824.7	20.7	V	0	0.64	20.06	38.45
824.7	116.00	160	1.2	H	824.7	23.8	H	0	0.64	23.16	38.45

EIRP for PCS Band (Part 24E)

US-PCS: BC1

Indicated		Table Angle Degree	Test Antenna		Substituted			Antenna Gain Correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Part 24E Limit (dBm)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)				
Middle Channel											
1880.0	113.20	140	1.9	H	1880.0	14.4	H	6.10	1.00	19.50	33
1880.0	115.50	190	1.6	V	1880.0	17.3	V	6.10	1.00	22.40	33

BLOCK-G: BC14

Indicated		Table Angle Degree	Test Antenna		Substituted			Antenna Gain Correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Part 24E Limit (dBm)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)				
Middle Channel											
1882.5	113.49	160	1.1	H	1882.5	14.7	H	6.10	1.00	19.80	33
1882.5	115.67	180	1.9	V	1882.5	17.4	V	6.10	1.00	22.50	33

Note: all above data were tested with no amplifier.

FCC §2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH


Applicable Standard

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 3 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0kPa

The testing was performed by Brown Lu on 2012-02-12 and 2012-02-13.

Test Result: Compliance

Please refer to the following tables and plots:

BPSK Modulation:

Cellular Band (Part 22H)

Cellular Band: BC0

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
384	836.52	1.287	1.443

PCS Band (Part 24E)

US-PCS: BC1


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
600	1880.0	1.281	1.437

BLOCK-G: BC14


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Occupied Bandwidth (MHz)
650	1882.5	1.281	1.437

US-PCS: BC1 (Part 24E)

99% Occupied Bandwidth




26 dB Occupied Bandwidth




BLOCK-G: BC14 (Part 24E)

99% Occupied Bandwidth



26 dB Occupied Bandwidth



FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27
Wainwright Germany	Band Reject Filter	WRCG1850/1910-1835/1925-40/8SS	22	2011-02-28	2012-02-28
Wainwright Germany	Band Reject Filter	WRCG823/850-813/860-40/8SS	7	2011-02-28	2012-02-28
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07
Rohde & Schwarz	Spectrum Analyzer	ESCI	849720/019	2011-07-08	2012-07-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa


The testing was performed by Brown Lu on 2012-02-12 and 2012-02-13
Please refer to the following plots.

Cellular Band: BC0 (Part 22H)

30 MHz – 1 GHz - Middle Channel




1 GHz – 10 GHz - Middle Channel




US-PCS: BC1 (Part 24E)


30 MHz – 1 GHz - Middle Channel



1 GHz – 2 GHz - Middle Channel




2 GHz – 20 GHz - Middle Channel




BLOCK-G: BC14 (Part 24E)


30 MHz – 1 GHz - Middle Channel



1 GHz – 2 GHz - Middle Channel



2 GHz – 20 GHz - Middle Channel



FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TXpwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \text{ Log}_{10} (\text{power out in Watts})$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07
Mini-Circuits	Amplifier	ZVA-213+	T-E27H	2011-03-08	2012-03-07
HP	Signal Generator	HP8657A	2849U00982	2011-10-28	2012-10-27
HP	Amplifier	HP8447D	2944A09795	2011-08-02	2012-08-02
HP	Synthesized Sweeper	8341B	2624A00116	2011-11-07	2012-11-06
COM POWER	Dipole Antenna	AD-100	041000	2011-09-25	2012-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2011-05-17	2012-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Brown Lu on 2012-02-13

Test mode: Transmitting (worst case)

30 MHz ~10 GHz:

Cellular Band (Part 22H)

Cellular Band: BC0

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dB)	Cable Loss (dB)			
Middle Channel											
3607.1	34.43	130	1.7	V	3607.1	-58.8	7.10	1.44	-53.14	-13	40.14
2379.5	34.26	50	1.1	V	2379.5	-61.0	7.40	1.16	-54.76	-13	41.76
1675.8	36.50	130	1.9	V	1673.4	-63.5	6.15	0.98	-58.33	-13	45.33
2844.3	34.77	190	1.5	H	2844.3	-64.8	7.30	1.26	-58.76	-13	45.76
1944.6	35.11	120	2.1	H	1944.6	-63.9	6.15	1.03	-58.78	-13	45.78
1675.8	37.44	150	1.1	H	1673.4	-65.3	6.15	0.98	-60.13	-13	47.13

30 MHz ~20 GHz:

PCS Band (Part 24E)

US-PCS: BC1

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dB)	Cable Loss (dB)			
Middle Channel											
6011.8	34.11	160	1.3	V	6011.8	-55.0	8.20	1.82	-48.62	-13	35.62
3774.8	38.42	120	1.1	H	3774.8	-54.7	6.85	1.50	-49.35	-13	36.35
3774.8	37.51	240	1.8	V	3774.8	-55.5	6.85	1.50	-50.15	-13	37.15
5142.1	35.04	50	1.5	H	5142.1	-57.2	7.90	1.73	-51.03	-13	38.03
3149.2	34.82	120	1.0	V	3149.2	-60.0	7.20	1.32	-54.12	-13	41.12
2411.5	35.19	280	1.4	H	2411.5	-65.6	7.40	1.16	-59.36	-13	46.36

BLOCK-G: BC14

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dB)	Cable Loss (dB)			
Middle Channel											
7433.1	34.18	170	1.9	V	7433.1	-52.9	7.80	2.10	-47.20	-13	34.20
3754.8	38.44	130	1.4	H	3754.8	-54.7	6.85	1.50	-49.35	-13	36.35
5102.6	35.06	160	1.0	H	5102.6	-57.1	8.10	1.73	-50.73	-13	37.73
4836.7	34.75	10	1.2	V	4836.7	-57.3	8.30	1.69	-50.69	-13	37.69
3754.8	36.18	210	1.1	V	3754.8	-56.8	6.85	1.50	-51.45	-13	38.45
4211.5	35.49	250	1.5	H	4211.5	-58.6	7.60	1.60	-52.6	-13	39.60

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 10 kHz.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Brown Lu on 2012-02-12 and 2012-02-20.

Please refer to the following tables and plots.

Cellular Band (Part 22H)

Cellular Band: BC0

Frequency (MHz)	Emission (dBm)	Limit (dBm)
824.000	-13.80	<-13
849.000	-13.57	<-13

PCS Band (Part 24E)


US-PCS: BC1

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.414	-22.24	<-13
1910.055	-20.97	<-13


BLOCK-G: BC14

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.922	-21.43	<-13
1915.055	-14.12	<-13


Cellular Band, Left Band Edge




Cellular Band, Right Band Edge





US-PCS, Left Band Edge



US-PCS, Right Band Edge



BLOCK-G, Left Band Edge**BLOCK-G, Right Band Edge**

FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
WUHUAN	Temperature & Humidity Chamber	HTP205	20021115	2011-06-04	2012-06-03
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2011-10-28	2012-10-27
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Brown Lu on 2012-02-13

Cellular Band (Part 22H)

Cellular Band: BC0

Middle Channel, $f_0 = 836.52$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	25	0.03108115	2.5
-20		24	0.02749486	2.5
-10		23	0.02869029	2.5
0		22	0.02749486	2.5
10		18	0.02510400	2.5
20		14	0.02390857	2.5
30		18	0.03108115	2.5
40		22	0.02869029	2.5
50		26	0.03227657	2.5
25	4.2	14	0.02390857	2.5
25	3.5	23	0.02629943	2.5

PCS Band (Part 24E)

US-PCS: BC1

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	26	0.01382979	Pass
-20		23	0.01223404	Pass
-10		24	0.01276596	Pass
0		23	0.01223404	Pass
10		21	0.01117021	Pass
20		20	0.01063830	Pass
30		26	0.01382979	Pass
40		24	0.01276596	Pass
50		27	0.01436170	Pass
25	4.2	20	0.01063830	Pass
25	3.5	22	0.01170213	Pass

BLOCK-G: BC14

Middle Channel, $f_0 = 1882.50$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	27	0.01434263	Pass
-20		25	0.01328021	Pass
-10		24	0.01274900	Pass
0		23	0.01221780	Pass
10		21	0.01115538	Pass
20		18	0.00956175	Pass
30		22	0.01168659	Pass
40		24	0.01274900	Pass
50		27	0.01434263	Pass
25	4.2	20	0.01062417	Pass
25	3.5	22	0.01168659	Pass

DECLARATION LETTER



Teleepoch Limited
5A,B1 Building, Digital Tech Zone, High-Tech Park(south), Nanshan district, Shenzhen, Guangdong Province, China
Tel: +86-755-26037146 Fax: +86-0755-26037077

Product Similarity Declaration

To Whom It May Concern,

We, Teleepoch Limited, hereby declare that our Mobile phone, Model Number: FLIP/MXC-628 are electrically identical with the Model Number: C5620 that was certified by BACL. They are named differently due to marketing purposes.

Please contact me if you have any question.

Signature:

Maggie Zhang

Project Manager

2012.02.29

***** END OF REPORT *****