FCC ID: U4A-YRHCPTN0FM IC: 6982A-YRHCPTN0FM

HVIN: YRMTH1

FCC 447498 D01 General RF Exposure Guidance v06

7.2 Transmitters used in mobile device exposure conditions for simultaneous transmission operations

Canada RSS-102 Issue 5 2.5 Exemption Limits for Routine Evaluation

4 Exposure Limits

Freq. MHz	Power dBm	Power mW	Power W	Gain G dBi	Dist. cm	EIRP W	PD mW/cm^2	FCC Limit mW/cm^2	PD W/m^2	IC Limit W/m^2	IC Exemption Threshold W
2405	15.67	37	0.037	3.3	20	0.079	0.016	1	0.16	5.36	2.68
2440	17.06	51	0.051	3.3	20	0.11	0.022	1	0.22	5.41	2.71
2465	18.28	67	0.067	3.3	20	0.14	0.029	1	0.29	5.45	2.72
2470	14.78	30	0.030	3.3	20	0.064	0.013	1	0.13	5.45	2.73
2475	7.28	5	0.005	3.3	20	0.011	0.0023	1	0.023	5.46	2.73
2402	-0.43	0.91	0.00091	1.8	20	0.0014	0.00027	1	0.0027	5.35	2.68
2440	-0.55	0.88	0.00088	1.8	20	0.0013	0.00027	1	0.0027	5.41	2.71
2480	-0.62	0.87	0.00087	1.8	20	0.0013	0.00026	1	0.0026	5.47	2.74
FCC	FCC										
PD1/Limit	PD2/Limit	Σ									
0.029	0.00027	0.029	<1								
IC	IC										
PD1/Limit	PD2/Limit	Σ									
0.053	0.00051	0.053	<1								