

FCC MODULAR APPROVAL REQUEST (per Part 15.212 / KDB 996369 D01)

FCC ID: U4A-YRHCPIM10FM

ITEMS	TO BE COVERED	ANSWER FROM APPLICANT
1.	The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly.	Yes, Refer to photo exhibit
2.	The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal;	Yes, refer to schematics exhibits
3.	The module must contain power supply regulation on the module;	Yes, refer to schematics exhibits
4.	The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b);	Yes, refer to photo exhibit
5.	The module must demonstrate compliance in a stand-alone configuration;	Yes, refer to test reports exhibits
6.	The module must be labeled with its permanently affixed FCC ID label, or use an electronic display (see KDB Publication 784748);	Yes, refer to label sample exhibit
7.	The module must comply with all specific rules applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee;	Yes, refer to operational descriptions and test reports exhibits
8.	The module must comply with RF exposure requirements (see Clause V below).	Yes, refer to MPE exhibit

The Module must be used with a Yale Assure Lock or Yale nextTouch Lock, and cannot be used in conjunction with any other Yale Network Module.

Name of Applicant (or Authorized Representative): Jason Stewart

Date: 11/25/2019 Signature: