

# PARTIAL TEST REPORT

No.: 17-1-0180901T16a-C1

According to:

**FCC Regulations**

Part 15.205

Part 15.209







Part 15.407

for

Datalogic S.r.l.

**FALCON X4**  
**Type: E00ANM4HS0GF0A4**

FCC ID: U4GFX4WB

Laboratory Accreditation and Listings			
 <b>DAkkS</b> Deutsche Akkreditierungsstelle D-PL-12047-01-01	 FEDERAL COMMUNICATIONS COMMISSION <b>FCC</b> USA • MRA US-EU 0003	 Industry Canada  Reg. No.: 3462D-1 Reg. No.: 3462D-2 Reg. No.: 3462D-3	 Voluntary Controls for Electromagnetic Emissions  Reg. No.: R-2666 C-2914, T-1967, G-301
 <b>WiFi</b> ALLIANCE AUTHORIZED RF LABORATORY	 <b>ctia</b> Authorized™ Test Lab Lab Code: 20011130-00		
accredited according to DIN EN ISO/IEC 17025			
<p><b>CETECOM GmbH</b> Laboratory Radio Communications &amp; Electromagnetic Compatibility Im Teelbruch 116 • 45219 Essen • Germany Registered in Essen, Germany, Reg. No.: HRB Essen 8984 Tel.: + 49 (0) 20 54 / 95 19-954 • Fax: + 49 (0) 20 54 / 95 19-964 E-mail: info@cetecom.com • Internet: www.cetecom.com</p>			

## Table of Contents

<b>1. SUMMARY OF TEST RESULTS.....</b>	<b>3</b>
1.1. Tests measurement overview according to US CFR Title 47, Subpart 15C .....	3
<b>2. ADMINISTRATIVE DATA .....</b>	<b>6</b>
2.1. Identification of the testing laboratory .....	6
2.2. Test location .....	6
2.3. Organizational items .....	6
2.4. Applicant's details .....	6
2.5. Manufacturer's details .....	6
<b>3. EQUIPMENT UNDER TEST (EUT).....</b>	<b>7</b>
3.1. Certification Data of Main EUT declared by Applicant .....	7
3.2. WLAN 5 GHz 802.11a/n Technical Data Of Main EUT as Declared by Applicant .....	8
3.3. EUT: Type, S/N etc. and short descriptions used in this test report .....	9
3.4. Auxiliary Equipment (AE): Type, S/N etc. and short descriptions .....	9
3.5. EUT set-ups .....	9
3.6. EUT operating modes .....	10
3.7. Configuration of cables used for testing .....	10
<b>4. DESCRIPTION OF TEST SYSTEM SET-UP'S .....</b>	<b>11</b>
4.1. Test system set-up for conducted measurements on antenna port .....	11
4.2. Test system set-up for radiated magnetic field measurements below 30 MHz .....	13
4.3. Test system set-up for radiated electric field measurement 30 MHz to 1 GHz .....	14
4.4. Test system set-up for radiated electric field measurement above 1 GHz .....	15
<b>5. MEASUREMENTS .....</b>	<b>16</b>
5.1. Duty Cycle .....	16
5.2. RF-Parameter - Transmitter Peak output power (conducted and radiated) .....	18
5.3. General Limit - Radiated field strength emissions below 30 MHz .....	22
5.4. General Limit - Radiated field strength emissions, 30 MHz - 1 GHz .....	25
5.5. General Limit - Radiated emissions, above 1 GHz .....	27
5.6. RF-Parameter - Radiated Band-Edge compliance measurements .....	31
5.7. Measurement uncertainties .....	37
<b>6. ABBREVIATIONS USED IN THIS REPORT .....</b>	<b>38</b>
<b>7. ACCREDITATION DETAILS OF CETECOM'S LABORATORIES AND TEST SITES .....</b>	<b>38</b>
<b>8. INSTRUMENTS AND ANCILLARY .....</b>	<b>39</b>
TC" .....	39
<b>9. VERSIONS OF TEST REPORTS (CHANGE HISTORY) .....</b>	<b>42</b>

Table of Annex			
Annex No.	Contents	Reference Description	Total Pages
Annex 1	Test results	CETECOM_TR17-1-0180901T16a-A1	100
Annex 2	External photographs of EUT	CETECOM_TR17-1-0180901T16a-A2	9
Annex 3	Internal photographs of EUT	CETECOM_TR17-1-0180901T16a-A3	12
Annex 4	Test set-up photographs	CETECOM_TR17-1-0180901T16a-A4	12
The listed attachments are an integral part of this report.			

## 1. Summary of test results

The test results apply exclusively to the test samples as presented in this Report. The CETECOM GmbH does not assume responsibility for any conclusions and generalizations taken in conjunction with other specimens or samples of the type of the item presented to tests.

**The test results apply exclusively to the test samples as presented in this report. The CETECOM GmbH does not assume responsibility for any conclusions and generalizations taken in conjunction with other specimens or samples of the type of the item presented to tests. Also we refer on special conditions which the applicant should fulfill according §2.927 to §2.948, special focus regarding modification of the equipment and availability of sample equipment for market surveillance tests.**

The presented Equipment Under Test (in this report, hereinafter referred as EUT) : **FALCON X4** integrates total 1 of pre-certified module **WL18MODGI (FCC ID: Z64-WL18DBMOD)** & supports following technologies :

EUT supported Technologies which are not tested within this test report

EUT supported Technology	Test Report Reference
Bluetooth FHSS (BR-EDR) Modes: 2402 – 2480 MHz	CETECOM_TR17-1-0180901T10a
Bluetooth Low Energy Modes: 2402 – 2480 MHz	CETECOM_TR17-1-0180901T11a
WLAN 802.11b/g/n(HT20) Modes: 2412 – 2462 MHz	CETECOM_TR17-1-0180901T12a
AC Power Lines - Internal Battery Charging	CETECOM_TR17-1-0180901T18a

EUT supported Technologies which are tested within this test report

- **WLAN 802.11a/n(HT20)/n(HT40)Modes: 5150–5850 MHz**

Following test cases have been performed to show compliance with valid Part 15.205/15.209/15.407 of the FCC CFR Title 47 Rules, Edition 4<sup>th</sup> November 2016.

### 1.1. Tests measurement overview according to US CFR Title 47, Subpart 15C

Test cases	Port	References and Limits		EUT set-up	EUT op. mode	Result
		FCC Standard	Test limit			
TX-Mode						
99% occupied bandwidth	Antenna terminal (conducted)	2.1049(h)	99% Power bandwidth	--	--	Not Performed
26 dB bandwidth	Antenna terminal (conducted)	§15.303 + §15.407(a)(2)(5)	26 dB spectral density bandwidth	--	--	Remark 2)
Duty-Cycle	Antenna terminal (conducted)	KDB789033 + ANSI C63.10:2013	No Limit Criteria	2	1	Performed
Transmitter frequency stability	Antenna terminal (conducted)	§ 2.1055 + §15.407(g)	Operation within designated operational band	--	--	Remark 2)
Maximum output power	Antenna terminal (conducted)	§15.407(a)(1)(iv) 5.15-5.25 GHz Client devices (2) 5.25-5.35 GHz & 5.47-5.725 GHz (3) 5.725-5.85 GHz	Power Limits (if Antenna Gain < 6 dBi)  250 mW  lesser of 250mW or 11dBm+10logB  1 W	2	1	Pass

Peak Power Spectral density	Antenna terminal (conducted)	§15.407(a) (1)(iv) 5.15-5.25 GHz Client devices (2) 5.25-5.35 GHz & 5.47-5.725 GHz (3) 5.725-5.85 GHz	Power Spectral Density Limits (if Antenna Gain < 6 dBi)  11dBm/MHz  11dBm/MHz  30dBm/500kHz	--	--	Remark 2)
Maximum e.i.r.p. power	Antenna terminal (conducted) + Antenna Gain	§15.407(a) (1)(iv) 5.15-5.25 GHz Client devices (2) 5.25-5.35 GHz & 5.47-5.725 GHz (3) 5.725-5.85 GHz	e.i.r.p. Limits (if Antenna Gain < 6 dBi)  250 mW + 6 dBi  lesser of 250mW or 11dBm+10logB + 6 dBi  1 W + 6 dBi	2	1	Pass + Applicants declaration: Antenna Gain 3.66 dBi
Antenna gain information	Antenna terminal (conducted)	§15.407(a) (1)(2)(3)	< 6dBi or if Antenna directional Gain > 6dBi reduction of Max. power & power spectral density by the amount in dB that the directional gain of the antenna exceeds 6 dBi	--	--	Applicants declaration: Antenna Gain 3.66 dBi
General field strength emissions within restricted bands + Band-Edge compliance radiated	Enclosure + Inter-connecting cables (radiated)	§15.407(b) (1)(2)(3)(4)(5)(6) (7)(8)  §15.205 + §15.209	5150-5250 MHz   5250-5350 MHz 5470-5725 MHz all emissions outside operating band shall not exceed -27 dBm/MHz e.i.r.p.  5725-5850 MHz Spectrum Mask acc. to (4)(i)  Restricted band limits + General field strength limits	1	1	Pass
Transmit power control + Dynamic frequency selection (DFS)	Antenna terminal (conducted)	§15.407 (h1)(h2)	Requirements: Masters Active clients Passive clients	--	--	Remark 3)
Discontinuous transmissions + Device security	FIRMWARE	§15.407(c) + §15.407(i)	No transmissions in case of either absence of information to transmit or operational failure + Protection of firmware by unauthorized parties	--	--	Not tested  Applicants declaration of implementation
AC-Power Lines Conducted Emissions	AC-Power lines or Battery Charger	§15.207(a)	AC Power line conducted limits	--	--	Remark 1)

Remark 1) :Not tested in this report as WLAN 5 GHz test configuration was operated using fully charged internal battery

Refer CETECOM\_TR17-1-0180901T13

Remark 2) : Refer WL18MODGI (FCC ID: Z64-WL18DBMOD) Report No. FR4O0971D, Rev.01, issued date Dec. 19,2014  
Report No. FR4O0971E, Rev.01, issued date Dec. 19,2014

Remark 3): Refer WL18MODGI (FCC ID: Z64-WL18DBMOD) Report No. FZ4O0971, Rev.01, issued date Dec. 19,2014.

Specific Absorption Rate (SAR) Measurements (separation distance user to RF-radiating element within 20cm)						
Test cases	Port	References & Limits		EUT set-up	EUT op. mode	Result
		FCC Standard	Test Limit			
Specific Absorption Rate (SAR) requirements	Cabinet + Inter- connecting cables (radiated)	§2.1091 §2.1093 + IEEE 1528-2013 + KDB 865664D01v0r04	<b>Specific Absorption Rate (SAR)</b> for Devices Used by the General Public <b>(Uncontrolled Environment)</b> : 1.6 W/Kg as averaged over any 1 g tissue	--	--	Refer test report CETECOM_TR17- 1-0180901T09a

The current version of the Test Report CETECOM\_TR17-1-0180901T16a-C1 replaces the Test Report CETECOM\_TR17-1-017-1-0180901T16a -C2 dated 2017-12-29. The replaced test report is herewith invalid.

.....  
Dipl.-Ing. Rachid Acharkaoui  
Responsible for test section

.....  
Dipl.-Ing N. Perez  
Responsible for test report

## 2. Administrative Data

### 2.1. Identification of the testing laboratory

Company name:	CETECOM GmbH
Address:	Im Teelbruch 116 45219 Essen - Kettwig Germany
Responsible for testing laboratory:	Dipl.-Ing. Rachid Acharkaoui
Deputy:	Dipl.-Ing. Niels Jeß

### 2.2. Test location

#### 2.2.1. Test laboratory “CTC”

Company name:	see chapter 2.1. Identification of the testing laboratory
---------------	---

### 2.3. Organizational items

Responsible for test report and Project leader:	Dipl.-Ing N. Perez
Receipt of EUT:	2017-10-20
Date(s) of test:	2017-10-22 to 2017-12-25
Date of report:	2018-02-26
-----	
Version of template:	13.02

### 2.4. Applicant's details

Applicant's name:	Datalogic S.r.l.
Address:	Via S. Vitalino, 13 40012, Lippo di Calderara di Reno (BO) ITALY
Contact :	Mr. Francesco Rossi

### 2.5. Manufacturer's details

Manufacturer's name:	same as Applicant
Address:	same as Applicant

### 3. Equipment under test (EUT)

#### 3.1. Certification Data of Main EUT declared by Applicant

EUT Model	FALCON X4		
EUT Model Type	E00ANM4HS0GF0A4		
EUT Type	Portable Mobile Computer		
EUT Applications	Shopping Applications & General Purpose Mobile Computer		
FCC ID	U4GFX4WB		
Additional Information: Integrated Module			
Integrated Module	WL18MODGI		
Module Certification FCC ID	Z64-WL18DBMOD		
Number of Integrated Modules	1		
Additional Information : Supported Technologies			
Technology	Modes	Frequency Range	Remarks
WLAN 5 GHz	WLAN 802.11a/n(HT20)/n(HT40)	5150 MHz –5850 MHz	refer chapter 3.2
Bluetooth FHSS	Bluetooth BR-EDR	2402 MHz – 2480 MHz	not tested under this report
Bluetooth LE	Bluetooth Low Energy	2402 MHz – 2480 MHz	not tested under this report
WLAN 2.4 GHz	WLAN 802.11b/g/n(HT20)	2412 MHz – 2462 MHz	not tested under this report

### 3.2. WLAN 5 GHz 802.11a/n Technical Data Of Main EUT as Declared by Applicant

EUT Model	FALCON X4				
EUT Model Type	E00ANM4HS0GF0A4				
EUT Type	Portable Mobile Computer				
EUT Applications	Shopping applications & general purpose mobile computer				
Hardware Version	BETA				
Software Version	Android 4.4.4				
Firmware Version	2.01.46.20180109				
Frequency   Channel   B.W. (USA bands only)**	U-NII 1: 5150-5250 MHz	<input checked="" type="checkbox"/> Ch 36   40   44   48	<input checked="" type="checkbox"/> Bandwidth 20 MHz		
		<input checked="" type="checkbox"/> Ch. 38   46	<input checked="" type="checkbox"/> Bandwidth 40 MHz		
	U-NII2A: 5250-5350 MHz	<input checked="" type="checkbox"/> Ch 52   56   60   64	<input checked="" type="checkbox"/> Bandwidth 20 MHz		
		<input checked="" type="checkbox"/> Ch. 54   62	<input checked="" type="checkbox"/> Bandwidth 40 MHz		
	U-NII 2C: 5470-5725 MHz	<input checked="" type="checkbox"/> Ch 100   104   108	<input checked="" type="checkbox"/> Bandwidth 20 MHz		
		<input checked="" type="checkbox"/> Ch 112   116   120			
		<input checked="" type="checkbox"/> Ch 124   128   132			
		<input checked="" type="checkbox"/> Ch 136   140	<input checked="" type="checkbox"/> Bandwidth 40 MHz		
		<input checked="" type="checkbox"/> Ch. 102   110   118			
		<input checked="" type="checkbox"/> Ch 126   134			
	U-NII 3: 5725 -5850 MHz	<input checked="" type="checkbox"/> Ch 149   153   157	<input checked="" type="checkbox"/> Bandwidth 20 MHz		
		<input checked="" type="checkbox"/> Ch 161   165			
		<input checked="" type="checkbox"/> Ch 151   159	<input checked="" type="checkbox"/> Bandwidth 40 MHz		
Channels Power Settings	+20 dBm All Other Channels (According to Applicant's Declaration Max. Rated Power Values)				
	+15.5 dBm Ch:153  157 161 (According to Applicant's Declaration Max. Rated Power Values)				
802.11a – Mode OFDM Modulation   Data Rates	<input checked="" type="checkbox"/> BPSK   6 Mbps / 9 Mbps <input checked="" type="checkbox"/> QPSK   12 Mbps / 18 Mbps <input checked="" type="checkbox"/> 16-QAM   24 Mbps / 36 Mbps <input checked="" type="checkbox"/> 64-QAM   48 Mbps / 54 Mbps				
802.11n – Mode OFDM Modulation   Data Rates	<input checked="" type="checkbox"/> HT20 (MCS0 – MCS7)   7.2/14.4/21.7/28.9/43.3/57.8/65/72.2 Mbps <input checked="" type="checkbox"/> HT40 (MCS0 – MCS7)   15/30/45/60/90/120/135/150 Mbps				
Antenna Details	Integrated (ANT1 & ANT2)				
Antenna Connections	Primary Antenna: ANT1(WLAN 5 GHz)   Secondary Antenna: ANT2 not used				
Antenna Type	Laird PCBA Antenna				
ANT1 Gain (Peak)	3.66 dBi (4900 MHz – 5900 MHz) (According to Applicant's Declaration)				
ANT2 Gain (Peak)	2.21 dBi (4900 MHz – 5900 MHz) (According to Applicant's Declaration)				
Total Number of Modules	1 (WL18MODGI Module FCC ID: Z64-WL18DBMOD)				
Total Number of Antennas	2   Primary ANT1 : WLAN 5 GHz   Secondary ANT2: not used				
Test Mode Settings	Datalogic WiFi Test Application				
MAX Field Strength (Radiated@3m) For AV RMS Values Duty-Cycle Correction refer chapter 5.1	U-NII 1: 5150-5250 MHz	106.925 dBμV/m (PK)	99.364 dBμV/m (AV)		
	U-NII2A: 5250-5350 MHz	107.665 dBμV/m (PK)	98.531 dBμV/m (AV)		
	U-NII 2C: 5470-5725 MHz	106.428 dBμV/m (PK)	98.775 dBμV/m (AV)		
	U-NII 3: 5725-5850 MHz	108.727 dBμV/m (PK)	101.137 dBμV/m (AV)		
Power Supply	<input checked="" type="checkbox"/> Internal Battery: BT-26  Li-ion 3.7- 4.2VDC 5200mAh(2Cylindrical Cells)				
Special EMI Components	--				
EUT Sample Type	<input checked="" type="checkbox"/> Production <input type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering				
Firmware	<input type="checkbox"/> for normal use <input checked="" type="checkbox"/> Special version for test execution : Datalogic WiFi Test				
FCC label attached	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No				
For further details refer Applicants Declaration & following technical documents					
Description of Reference Document (supplied by applicant)	Version		Total Pages		
FALCON X4_Test-Tools_Quick_Start_Instructions	Rev: 0 Date: 14/09/2017		45		
FALCON X4_Quick Start Guide	822002580 Rev: A December 2017		2		
FALCON X4 Hardware Modifications	December 2017		7		
Datalogic Falcon FX4 Antenna_Rev E	Rev:E Date : 30/10/2017		15		
** Until further notice, devices subject to RSS-247, Issue 2,February 2017 section 6.2.3					
Operating in Frequency bands 5470-5600 MHz and 5650-5725 MHz shall not transmit in the band 5600-5650 MHz. This restriction is for the protection of Environment Canada's weather radars operating in this band.					



### 3.3. EUT: Type, S/N etc. and short descriptions used in this test report

Short Description*)	EUT	Type	Serial Number	Hardware Status	Software Status
EUT A	FALCON X4	E00ANM4HS0GF0A4	Z17P02008	HW Version: BETA P/N: 945550001	SW Version: Android 4.4.4 Firmware Version: 2.01.46.2018 0109
EUT B	FALCON X4	E00ANM4HS0GF0A4	Z17P02012	HW Version: BETA P/N: 945550001	SW Version: Android 4.4.4 Firmware Version: 2.01.46.2018 0109

\*) EUT short description is used to simplify the identification of the EUT in this test report.

### 3.4. Auxiliary Equipment (AE): Type, S/N etc. and short descriptions

AE short description *)	Auxiliary Equipment	Type	S/N serial number	HW hardware status	SW software status
AE 1	--	--	--	--	--

\*) AE short description is used to simplify the identification of the auxiliary equipment in this test report.

### 3.5. EUT set-ups

EUT set-up no. *)	Combination of EUT and AE	Description
set. 1	EUT A	Radiated measurements
set. 2	EUTB + Cable 1 + Cable 2	Conducted measurements

\*) EUT set-up no. is used to simplify the identification of the EUT set-up in this test report.

### 3.6. EUT operating modes

EUT operating mode no.*)	Description of operating modes	Additional information
op. 1	WLAN 5 GHz 802.11a/n*  TX-Fixed Channel (Modulated)	<p>For WLAN 5 GHz 802.11a/n(HT20) &amp; n(HT40) Modes tests are carried out with different Modes  Channels   Modulation   Data Rate   Bandwidth Combinations with help of Datalogic WiFi Test Application.</p> <p>The EUT was put to <b>Fixed Channel (Modulated) Continuous transmissions mode</b> with help of Datalogic WiFi Test Application</p> <p><b>Channel Power Settings : +20 dBm</b></p> <p>*Other supported wireless technologies were put in idle mode using special test software</p>
op. 2	WLAN 5 GHz 802.11a/n*  RX-Fixed Channel (Modulated)	<p>The EUT was put to <b>Fixed Channel (Modulated) Continuous receiving mode</b> with help of Datalogic WiFi Test Application.</p> <p>*Other supported wireless technologies were put in idle mode using special test software</p>

\*) EUT operating mode no. is used to simplify the test report.

### 3.7. Configuration of cables used for testing

Cable number	Description	Connections	Cable length
Cable 1	RF –SMA Cable	EUT ANT1 to Power Meter/ Spectrum Analyzer	0.08 m
Cable 2	RF –SMA Cable	EUT ANT2 to 50 $\Omega$ Termination	0.08 m

## 4. Description of test system set-up's

### 4.1. Test system set-up for conducted measurements on antenna port


#### Conducted Set-up W1

##### Conducted RF-Setup 1 (W1 Set-up)

#### General description:

The EUT's RF-signal is coupled out by a suitable antenna coupling connector (1). The signal is first attenuated (2) then connected to the power meter (3) for conducted power measurements. The specific attenuation loss is determined prior to the measurement within a set-up attenuation measurement. These are then taken into account by correcting the measurement readings.

#### Schematic:



#### Testing method:

ANSI C63.10:2013,  
KDB 789033 D02 General UNII Test Procedures New Rules v01r03

#### Used Equipment

##### Passive Elements

- ☒ 20 dB Attenuator
- ☒ Low loss RF-cables
- ☒

##### Test Equipment

- ☒ Power Meter
- ☒ DC-Power Supply
- ☒ Spectrum-Analyser

##### Remark:

See List of equipment under each test case and chapter 6 for calibration info

#### Measurement uncertainty

See chapter 5.7


## Conducted Set-up W2

### Conducted RF-Setup 2 (W2 Set-up)

#### General description:

The EUT's RF-signal is coupled out by a suitable antenna coupling connector (1). The signal is first attenuated (2) then connected to spectrum-analyzer (4) for RF-conducted measurements. The specific attenuation loss is determined prior to the measurement within a set-up attenuation measurement. These are then taken into account by correcting the measurement readings of the spectrum-analyzer.

#### Schematic:



#### Testing method:

ANSI C63.10:2013,  
KDB 789033 D02 General UNII Test Procedures New Rules v01r03

#### Used Equipment

Passive Elements	Test Equipment	Remark:
<input checked="" type="checkbox"/> 20 dB Attenuator	<input checked="" type="checkbox"/> Power Meter	See List of equipment under each test case and chapter 6 for calibration info
<input checked="" type="checkbox"/> Low loss RF-cables	<input checked="" type="checkbox"/> DC-Power Supply	
	<input checked="" type="checkbox"/> Spectrum-Analyser	

#### Measurement uncertainty

See chapter 5.7


## 4.2. Test system set-up for radiated magnetic field measurements below 30 MHz

**Specification:** ANSI C63.4-2014 §5.3, §8.2.1, §8.3.1.1+§8.3.2.1 , ANSI C63.10-2013 chapter 6.4 (§6.4.4.2)

**General Description:** Evaluating the radiated field emissions are done first by an exploratory emission measurement and a final measurement for most critical frequencies determined.

The loop antenna was placed at 1 m height above ground plane and 3 m measurement distance from set-up for investigations. Because of reduced measurement distance, correction data were applied, as stated in chapter “General Limit - Radiated field strength emissions below 30 MHz”. The tests are performed in the semi anechoic room recognized by the regulatory commission.

**Schematic:**



**Testing method:**

### Exploratory, preliminary measurement

The EUT and it's associated accessories are placed on a non-conductive position manipulator (tipping device) of 0.8 m height which is placed on the turntable. By rotating the turntable (step 90°, range 0° to 360°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT), the emission spectrum was recorded. The loop antenna was moved at least to 2-perpendicular axes (antenna vector in direction of EUT and parallel to EUT) in order to maximize the emissions. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a data reduction table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

### Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself either over 3-orthogonal axis (not defined usage position) or 2-orthogonal axis (defined usage position).

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

**Formula:**

$$E_C = E_R + AF + C_L + D_F - G_A$$

$$M = L_T - E_C$$

AF = Antenna factor

C<sub>L</sub> = Cable loss

D<sub>F</sub> = Distance correction factor

E<sub>C</sub> = Electrical field – corrected value

E<sub>R</sub> = Receiver reading

G<sub>A</sub> = Gain of pre-amplifier (if used)

L<sub>T</sub> = Limit

M = Margin

All units are dB-units, positive margin means value is below limit.

**Distance correction:**

Reference for applied correction (extrapolating) factors due to reduced measurement distance:


ANSI C63.10:2013, §6.4.4.2 - Equations (2) + (3) + (4)

### 4.3. Test system set-up for radiated electric field measurement 30 MHz to 1 GHz

**Specification:** ANSI C63.4-2014 chapter 8.2.3, ANSI C63.10-2013 chapter 6.5

**General Description:** Evaluating the field emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a NSA-compliant semi anechoic room (SAR) recognized by the regulatory commissions.

**Schematic:**



**Testing method:**

#### Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 0.8 m height which is placed on the turntable. By rotating the turntable (range 0° to 360°, step 90°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT) the emission spectrum and its characteristics was recorded with an EMI-receiver, broadband antenna and software.

Measurement antenna: horizontal and vertical, heights: 1,0 m and 1,82 m as worst-case determined by an exploratory emission measurements. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case of them. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

#### Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc. either on 10m OATS or 3m semi-anechoic room.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself either over 3-orthogonal axis (not defined usage position) or 2-orthogonal axis (defined usage position). The measurement antenna height between 1 m and 4 m.

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

**Formula:**

$$E_C = E_R + AF + C_L + D_F - G_A \quad (1)$$

$$M = L_T - E_C \quad (2)$$

AF = Antenna factor

C<sub>L</sub> = Cable loss

D<sub>F</sub> = Distance correction factor (if used)

E<sub>C</sub> = Electrical field – corrected value

E<sub>R</sub> = Receiver reading

G<sub>A</sub> = Gain of pre-amplifier (if used)

L<sub>T</sub> = Limit

M = Margin


All units are dB-units, positive margin means value is below limit.

## 4.4. Test system set-up for radiated electric field measurement above 1 GHz

**Specification:** ANSI C63.4-2014 chapter 8.3, ANSI C63.10-2013 chapter 6.6.3.3 & 6.6.4

**General Description:** Evaluating the emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a CISPR 16-1-4:2010 compliant fully anechoic room (FAR) recognized by the regulatory commission. The measurement distance was set to 3 meter for frequencies up to 18 GHz and 2 meter above 18 GHz. A logarithmic periodic antenna is used for the frequency range 30 MHz to 1 GHz. Horn antennas are used for frequency range 1 GHz to 40 GHz. The EUT is aligned within 3 dB beam width of the measurement antenna with three orthogonal axis measurements on the EUT.

**Schematic:**



**Testing method:**

### Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 1.55 m height which is placed on the turntable. By rotating the turntable (range 0° to 360°, step 15°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT) the emission spectrum and its characteristics was recorded with an EMI-receiver, broadband antenna and software.

The measurements are performed in horizontal and vertical polarization of the measurement antennas. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case of them. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

### Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined. Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself over 3-orthogonal axis and the height for EUT with large dimensions.

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out. On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

**Formula:**

$$E_C = E_R + AF + C_L + D_F - G_A \quad (1)$$

$$M = L_T - E_C \quad (2)$$

$E_C$  = Electrical field – corrected value

$E_R$  = Receiver reading

$M$  = Margin

$L_T$  = Limit

$AF$  = Antenna factor

$C_L$  = Cable loss

$D_F$  = Distance correction factor (if used)

$G_A$  = Gain of pre-amplifier (if used)

All units are dB-units, positive margin means value is below limit.

## 5. Measurements

### 5.1. Duty Cycle

5.1.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

Ambient Climatic conditions			Temperature: (22±2)°C		Rel. humidity: (45±15)%	
Test Site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 348 EMI cond.	<input type="checkbox"/> 443 EMI FAR	<input checked="" type="checkbox"/> 347 Radio.lab.	<input type="checkbox"/> 337 OATS	<input type="checkbox"/>
Equipment	<input type="checkbox"/> 331 HC 4055	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> 693 TS8997	<input type="checkbox"/>	<input type="checkbox"/>
Spectr. Analys.	<input checked="" type="checkbox"/> 683 FSU26	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK	<input checked="" type="checkbox"/> 693 TS8997	<input type="checkbox"/>	<input type="checkbox"/>
Power Meter	<input type="checkbox"/> 262 NRV-S	<input type="checkbox"/> 266 NRV-Z31	<input type="checkbox"/> 265 NRV-Z33	<input type="checkbox"/> 261 NRV-Z55	<input type="checkbox"/> 356 NRV-Z1	<input type="checkbox"/>
Multimeter	<input type="checkbox"/> 341 Fluke 112	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
DC Power	<input type="checkbox"/> 086 LNG50-10	<input type="checkbox"/> 087 EA3013	<input type="checkbox"/> 354 NGPE 40	<input type="checkbox"/> 349 car battery	<input type="checkbox"/> 350 Car battery	<input type="checkbox"/> 463 HP3245A
Supply Voltage	<input type="checkbox"/> 230 V 50 Hz via public mains		<input checked="" type="checkbox"/> 4.20 V DC (fully charged internal battery)			
Otherwise	<input checked="" type="checkbox"/> 530 Attenuator 10dB	<input checked="" type="checkbox"/> K4 Cable				

Method of measurement: ☒ conducted  
☐ radiated

**A special firmware program is used for test purposes. In contrast to normal operating mode a higher duty-cycle is set in order to facilitate the measurements. This is maximized at the extent possible.**

The necessary duty-cycle correction factor is determined on nominal conditions on 1 channel for all sub-bands. It is assumed that no noticeable changes occur when tested on other channels or climatic conditions.

Calculated with following formulas:

Duty cycle:	$x = \frac{T_{x_{on}}}{T_{x_{on}} + T_{x_{off}}}$	Duty cycle factor [dB]:	$10\log\left(\frac{1}{x}\right)$
-------------	---	-------------------------	----------------------------------



## Results:

Set-up No.:	2
Op. Mode:	1

DUTY-CYCLE Measurement								
WLAN 5 GHz	Marker 1	Marker 2	Marker 3	TX ON Marker 2 - Marker 1	TX OFF Marker 3 - Marker 2	Duty Cycle	Correction- Factor: 100log(1/DC)	Plot No.
Data Rate	ms	ms	ms	ms	ms	(%)	(dB)	(Remark 1)
WLAN 5 GHz a-Mode   Ch 36 (5180 MHz)								
6MBit	0,403846	5,855769	6,112179	5,45192	0,25641	95,51	0,20	1
54MBit	0,160256	0,772436	1,016026	0,61218	0,24359	71,54	1,45	2
WLAN 5 GHz n(HT20)-Mode   Ch 36 (5180 MHz)								
MCS0	0,737179	5,753205	6,054487	5,01603	0,30128	94,33%	0,25	3
MCS7	0,622596	1,158654	1,387019	0,53606	0,22837	70,13%	1,54	4
WLAN 5 GHz n(HT40)-Mode   Ch 38 (5190 MHz)								
MCS0	0,891025	3,278846	3,551282	2,38782	0,27244	89,76%	0,47	5
MCS7	0,362179	0,634615	0,865385	0,27244	0,23077	54,14%	2,66	6

Remark 1: For further details please refer → Annex 1: Test results CETECOM\_TR17-1-0180901T16a-A1

- ☒ The results were corrected in order to evaluate for worst-case result each time when average values are necessary for example average radiated emissions or similar
- ☐ No correction necessary: Duty-Cycle > 98%

## 5.2. RF-Parameter - Transmitter Peak output power (conducted and radiated)

### 5.2.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)		<input type="checkbox"/> 443 System CTC-FAR-EMI-		<input type="checkbox"/> Please see Chapter. 2.2.3	
test site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 487 SAR NSA	<input type="checkbox"/> 337 OATS	<input checked="" type="checkbox"/> 347 Radio.lab.	<input type="checkbox"/>	<input type="checkbox"/>
receiver	<input type="checkbox"/> 377 ESCS30	<input type="checkbox"/> 001 ESS	<input type="checkbox"/> 489 ESU 40	<input type="checkbox"/> 620 ESU 26	<input type="checkbox"/>	<input type="checkbox"/>
otherwise	<input checked="" type="checkbox"/> 600 NRVD	<input checked="" type="checkbox"/> 357 NRV-Z1	<input checked="" type="checkbox"/> 693 TS8997			
spectr. analys.	<input type="checkbox"/> 215 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
power supply	<input type="checkbox"/> 456 EA 3013A	<input type="checkbox"/> 457 EA 3013A	<input type="checkbox"/> 459 EA 2032-50	<input type="checkbox"/> 268 EA- 3050	<input type="checkbox"/> 494 AG6632A	<input type="checkbox"/> 354 NGPE 40
otherwise	<input checked="" type="checkbox"/> 613 20 dB Attenuator	<input type="checkbox"/> 248 6 dB Attenuator	<input type="checkbox"/> 529 Power divider	<input type="checkbox"/> - cable OTA20	<input type="checkbox"/> 530 10dB Atten	<input type="checkbox"/> K5 Cable
Supply voltage	<input type="checkbox"/> 230 V 50 Hz via public mains		<input checked="" type="checkbox"/> 4.20 V DC (fully charged internal battery)			

### 5.2.2. Reference:

FCC	<input checked="" type="checkbox"/> Part 15 Subpart C, §15.407(a)(1)(2)(3)(4)
ANSI	<input checked="" type="checkbox"/> C63.10-2013
KDB Guidance no.	<input checked="" type="checkbox"/> KDB 789033 D02 General UNII Test Procedures New Rules v01r03: Subchapter E, Method PM (3)(a) <input type="checkbox"/> KDB 662911 D01 Multiple Transmitter Output v02r01 ( MIMO, Smart-antenna)
Limits	<input checked="" type="checkbox"/> <b>Frequency Band 5150 – 5250 MHz</b>  <input type="checkbox"/> <b>Outdoor access point:</b> maximum conducted power shall not exceed 1 W if Antenna Gain < 6 dBi if Antenna Gain > 6 dBi maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi  <input type="checkbox"/> <b>Indoor access point:</b> maximum conducted power shall not exceed 1 W if Antenna Gain < 6 dBi if Antenna Gain > 6 dBi maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi  <input type="checkbox"/> <b>Fixed point to point access point:</b> maximum conducted power shall not exceed 1 W if Antenna Gain < 6 dBi if Antenna Gain > 6 dBi maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi  <input checked="" type="checkbox"/> <b>Client devices:</b> maximum conducted power shall not exceed 250 mW if Antenna Gain < 6 dBi if Antenna Gain > 6 dBi maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi  <input checked="" type="checkbox"/> <b>Frequency Band 5250 – 5350 MHz</b> <input checked="" type="checkbox"/> <b>Frequency bands 5470- 5725 MHz</b>  <input checked="" type="checkbox"/> <b>All Devices:</b> maximum conducted power lesser of 250 mW or $11 + 10 \log_{10} B$ , dBm ( B:26 dB emission B.W. in MHz)  <input checked="" type="checkbox"/> <b>Frequency band 5725-5850 MHz</b>  <input checked="" type="checkbox"/> <b>All Devices:</b> maximum conducted power shall not exceed 1 W if Antenna Gain < 6 dBi if Antenna Gain > 6 dBi maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

### 5.2.3. Antenna characteristics:

- ☒ directional gain < 6 dBi (Applicants declaration)  
☐ directional gain > 6 dBi (measured / applicant's declaration) -> conducted power reduction necessary

### 5.2.4. EUT settings:

The EUT was instructed to send with maximum power (if adjustable) according applicants instructions.

### 5.2.5. Measurement method:

Method used	Reference to KDB	Remarks:
<input type="checkbox"/> SA	KDB 789033 D02 General UNII Test Procedures New Rules v01r03	Integration bandwidth method
<input checked="" type="checkbox"/> Power Meter	a.) Method PM	A wideband thermocouple RF-power meter as described by KDB was used. <input checked="" type="checkbox"/> Duty-Cycle correction necessary <input type="checkbox"/> A value correction is not necessary since the EUT is transmitting continuously at duty-cycle > 98%.

### 5.2.6. Conducted power measurement and EIRP calculations

- Applicant's declared Maximum Directional Antenna Peak Gain : 3.66 dBi at 5 GHz Band Range

Set-up No.:	2
Op. Mode:	1 (WLAN 5 GHz   a Mode   B.W. 20 MHz )
Power Settings:	All other channels Power Settings: +20 dBm   Ch 153   157   161: 15.5 dBm

Operational Bands:	U-NII 1			U-NII-2A			U-NII 2C			U-NII-3		
Frequency Range:	5150 - 5250 MHz			5250 - 5350 MHz			5470 - 5600 MHz   5650 - 5725 MHz			5725 - 5850 MHz		
Channel No. (Channel Frequency)	Channel 36 (5180MHz)	Channel 40 (5200MHz)	Channel 48 (5240MHz)	Channel 52 (5260MHz)	Channel 56 (5280MHz)	Channel 64 (5320MHz)	Channel 100 (5500MHz)	Channel 116 (5580MHz)	Channel 140 (5700MHz)	Channel 149 (5745MHz)	Channel 157 (5785MHz)	Channel 165 (5825MHz)
WLAN 5 GHz-a Mode   B.W. 20 MHz   Power Settings +20dBm												
Data Rate	Measured Conducted Power values ( using RF Average Power Meter ) + Including Duty Cycle Correction factors											
6Mbit	13,20	13,10	13,69	10,48	11,68	11,20	12,55	12,82	7,93	8,24	13,40	9,18
9Mbit	13,09	12,91	13,64	10,28	11,52	10,63	12,11	12,72	8,24	8,16	13,26	9,22
12Mbit	12,98	12,80	13,59	10,48	11,60	10,60	12,31	12,52	8,00	8,01	13,25	9,04
18Mbit	12,78	12,67	13,35	9,96	11,25	10,44	12,31	12,56	7,80	7,71	13,12	8,95
24Mbit	12,56	12,78	13,68	9,78	11,06	10,09	11,95	12,31	7,35	7,33	11,87	8,68
36Mbit	12,17	12,54	13,28	9,37	10,60	9,95	11,49	12,01	6,94	7,12	10,73	8,48
48Mbit	12,07	11,74	12,78	9,23	10,36	9,69	11,23	11,50	6,84	6,92	9,30	8,24
54Mbit	10,61	10,67	11,77	9,04	10,08	9,45	11,16	11,03	6,54	6,61	8,22	7,98
FCC15.407 Limits & Verdict												
Operational Bands:	U-NII 1			U-NII-2A			U-NII 2C			U-NII 3		
Highest Conducted Value Subband [dBm]	13,69			11,68			12,82			13,40		
Conducted Limits [dBm]	23,98			23,98			23,98			30,00		
Margin to Conducted Limits [dB]	10,29			12,30			11,16			16,60		
Conducted Verdict PASS / FAIL ?	PASS			PASS			PASS			PASS		
Antenna Gain[dBi]	3,66			3,66			3,66			3,66		
Highest E.I.R.P. Value Subband [dBm]	17,35			15,34			16,48			17,06		
E.I.R.P. Limits[dBm]	29,98			29,98			29,98			36,00		
Margin to E.I.R.P. Limits [dB]	12,63			14,64			13,50			18,94		
E.I.R.P. Verdict PASS / FAIL ?	PASS			PASS			PASS			PASS		

Remark : Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor

Set-up No.:	2
Op. Mode:	1 (WLAN 5 GHz   n Mode   B.W. 20 MHz )
Power Settings:	All other channels Power Settings: +20 dBm   Ch 153   157   161: 15.5 dBm

Operational Bands:	U-NII 1			U-NII-2A			U-NII 2C			U-NII-3		
Frequency Range:	5150 - 5250 MHz			5250 - 5350 MHz			5470 - 5600 MHz   5650 - 5725 MHz			5725 - 5850 MHz		
Channel No. (Channel Frequency)	Channel 36 (5180MHz)	Channel 40 (5200MHz)	Channel 48 (5240MHz)	Channel 52 (5260MHz)	Channel 56 (5280MHz)	Channel 64 (5320MHz)	Channel 100 (5500MHz)	Channel 116 (5580MHz)	Channel 140 (5700MHz)	Channel 149 (5745MHz)	Channel 157 (5785MHz)	Channel 165 (5825MHz)
WLAN 5 GHz-n Mode   B.W. 20 MHz   Power Settings +20dBm												
Data Rate	Measured Conducted Power values ( using RF Average Power Meter) + Including Duty Cycle Correction factors											
MCS0 - 6.5Mbps	12,99	12,96	13,10	10,39	10,79	10,95	12,49	12,80	8,20	8,26	13,09	9,19
MCS1 - 13Mbps	12,86	12,87	12,98	10,23	10,59	10,82	12,29	12,59	7,96	8,06	13,00	9,10
MCS2 - 19.5Mbps	12,75	12,79	12,88	10,11	10,29	10,67	12,25	12,46	7,73	7,99	12,70	9,07
MCS3 - 26Mbps	12,61	12,55	12,67	9,92	10,24	10,50	12,02	12,38	7,66	7,68	12,58	8,72
MCS4 - 39Mbps	12,11	12,06	12,19	9,42	9,65	10,03	11,60	12,09	7,15	7,15	10,53	8,19
MCS5 - 52Mbps	11,73	11,68	11,75	9,05	9,37	9,69	11,12	11,70	6,93	7,02	9,38	7,97
MCS6 - 58.5Mbps	10,69	10,67	10,74	9,19	9,44	9,53	11,29	10,48	6,85	6,86	8,39	7,85
MCS7 - 65Mbps	9,53	9,50	9,52	9,14	9,28	9,33	10,09	8,99	6,42	6,75	7,25	7,03
FCC15.407 Limits & Verdict												
Operational Bands:	U-NII 1			U-NII-2A			U-NII 2C			U-NII 3		
Highest Conducted Value Subband [dBm]	13,10			10,95			12,80			13,09		
Conducted Limits [dBm]	23,98			23,98			23,98			30,00		
Margin to Conducted Limits [dB]	10,88			13,03			11,18			16,91		
Conducted Verdict PASS / FAIL ?	PASS			PASS			PASS			PASS		
Antenna Gain[dBi]	3,66			3,66			3,66			3,66		
Highest E.I.R.P. Value Subband [dBm]	16,76			14,61			16,46			16,75		
E.I.R.P. Limits[dBm]	29,98			29,98			29,98			36,00		
Margin to E.I.R.P. Limits [dB]	13,22			15,37			13,52			19,25		
E.I.R.P. Verdict PASS / FAIL ?	PASS			PASS			PASS			PASS		

Remark : Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor

Set-up No.:	2
Op. Mode:	1 (WLAN 5 GHz   n Mode   B.W. 40 MHz)
Power Settings:	All other channels Power Settings: +20 dBm   Ch 153   157   161: 15.5 dBm

Operational Bands:	U-NII 1		U-NII-2A		U-NII 2C			U-NII-3	
Frequency Range:	5150 - 5250 MHz		5250 - 5350 MHz		5470 - 5600 MHz   5650 - 5725 MHz			5725 - 5850 MHz	
Channel No. (Channel Frequency)	Channel 38 (5190MHz)	Channel 46 (5230MHz)	Channel 54 (5270MHz)	Channel 62 (5310MHz)	Channel 102 (5510MHz)	Channel 110 (5550MHz)	Channel 134 (5670MHz)	Channel 151 (5755MHz)	Channel 159 (5795MHz)
WLAN 5 GHz-a Mode   B.W. 20 MHz   Power Settings +20dBm									
Data Rate	Measured Conducted Power values ( using RF Average Power Meter) + Including Duty Cycle Correction factors								
MCS0 - 6.5Mbps	7,78	11,92	11,84	8,88	9,86	12,05	10,15	5,29	9,91
MCS1 - 13Mbps	7,25	11,79	11,66	8,52	9,62	11,63	9,89	5,22	9,79
MCS2 - 19.5Mbps	6,91	11,53	11,43	8,25	9,19	11,42	9,56	5,19	9,47
MCS3 - 26Mbps	6,67	11,29	11,26	8,19	8,96	11,15	9,38	4,52	9,26
MCS4 - 39Mbps	6,29	10,65	10,59	7,33	8,35	10,52	8,95	4,01	8,53
MCS5 - 52Mbps	5,62	9,23	10,25	6,79	7,92	9,19	8,35	3,75	8,13
MCS6 - 58.5Mbps	5,43	9,58	9,33	6,55	7,73	9,05	7,73	3,53	7,84
MCS7 - 65Mbps	5,65	6,97	8,01	6,62	7,46	7,29	7,51	3,25	6,33
FCC15.407 Limits & Verdict									
Operational Bands:	U-NII 1		U-NII-2A		U-NII 2C			U-NII 3	
Highest Conducted Value Subband [dBm]	11,92		11,84		12,05			9,91	
Conducted Limits [dBm]	23,98		23,98		23,98			30,00	
Margin to Conducted Limits [dB]	12,06		12,14		11,93			20,09	
Conducted Verdict PASS / FAIL ?	PASS		PASS		PASS			PASS	
Antenna Gain[dBi]	3,66		3,66		3,66			3,66	
Highest E.I.R.P. Value Subband [dBm]	15,58		15,50		15,71			13,57	
E.I.R.P. Limits [dBm]	29,98		29,98		29,98			36,00	
Margin to E.I.R.P. Limits [dB]	14,40		14,48		14,27			22,43	
E.I.R.P. Verdict PASS / FAIL ?	PASS		PASS		PASS			PASS	

Remark : Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor

## 5.2.7. Verdict: Pass

### 5.3. General Limit - Radiated field strength emissions below 30 MHz

#### 5.3.1. Test location and equipment

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)	<input type="checkbox"/> Please see Chapter. 2.2.2	<input type="checkbox"/> Please see Chapter. 2.2.3
test site	<input checked="" type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 487 SAR NSA	<input type="checkbox"/> 347 Radio.lab.
receiver	<input type="checkbox"/> 377 ESCS30	<input checked="" type="checkbox"/> 001 ESS	<input type="checkbox"/>
spectr. analys.	<input type="checkbox"/> 584 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK
antenna	<input type="checkbox"/> 574 BTA-L	<input type="checkbox"/> 133 EMCO3115	<input type="checkbox"/> 302 BBHA9170
signaling	<input type="checkbox"/> 392 MT8820A	<input type="checkbox"/> 371 CBT32	<input type="checkbox"/> 547 CMU
otherwise	<input type="checkbox"/> 400 FTC40x15E	<input type="checkbox"/> 401 FTC40x15E	<input type="checkbox"/> 110 USB LWL
DC power	<input type="checkbox"/> 671 EA-3013S	<input type="checkbox"/> 457 EA 3013A	<input type="checkbox"/> 459 EA 2032-50
Supply voltage	<input type="checkbox"/> 230 V 50 Hz via public mains	<input checked="" type="checkbox"/> 4.20 V DC (fully charged internal battery)	

#### 5.3.2. Requirements

FCC	Part 15, Subpart C, §15.205 & §15.209			
ANSI	C63.10-2013			
Frequency [MHz]	Field strength limit [μV/m]		Distance [m]	Remarks
0.009 – 0.490	2400/f (kHz)	67.6 – 20Log(f) (kHz)	300	Correction factor used due to measurement distance of 3 m
0.490 – 1.705	24000/f (kHz)	87.6 – 20Log(f) (kHz)	30	Correction factor used due to measurement distance of 3 m
1.705 – 30	30	29.5	30	Correction factor used due to measurement distance of 3 m

#### 5.3.3. Test condition and test set-up

Signal link to test system (if used):		<input type="checkbox"/> air link	<input type="checkbox"/> cable connection	<input checked="" type="checkbox"/> none
EUT-grounding		<input checked="" type="checkbox"/> none	<input type="checkbox"/> with power supply	<input type="checkbox"/> additional connection
Equipment set up		<input checked="" type="checkbox"/> table top		<input type="checkbox"/> floor standing
Climatic conditions		Temperature: (22±3°C)		Rel. humidity: (40±20)%
EMI-Receiver or Analyzer Settings	Scan data	<input checked="" type="checkbox"/> 9 – 150 kHz RBW/VBW = 200 Hz Scan step = 80 Hz		
		<input checked="" type="checkbox"/> 150 kHz – 30 MHz RBW/VBW = 9 kHz Scan step = 4 kHz		
	Detector Mode: Sweep-Time	<input type="checkbox"/> other:		
		<input checked="" type="checkbox"/> 6 dB EMI-Receiver Mode <input type="checkbox"/> 3dB Spectrum analyser Mode		
		Peak (pre-measurement) and Quasi-PK/Average (final if applicable)		
		Repetitive-Scan, max-hold		
		Coupled – calibrated display if continuous signal otherwise adapted to EUT's individual transmission duty-cycle		
General measurement procedures		Please see chapter “Test system set-up radiated magnetic field measurements below 30 MHz”		

### 5.3.4. Radiated Field Strength Emissions – 9 kHz to 30 MHz Results

Radiated Field Strength Emissions – 9 kHz to 30 MHz								
Temperature :+21 °C		Technology: WLAN 5 GHz 802.11a/n		TX-Fixed Channel (Modulated)				
Diagram No. (Remark 1)	Test Settings Mode   B.W.   Data Rate   Frequency Band - Channel (Frequency)		Set-up no.	OP-mode no.	Used detector			Verdict
					PK	AV	QP	
2.31	a Mode   20 MHz   6 Mbit   U-NII-1-Ch 48 (5240 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.32	a Mode   20 MHz   6 Mbit   U-NII-2A-Ch 56 (5280 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.33	a Mode   20 MHz   6 Mbit   U-NII-2C-Ch 116 (5580 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.34	a Mode   20 MHz   6 Mbit   U-NII-3-Ch 157 (5785 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.35	n Mode   20 MHz   MCS0   U-NII-1-Ch 48 (5240 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.36	n Mode   20 MHz   MCS0   U-NII-2A-Ch 64 (5320 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.37	n Mode   20 MHz   MCS0   U-NII-2C-Ch 116 (5580 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.38	n Mode   20 MHz   MCS0   U-NII-3-Ch 157 (5785 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.39	n Mode   40 MHz   MCS0   U-NII-1-Ch 46 (5230 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.40	n Mode   40 MHz   MCS0   U-NII-2A-Ch 54 (5270 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.41	n Mode   40 MHz   MCS0   U-NII-2C-Ch 110 (5550 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.42	n Mode   40 MHz   MCS0   U-NII-3-Ch 159 (5795 MHz)		1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
Remark 1: For further details please refer → Annex 1: Test results CETECOM_TR17-1-0180901T16a-A1								
Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm								

### 5.3.5. Correction factors due to reduced meas. distance (f< 30 MHz)

The used correction factors when the measurement distance is reduced compared to regulatory measurement distance, are calculated according Extrapolation formulas valid for EUT's with maximum dimension of 0.625xLambda. Formula 2+3+4 as presented in ANSI C63.10, Chapter 6.4.4 are used for the calculations of proper extrapolation factors.

Frequency -Range	f [kHz/MHz]	Lambda [m]	Far-Field Point [m]	Distance Limit accord. 15.209 [m]	1st Condition (d <sub>meas</sub> < D <sub>near-field</sub> )	2 <sup>te</sup> Condition (Limit distance bigger d <sub>near-field</sub> )	Distance Correction accord. Formula
kHz	9,00E+03	33333,33	5305,17	300	fulfilled	not fulfilled	-80,00
	1,00E+04	30000,00	4774,65		fulfilled	not fulfilled	-80,00
	2,00E+04	15000,00	2387,33		fulfilled	not fulfilled	-80,00
	3,00E+04	10000,00	1591,55		fulfilled	not fulfilled	-80,00
	4,00E+04	7500,00	1193,66		fulfilled	not fulfilled	-80,00
	5,00E+04	6000,00	954,93		fulfilled	not fulfilled	-80,00
	6,00E+04	5000,00	795,78		fulfilled	not fulfilled	-80,00
	7,00E+04	4285,71	682,09		fulfilled	not fulfilled	-80,00
	8,00E+04	3750,00	596,83		fulfilled	not fulfilled	-80,00
	9,00E+04	3333,33	530,52		fulfilled	not fulfilled	-80,00
	1,00E+05	3000,00	477,47		fulfilled	not fulfilled	-80,00
	1,25E+05	2400,00	381,97		fulfilled	not fulfilled	-80,00
	2,00E+05	1500,00	238,73		fulfilled	fulfilled	-78,02
	3,00E+05	1000,00	159,16		fulfilled	fulfilled	-74,49
	4,00E+05	750,00	119,37		fulfilled	fulfilled	-72,00
	4,90E+05	612,24	97,44		fulfilled	fulfilled	-70,23
	5,00E+05	600,00	95,49	30	fulfilled	not fulfilled	-40,00
	6,00E+05	500,00	79,58		fulfilled	not fulfilled	-40,00
	7,00E+05	428,57	68,21		fulfilled	not fulfilled	-40,00
	8,00E+05	375,00	59,68		fulfilled	not fulfilled	-40,00
	9,00E+05	333,33	53,05		fulfilled	not fulfilled	-40,00
	1,00	300,00	47,75		fulfilled	not fulfilled	-40,00
	1,59	188,50	30,00		fulfilled	not fulfilled	-40,00
	2,00	150,00	23,87		fulfilled	fulfilled	-38,02
	3,00	100,00	15,92		fulfilled	fulfilled	-34,49
	4,00	75,00	11,94		fulfilled	fulfilled	-32,00
MHz	5,00	60,00	9,55		fulfilled	fulfilled	-30,06
	6,00	50,00	7,96		fulfilled	fulfilled	-28,47
	7,00	42,86	6,82		fulfilled	fulfilled	-27,13
	8,00	37,50	5,97		fulfilled	fulfilled	-25,97
	9,00	33,33	5,31		fulfilled	fulfilled	-24,95
	10,00	30,00	4,77		fulfilled	fulfilled	-24,04
	10,60	28,30	4,50		fulfilled	fulfilled	-23,53
	11,00	27,27	4,34		fulfilled	fulfilled	-23,21
	12,00	25,00	3,98		fulfilled	fulfilled	-22,45
	13,56	22,12	3,52		fulfilled	fulfilled	-21,39
	15,00	20,00	3,18		fulfilled	fulfilled	-20,51
	15,92	18,85	3,00		fulfilled	fulfilled	-20,00
	17,00	17,65	2,81		not fulfilled	fulfilled	-20,00
	18,00	16,67	2,65		not fulfilled	fulfilled	-20,00
	20,00	15,00	2,39		not fulfilled	fulfilled	-20,00
	21,00	14,29	2,27		not fulfilled	fulfilled	-20,00
	23,00	13,04	2,08		not fulfilled	fulfilled	-20,00
	25,00	12,00	1,91		not fulfilled	fulfilled	-20,00
	27,00	11,11	1,77		not fulfilled	fulfilled	-20,00
	29,00	10,34	1,65		not fulfilled	fulfilled	-20,00
	30,00	10,00	1,59		not fulfilled	fulfilled	-20,00



## 5.4. General Limit - Radiated field strength emissions, 30 MHz - 1 GHz

### 5.4.1. Test location and equipment

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)	<input type="checkbox"/> Please see Chapter. 2.2.2	<input type="checkbox"/> Please see Chapter. 2.2.3
test site	<input checked="" type="checkbox"/> 441 EMI SAR <input checked="" type="checkbox"/> 487 SAR NSA		
receiver	<input type="checkbox"/> 377 ESCS30 <input checked="" type="checkbox"/> 001 ESS	<input type="checkbox"/> 489 ESU 40 <input type="checkbox"/> 620 ESU 26	
spectr. analys.	<input type="checkbox"/> 584 FSU <input type="checkbox"/> 120 FSEM <input type="checkbox"/> 264 FSEK		
antenna	<input checked="" type="checkbox"/> 574 BTA-L <input type="checkbox"/> 133 EMCO3115 <input type="checkbox"/> 302 BBHA9170 <input type="checkbox"/> 289 CBL 6141 <input type="checkbox"/> 030 HFH-Z2 <input type="checkbox"/> 477 GPS		
signaling	<input type="checkbox"/> 392 MT8820A <input type="checkbox"/> 371 CBT32 <input type="checkbox"/> 547 CMU <input type="checkbox"/> 594 CMW		
otherwise	<input type="checkbox"/> 400 FTC40x15E <input type="checkbox"/> 401 FTC40x15E <input type="checkbox"/> 110 USB LWL <input checked="" type="checkbox"/> 482 Filter Matrix		
DC power	<input type="checkbox"/> 671 EA-3013S <input type="checkbox"/> 457 EA 3013A <input type="checkbox"/> 459 EA 2032-50 <input type="checkbox"/> 268 EA- 3050 <input type="checkbox"/> 494 AG6632A <input type="checkbox"/> 498 NGPE		
Supply voltage	<input type="checkbox"/> 230 V 50 Hz via public mains <input checked="" type="checkbox"/> 4.20 V DC (fully charged internal battery)		

### 5.4.2. Requirements/Limits

FCC		<input type="checkbox"/> Part 15 Subpart B, §15.109, class B <input checked="" type="checkbox"/> Part 15 Subpart C, §15.209 @ frequencies defined in §15.205	
ANSI		<input type="checkbox"/> C63.4-2014 <input checked="" type="checkbox"/> C63.10-2013	
Limit	Frequency [MHz]	Radiated emissions limits, 3 meters	
		QUASI Peak [µV/m]	QUASI-Peak [dBµV/m]
	30 - 88	100	40.0
	88 - 216	150	43.5
	216 - 960	200	46.0
	above 960	500	54.0

### 5.4.3. Restricted bands of operation (FCC §15.205)

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.20725-4.20775	37.5-38.25	1645.5-1646.5	9.3-9.5
6.215-6.218	73-74.6	1660-1710	10.6-12.7
6.26775-6.26825	74.8-75.2	1718.8-1722.2	13.25-13.4
6.31175-6.31225	108-121.94	2200-2300	14.47-14.5
8.291-8.294	123-138	2310-2390	15.35-16.2
8.362-8.366	149.9-150.05	2483.5-2500	17.7-21.4
8.37625-8.38675	156.52475-156.52525	2690-2900	22.01-23.12
8.41425-8.41475	156.7-156.9	3260-3267	23.6-24.0
12.29-12.293	162.0125-167.17	3332-3339	31.2-31.8
12.51975-12.52025	167.72-173.2	3345.8-3358	36.43-36.5
12.57675-12.57725	240-285	3600-4400	--
13.36-13.41	322-335.4	--	--

Remark: only spurious emissions are allowed within these frequency bands not exceeding the limits per §15.209

#### 5.4.4. Test condition and measurement test set-up

Signal link to test system (if used):	<input type="checkbox"/> air link	<input type="checkbox"/> cable connection	<input checked="" type="checkbox"/> none
EUT-grounding	<input checked="" type="checkbox"/> none	<input type="checkbox"/> with power supply	<input type="checkbox"/> additional connection
Equipment set up	<input checked="" type="checkbox"/> table top 0.8m height	<input type="checkbox"/> floor standing	
Climatic conditions	Temperature: (22±3°C)	Rel. humidity: (40±20)%	
EMI-Receiver (Analyzer) Settings	Scan frequency range: <input checked="" type="checkbox"/> 30 – 1000 MHz <input type="checkbox"/> other: Scan-Mode: <input checked="" type="checkbox"/> 6 dB EMI-Receiver Mode <input type="checkbox"/> 3 dB spectrum analyser mode Detector: Peak / Quasi-peak RBW/VBW: 100 kHz/300 kHz Mode: Repetitive-Scan, max-hold Scan step: 80 kHz Sweep-Time: Coupled – calibrated display if continuous tx-signal otherwise adapted to EUT's individual duty-cycle		
General measurement procedures	Please see chapter "Test system set-up for electric field measurement in the range 30 MHz to 1 GHz"		

#### 5.4.5. Radiated Field Strength Emissions – 30 MHz to 1 GHz Results

Radiated Field Strength Emissions – 30 MHz to 1 GHz									
Temperature :+21 °C		Technology: WLAN 5 GHz 802.11a/n		TX-Fixed Channel (Modulated)					
Diagram No. (Remark 1)	Test Settings Mode   B.W.   Data Rate   Frequency Band - Channel (Frequency)			Set-up no.	OP-mode no.	Used detector			Verdict
	PK	AV	QP						
3.31	a Mode   20 MHz   6 Mbit   U-NII-1-Ch 48 (5240 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.32	a Mode   20 MHz   6 Mbit   U-NII-2A-Ch 56 (5280 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.33	a Mode   20 MHz   6 Mbit   U-NII-2C-Ch 116 (5580 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.34	a Mode   20 MHz   6 Mbit   U-NII-3-Ch 157 (5785 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.35	n Mode   20 MHz   MCS0   U-NII-1-Ch 48 (5240 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.36	n Mode   20 MHz   MCS0   U-NII-2A-Ch 64 (5320 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.37	n Mode   20 MHz   MCS0   U-NII-2C-Ch 116 (5580 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.38	n Mode   20 MHz   MCS0   U-NII-3-Ch 157 (5785 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.39	n Mode   40 MHz   MCS0   U-NII-1-Ch 46 (5230 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.40	n Mode   40 MHz   MCS0   U-NII-2A-Ch 54 (5270 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.41	n Mode   40 MHz   MCS0   U-NII-2C-Ch 110 (5550 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
3.42	n Mode   40 MHz   MCS0   U-NII-3-Ch 159 (5795 MHz)			1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Pass
Remark 1: For further details please refer → Annex 1: Test results CETECOM_TR17-1-0180901T16a-A1									
Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm									

## 5.5. General Limit - Radiated emissions, above 1 GHz

### 5.5.1. Test location and equipment FAR

test site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 348 EMI cond.	<input checked="" type="checkbox"/> 443 EMI FAR	<input type="checkbox"/> 347 Radio.lab.	<input type="checkbox"/> 337 OATS	<input type="checkbox"/>
spectr. analys.	<input type="checkbox"/> 584 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK	<input checked="" type="checkbox"/> 489 ESU 40	<input type="checkbox"/>	<input type="checkbox"/>
antenna meas	<input type="checkbox"/> 574 BTA-L	<input type="checkbox"/> 289 CBL 6141	<input type="checkbox"/> 608 HL 562	<input checked="" type="checkbox"/> 549 HL025	<input checked="" type="checkbox"/> 302 BBHA9170	<input type="checkbox"/> 477 GPS
antenna meas	<input type="checkbox"/> 123 HUF-Z2	<input type="checkbox"/> 132 HUF-Z3	<input type="checkbox"/> 030 HFH-Z2	<input checked="" type="checkbox"/> 376 BBHA9120E		<input type="checkbox"/>
antenna subst	<input type="checkbox"/> 071 HUF-Z2	<input type="checkbox"/> 020 EMCO3115	<input type="checkbox"/> 063 LP 3146	<input type="checkbox"/> 303 BBHA9170	<input type="checkbox"/>	<input type="checkbox"/>
multimeter	<input type="checkbox"/> 341 Fluke 112	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
signaling	<input type="checkbox"/> 392 MT8820A	<input type="checkbox"/> 371 CBT32	<input type="checkbox"/> 547 CMU	<input type="checkbox"/> 594 CMW		
DCpower	<input type="checkbox"/> 611 E3632A	<input type="checkbox"/> 087 EA3013	<input type="checkbox"/> 354 NGPE 40	<input type="checkbox"/> 349 car battery	<input type="checkbox"/> 350 Car battery	<input type="checkbox"/>
Supply voltage	<input type="checkbox"/> 230 V 50 Hz via public mains		<input checked="" type="checkbox"/> 4.20 V DC (fully charged internal battery)			

### 5.5.2. Requirements/Limits

<b>FCC</b>	<input type="checkbox"/> Part 15 Subpart B, §15.109 class B <input checked="" type="checkbox"/> Part 15 Subpart C, §15.209 for frequencies defined in §15.205 <input checked="" type="checkbox"/> Part 15 Subpart C, §15.407(b)(1)(2)(3)(4)(5)(6)(7)(8)			
<b>ANSI</b>	<input type="checkbox"/> C63.4-2014 <input checked="" type="checkbox"/> C63.10-2013			
Frequency [MHz]	Limits			
	AV [µV/m]	AV [dBµV/m]	Peak [µV/m]	Peak [dBµV/m] or [dBm/MHz]
above 1 GHz for frequencies as defined in §15.205	500	54.0	5000	74.0 dBµV/m
§15.407(b)(1)(2)(3)(4)	--	--	--	(b)(1): 5.15-5.25GHz: -27dBm eirp (b)(2): 5.25-5.35GHz: -27dBm eirp (b)(3): 5.47-5.725 GHz: -27dBm eirp (b)(4): 5725-5.85GHz: Spectrum mask

### 5.5.3. Test condition and measurement test set-up

Signal link to test system (if used):	<input type="checkbox"/> air link	<input type="checkbox"/> cable connection	<input checked="" type="checkbox"/> none
EUT-grounding	<input checked="" type="checkbox"/> none	<input type="checkbox"/> with power supply	<input type="checkbox"/> additional connection
Equipment set up	<input checked="" type="checkbox"/> table top 1.5m height		
Climatic conditions	Temperature: (22±3°C)		
	Rel. humidity: (40±20)%		
Spectrum-Analyzer settings	Scan frequency range: <input checked="" type="checkbox"/> 1 – 18 GHz <input type="checkbox"/> 18 – 25 GHz <input checked="" type="checkbox"/> 18 – 40 GHz <input type="checkbox"/> other: Scan-Mode: <input checked="" type="checkbox"/> 6 dB EMI-Receiver Mode <input type="checkbox"/> 3 dB Spectrum analyser Mode Detector: Peak and Average RBW/VBW: 1 MHz / 3 MHz Mode: Repetitive-Scan, max-hold Scan step: 400 kHz Sweep-Time: Coupled – calibrated display if CW signal otherwise adapted to EUT's individual duty-cycle		
General measurement procedures	Please see chapter "Test system set-up for radiated electric field measurements above 1 GHz"		

#### 5.5.4. Radiated Field Strength Emissions – 1 GHz to 7 GHz Results

Radiated Field Strength Emissions – 1 GHz to 7 GHz								
Temperature :+21 °C		Technology: WLAN 5 GHz 802.11a/n		TX-Fixed Channel (Modulated)				
Diagram No. (Remark 1)	Test Settings Mode   B.W.   Data Rate   Frequency Band - Channel (Frequency)		Set-up no.	OP-mode no.	Used detector			Verdict
					PK	AV	QP	
4.31	a Mode   20 MHz   6 Mbit   U-NII-1-Ch 48 (5240 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.32	a Mode   20 MHz   6 Mbit   U-NII-2A-Ch 56 (5280 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.33	a Mode   20 MHz   6 Mbit   U-NII-2C-Ch 116 (5580 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.34	a Mode   20 MHz   6 Mbit   U-NII-3-Ch 157 (5785 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.35	n Mode   20 MHz   MCS0   U-NII-1-Ch 48 (5240 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.36	n Mode   20 MHz   MCS0   U-NII-2A-Ch 64 (5320 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.37	n Mode   20 MHz   MCS0   U-NII-2C-Ch 116 (5580 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.38	n Mode   20 MHz   MCS0   U-NII-3-Ch 157 (5785 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.39	n Mode   40 MHz   MCS0   U-NII-1-Ch 46 (5230 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.40	n Mode   40 MHz   MCS0   U-NII-2A-Ch 54 (5270 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.41	n Mode   40 MHz   MCS0   U-NII-2C-Ch 110 (5550 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.42	n Mode   40 MHz   MCS0   U-NII-3-Ch 159 (5795 MHz)		1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
Remark 1: For further details please refer → Annex 1: Test results CETECOM_TR17-1-0180901T16a-A1								
Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm								
Remark 3: Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor								

### 5.5.5. Radiated Field Strength Emissions – 7 GHz to 18 GHz Results

Radiated Field Strength Emissions – 7 GHz to 18 GHz							
Temperature :+21 °C		Technology: WLAN 5 GHz 802.11a/n		TX-Fixed Channel (Modulated)			
Diagram No. (Remark 1)	Test Settings Mode   B.W.   Data Rate   Frequency Band - Channel (Frequency)	Set-up no.	OP-mode no.	Used detector			Verdict
				PK	AV	QP	
4.31a	a Mode   20 MHz   6 Mbit   U-NII-1-Ch 48 (5240 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.32a	a Mode   20 MHz   6 Mbit   U-NII-2A-Ch 56 (5280 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.33a	a Mode   20 MHz   6 Mbit   U-NII-2C-Ch 116 (5580 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.34a	a Mode   20 MHz   6 Mbit   U-NII-3-Ch 157 (5785 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.35a	n Mode   20 MHz   MCS0   U-NII-1-Ch 48 (5240 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.36a	n Mode   20 MHz   MCS0   U-NII-2A-Ch 64 (5320 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.37a	n Mode   20 MHz   MCS0   U-NII-2C-Ch 116 (5580 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.38a	n Mode   20 MHz   MCS0   U-NII-3-Ch 157 (5785 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.39a	n Mode   40 MHz   MCS0   U-NII-1-Ch 46 (5230 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.40a	n Mode   40 MHz   MCS0   U-NII-2A-Ch 54 (5270 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.41a	n Mode   40 MHz   MCS0   U-NII-2C-Ch 110 (5550 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.42a	n Mode   40 MHz   MCS0   U-NII-3-Ch 159 (5795 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
Remark 1: For further details please refer → Annex 1: Test results CETECOM_TR17-1-0180901T16a-A1							
Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm							
Remark 3: Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor							

### 5.5.6. Radiated Field Strength Emissions – 18 GHz to 40 GHz Results

Radiated Field Strength Emissions – 18 GHz to 40 GHz							
Temperature :+21 °C		Technology: WLAN 5 GHz 802.11a/n		TX-Fixed Channel (Modulated)			
Diagram No. (Remark 1)	Test Settings Mode   B.W.   Data Rate   Frequency Band - Channel (Frequency)	Set-up no.	OP-mode no.	Used detector			Verdict
				PK	AV	QP	
4.31b	a Mode   20 MHz   6 Mbit   U-NII-1-Ch 48 (5240 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.32b	a Mode   20 MHz   6 Mbit   U-NII-2A-Ch 56 (5280 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.33b	a Mode   20 MHz   6 Mbit   U-NII-2C-Ch 116 (5580 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.34b	a Mode   20 MHz   6 Mbit   U-NII-3-Ch 157 (5785 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.35b	n Mode   20 MHz   MCS0   U-NII-1-Ch 48 (5240 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.36b	n Mode   20 MHz   MCS0   U-NII-2A-Ch 64 (5320 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.37b	n Mode   20 MHz   MCS0   U-NII-2C-Ch 116 (5580 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.38b	n Mode   20 MHz   MCS0   U-NII-3-Ch 157 (5785 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.39b	n Mode   40 MHz   MCS0   U-NII-1-Ch 46 (5230 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.40b	n Mode   40 MHz   MCS0   U-NII-2A-Ch 54 (5270 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.41b	n Mode   40 MHz   MCS0   U-NII-2C-Ch 110 (5550 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.42b	n Mode   40 MHz   MCS0   U-NII-3-Ch 159 (5795 MHz)	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
Remark 1: For further details please refer → Annex 1: Test results CETECOM_TR17-1-0180901T16a-A1							
Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm							
Remark 3: Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor							

## 5.6. RF-Parameter - Radiated Band-Edge compliance measurements

### 5.6.1. Test location and equipment FAR

test site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 348 EMI cond.	<input checked="" type="checkbox"/> 443 EMI FAR	<input type="checkbox"/> 347 Radio.lab.	<input type="checkbox"/> 337 OATS	<input type="checkbox"/>
spectr. analys.	<input type="checkbox"/> 584 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK	<input checked="" type="checkbox"/> 489 ESU 40	<input type="checkbox"/>	<input type="checkbox"/>
antenna meas	<input type="checkbox"/> 574 BTA-L	<input type="checkbox"/> 289 CBL 6141	<input type="checkbox"/> 608 HL 562	<input checked="" type="checkbox"/> 549 HL025	<input type="checkbox"/> 302 BBHA9170	<input type="checkbox"/> 477 GPS
antenna meas	<input type="checkbox"/> 123 HUF-Z2	<input type="checkbox"/> 132 HUF-Z3	<input type="checkbox"/> 030 HFH-Z2	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
antenna subst	<input type="checkbox"/> 071 HUF-Z2	<input type="checkbox"/> 020 EMCO3115	<input type="checkbox"/> 063 LP 3146	<input type="checkbox"/> 303 BBHA9170	<input type="checkbox"/>	<input type="checkbox"/>
multimeter	<input type="checkbox"/> 341 Fluke 112	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
signaling	<input type="checkbox"/> 392 MT8820A	<input type="checkbox"/> 371 CBT32	<input type="checkbox"/> 547 CMU	<input type="checkbox"/> 594 CMW	<input type="checkbox"/>	<input type="checkbox"/>
DC power	<input type="checkbox"/> 611 E3632A	<input type="checkbox"/> 087 EA3013	<input type="checkbox"/> 354 NGPE 40	<input type="checkbox"/> 349 car battery	<input type="checkbox"/> 350 Car battery	<input type="checkbox"/>
Supply voltage	<input type="checkbox"/> 230 V 50 Hz via public mains		<input checked="" type="checkbox"/> 4.20 V DC (fully charged internal battery)			

### 5.6.2. Requirements/Limits

<b>FCC</b>	<input type="checkbox"/> Part 15 Subpart B, §15.109 class B <input checked="" type="checkbox"/> Part 15 Subpart C, §15.209 for frequencies defined in §15.205 <input checked="" type="checkbox"/> Part 15 Subpart C, §15.407(b)(1)(2)(3)(4)(5)(6)(7)(8)			
<b>ANSI</b>	<input type="checkbox"/> C63.4-2014 <input checked="" type="checkbox"/> C63.10-2013 Chapter 6.10.6			
Frequency [MHz]	Limits			
	AV [µV/m]	AV [dBµV/m]	Peak [µV/m]	Peak [dBµV/m] or [dBm/MHz]
above 1 GHz for frequencies as defined in §15.205	500	54.0	5000	74.0 dBµV/m
§15.407(b)(1)(2)(3)(4)	--	--	--	(b)(1): 5.15-5.25GHz: -27dBm eirp (b)(2): 5.25-5.35GHz: -27dBm eirp (b)(3): 5.47-5.725 GHz: -27dBm eirp (b)(4): 5725-5.85GHz: Spectrum mask

### 5.6.3. Test condition and measurement test set-up

Signal link to test system (if used):	<input type="checkbox"/> air link	<input type="checkbox"/> cable connection	<input checked="" type="checkbox"/> none
EUT-grounding	<input checked="" type="checkbox"/> none	<input type="checkbox"/> with power supply	<input type="checkbox"/> additional connection
Equipment set up	<input checked="" type="checkbox"/> table top 1.5m height		
Climatic conditions	Temperature: (22±3°C) Rel. humidity: (40±20)%		
Spectrum-Analyzer settings	Scan frequency range: <input type="checkbox"/> 1 – 18 GHz <input type="checkbox"/> 18 – 25 GHz <input type="checkbox"/> 18 – 40 GHz <input checked="" type="checkbox"/> other: see diagrams Scan-Mode: <input type="checkbox"/> 6 dB EMI-Receiver Mode <input checked="" type="checkbox"/> 3 dB Spectrum analyzer Mode Detector: Peak and Average RBW/VBW: Left band-edge: 100kHz/300kHz Right band-edge: 1 MHz / 3 MHz Mode: Repetitive-Scan, max-hold Scan step: 40kHz or 400 kHz Sweep-Time: Coupled – calibrated display if CW signal otherwise adapted to EUT's individual duty-cycle		
General measurement procedures	Please see chapter "Test system set-up for radiated electric field measurements above 1 GHz" for general measurements procedures in anechoic chamber.		

#### 5.6.4. Measurement Method

For uncritical results where a measurement resolution bandwidth of 1MHz can clearly show the compliance without influencing the results, a field strength measurement was performed to show compliance.

For critical results a Marker-Delta marker method was used for showing compliance to restricted bands. The method is according ANSI C63.10:2013, Chapter 6.10.6 “Marker-Delta method”. The method consists of three independent steps:

- 1. Step:** Prior to the measurement the fundamental radiated In-Band field strength was performed. The determined value is used as reference value.
- 2. Step:** Second step consist of finding the relative attenuation between the fundamental emission and the maximum local out-of-band emission (within 2 MHz range around the band edge either on the band-edge directly or some modulation product if the level is greater than that on the band-edge) when measured with lower resolution bandwidth.
- 3. Step:** The delta value recorded in step 2 will be subtracted from value recorded in step 1, thus giving the required field strength at the band-edge. This value must fulfil the requirements for radiated spurious emissions in restricted bands in FCC §15.205 with the general limits of FCC §15.209.

#### 5.6.5. EUT settings

The EUT was instructed to send with maximum power (if adjustable) according to applicants instructions.

#### 5.6.6. Results for non-restricted bands near-by

##### 5.6.6.1. Non-restricted bands near-by - limits according to FCC §15.407 limits

Technology:	WLAN 5 GHz 802.11a Mode B.W. 20 MHz								
Set-up No.:	1								
Op. Mode:	1								
Diagram no.	Channel no.	Restricted band ?	Fundamental Value [dBuV/m]		Peak-Value at Band-Edge [dBuV/m]	Limit: [dBuV/m @3m]	Margin: [dB]	Verdict	Remark: Mode-B.W.-Data Rate-Power
			Peak -Value	Average -Value + Duty Cycle Correction					
9.49	5240	NO	105,19	97,20	51,98	68,20	16,22	PASS	a-Mode-20 MHz-6Mbit+20dBm
9.50	5260	NO	102,37	Not measured	52,50	68,20	15,70	PASS	a-Mode-20 MHz-6Mbit+20dBm
9.33	5500	NO	103,37	93,75	56,99	68,20	11,21	PASS	a-Mode-20 MHz-6Mbit+20dBm
9.34	5700	NO	106,36	98,06	64,49	68,20	3,71	PASS	a-Mode-20 MHz-6Mbit+20dBm
9.35	5745	NO	100,20	92,08	61,82	122,20	60,38	PASS	a-Mode-20 MHz-6Mbit+20dBm
9.36	5825	NO	108,73	101,14	58,87	122,20	63,33	PASS	a-Mode-20 MHz-6Mbit+20dBm
Remark 1: For further details please refer → Annex 1: Test results - CETECOM_TR17-1-0180901T16a-A1 Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm Remark 3: Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor									



SS

Technology:		WLAN 5 GHz 802.11n Mode B.W. 20 MHz							
Set-up No.:		1							
Op. Mode:		1							
Diagram no.	Channel no.	Restricted band ?	Fundamental Value [dBuV/m]		Peak-Value at Band-Edge [dBuV/m]	Limit: [dBuV/m @3m]	Margin: [dB]	Verdict	Remark: Mode-B.W.-Data Rate-Power
			Peak -Value	Average -Value + Duty Cycle Correction					
9.51	5240	NO	107,67	100,14	52,87	68,20	15,33	PASS	n-Mode-20 MHz-MCS0+20dBm
9.52	5260	NO	100,30	Not measured	52,50	68,20	15,70	PASS	n-Mode-20 MHz-MCS0+20dBm
9.39	5500	NO	106,39	98,51	61,25	68,20	6,95	PASS	n-Mode-20 MHz-MCS0+20dBm
9.40	5700	NO	106,35	98,78	62,40	68,20	5,80	PASS	n-Mode-20 MHz-MCS0+20dBm
9.41	5745	NO	107,00	99,48	74,10	122,20	48,10	PASS	n-Mode-20 MHz-MCS0+20dBm
9.42	5825	NO	107,77	99,67	67,20	122,20	55,00	PASS	n-Mode-20 MHz-MCS0+20dBm
Remark 1: For further details please refer → Annex 1: Test results - CETECOM_TR17-1-0180901T16a-A1 Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm Remark 3: Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor									

Technology:		WLAN 5 GHz 802.11n Mode B.W. 40 MHz							
Set-up No.:		1							
Op. Mode:		1							
Diagram no.	Channel no.	Restricted band ?	Fundamental Value [dBuV/m]		Peak-Value at Band-Edge [dBuV/m]	Limit: [dBuV/m @3m]	Margin: [dB]	Verdict	Remark: Mode-B.W.-Data Rate-Power
			Peak -Value	Average -Value + Duty Cycle Correction					
9.53	5230	NO	104,58	96,86	51,84	68,20	16,36	PASS	n-Mode-40 MHz-MCS0+20dBm
9.54	5270	NO	101,58	Not measured	52,50	68,20	15,70	PASS	n-Mode-40 MHz-MCS0+20dBm
9.45	5510	NO	102,51	94,21	67,60	68,20	0,60	PASS	n-Mode-40 MHz-MCS0+20dBm
9.46	5670	NO	104,63	96,55	59,35	68,20	8,85	PASS	n-Mode-40 MHz-MCS0+20dBm
9.47	5755	NO	102,23	93,77	68,90	122,20	53,30	PASS	n-Mode-40 MHz-MCS0+20dBm
9.48	5795	NO	105,96	97,98	59,08	122,20	63,12	PASS	n-Mode-40 MHz-MCS0+20dBm
Remark 1: For further details please refer → Annex 1: Test results - CETECOM_TR17-1-0180901T16a-A1 Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm Remark 3: Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor									

### 5.6.6.2. Results for restricted bands near-by with limits accord. FCC §15.205 §15.209

Technology:		WLAN 5 GHz 802.11a Mode B.W. 20 MHz										
Set-up No.:		1										
Op. Mode:		1										
Diagram no.	Channel no.	Restricted band ?	Fundamental Value [dBuV/m]		Value at Band-Edge [dBuV/m]		Limits [dBuV/m]		Margin [dB]		Verdict	Remark: Mode-B.W.-Data Rate-Power
			Peak -Value	Average -Value + Duty Cycle Correction	Peak -Value	Average -Value + Duty Cycle Correction	Peak -Value	Average -Value	Peak	Average		
9.31	5180	YES	106,93	99,36	60,23	44,40	74,00	54,00	13,77	9,60	PASS	a-Mode-20 MHz-6Mbit+20dBm
9.32	5320	YES	106,05	98,19	58,30	43,77	74,00	54,00	15,70	10,23	PASS	a-Mode-20 MHz-6Mbit+20dBm
Remark 1: For further details please refer → Annex 1: Test results - CETECOM_TR17-1-0180901T16a-A1 Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm Remark 3: Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor												

Technology:		WLAN 5 GHz 802.11n Mode B.W. 20 MHz										
Set-up No.:		1										
Op. Mode:		1										
Diagram no.	Channel no.	Restricted band ?	Fundamental Value [dBuV/m]		Value at Band-Edge [dBuV/m]		Limits [dBuV/m]		Margin [dB]		Verdict	Remark: Mode-B.W.-Data Rate-Power
			Peak -Value	Average -Value + Duty Cycle Correction	Peak -Value	Average -Value + Duty Cycle Correction	Peak -Value	Average -Value	Peak	Average		
9.35	5180	YES	102,41	94,36	56,33	42,25	74,00	54,00	17,68	11,75	PASS	n-Mode-20 MHz-MCS0+20dBm
9.38	5320	YES	106,43	98,53	59,80	43,15	74,00	54,00	14,20	10,85	PASS	n-Mode-20 MHz-MCS0+20dBm
Remark 1: For further details please refer → Annex 1: Test results - CETECOM_TR17-1-0180901T16a-A1 Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm Remark 3: Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor												

Technology:	WLAN 5 GHz 802.11n Mode B.W. 40 MHz
Set-up No.:	1
Op. Mode:	1

Diagram no.	Channel no.	Restricted band ?	Fundamental Value [dBuV/m]		Value at Band-Edge [dBuV/m]		Limits [dBuV/m]		Margin [dB]		Verdict	Remark: Mode-B.W.-Data Rate-Power
			Peak -Value	Average -Value + Duty Cycle Correction	Peak -Value	Average -Value + Duty Cycle Correction	Peak -Value	Average -Value	Peak	Average		
9.43	5190	YES	98,58	91,77	59,23	48,57	74,00	54,00	14,77	5,43	PASS	n-Mode-40 MHz-MCS0+20dBm
9.44	5310	YES	101,08	92,69	61,10	47,34	74,00	54,00	12,90	6,66	PASS	n-Mode-40 MHz-MCS0+20dBm

Remark 1: For further details please refer → Annex 1: Test results - CETECOM\_TR17-1-0180901T16a-A1  
 Remark 2: Measurements results are only valid and compliant with power setting: +20 dBm  
 Remark 3: Please refer Chapter 5.1 for applicable Duty-Cycle Correction Factor

#### 5.6.7. Verdict: Pass

## 5.7. Measurement uncertainties

The reported uncertainties are calculated based on the standard uncertainty multiplied with the appropriate coverage factor **k**, such that a confidence level of approximately 95% is achieved.

For uncertainty determination, each component used in the concrete measurement set-up was taken in account and it's contribution to the overall uncertainty according it's statistical distribution calculated.

Following table shows expectable uncertainties for each measurement type performed.

RF-Measurement	Reference	Frequency range	Calculated uncertainty based on a confidence level of 95%							Remarks
Conducted emissions (U <sub>CISPR</sub> )	CISPR 16-2-1	9 kHz - 150 kHz 150 kHz - 30 MHz	4.0 dB 3.6 dB							-
Radiated emissions Enclosure	CISPR 16-2-3	30 MHz - 1 GHz 1 GHz - 18 GHz	4.2 dB 5.1 dB							E-Field
Disturbance power	CISPR 16-2-2	30 MHz - 300 MHz	-							-
Power Output radiated	-	30 MHz - 4 GHz	3.17 dB							Substitution method
Power Output conducted	-	Set-up No.	Cel-C1	Cel-C2	BT1	W1	W2	--	-	
		9 kHz - 12.75 GHz	N/A	0.60	0.7	0.25	N/A	--		
		12.75 - 26.5GHz	N/A	0.82	--	N/A	N/A	--		
Conducted emissions on RF-port	-	9 kHz - 2.8 GHz	0.70	N/A	0.70	N/A	0.69	--	N/A - not applicable	
		2.8 GHz - 12.75GHz	1.48	N/A	1.51	N/A	1.43	--		
		12.75 GHz - 18GHz	1.81	N/A	1.83	N/A	1.77	--		
		18 GHz - 26.5GHz	1.83	N/A	1.85	N/A	1.79	--		
Occupied bandwidth	-	9 kHz - 4 GHz	0.1272 ppm (Delta Marker)							Frequency error
			1.0 dB							Power
Emission bandwidth	-	9 kHz - 4 GHz	0.1272 ppm (Delta Marker)							Frequency error
	-		See above: 0.70 dB							Power
Frequency stability	-	9 kHz - 20 GHz	0.0636 ppm							-
Radiated emissions Enclosure	-	150 kHz - 30 MHz	5.0 dB							Magnetic field E-field Substitution
		30 MHz - 1 GHz	4.2 dB							
		1 GHz - 20 GHz	3.17 dB							

**Table: measurement uncertainties, valid for conducted/radiated measurements**

## 6. Abbreviations used in this report

The abbreviations	
ANSI	American National Standards Institute
AV, AVG, CAV	Average detector
EIRP	Equivalent isotropically radiated power, determined within a separate measurement
EGPRS	Enhanced General Packet Radio Service
EUT	Equipment Under Test
FCC	Federal Communications Commission, USA
IC	Industry Canada
n.a.	not applicable
Op-Mode	Operating mode of the equipment
PK	Peak
RBW	resolution bandwidth
RF	Radio frequency
RSS	Radio Standards Specification, Documents from Industry Canada
Rx	Receiver
TCH	Traffic channel
Tx	Transmitter
QP	Quasi peak detector
VBW	Video bandwidth
ERP	Effective radiated power

## 7. Accreditation details of CETECOM's laboratories and test sites

Ref.-No.	Accreditation Certificate	Valid for laboratory area or test site	Accreditation Body
-	D-PL-12047-01-01	All laboratories and test sites of CETECOM GmbH, Essen	DAkkS, Deutsche Akkreditierungsstelle GmbH
337 487 558 348 348	(MRA US-EU 0003)	Radiated Measurements 30 MHz to 1 GHz, 3 m / 10 m (OATS) Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements above 1 GHz, 3 m (FAR) Mains Ports Conducted Interference Measurements Telecommunication Ports Conducted Interference Measurement.	FCC, Federal Communications Commission Laboratory Division, USA
337 487 550 558	3462D-1 3462D-2 3462D-2 3462D-3	Radiated Measurements 30 MHz to 1 GHz, 3 m / 10 m (OATS) Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements 1 GHz to 6 GHz, 3 m (SAR) Radiated Measurements above 1 GHz, 3 m (FAR)	IC, Industry Canada Certification and Engineering Bureau
487 550 348 348	R-2666 G-301 C-2914 T-1967	Radiated Measurements 30 MHz to 1 GHz, 3 m (SAR) Radiated Measurements 1 GHz to 6 GHz, 3 m (SAR) Mains Ports Conducted Interference Measurements Telecommunication Ports Conducted Interference Measurement.	VCCI, Voluntary Control Council for Interference by Information Technology Equipment, Japan
OATS = Open Area Test Site, SAR = Semi Anechoic Room, FAR = Fully Anechoic Room			

## 8. Instruments and Ancillary

### TC”

The “Ref.-No” in the left column of the following tables allows the clear identification of the laboratory equipment.

#### 8.1.1. Test software and firmware of equipment

Ref.-No.	Equipment	Type	Serial-No.	Version of Firmware or Software during the test
001	EMI Test Receiver	ESS	825132/017	Firm.= 1.21 , OTP=2.0, GRA=2.0
012	Signal Generator (EMS-cond.)	SMY 01	839069/027	Firm.= V 2.02
013	Power Meter (EMS cond.)	NRVD	839111/003	Firm.= V 1.51
017	Digital Radiocommunication Tester	CMD 60 M	844365/014	Firmware = V 3.52 .22.01.99, DECT = D2.87 13.01.99
053	Audio Analyzer	UPA3	860612/022	Firm. V 4.3
119	RT Harmonics Analyzer dig. Flickermeter	B10	G60547	Firm.= V 3.1DHG
140	Signal Generator	SMHU	831314/006	Firm.= 3.21
261	Thermal Power Sensor	NRV-Z55	825083/0008	EPROM-Datum 02.12.04, SE EE 1 B
262	Power Meter	NRV-S	825770/0010	Firm.= 2.6
263	Signal Generator	SMP 04	826190/0007	Firm.=3.21
295	Racal Digital Radio Test Set	6103	1572	UNIT Firmware= 4.04, SW-Main=4.04, SW-BBP=1.04, SW-DSP=1.02, Hardboot=1.02, Softboot=2.02
298	Univ. Radio Communication Tester	CMU 200	832221/091	R&S Test Firmware =3.53 /3.54 (current Testsoftw. f. all band used
323	Digital Radiocommunication Tester	CMD 55	825878/0034	Firm.= 3.52 .22.01.99
335	CTC-EMS-Conducted	System EMS Conducted	-	EMC 32 V 8.52
340	Digital Radiocommunication Tester	CMD 55	849709/037	Firm.= 3.52 .22.01.99
355	Power Meter	URV 5	891310/027	Firm.= 1.31
365	10V Insertion Unit 50 Ohm	URV5-Z2	100880	Eprom Data = 31.03.08
366	Ultra Compact Simulator	UCS 500 M4	V0531100594	Firm. UCS 500=001925/3.06a02, rc=ISMIEC 4.10
371	Bluetooth Tester	CBT32	100153	CBT V5.30+ SW-Option K55, K57
377	EMI Test Receiver	ESCS 30	100160	Firm.= 2.30, OTP= 02.01, GRA= 02.36
378	Broadband RF Field Monitor	RadiSense III	03D00013SNO-08	Firm.= V.03D13
389	Digital Multimeter	Keithley 2000	0583926	Firm. = A13 (Mainboard) A02 (Display)
392	Radio Communication Tester	MT8820A	6K00000788	Firm.= 4.50 #005, IPL=4.01#001, OS=4.02#001, GSM=4.41#013, W-CDMA= 4.54#004, scenario= 4.52#002
436	Univ. Radio Communication Tester	CMU 200	103083	R&S Test Firmware Base=5.14, Mess-Software= GSM:5.14 WCDMA:5.14 (current Testsoftw. F. all band
441	CTC-SAR-EMI Cable Loss	System EMI field (SAR)	-	EMC 32 Version 8.52
442	CTC-SAR-EMS	System EMS field (SAR)	-	EMC 32 Version 8.40
443	CTC-FAR-EMI-RSE	System CTC-FAR-EMI-RSE	-	Spuri 7.2.5 or EMC 32 Ver. 9.15.00
444	CTC-FAR-EMS field	System-EMS-Field (FAR)	-	EMC 32 Version 9.15.00
460	Univ. Radio Communication Tester	CMU 200	108901	R&S Test Firmware Base=5.14, GSM=5.14 WCDMA=5.14 (current Testsoftw..f. all band to be used,
489	EMI Test Receiver	ESU40	1000-30	Firmware=4.43 SP3, Bios=V5.1-16-3, Spec. =01.00
491	ESD Simulator dito	ESD dito	dito307022	V 2.30
524	Voltage Drop Simulator	VDS 200	0196-16	Software Nr. 000037 Version V4.20a01
526	Burst Generator	EFT 200 A	0496-06	Software Nr. 000034 Version V2.32
527	Micro Pulse Generator	MPG 200 B	0496-05	Software-Nr. 000030 Version V2.43
528	Load Dump Simulator	LD 200B	0496-06	Software-Nr. 000031 Version V2.35a01
546	Univ. Radio Communication Tester	CMU 200	106436	R&S Test Firmware Base=5.14, GSM=5.14 WCDMA=5.14 (current Testsoftw..f. all band to be used
547	Univ. Radio Communication Tester	CMU 200	835390/014	R&S Test Firmware Base=V5.1403 (current Testsoftw., f. all band used, GSM = 5.14 WCDMA: = 5.14
584	Spectrum Analyzer	FSU 8	100248	2.82_SP3
597	Univ. Radio Communication Tester	CMU 200	100347	R&S Test Firmware Base=5.01, GSM=5.02 WCDMA= not installed, Mainboard= µP1=V.850
598	Spectrum Analyzer	FSEM 30	831259/013	Firmware Bios 3.40 , Analyzer 3.40 Sp 2
607	Signal Generator	SMR 20	832033/011	V1.25
620	EMI Test Receiver	ESU 26	100362	4.43_SP3
642	Wideband Radio Communication Tester	CMW 500	126089	Setup V03.26, Test programm component V03.02.20
670	Univ. Radio Communication Tester	CMU 200	106833	µP1 =V8.50, Firmware = V.20
689	Vector Signal Generator	SMU200	100970	02.20.360.142
692	Bluetooth Tester	CBT 32	100236	CBT V 5.40, FW: V.2.41 (FPGA Digital, V. 3.09 FPGA RF)

### 8.1.2. Single instruments and test systems

Ref.-No.	Equipment	Type	Serial-No.	Manufacturer	Interval of calibration	Remark	Cal due
001	EMI Test Receiver	ESS	825132/017	Rohde & Schwarz	12 M	-	16.05.2018
005	AC - LISN (50 Ohm/50µH, test site 1)	ESH2-Z5	861741/005	Rohde & Schwarz	12 M	-	15.05.2018
007	Single-Line V-Network (50 Ohm/5µH)	ESH3-Z6	892563/002	Rohde & Schwarz	12 M	-	17.05.2018
009	Power Meter (EMS-radiated)	NRV	863056/017	Rohde & Schwarz	24 M	-	15.05.2019
016	Line Impedance Simulating Network	Op. 24-D	B6366	Spitzenberger+Spies	36 M	-	30.05.2019
021	Loop Antenna (H-Field)	6502	9206-2770	EMCO	36 M	-	30.04.2018
030	Loop Antenna (H-field)	HFH-Z2	879604/026	Rohde & Schwarz	36 M	-	30.04.2018
033	RF-current probe (100kHz-30MHz)	ESH2-Z1	879581/18	Rohde & Schwarz	24 M	-	15.05.2019
057	relay-switch-unit (EMS system)	RSU	494440/002	Rohde & Schwarz	pre-m	1a	
060	power amplifier (DC-2kHz)	PAS 5000	B6363	Spitzenberger+Spies	-	3	
086	DC - power supply, 0 -10 A	LNG 50-10	-	Heinzinger Electronic	pre-m	2	
087	DC - power supply, 0 -5 A	EA-3013 S	-	Elektro Automatik	pre-m	2	
091	USB-LWL-Converter	OLS-1	007/2006	Ing. Büro Scheiba	-	4	
099	passive voltage probe	ESH2-Z3	299.7810.52	Rohde & Schwarz	36 M	-	30.04.2018
100	passive voltage probe	Probe TK 9416	without	Schwarzbeck	36 M	-	30.04.2018
110	USB-LWL-Converter	OLS-1	-	Ing. Büro Scheiba	-	4	
119	RT Harmonics Analyzer dig. Flickermeter	B10	G60547	BOCONSULT	36 M	-	30.05.2019
133	horn antenna 18 GHz (Meas 1)	3115	9012-3629	EMCO	36 M	1c	10.03.2020
134	horn antenna 18 GHz (Subst 2)	3115	9005-3414	EMCO	36 M	-	10.03.2020
136	adjustable dipole antenna (Dipole 1)	3121C-DB4	9105-0697	EMCO	36 M	-	30.04.2018
140	Signal Generator	SMHU	831314/006	Rohde & Schwarz	24 M	-	30.05.2018
248	attenuator	SMA 6dB 2W	-	Radiall	pre-m	2	
249	attenuator	SMA 10dB 10W	-	Radiall	pre-m	2	
252	attenuator	N 6dB 12W	-	Radiall	pre-m	2	
256	attenuator	SMA 3dB 2W	-	Radiall	pre-m	2	
257	hybrid	4031C	04491	Narda	pre-m	2	
260	hybrid coupler	4032C	11342	Narda	pre-m	2	
261	Thermal Power Sensor	NRV-Z55	825083/0008	Rohde & Schwarz	24 M	-	30.05.2018
262	Power Meter	NRV-S	825770/0010	Rohde & Schwarz	24 M	-	30.05.2018
263	Signal Generator	SMP 04	826190/0007	Rohde & Schwarz	36 M	-	30.05.2019
265	peak power sensor	NRV-Z33, Model 04	840414/009	Rohde & Schwarz	24 M	-	30.05.2018
266	Peak Power Sensor	NRV-Z31, Model 04	843383/016	Rohde & Schwarz	24 M	-	30.05.2018
267	notch filter GSM 850	WRCA 800/960-6EEK	9	Wainwright GmbH	pre-m	2	
270	termination	1418 N	BB6935	Weinschel	pre-m	2	
271	termination	1418 N	BE6384	Weinschel	pre-m	2	
272	attenuator (20 dB) 50 W	Model 47	BF6239	Weinschel	pre-m	2	
273	attenuator (10 dB) 100 W	Model 48	BF9229	Weinschel	pre-m	2	
274	attenuator (10 dB) 50 W	Model 47 (10 dB) 50 W	BG0321	Weinschel	pre-m	2	
275	DC-Block	Model 7003 (N)	C5129	Weinschel	pre-m	2	
276	DC-Block	Model 7006 (SMA)	C7061	Weinschel	pre-m	2	
279	power divider	1515 (SMA)	LH855	Weinschel	pre-m	2	
298	Univ. Radio Communication Tester	CMU 200	832221/091	Rohde & Schwarz	pre-m	3	
300	AC LISN (50 Ohm/50µH, 1-phase)	ESH3-Z5	892 239/020	Rohde & Schwarz	12 M	-	17.05.2018
301	attenuator (20 dB) 50W, 18GHz	47-20-33	AW0272	Lucas Weinschel	pre-m	2	
302	horn antenna 40 GHz (Meas 1)	BBHA9170	155	Schwarzbeck	36 M	-	14.03.2020
303	horn antenna 40 GHz (Subst 1)	BBHA9170	156	Schwarzbeck	36 M	-	20.03.2020
331	Climatic Test Chamber -40/+180 Grad	HC 4055	43146	Heraeus Vötsch	24 M	-	30.10.2018
341	Digital Multimeter	Fluke 112	81650455	Fluke	24 M	-	30.05.2018
342	Digital Multimeter	Voltcraft M-4660A	IB 255466	Voltcraft	24 M	-	17.05.2019
347	laboratory site	radio lab.	-	-	-	5	
348	laboratory site	EMI conducted	-	-	-	5	
354	DC - Power Supply 40A	NGPE 40/40	448	Rohde & Schwarz	pre-m	2	
355	Power Meter	URV 5	891310/027	Rohde & Schwarz	24 M	-	30.05.2018
357	power sensor	NRV-Z1	861761/002	Rohde & Schwarz	24 M	-	24.05.2019
371	Bluetooth Tester	CBT32	100153	R&S	36 M	-	30.05.2019
373	Single-Line V-Network (50 Ohm/5µH)	ESH3-Z6	100535	Rohde & Schwarz	12 M	-	17.05.2018
377	EMI Test Receiver	ESCS 30	100160	Rohde & Schwarz	12 M	-	15.05.2018
392	Radio Communication Tester	MT8820A	6K00000788	Anritsu	12 M	-	18.05.2018
405	Thermo-/Hygrometer	OPUS 10 THI	126.0604.0003.3.3.3.2	LUFFT Mess u. Regeltechnik	24 M	-	30.03.2019
431	Model 7405	Near-Field Probe Set	9305-2457	EMCO	-	4	
436	Univ. Radio Communication Tester	CMU 200	103083	Rohde & Schwarz	12 M	-	24.05.2018
439	UltraLog-Antenna	HL 562	100248	Rohde & Schwarz	36 M	-	10.03.2020
454	Oscilloscope	HM 205-3	9210 P 29661	Hameg	-	4	
456	DC-Power supply 0-5 A	EA 3013 S	207810	Elektro Automatik	pre-m	2	
459	DC -Power supply 0-5 A , 0-32 V	EA-PS 2032-50	910722	Elektro Automatik	pre-m	2	
460	Univ. Radio Communication Tester	CMU 200	108901	Rohde & Schwarz	12 M	-	16.06.2018
463	Universal source	HP3245A	2831A03472	Agilent	-	4	
466	Digital Multimeter	Fluke 112	89210157	Fluke USA	24 M	-	30.05.2018



Ref.-No.	Equipment	Type	Serial-No.	Manufacturer	Interval of calibration	Remark	Cal due
467	Digital Multimeter	Fluke 112	89680306	Fluke USA	36 M	-	30.04.2018
468	Digital Multimeter	Fluke 112	90090455	Fluke USA	36 M	-	30.04.2018
477	ReRadiating GPS-System	AS-47	-	Automotive Cons. Fink	-	3	
480	power meter (Fula)	NRVS	838392/031	Rohde & Schwarz	24 M	-	16.05.2019
482	filter matrix	Filter matrix SAR 1	-	CETECOM (Brl)	-	1d	
487	System CTC NSA-Verification SAR-EMI	System EMI field (SAR) NSA	-	ETS Lindgren / CETECOM	24 M	-	31.03.2019
489	EMI Test Receiver	ESU40	1000-30	Rohde & Schwarz	12 M	-	18.05.2019
502	band reject filter	WRCG 1709/1786-1699/1796-	SN 9	Wainwright	pre-m	2	
503	band reject filter	WRCG 824/849-814/859-	SN 5	Wainwright	pre-m	2	
512	notch filter GSM 850	WRCA 800/960-02/40-6EEK	SN 24	Wainwright	12 M	1c	30.06.2017
517	relais switch matrix	HF Relais Box Keithley	SE 04	Keithley	pre-m	2	
523	Digital Multimeter	L4411A	MY46000154	Agilent	24 M	-	18.05.2019
529	6 dB Broadband resistive power divider	Model 1515	LH 855	Weinschel	pre-m	2	
530	10 dB Broadband resistive power divider	R 416110000	LOT 9828	-	pre-m	2	
546	Univ. Radio Communication Tester	CMU 200	106436	R&S	12 M	-	30.03.2018
547	Univ. Radio Communication Tester	CMU 200	835390/014	Rohde & Schwarz	12 M	-	05.07.2018
549	Log.Per-Antenna	HL025	1000060	Rohde & Schwarz	36/12 M	-	31.07.2018
550	System CTC S-VSWR Verification SAR-EMI	System EMI Field SAR S-VSWR	-	ETS Lindgren/CETECOM	24 M	-	30.03.2019
558	System CTC FAR S-VSWR	System CTC FAR S-VSWR	-	CTC	24 M	-	08.08.2019
574	Biconilog Hybrid Antenna	BTA-L	980026L	Frankonia	36/12 M	-	31.03.2019
584	Spectrum Analyzer	FSU 8	100248	Rohde & Schwarz	pre-m	-	
597	Univ. Radio Communication Tester	CMU 200	100347	Rohde & Schwarz	pre-m	-	
600	power meter	NRVD (Reserve)	834501/018	Rohde & Schwarz	24 M	-	17.05.2019
601	medium-sensitivity diode sensor	NRV-Z5 (Reserve)	8435323/003	Rohde & Schwarz	24 M	-	15.05.2019
602	peak power sensor	NRV-Z32 (Reserve)	835080	Rohde & Schwarz	24 M	-	
611	DC power supply	E3632A	KR 75305854	Agilent	pre-m	2	
612	DC power supply	E3632A	MY 40001321	Agilent	pre-m	2	
613	Attenuator	R416120000 20dB 10W	Lot. 9828	Radiall	pre-m	2	
616	Digitalmultimeter	Fluke 177	88900339	Fluke	24 M	-	30.05.2018
617	Power Splitter/Combiner	ZFSC-2-2-S+	S F987001108	Mini Circuits	-	2	
618	Power Splitter/Combiner	50PD-634	600994	JFW Industries USA	-	2	
619	Power Splitter/Combiner	50PD-634	600995	JFW Industries, USA	-	3	
620	EMI Test Receiver	ESU 26	100362	Rohde-Schwarz	12 M	-	16.05.2018
621	Step Attenuator 0-139 dB	RSP	100017	Rohde & Schwarz	pre-m	2	
625	Generic Test Load USB	Generic Test Load USB	-	CETECOM	-	2	
627	data logger	OPUS 1	201.0999.9302.6.4.1.4 3	G. Lufft GmbH	24 M	-	30.03.2019
634	Spectrum Analyzer	FSM (HF-Unit)	826188/010	Rohde & Schwarz	pre-m	2	
637	High Speed HDMI with Ethernet 1m	HDMI cable with Ethernet 1m	-	Kogilink	-	2	
638	HDMI Kabel with Ethernet 1,5 m flach	HDMI cable with Ethernet	-	Reichelt	-	2	
640	HDMI cable 2m rund	HDMI cable 2m rund	-	Reichelt	-	2	
641	HDMI cable with Ethernet	Certified HDMI cable with	-	PureLink	-	2	
642	Wideband Radio Communication Tester	CMW 500	126089	Rohde&Schwarz	12 M	-	24.05.2018
644	Amplifier	ZX60-2534M+	SN865701299	Mini-Circuits	-	-	
670	Univ. Radio Communication Tester	CMU 200	106833	Rohde & Schwarz	24 M	-	30.05.2018
671	DC-power supply 0-5 A	EA-3013S	-	Elektro Automatik	pre-m	2	
678	Power Meter	NRP	101638	Rohde&Schwarz	pre-m	-	
683	Spectrum Analyzer	FSU 26	200571	Rohde & Schwarz	12 M	-	17.05.2018
686	Field Analyzer	EHP-200A	160WX30702	Narda Safety Test Solutions	24 M	-	29.03.2019
687	Signal Generator	SMF 100A	102073	Rohde&Schwarz	12 M	-	17.05.2018
688	Pre Amp	JS-18004000-40-8P	1750117	Miteq	pre-m	-	
690	Spectrum Analyzer	FSU	100302/026	Rohde&Schwarz	12 M	-	16.05.2018
691	OSP120 Base Unit	OSP120	101183	Rohde & Schwarz	12 M	-	22.05.2018
692	Bluetooth Tester	CBT 32	100236	Rohde & Schwarz	36 M	-	29.05.2020
697	Power Splitter	ZN4PD-642W-S+	165001445	Mini-Circuits	-	2	
703	INNCO Antennen Mast	MA 4010-KT080-XPET-ZSS3	MA4170-KT100-XPET-	INNCO	pre-m	-	
704	INNCON Controllor	CO 3000-4port	CO3000/933/3841051 6/L	INNCO Systems GmBh	pre-m	-	
711	Harmonic Mixer 90 GHz - 140GHz	RPG FS-Z140	101004	RPG	12 M	-	22.02.2018
712	Harmonic Mixer 75 GHz - 110GHz	FS-Z110	101468	Rohde & Schwarz	12 M	-	22.02.2018
713	Harmonic Mixer, 50 GHz - 75GHz	FS-Z75	101022	Rohde & Schwarz	12 M	-	22.05.2018
714	Signal Analyzer 67GHz	FSW67	104023	Rohde & Schwarz	24 M	-	03.03.2019
715	Harmonic Mixer, 140 GHz - 220GHz	FS-Z220	101009	RPG Radiometer Physics	12 M	-	03.08.2018
716	Harmonic Mixer 220 GHz to 325 GHZ	FS-Z325	101005	RPG Radiometer Physics	12 M	-	13.02.2018
747	Spectrum Analyzer	FSU 26	200152	Rohde & Schwarz	12 M	-	18.05.2018

Ref.-No.	Equipment	Type	Serial-No.	Manufacturer	Interval of calibration	Remark	Cal due
748	Pickett-Potter Horn Antenna	FH-PP 4060	010001	Radiometer Physiscs	-	-	
749	Pickett-potter Horn Antenna	FH-PP 60-90	010003	Radiometer Physics	-	-	
750	Pickett-Potter Horn Antenna	FH-PP 140-220	010011	Radiometer Physics	-	-	

### 8.1.3. Legend

Note / remarks	Calibrated during system calibration:
1a	System CTC-SAR-EMS (Ref.-No. 442)
1b	System-CTC-EMS-Conducted (Ref.-No. 335)
1c	System CTC-FAR-EMI-RSE (Ref.-No . 443)
1d	System CTC-SAR-EMI (Ref.-No . 441)
1e	System CTC-OATS (EMI radiated) (Ref.-No. 337)
1 f	System CTC-CTIA-OTA (Ref.-No . 420)
1 g	System CTC-FAR-EMS (Ref.-No . 444)
2	Calibration or equipment check immediately before measurement
3	Regulatory maintained equipment for functional check or support purpose
4	Ancillary equipment without calibration e.g. mechanical equipment or monitoring equipment
5	Test System

Interval of calibration	12 M	12 month
	24 M	24 month
	36 M	36 month
	24/12 M	Calibration every 24 months. between this every 12 months internal validation
	36/12 M	Calibration every 36 months. between this every 12 months internal validation
	Pre-m	Check before starting the measurement
	-	Without calibration

## 9. Versions of test reports (change history)

Version	Applied changes	Date of release
--	Initial release	2017-12-29
--	DFS remarks corrected	2018-02-26
--	--	--