Nebraska Center for Excellence in Electronics

4740 Discovery Drive Lincoln, NE 68521 Phone: 402-472-5880 Fax: 402-472-5881



## FCC ID: U4NNCLASS

# **RF Exposure Statement for U4NNSERIES:**

## **Notice in Installation Manual:**

FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 0.66cm (2.30 inches) between the radiator and your body.

## **RF Exposure Calculations:**

The following information provides the minimum separation distances for the two major antenna types used in this system.

### **Directional Antenna:**

The antenna is internal to the EUT and has a gain of at most 0dBi. The minimum separation distance is calculated from **FCC OET 65 Appendix B, Table 1B** Guidelines for General Population/Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain. The exposure limit for a transmitter operating at 902.78 MHz is found in mW/cm^2 using the equations f/1200. Since the operating frequency for channel 0 produced the lowest limit, that limit will be used in calculation. (902.78/1200 = 0.75mW/cm^2)

$$S = (Po * G) / (4 * Pi * r^2) \text{ or } r = SQRT [ (Po * G) / (4 * Pi * S) ]$$

Where  $S = 0.75 \text{ mW/cm}^2 \text{ for } 902.78 \text{ MHz}$ 

Where Po = 4.15 mW (Peak RF, 6.18dBm)

Where G = 1 (numeric equivalent to 0dBi antenna gain with 0.0 dB cable loss)

Where r = Minimum Safe Distance from antenna (cm)

For Po = 
$$4.15$$
mW,  $r = 0.66$ cm (  $2.30$  inches)

For a distance [r] of 20cm from this antenna, the field density  $S = 0.064 \text{ mW/cm}^2$ 

#### Notes:

- 1. The minimum safe distance is based on a conservative "worst case" prediction, i.e. using the formula shown above and no duty factor. In practice the minimum distance will be much shorter. (Ref. 2)
- 2. The minimum safe distance has been calculated for the maximum allowed Power Density (S) limit of 0.75 mW/cm<sup>2</sup> for the frequency 902.78 MHz for uncontrolled environments (Ref. 2).

#### References:

- 1. FCC Part 15, sub-clause 15.247 (b) (4) (i)
- 2. FCC OET Bulletin 65, Edition 97-01
- 3. FCC Supplement C to OET Bulletin 65, edition 01-01