

TEST REPORT For FCC

Test Report No. : 2008050014
Date of Issue : May 12, 2008
FCC ID : U5MIF-BT
Model/Type No. : IF-BT
Kind of Product : Bluetooth Interface
Applicant : BIXOLON Co., Ltd.
Applicant Address : A 502~508, Digital Empire Bldg, 980-3, Yeongtong-Dong,
Yeongtong-Gu, Suwon, Gyeonggi-Do, Korea 443-813
Manufacturer : BIXOLON Co., Ltd.
Manufacturer Address : A 502~508, Digital Empire Bldg, 980-3, Yeongtong-Dong,
Yeongtong-Gu, Suwon, Gyeonggi-Do, Korea 443-813
Contact Person : Chi Young, Ahn / Assistant Manager
Telephone : +82-31-218-5582
Received Date : May 01, 2008
Test period : Start : May 01, 2008 End : May 12, 2008
Test Results : ☒ In Compliance ☐ Not in Compliance


The test results presented in this report relate only to the object tested.

Tested by



Kyu-Chul, You
Test Engineer
Date: May 12, 2008

Reviewed by



Young-Joon, Park
Technical Manager
Date: May 12, 2008



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

REPORT REVISION HISTORY

Date	Revision	Page No
May 12, 2008	Issued (2008050014)	All

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.



CTK Co., Ltd.
The Prime Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
1.0 General Product Description	4
1.1 Tested Frequency	4
1.2 Tested Mode	4
1.3 Model Differences	5
1.4 Device Modifications	5
1.5 Peripheral Devices	5
1.6 Calibration Details of Equipment Used for Measurement	6
1.7 Test Facility.....	6
1.8 Laboratory Accreditations and Listings	6
2.0 Summary of tests	7
2.1 Technical Characteristic Test.....	8
2.1.1 Carrier Frequency Separation	8
2.1.2 Number of Hopping Frequencies	10
2.1.3 20 dB bandwidth	12
2.1.4 Time of Occupancy (Dwell Time)	14
2.1.5 Maximum peak Conducted Output Power.....	19
2.1.6 Band-edge.....	24
2.1.7 Field Strength of Emissions	32
2.1.8 AC Conducted Emissions.....	37
APPENDIX A – Test Equipment Used For Tests	40

1.0 General Product Description

Equipment model name : IF-BT

Serial number : Prototype

EUT condition : Pre-production, not damaged

Antenna type : Chip antenna Gain 1.79dBi

Frequency Range : 2402 ~ 2480 MHz(Bluetooth)

RF output power : 11.40 dBm Peak Conducted (GFSK)
: 11.29 dBm Peak Conducted (8-DPSK)

Number of channels : 79(Bluetooth)

Type of Modulation(Data Rate) : GFSK(1Mbps), DQPSK(2Mbps), 8-DPSK(3Mbps)

Duty cycle TX power : GFSK - 86% , 8-DPSK – 83%

Power Source : DC 5V

1.1 Tested Frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

1.2 Tested Mode

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Tested Ch	Modulation Technology	Modulation Type	Packet Type
Low,Mid, High	FHSS	GFSK	DH5
Low,Mid, High	FHSS	8-DPSK	DH5



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

1.3 Model Differences

Not applicable

1.4 Device Modifications

The following modifications were necessary for compliance:

Not applicable

1.5 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.	FCC ID or DoC
Notebook PC	DELL	LATITUDE D505	32775808960	DoC






1.6 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

1.7 Test Facility

The measurement facility is located at 386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.8 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	 93250
JAPAN	VCCI	10 meter Open Area Test Site and one conducted site.	 R-948, C-986
KOREA	MIC	EMI (10 meter Open Area Test Site and two conducted sites) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 No. 51, KR0025
International	KOLAS	EMC	 KOLAS KOREA LABORATORY ACCREDITATION SCHEME TESTING NO. 119
Europe	GLAS	EMC EN 55011, EN 55022, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 50130-4, EN 55024, EN 61204-3, EN 60601-1-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11	 TÜV No.13000796-02



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

2.0 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz	Conducted	C
15.247(a)	Number of Hopping Frequencies	> 75 hops		C
15.247(a)	20 dB Bandwidth	< 1 MHz		C
15.247	Dwell Time	< 0.4 seconds		C
15.247(b)	Transmitter Output Power	< 1Watt		C
15.247(d)	Conducted Spurious emission	> 20 dBc		C
15.247(d)	Band Edge	> 20 dBc		C
15.209	Field Strength of Harmonics	< 54 dBuV (at 3m)	Radiated	C
15.207	AC Conducted Emissions	EN 55022	Line Conducted	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The sample was tested according to the following specification:
- FCC Part 15.247, ANSI C63.4-2003

2.1 Technical Characteristic Test

2.1.1 Carrier Frequency Separation

Test Location

RF Test Room

Test Procedures

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled. After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 3 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 30 kHz ($\geq 1\%$ of the span) Sweep = auto

VBW = 30 kHz (\geq RBW) Detector function = peak

Trace = max hold




Figure 1 : Measurement setup for the carrier frequency separation

Limit

The EUT shall have hopping channel carrier frequencies separated minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Test Results

Data Rate : GFSK

Channel	Adjacent Hopping Channel Separation (kHz)	Two-third of 20dB bandwidth (kHz)	Minimum Bandwidth (kHz)	Result
2441MHz	996.0	626.67	25	Complies

Data Rate : 8-DPSK

Channel	Adjacent Hopping Channel Separation (kHz)	Two-third of 20dB bandwidth (kHz)	Minimum Bandwidth (kHz)	Result
2441MHz	1002.0	668.00	25	Complies

See next pages for actual measured spectrum plots.




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Carrier Frequency Separation Data Rate : GFSK



Data Rate : 8-DPSK



2.1.2 Number of Hopping Frequencies

Test Location

RF Test Room


Test Procedures

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

Frequency range 1: Start = 2389.5 MHz, Stop = 2439.5 MHz
 2: Start = 2439.5 MHz, Stop = 2489.5 MHz

Span = 50 MHz
RBW = 300 kHz ($\geq 1\%$ of the span)
VBW = 300 kHz (\geq RBW)
Trace = max hold
Sweep = auto
Detector function = peak



Limit

The EUT in the 2400-2483.5 MHz band shall use at least 75 channels.

Test Results

Total number of Hopping Channels	Result
79	Complies

See next pages for actual measured spectrum plots.





CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Number of Hopping Frequencies



2.1.3 20 dB bandwidth

Test Location

RF Test Room

Test Procedures

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels. After the trace being stable, Use the marker-to peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 2 MHz (approximately 2 or 3 times of the 20 dB bandwidth)


RBW = 30 kHz ($\geq 1\%$ of the span)

Sweep = auto

VBW = 30 kHz (\geq RBW)

Detector function = peak

Trace = max hold



Limit

The Transmitter shall have a maximum 20 dB bandwidth of 1 MHz.

Test Results

Data Rate : GFSK

Frequency (MHz)	Channel Number.	Measured Bandwidth (MHz)	Result
2441	39	0.940	Complies

Data Rate : 8-DPSK

Frequency (MHz)	Channel Number.	Measured Bandwidth (MHz)	Result
2441	39	1.256	Complies

See next pages for actual measured spectrum plots.(worst case)




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com


20 dB Bandwidth

Data Rate : GPSK



Date: 1.MAY.2008 12:47:44

Data Rate : 8-DPSK



Date: 1.MAY.2008 12:49:50

2.1.4 Time of Occupancy (Dwell Time)

Test Location

RF Test Room

Test Procedures

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

Span = zero


RBW = 1 MHz

Trace = max hold

VBW = 1 MHz (\geq RBW)

Detector function = peak

Sweep = as necessary to capture the entire dwell time per hopping channel



Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Results

Data Rate - GFSK

Channel Number	Channel Frequency (MHz)	Packet Type	Test Results	
			Dwell Time (ms)	Result
39	2441	DH 1	124.84	Complies
		DH 3	267.53	Complies
		DH 5	308.82	Complies

Data Rate – 8-DPSK

Channel Number	Channel Frequency (MHz)	Packet Type	Test Results	
			Dwell Time (ms)	Result
39	2441	DH 1	128.04	Complies
		DH 3	264.30	Complies
		DH 5	307.76	Complies

See next pages for actual measured spectrum plots.(Worst case)




CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Time of Occupancy for PACKET Type DH 1(GFSK)



Time of Occupancy for PACKET Type DH 3(GFSK)






CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Time of Occupancy for PACKET Type DH 5(GFSK)






CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Time of Occupancy for PACKET Type DH 1(8-DPSK)



Time of Occupancy for PACKET Type DH 3(8-DPSK)






CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Time of Occupancy for PACKET Type DH 5(8-DPSK)



2.1.5 Maximum peak Conducted Output Power

Test Location

RF Test Room

Test Procedures

The maximum peak conducted output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

Span = 5 MHz (approximately 5 times of the 20 dB bandwidth)


RBW = 1 MHz (greater than the 20 dB bandwidth of the emission being measured)

VBW = 1 MHz (\geq RBW)

Detector function = peak

Trace = max hold

Sweep = auto



Limit

 $< 1 \text{ W}$

Test Results

Data Rate : GFSK

Frequency (MHz)	Channel No.	Peak output power(dBm)	Peak output power(mW)	Result
2402	0	8.64	7.311	Complies
2441	39	10.01	10.023	Complies
2480	78	11.40	13.804	Complies

Data Rate : 8-DPSK

Frequency (MHz)	Channel No.	Peak output power(dBm)	Peak output power(mW)	Result
2402	0	7.73	5.929	Complies
2441	39	10.29	10.691	Complies
2480	78	11.29	13.459	Complies

See next pages for actual measured spectrum plots.





CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Maximum peak Conducted Output Power - GFSK








CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com



Maximum peak Conducted Output Power – 8-DPSK





CTK Co., Ltd.


The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com



2.1.6 Band-edge

Test Location

RF Test Room

Test Procedures

The bandwidth at 20 dB down from the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:

Center frequency = the highest, middle, and the lowest channels

RBW = 100 kHz


VBW = 100 kHz (\geq RBW)

Span = 100 MHz

Trace = max hold

Detector function = peak

Sweep = auto



Limit

> 20 dBc

Test Results

All conducted emission in any 100 kHz bandwidth outside of the spectrum band was at least 20 dB lower than the highest inband spectral density.
Therefore the applying equipment meets the requirement.
See next pages for actual measured spectrum plots.



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Band – edge (With Hopping) - GFSK





CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Band – edge (With Hopping) – 8-DPSK







CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Band – edge (Without Hopping) - GFSK





CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea



Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Band – edge (Without Hopping) – 8-DPSK



Band – edge (at 20 dB blow) – Low channel
Frequency Range = 30 MHz ~ 10th harmonic







CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Band – edge (at 20 dB blow) – Mid channel Frequency Range = 30 MHz ~ 10th harmonic







CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Band – edge (at 20 dB blow) – High channel Frequency Range = 30 MHz ~ 10th harmonic



2.1.7 Field Strength of Emissions

Test Location

☒ Testing was performed at a test distance of 3 meter Open Area Test Site

Test Procedures

The height of the measuring antenna was varied between 1 to 4 m and the table was rotated a full revolution in order to obtain maximum values of the electric field intensity. The measurement was made in both the vertical and horizontal polarization, and the maximum value is presented in the report.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 30 MHz ~ 10th harmonic


RBW = 120 kHz (30 MHz ~ 1 GHz) VBW ≥ RBW

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz

Detector function = Quasi-peak

Trace = max hold



Limit

- 15.209(a)

Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m
30-88	100**	40
88-216	150**	43.5
216-960	200**	46
Above 960	500	54

** Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Test Results

EUT	Bluetooth Interface	Measurement Detail	
Model	IF-BT	Frequency Range	Below 1000MHz
Channel	Normal linking	Detector function	Quasi-Peak

The requirements are:

☒ Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
810.50	33.9	12.1	Quasi-Peak

Test Data

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor		Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
				Antenna	Cable			
45.38	10.5	V	1.0	11.3	0.2	40.0	22.0	18.0
201.25	14.7	H	2.0	7.6	1.6	43.5	23.9	19.6
300.00	13.8	H	1.1	11.0	2.4	46.0	27.2	18.8
356.25	12.4	V	2.1	12.6	2.7	46.0	27.7	18.3
810.50	9.6	H	4.0	19.9	4.4	46.0	33.9	12.1
845.50	8.2	V	2.0	20.4	4.6	46.0	33.2	12.8

H : Horizontal, V : Vertical

Test Results

EUT	Bluetooth Interface	Measurement Detail	
Model	IF-BT	Frequency Range	1-25GHz
Channel	Channel 0 (GFSK)	Detector function	Average/Peak

The requirements are:

☒ Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4803.72	50.48/65.13	3.52/8.87	Average/Peak

Test Data

Frequency [MHz]	Reading A/P [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits/ Detector A/P [dBuV/m]	Result A/P [dBuV/m]	Margin A/P [dB]
				Antenna	Amp. Gain	Cable			
4803.72	44.28/58.93	H	4.0	33.7	34.8	7.3	54.0 /74.0	50.48/65.13	3.52/8.87

* No emissions were detected at a level greater than 20dB below limit

Remark :

1. We have tested three mode (X, Y, Z). The worst mode (X axis) for final test.
2. Test mode is GFSK and worst case was recorded.

Restricted band edge test data

Measured frequency range : 2310-2390 MHz, 2483.5-2500 MHz

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
				Antenna	Amp. Gain	Cable			
No emissions were detected at a level greater than 20dB below limit.									



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Test Results

EUT	Bluetooth Interface	Measurement Detail	
Model	IF-BT	Frequency Range	1-25GHz
Channel	Channel 39 (GFSK)	Detector function	Average/Peak

The requirements are:

☒ Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4881.99	51.52/64.44	2.48/9.56	Average/Peak

Test Data

Frequency [MHz]	Reading A/P [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits/ Detector A/P [dBuV/m]	Result A/P [dBuV/m]	Margin A/P [dB]
				Antenna	Amp.Gain	Cable			
4881.99	42.32/55.24	H	4.0	32.7	34.9	11.4	54.0 /74.0	51.52/64.44	2.48/9.56

* No emissions were detected at a level greater than 20dB below limit

Remark :

1. We have tested three mode (X, Y, Z). The worst mode (X axis) for final test.
2. Test mode is GFSK and worst case was recorded.



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

Test Results

EUT	Bluetooth Interface	Measurement Detail	
Model	IF-BT	Frequency Range	1-25GHz
Channel	Channel 78 (GFSK)	Detector function	Average/Peak

The requirements are:

☒ Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4959.97	51.90/64.70	2.10/9.30	Average/Peak

Test Data

Frequency [MHz]	Reading A/P [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits/ Detector A/P [dBuV/m]	Result A/P [dBuV/m]	Margin A/P [dB]
				Antenna	Amp. Gain	Cable			
4959.97	42.70/55.50	V	1.0	32.7	34.9	11.4	54.0 /74.0	51.90/64.70	2.10/9.30

* No emissions were detected at a level greater than 20dB below limit

Remark :

1. We have tested three mode (X, Y, Z). The worst mode (X axis) for final test.
2. Test mode is GFSK and worst case was recorded.

Restricted band edge test data

Measured frequency range : 2310-2390 MHz, 2483.5-2500 MHz

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor			Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
				Antenna	Amp. Gain	Cable			
No emissions were detected at a level greater than 20dB below limit.									



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea
Tel: +82-31-339-9970 Fax: +82-31-339-9855
www.e-ctk.com

2.1.8 AC Conducted Emissions

Test Location

Shielded Room

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Procedures

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit

- 15.207(a)

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency.

Test Results

The requirements are:

☒ Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
0.15	61.2	4.8	Quasi-peak



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

Test Data

Frequency [MHz]	Correction Factor		Line	Quasi-peak				Average			
				Limit	Reading	Result	Margin	Limit	Reading	Result	Margin
	LISN	Cable		[dBuV]	[dBuV]	[dBuV]	[dB]	[dBuV]	[dBuV]	[dBuV]	[dB]
0.15	0.1	0.4	H	66.0	60.7	61.2	4.8	56.0	28.2	28.7	27.3
0.17	0.1	0.4	H	65.0	56.3	56.8	8.2	55.0	41.9	42.4	12.6
0.25	0.1	0.4	N	61.8	48.6	49.1	12.7	51.8	38.2	38.7	13.1
0.29	0.1	0.4	N	60.5	47.9	48.4	12.1	50.5	44.2	44.7	5.8
0.30	0.1	0.6	H	60.2	47.8	48.5	11.7	50.2	44.3	45.0	5.2
16.51	0.6	0.9	H	60.0	49.5	51.0	9.0	50.0	37.3	38.8	11.2

H : HOT, N : NEUTRAL



CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance


CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea


Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

[HOT]



[NEUTRAL]





CTK Co., Ltd.
The Power Leader of Global Regulatory Compliance

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea

Tel: +82-31-339-9970 Fax: +82-31-339-9855

www.e-ctk.com

APPENDIX A – Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date
1	Spectrum Analyzer	Agilent	8564E	3551A0041	2008-11-01
2	Spectrum Analyzer	HP	E4403B	US39440619	2008-09-03
3	Spectrum Analyzer	Rohde & Schwarz	FSP-30	100994	2008-11-19
4	EMI Test Receiver	Rohde & Schwarz	ESVS30	826638/008	2008-05-30
5	ULTRA Broadband Antenna	Rohde & Schwarz	HL562	361324/014	2008-06-12
6	LOOP ANTENNA	EMCO	6502	9107-2652	2008-10-17
7	System Power Supply	HP	6032A	3440A-10521	2008-07-16
8	EPM Series Power Meter	HP	E4418A	GB38272734	2008-11-03
9	Power Sensor	HP	8481A	331BA92056	2008-11-03
10	Power Sensor	HP	8482B	331BA05406	2008-11-03
11	Audio Analyzer	HP	8903B	2747A03432	2008-11-01
12	ESG-D Series Signal Generator	Agilent	E4432B	US40054094	2008-11-01
13	SYNTHESIZED SWEEPER	HP	8341B	2819A01563	2008-11-22
14	Modulation Analyzer	HP	8901B	3438A05228	2008-11-08
15	Attenuator	HP	8494A	3308A33351	2008-11-06
16	Attenuator	HP	8496A	3308A15142	2008-11-06
17	Temp&Humi Chamber	Kunpoong	KP-1000	2002KP050041	2009-01-21
18	Temp&Humi Chamber	Kunpoong	KP-RC2000	2002KP650042	2009-01-21
19	EMC Analyzer	Agilent	E7403A	MY42000054	2008-10-22
20	Horn Antenna	ETS-Lindgren	3115	00078894	2008-11-29
21	Horn Antenna	ETS-Lindgren	3115	00078895	2008-11-29
22	Horn Antenna	ETS-Lindgren	3116	00062504	2008-11-27
23	Horn Antenna	ETS-Lindgren	3116	00062916	2008-11-27
24	Dipole Antenna	SCHWARZBECK	VHA 9103	VHA91032557	2009-11-27
25	Dipole Antenna	SCHWARZBECK	UHA 9105	UHA91052417	2009-11-27
26	OPT H64 AMPLIFIER	HP	8447F	3113A06814	2009-03-13
27	PREAMPLIFIER	Agilent	8449B	3008A02307	2008-11-05
28	Radio Communication Tester	Rohde & Schwarz	CMU200	106765	2009-02-14
29	Band Reject Filter	Wainwright Instruments	WRCG824	-	2009-04-01
30	Band Reject Filter	Wainwright Instruments	WRCG1750	-	2009-04-01
31	LISN	Rohde & Schwarz	ESH3-Z5	100207	2008-12-20
32	LISN	EMCO	3825/2	9206-1971	2008-12-20