

TEST REPORT For FCC

FCC Standards: FCC 47CFR part 15 subpart C

Test Report No.	:	CTK-2015-00133
rest report No.	•	CIN 2013 00133

Date of Issue 2015-02-05

FCC ID U5MSRP350IIOBE

Basic Model/Type No. SRP-35*IIOBEz

Kind of Product THERMAL RECEIPT PRINTER

Applicant BIXOLON Co., Ltd.

7th-8th FL, Miraeasset Venture Tower, 20, Pangyoyeok-ro **Applicant Address**

241beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea

Manufacturer BIXOLON Co., Ltd.

Manufacturer Address 7th-8th FL, Miraeasset Venture Tower, 20, Pangyoyeok-ro

241beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea

Contact Person Shin Ji Sung / Assistant Manager

+82-31-218-5582 Telephone

Received Date 2015-01-14 :

Test period Start: 2014-11-20 End: 2014-11-24

■ Not in Compliance Test Results

The test results presented in this report relate only to the object tested.

Tested by

Young-taek Lee Test Engineer Date: 2015-02-05 Reviewed by

Young-Joon, Park Technical Manager

Date: 2015-02-05

Test Report No.: CTK-2015-00133

Date: 2015-02-05

Page 1 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

REPORT REVISION HISTORY

Date	Revision	Page No
2015-02-05	Issued (CTK-2015-00133)	All

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

Test Report No.: CTK-2015-00133 Page 2 of 55



TABLE OF CONTENTS

REPORT	REVISION HISTORY	2
1.0	General Product Description	
1.1	Tested Frequency	
1.2	Tested Mode	4
1.3	Model Differences	
1.4	Device Modifications	5
1.5	Peripheral Devices	
1.6	Calibration Details of Equipment Used for Measurement	5
1.7	Test Facility	5
1.8	Laboratory Accreditations and Listings	6
2.0	Summary of tests	
2.1	Transmitter Requirements	
2.1.	1 Carrier Frequency Separation	8
2.1.	2 Number of Hopping Frequencies 1	0
2.1.		
2.1.	5 Maximum peak Conducted Output Power	25
2.1.	6 RF Conducted Emissions 3	30
2.1.	7 Field Strength of Emissions4	ŀ1
2.1.	8 AC Conducted Emissions5	50
APPEND	IX A – Test Equipment Used For Tests	55

Test Report No.: CTK-2015-00133 Date: 2015-02-05





1.0 General Product Description

Equipment model name	SRP-35*IIOBEz	
Serial number	Prototype	
EUT condition	Pre-production, not damaged	
Antenna type	Chip antenna Gain 0.55 dBi	
Frequency Range	2402 MHz - 2480 MHz	
RF power	8.00 dBm Peak Conducted (GFSK) 9.30 dBm Peak Conducted (8-DPSK)	
Type of Modulation	Frequency Hopping Spread Spectrum	
Number of channels	79	
Channel Spacing	1 MHz	
Channel Access Protocol	Frequency Hopping	
Type of Modulation GFSK(1Mbps), DQPSK(2Mbps), 8-DPSK(3Mbps)		
Power Source	AC/DC ADAPTER INPUT: 100-240V~, 1.5A OUTPUT: 24 VDC/2.5A	

1.1 Tested Frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2441	2480

1.2 Tested Mode

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Tested Ch	Modulation Technology	Modulation Type	Packet Type
Low, Mid, High	FHSS	GFSK	DH5
Low, Mid, High	FHSS	8-DPSK	3-DH5

Test Report No.: CTK-2015-00133 Page 4 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

1.3 Model Differences

Model(SRP-35*IIOBEz) is identical to each other only except for below chart.

'*' means a resolution and may be 0 or 2.

'z' means a buyer or optional function and may be blank or any alphanumeric.

1.4 Device Modifications

The following modifications were necessary for compliance:

Not applicable

1.5 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.
Personal Computer	Samsung Electronics Co.,Ltd.	DM-Z48	399F96BL503602X
LCD Monitor	Samsung Electronics Co.,Ltd.	LS19A350	-

1.6 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

1.7 Test Facility

The measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea.

Test Report No.: CTK-2015-00133 Page 5 of 55



Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Registration Number	Logo
USA	FCC	FCC Part 15 & 18 EMI (Electromagnetic Interference / Emission)	805871	H
JAPAN	VCCI	VCCI V-3 EMI (Electromagnetic Interference / Emission)	C-986 T-1843 R-3627 G-387	V€I
KOREA	MSIP	EMI (Electromagnetic Interference / Emission) EMS (Electromagnetic Susceptibility / Immunity)	KR0025	W

Test Report No.: CTK-2015-00133 Page 6 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

2.0 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	Carrier Frequency Separation	> 25 kHz		С
15.247(a)	Number of Hopping Frequencies	> 15 hops		С
15.247(a)	20 dB Bandwidth	NA		С
15.247(a)	Dwell Time	< 0.4 seconds	Conducted	С
15.247(b)	Transmitter Output Power	< 0.125 Watts		С
15.247(d)	Conducted Spurious emission	> 20 dBc		С
15.247(d)	Band Edge	> 20 dBc		С
15.209	Field Strength of Harmonics	15.209(a)	Radiated	С
15.207	AC Conducted Emissions	15.207(a)	Line Conducted	С

The sample was tested according to the following specification:

The tests were performed according to the method of measurements prescribed in DA 00-705.

Test Report No.: CTK-2015-00133 Page 7 of 55

⁻ FCC Part 15.247, ANSI C63.4-2009



2.1 Transmitter Requirements

2.1.1 Carrier Frequency Separation

Test Location

RF Test Room

Test Procedures

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

Span = 5 MHz (wide enough to capture the peaks of two adjacent channels)

RBW = 30 kHz (\geq 1% of the span) Sweep = auto

 $VBW = 30 \text{ kHz} (\geq RBW)$ Detector function = peak

Trace = max hold




Figure 1: Measurement setup for the carrier frequency separation

Limit

§15.247(a)(1) Frequency hopping system operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-third of 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Results

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Channel	Adjacent Hopping Channel Separation (kHz)	Two-third of 20dB bandwidth (kHz)	Minimum Bandwidth (kHz)	Result
2441MHz	1000	560.0	25	Complies

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

i cst illouc .	o bi sit, ci o i it i acite	L Type . Si I deket s	120 . 1021(30	<i>,</i>
	Adjacent Hopping	Two-third of 20dB	Minimum	
Channel	Channel Separation	bandwidth	Bandwidth	Result
	(kHz)	(kHz)	(kHz)	
2441MHz	1000	826.7	25	Complies

See next pages for actual measured spectrum plots.


Test Report No.: CTK-2015-00133 Page 8 of 55

Carrier Frequency Separation

Test mode: GFSK



Date: 22.JAN.2015 16:31:20



Date: 3.FEB.2015 14:03:20

Test Report No.: CTK-2015-00133 Page 9 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

2.1.2 Number of Hopping Frequencies

Test Location

RF Test Room

Test Procedures

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:


Frequency range 1: Start = 2389.5 MHz, Stop = 2439.5 MHz

2: Start = 2439.5 MHz, Stop = 2489.5 MHz

RBW = 300 kHz (\geq 1% of the span) Sweep = auto

VBW = 300 kHz (≥ RBW) Detector function = peak

Trace = max hold



Limit

§15.247(a)(1)(iii) For frequency hopping system operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.

Test Results

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Total number of Hopping Channels	Result
79	Complies


Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Total number of Hopping Channels	Result
79	Complies


See next pages for actual measured spectrum plots.

Test Report No.: CTK-2015-00133 Page 10 of 55

Number of Hopping Frequencies(GFSK)




Date: 22.JAN.2015 16:34:58




Date: 22.JAN.2015 16:36:22

Test Report No.: CTK-2015-00133 Page 11 of 55

Number of Hopping Frequencies(8-DPSK)



Date: 3.FEB.2015 14:10:06



Date: 3.FEB.2015 14:18:31

Test Report No.: CTK-2015-00133 Page 12 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

2.1.3 20 dB bandwidth

Test Location

RF Test Room

Test Procedures

The bandwidth at 20 dB below the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels. After the trace being stable, Use the marker-to peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = approximately 2 or 3 times of the 20 dB bandwidth

RBW = 30 kHz (\geq 1% of the 20 dB bandwidth) Sweep = auto

VBW = 30 kHz (≥ RBW) Detector function = peak

Trace = max hold

EUT _____ Spectrum Analyzer

Limit

Limit: N/A

Test Report No.: CTK-2015-00133 Page 13 of 55 Date: 2015-02-05



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

Test Results

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

1000 1110 40 1 01 011, 01 0 1 111 1 401100 1 ,		, pe : == : delite = == : 555 (2:15)		
Frequency (MHz)	Channel Number.	Measured Bandwidth (MHz)	Result	
2402	0	0.834	Complies	
2441	39	0.840	Complies	
2480	78	0.846	Complies	


Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

TOSC IIIOGC TO BIO	1 1011(55115)		
Frequency (MHz)	Channel Number.	Measured Bandwidth (MHz)	Result
2402	0	1.240	Complies
2441	39	1.240	Complies
2480	78	1.220	Complies


See next pages for actual measured spectrum plots.

Test Report No.: CTK-2015-00133 Page 14 of 55

20 dB Bandwidth - GFSK




Date: 22.JAN.2015 16:09:05



Date: 22.JAN.2015 16:07:19

Test Report No.: CTK-2015-00133 Page 15 of 55







Date: 22.JAN.2015 16:05:42

Test Report No.: CTK-2015-00133 Page 16 of 55 Date: 2015-02-05

20 dB Bandwidth - 8-DPSK




Date: 3.FEB.2015 14:23:15



Date: 3.FEB.2015 14:24:24

Test Report No.: CTK-2015-00133 Page 17 of 55





Date: 3.FEB.2015 14:25:45

Page 18 of 55 Test Report No.: CTK-2015-00133

Date: 2015-02-05 This Report shall not be reproduced except in full without the written approval of CTK

Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)



2.1.4 Time of Occupancy (Dwell Time)

Test Location

RF Test Room

Test Procedures

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3. Adjust the center frequency of spectrum analyzer on any frequency be measured and set spectrum analyzer to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- 4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- 5. Repeat above procedures until all frequencies measured were complete.
- 6. The SRP-35*IIOBEz has 3 type of payload, DH1, DH3, DH5. The hopping rate is 1600 per second.

The spectrum analyzer is set to:


Center frequency = the highest, middle, and the lowest channels

Span = zero

RBW = 1 MHz Trace = max hold

 $VBW = 1 MHz (\ge RBW)$ Detector function = peak

Sweep = as necessary to capture the entire dwell time per hopping channel



Limit

 $\S15.247(a)(1)(iii)$ For frequency hopping system operating in 2400-2483.5 MHz band, the average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Report No.: CTK-2015-00133 Page 19 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

Test Results

Time of occupancy on the TX channel in 31.6 sec = time domain slot length \times hop rate \div number of hop per channel \times 31.6

Test mode: GFSK

Channel	ncy Packet Type		Test Results		
Frequency (MHz)		Dwell Time (ms)	Time of occupancy on the TX channel in 31.6sec (ms)	Result	
	DH 1	0.440	140.80	Complies	
2402	DH 3	1.710	273.60	Complies	
	DH 5	2.950	314.67	Complies	

DH1 Dwell time = $0.440 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 140.80 \text{ ms}$ DH3 Dwell time = $1.710 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 273.60 \text{ ms}$ DH5 Dwell time = $2.950 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 314.67 \text{ ms}$

Test mode: 8-DPSK


1 COC INICAC I O DI OK					
Channel	v Packet Type DWell		Test Results		
Frequency (MHz)		Dwell Time (ms)	Time of occupancy on the TX channel in 31.6sec (ms)	Result	
	3DH 1	0.452	144.64	Complies	
2480	3DH 3	1.710	273.60	Complies	
	3DH 5	2.940	313.60	Complies	

DH1 Dwell time = $0.452 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 144.64 \text{ ms}$ DH3 Dwell time = $1.710 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 273.60 \text{ ms}$ DH5 Dwell time = $2.940 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 313.60 \text{ ms}$

See next pages for actual measured spectrum plots.


Test Report No.: CTK-2015-00133 Page 20 of 55

Time of Occupancy for PACKET Type DH1(GFSK)



Date: 22.JAN.2015 16:47:54


Time of Occupancy for PACKET Type DH3(GFSK)



Date: 22.JAN.2015 16:46:40

Test Report No.: CTK-2015-00133 Page 21 of 55 Date: 2015-02-05


Time of Occupancy for PACKET Type DH5(GFSK)



Date: 4.FEB.2015 13:01:23


Test Report No.: CTK-2015-00133 Page 22 of 55 Date: 2015-02-05

Time of Occupancy for PACKET Type 3DH1(8-DPSK)



Date: 3.FEB.2015 14:35:39

Time of Occupancy for PACKET Type 3DH3(8-DPSK)



Date: 3.FEB.2015 14:34:18


Test Report No.: CTK-2015-00133

Date: 2015-02-05

Page 23 of 55



Time of Occupancy for PACKET Type 3DH5(8-DPSK)



Date: 3.FEB.2015 14:32:38

Test Report No.: CTK-2015-00133 Page 24 of 55 Date: 2015-02-05



2.1.5 Maximum peak Conducted Output Power

Test Location

RF Test Room

Test Procedures

The maximum peak conducted output power was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:


Center frequency = the highest, middle, and the lowest channels

Span = approximately 5 times of the 20 dB bandwidth

RBW = 1 MHz (greater than the 20 dB bandwidth of the emission being measured)

 $VBW = 1 MHz (\ge RBW)$ Detector function = peak

Trace = \max hold Sweep = auto



Note:

The testing follows FCC Public Notice DA 00-705 Measurement Guidelines. The RF output of EUT was connected to the spectrum analyzer by low loss cable.

Limit

 $\S 5.247(b)(1)$ The Maximum Peak Output Power Measurement is 0.125 Watts for frequency hopping system operating in 2400-2483.5 MHz employing at least 15 Hopping channels.

Test Results

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency (MHz)	Channel No.	Peak output power(dBm)	Peak output power(mW)	Result
2402	0	7.85	6.10	Complies
2441	39	7.91	6.18	Complies
2480	78	8.00	6.31	Complies


Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency (MHz)	Channel No.	Peak output power(dBm)	Peak output power(mW)	Result
2402	0	9.05	8.04	Complies
2441	39	9.30	8.51	Complies
2480	78	8.93	7.82	Complies


See next pages for actual measured spectrum plots.

Test Report No.: CTK-2015-00133 Page 25 of 55

Maximum peak Conducted Output Power - GFSK




Date: 22.JAN.2015 15:56:40



Date: 22.JAN.2015 15:56:59

Test Report No.: CTK-2015-00133 Page 26 of 55







Date: 22.JAN.2015 15:57:33

Page 27 of 55 Test Report No.: CTK-2015-00133

Maximum peak Conducted Output Power - 8-DPSK




Date: 4.FEB.2015 16:28:46



Date: 4.FEB.2015 16:29:11

Test Report No.: CTK-2015-00133 Page 28 of 55





Date: 4.FEB.2015 16:29:43

Page 29 of 55 Test Report No.: CTK-2015-00133



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

2.1.6 RF Conducted Emissions

Test Location

RF Test Room

Test Procedures

The bandwidth at 20 dB down from the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:


Center frequency = the highest, middle, and the lowest channels

RBW = 100 kHz

 $VBW = 100 \text{ kHz} (\geq RBW)$

Span = 10 MHz Detector function = peak

Trace = \max hold Sweep = auto



Limit

> 20 dBc


Test Results

All conducted emission in any 100 kHz bandwidth outside of the spectrum band was at least 20 dB lower than the highest level of the inband spectral density. Therefore the applying equipment meets the requirement.


See next pages for actual measured spectrum plots.

Test Report No.: CTK-2015-00133 Page 30 of 55

Band - edge (Hopping mode) - GFSK




Date: 22.JAN.2015 16:27:15




Date: 22.JAN.2015 16:25:51

Test Report No.: CTK-2015-00133 Page 31 of 55

Band - edge (Hopping mode) - 8-DPSK




Date: 3.FEB.2015 13:51:39




Date: 3.FEB.2015 13:53:51

Test Report No.: CTK-2015-00133 Page 32 of 55

Band - edge (Non-Hopping mode) - GFSK




Date: 22.JAN.2015 16:28:20




Date: 22.JAN.2015 16:23:02

Test Report No.: CTK-2015-00133 Page 33 of 55

Band - edge (Non-Hopping mode) - 8-DPSK




Date: 3.FEB.2015 13:57:46




Date: 3.FEB.2015 13:54:37

Test Report No.: CTK-2015-00133 Page 34 of 55

Spurious (at 20 dB blow) - Low channel Frequency Range = 30 MHz ~ 10th harmonic (Test mode : GFSK)



Date: 22.JAN.2015 16:12:48



Date: 22.JAN.2015 16:14:24


Test Report No.: CTK-2015-00133

Date: 2015-02-05


Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)

Page 35 of 55

Spurious (at 20 dB blow) – Mid channel Frequency Range = 30 MHz $\sim 10^{th}$ harmonic (Test mode : GFSK)




Date: 22.JAN.2015 16:17:04




Date: 22.JAN.2015 16:17:39

Test Report No.: CTK-2015-00133

Spurious (at 20 dB blow) - High channel Frequency Range = 30 MHz ~ 10th harmonic (Test mode : GFSK)




Date: 22.JAN.2015 16:19:32




Date: 22.JAN.2015 16:20:04

Test Report No.: CTK-2015-00133 Date: 2015-02-05

Spurious (at 20 dB blow) – Low channel Frequency Range = 30 MHz \sim 10th harmonic (Test mode: 8-DPSK)




Date: 3.FEB.2015 18:43:41




Date: 3.FEB.2015 18:44:10

Test Report No.: CTK-2015-00133 Page 38 of 55

Spurious (at 20 dB blow) - Mid channel Frequency Range = 30 MHz ~ 10th harmonic (Test mode: 8-DPSK)




Date: 3.FEB.2015 18:47:07




Date: 3.FEB.2015 18:47:49

Test Report No.: CTK-2015-00133 Date: 2015-02-05

Spurious (at 20 dB blow) - High channel Frequency Range = 30 MHz ~ 10th harmonic (Test mode: 8-DPSK)



Date: 3.FEB.2015 18:53:37



Date: 3.FEB.2015 18:54:03

Test Report No.: CTK-2015-00133

Date: 2015-02-05

Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)

Page 40 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

2.1.7 Field Strength of Emissions

Test Location

 \boxtimes 10 m SAC (test distance : \square 10 m, \boxtimes 3 m) \boxtimes 3 m SAC (test distance : 3 m)

Test Procedures

- 1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency rage above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

The spectrum analyzer is set to:

Frequency Range = 9 kHz \sim 25 GHz (2.4 GHz 10^{th} harmonic) RBW = 1 MHz for f \geq 1 GHz, 100 kHz for f < 1 GHz, 9 kHz for f < 30 MHz VBW \geq RBW Sweep = auto

Test Report No.: CTK-2015-00133 Page 41 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

Limit

§ 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	MHz	GHz
0.09-0.11	8.37626-8.38675	73-74.6	399.9-410	2690-2900	10.6-12.7
¹ 0.495-0.505	8.41425-8.41475	74.8-75.2	608-614	3260-3267	13.25-13.4
2.1735-2.1905	12.29-12.293	108-121.94	960-1240	3332-3339	14.47-14.5
4.125-4.128	12.51975-12.52025	123-138	1300-1427	3345.8-3358	15.35-16.2
4.17725-4.17775	12.57675-12.57725	149.9-150.05	1435-1626.5	3600-4400	17.7-21.4
4.20725-4.20775	13.36-13.41	156.52475- 156.52525	1645.5-1646.5	4500-5150	22.01-23.12
6.215-6.218	16.42-16.423	156.7-156.9	1660-1710	5350-5460	23.6-24
6.26775-6.26825	16.69475-16.69525	162.0125-167.17	1718.8-1722.2	7250-7750	31.2-31.8
6.31175-6.31225	16.80425-16.80475	167.72-173.2	2200-2300	8025-8500	36.43-36.5
8.291-8.294	25.5-25.67	240-285	2310-2390	9000-9200	² Above 38.6
8.362-8.366	37.5-38.25	322-335.4	2483.5-2500	9300-9500	

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown is Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

Test Report No.: CTK-2015-00133 Page 42 of 55

² Above 38.6



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

§ 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency(MHz)	Field Strength	Field Strength	Deasurement
i requericy(MIIZ)	uV/m@3m	dBuV/m@3m	Distance (meters)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705-30	30	-	30
30-88	100**	40	3
88-216	150**	43.5	3
216-960	200**	46	3
Above 960	500	54	3

^{**} Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.

Note:

- 1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- 2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3m (AV) and 74 dBuV/m@3m (PK)
- 3) For measurement above 1GHz, the resolution bandwidth is set to 1 MHz and video bandwidth is set to 1 MHz for peak measurement and 10 Hz for average measurement.


Test Report No.: CTK-2015-00133 Page 43 of 55




(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

Test Setup:

1) For field strength of emissions from 9 kHz to 30 MHz



2) For field strength of emissions from 30 MHz to 1 GHz




Test Report No.: CTK-2015-00133



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

3) For field strength of emissions above 1 GHz



Test Results 1) 9 kHz to 30 MHz

EUT	EUT THERMAL RECEIPT PRINTER Measurement Detail						
Frequency Range		9 kHz – 30 MHz					
Test mode	GFSK (Worst case)	Detector function	Quasi-Peak				

The requirements are:

Frequency	Measured Data	Margin	Remark
(MHz)	(dBuV/m)	(dB)	
_	_	_	See note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB)

Test Report No.: CTK-2015-00133 Page 45 of 55

Date: 2015-02-05

Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

2) 30 MHz to 1 GHz


Test mode: Hopping(8DPSK), CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

	- F F 3 (- 7,	/	
EUT	THERMAL RECEIPT PRINTER	Measurement Detail	
Frequency	Range	Below 1000MHz	
Test mode	GFSK (Worst case)	Detector function	Quasi-Peak

The requirements are:

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
838.495	38.1	7.9	Quasi-Peak

Test Data



No.	Frequency	(P)	Reading QP	c.f	Result QP	Limit QP	Margin QP	Height	Angle
	[MHz]		[dB(uV)]	[dB(1/m)]	[dB(uV/m)]	[dB(uV/m)]	[dB]	[cm]	[deg]
1	240,005	Н	47.8	-10.6	37,2	46.0	8.8	100.0	47.0
2	292,749	Н	43.2	-9.3	33.9	46.0	12.1	100.0	196.0
3	417,636	V	39.3	-5.2	34.1	46.0	11.9	100.0	239.0
4	543,615	V	27.8	-2.1	25.7	46.0	20.3	305.0	52.0
5	546,525	Н	35.5	-2.0	33.5	46.0	12.5	400.0	239.0
6	838,495	Н	34.7	3.4	38,1	46.0	7.9	400.0	0.0

Remark:

- 1. The field strength of spurious emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
- 2. Result = Reading + Correction factor
- 3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator Amp Gain

Test Report No.: CTK-2015-00133 Page 46 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

3) above 1 GHz

EUT	THERMAL RECEIPT PRINTER	Measurement Detail	
Model	SRP-35*IIOBEz	Frequency Range	1-25GHz
Channel	Channel 0	Detector function	Peak

Remarks

We have tested three mode (X, Y, Z). The worst mode (Z axis) for final test.

The requirements are:

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4804	43.9	10.1	Average

Test Data

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Reading [dBuV/m]	Pol.	Height	Correction Factor				sult V/m]		rgin B]
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV /	/ Peak	AV ,	/ Peak	AV /	Peak
4804.00	30.0 40.4	V	1.0	13.9	54.0	74.0	43.9	54.3	10.1	19.7

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

							_				
Eroguenev	Rea	ding		Height	Correction	Limits		Re	sult	Ma	rgin
Frequency	[dBu	V/m]	Pol.	neight	Factor [dBuV/m] [dBu		V/m]	[dB]			
[MHz]	AV	/ Peak		[m]	Antenna + Amp. Gain + Cable	AV ,	/ Peak	AV ,	/ Peak	AV /	Peak
4804.00	26.8	39.7	V	1.0	13.9	54.0	74.0	40.7	53.6	13.3	20.4
		į							•		

Restricted band edge test data

Measured frequency range: 2310-2390 MHz, 2483.5-2500 MHz

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Reading [dBuV/m]	Pol.	Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak
2390.00	29.5 41.5	V	1.0	7.1	54.0 74.0	36.6 48.6	17.4 25.4

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency	Reading [dBuV/m]	Pol.	Height	Correction Factor	Limits [dBuV/m] AV / Peak				Margin [dB]	
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable					AV /	Peak
2390.00	30.9 43.3	V	1.0	7.1	54.0	74.0	38.0	50.4	16.0	23.6

Test Report No.: CTK-2015-00133

Date: 2015-02-05

-02-05
This Report shall not be reproduced except in full without the written approval of CTK

Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)

Page 47 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

EUT	THERMAL RECEIPT PRINTER	Measurement Detail	
Model	SRP-35*IIOBEz	Frequency Range	1-25GHz
Channel	Channel 39	Detector function	Peak

Remarks

We have tested three mode (X, Y, Z). The worst mode (Z axis) for final test.

The requirements are:

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
4882	39.0	15.0	Average

Test Data

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Reading [dBuV/m]	Pol.	Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak
4882.00	24.4 39.7	V	1.0	13.9	54.0 74.0	38.3 53.6	15.7 20.4

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency		ding V/m]	Pol.	Height Correction Limits Result Factor [dBuV/m] [dBuV/n						rgin B]	
[MHz]	AV	/ Peak		[m]	Antenna + Amp. Gain + Cable	AV	/ Peak	AV ,	/ Peak	AV /	Peak
4882.00	25.1	40.5	V	1.0	13.9	54.0	74.0	39.0	54.4	15.0	19.6

Restricted band edge test data

Measured frequency range: 2310-2390 MHz, 2483.5-2500 MHz

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Reading	Pol.	Height		Correction Factor		Limits	Result	Margin	
[MHz]	[dBuV/m]		[m]	Antenna	Amp. Gain	Cable	[dBuV/m]	[dBuV/m]	[dB]	
	No emissions were detected at a level greater than 20dB below limit.									

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency	Reading	Pol.	Height	Correction Factor		Limits	Result	Margin	
[MHz]	[dBuV/m]		[m]	Antenna	Amp. Gain	Cable	[dBuV/m]	[dBuV/m]	[dB]
No emissions were detected at a level greater than 20dB below limit.									

Test Report No.: CTK-2015-00133 Page 48 of 55



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

Test mode: GFSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

EUT	THERMAL RECEIPT PRINTER	Measurement Detail	
Model	SRP-35*IIOBEz	Frequency Range	1-25GHz
Channel	Channel 78	Detector function	Peak

Remarks

We have tested three mode (X, Y, Z). The worst mode (Z axis) for final test.

The requirements are:

□ Complies

□ complics			
Frequency	Measured Data	Margin	Remark
(MHz)	(dBuV/m)	(dB)	Keillaik
2483.5	47.7	6.3	Average

Test Data

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Reading [dBuV/m]	Pol.	Height		Result [dBuV/m]	Margin [dB]	
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak
4960.00	24.4 38.3	V	1.0	13.9	54.0 74.0	38.3 52.2	15.7 21.8

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency	Reading [dBuV/m]	Pol.	Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB] AV / Peak	
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak		
4960.00	24.9 39.4	V	1.0	13.9	54.0 74.0	38.8 53.3	15.2 20.7	

Restricted band edge test data

Measured frequency range: 2310-2390 MHz, 2483.5-2500 MHz

Test mode: GPSK, CFG PKT Packet Type: 15 Packet Size: 339(DH5)

Frequency	Frequency Reading [dBuV/m] Pol.		Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]	
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak	
2483.50	40.6 48.9	V	1.0	7.1	54.0 74.0	47.7 56.0	6.3 18.0	

Test mode: 8-DPSK, CFG PKT Packet Type: 31 Packet Size: 1021(3DH5)

Frequency	ency Reading [dBuV/m] Pol.		Height	Correction Factor	Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]	
[MHz]	AV / Peak		[m]	Antenna + Amp. Gain + Cable	AV / Peak	AV / Peak	AV / Peak	
2483.50	38.6 52.0	V	1.0	7.1	54.0 74.0	45.7 59.1	8.3 14.9	

Test Report No.: CTK-2015-00133 Page 49 of 55

Date: 2015-02-05

This Report shall not be reproduced except in full without the written approval of CTK Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)



(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501 www.e-ctk.com

2.1.8 AC Conducted Emissions

Test Location

Shielded Room

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Procedures

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit

- 15.207(a)

Frequency	Conducted Limit (dBuV)					
(MHz)	Quasi-peak	Average				
0.15 ~ 0.5	66 to 56*	56 to 46*				
0.5 ~ 5	56	46				
5 ~ 30	60	50				

^{*} Decreases with the logarithm of the frequency.

Test Results

The requirements are:

Test mode: Hopping(GFSK), CFG PKT Packet Type: 15,

Packet Size: 339(DH5)

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
20.175	34.9	15.1	Average

Hopping(8-DPSK), CFG PKT Packet Type: 31, Test mode:

Packet Size: 1021(3DH5)

Frequency	Measured Data	Margin	Remark
(MHz)	(dBuV/m)	(dB)	
20.175	34.4	15.6	Average


Test Report No.: CTK-2015-00133 Page 50 of 55

Date: 2015-02-05

Form No.: CTK-RF-EF-Part15 SubpartC(Rev.2)



Test Data_Hopping(GFSK)



Final Result 1

i illai ive	Suit i							
Frequency	QuasiPeak	Meas.	Bandwidth	Filter	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	Time	(kHz)			(dB)	(dB)	(dBµV)
		(ms)						
0.159000	41.0	1000.0	9.000	On	L1	9.8	24.5	65.5
0.186000	37.6	1000.0	9.000	On	L1	9.8	26.6	64.2
0.231000	34.4	1000.0	9.000	On	L1	9.7	28.0	62.4
0.343500	25.5	1000.0	9.000	On	L1	9.8	33.6	59.1
3.876000	21.5	1000.0	9.000	On	L1	9.7	34.5	56.0
12.097500	23.1	1000.0	9.000	On	L1	9.9	36.9	60.0
15.333000	25.1	1000.0	9.000	On	L1	9.9	34.9	60.0
16.138500	33.3	1000.0	9.000	On	L1	9.9	26.7	60.0
16.143000	33.5	1000.0	9.000	On	L1	9.9	26.5	60.0
20.175000	38.2	1000.0	9.000	On	L1	10.0	21.8	60.0
28.234500	29.5	1000.0	9.000	On	L1	10.0	30.5	60.0

Final Result 2

Frequency	CAverage	Meas.	Bandwidth	Filter	Line	Corr.	Margin	Limit
(MHz)	(dBµV)	Time	(kHz)			(dB)	(dB)	(dBµV)
		(ms)						
0.159000	20.0	1000.0	9.000	On	L1	9.8	35.6	55.5
0.186000	19.0	1000.0	9.000	On	L1	9.8	35.3	54.2
0.231000	19.6	1000.0	9.000	On	L1	9.7	32.8	52.4
0.343500	13.4	1000.0	9.000	On	L1	9.8	35.7	49.1
3.876000	14.3	1000.0	9.000	On	L1	9.7	31.7	46.0
12.097500	18.7	1000.0	9.000	On	L1	9.9	31.3	50.0
15.333000	20.6	1000.0	9.000	On	L1	9.9	29.4	50.0
16.138500	29.9	1000.0	9.000	On	L1	9.9	20.1	50.0
16.143000	29.0	1000.0	9.000	On	L1	9.9	21.0	50.0
20.175000	34.9	1000.0	9.000	On	L1	10.0	15.1	50.0
28.234500	25.3	1000.0	9.000	On	L1	10.0	24.7	50.0


Test Report No.: CTK-2015-00133

Date: 2015-02-05

Page 51 of 55







Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
		(ms)			2000			
0.159000	41.0	1000.0	9.000	On	N	9.7	24.5	65.5
0.195000	30.6	1000.0	9.000	On	N	9.8	33.2	63.8
0.231000	33.7	1000.0	9.000	On	N	9.7	28.7	62.4
0.298500	28.1	1000.0	9.000	On	N	9.7	32.2	60.3
16.134000	32.1	1000.0	9.000	On	N	9.9	27.9	60.0
20.166000	37.5	1000.0	9.000	On	N	9.9	22.5	60.0


Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.528000	12.1	1000.0	9.000	On	N	9.9	33.9	46.0
12.106500	21.0	1000.0	9.000	On	N	9.9	29.0	50.0
15.333000	20.9	1000.0	9.000	On	N	9.9	29.1	50.0
16.134000	28.5	1000.0	9.000	On	N	9.9	21.5	50.0
20.161500	32.9	1000.0	9.000	On	N	9.9	17.1	50.0
28.248000	24.8	1000.0	9.000	On	N	10.1	25.2	50.0

Page 52 of 55 Test Report No.: CTK-2015-00133



Test Data_Hopping(8-DPSK)



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.163500	39.2	1000.0	9.000	On	L1	9.8	26.1	65.3
0.186000	36.5	1000.0	9.000	On	L1	9.8	27.7	64.2
0.231000	32.9	1000.0	9.000	On	L1	9.7	29.5	62.4
0.298500	27.8	1000.0	9.000	On	L1	9.7	32.4	60.3
2.877000	19.7	1000.0	9.000	On	L1	9.8	36.3	56.0
12.106500	24.9	1000.0	9.000	On	L1	9.9	35.1	60.0
15.333000	24.8	1000.0	9.000	On	L1	9.9	35.2	60.0
16.125000	30.5	1000.0	9.000	On	L1	9.9	29.5	60.0
16.129500	29.0	1000.0	9.000	On	L1	9.9	31.0	60.0
20.175000	38.4	1000.0	9.000	On	L1	10.0	21.6	60.0
20.179500	38.8	1000.0	9.000	On	L1	10.0	21.2	60.0
28.239000	29.0	1000.0	9.000	On	L1	10.0	31.0	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
(111112)	(ССДТ)	(ms)	(14.12)			(ub)	(ub)	(авру)
0.163500	17.1	1000.0	9.000	On	L1	9.8	38.2	55.3
0.186000	18.0	1000.0	9.000	On	L1	9.8	36.2	54.2
0.231000	17.2	1000.0	9.000	On	L1	9.7	35.2	52.4
0.298500	13.0	1000.0	9.000	On	L1	9.7	37.3	50.3
2.877000	13.6	1000.0	9.000	On	L1	9.8	32.4	46.0
12.106500	21.5	1000.0	9.000	On	L1	9.9	28.5	50.0
15.333000	20.5	1000.0	9.000	On	L1	9.9	29.5	50.0
16.125000	25.5	1000.0	9.000	On	L1	9.9	24.5	50.0
16.129500	23.2	1000.0	9.000	On	L1	9.9	26.8	50.0
20.175000	34.4	1000.0	9.000	On	L1	10.0	15.6	50.0
20.179500	34.2	1000.0	9.000	On	L1	10.0	15.8	50.0
28.239000	24.9	1000.0	9.000	On	L1	10.0	25.1	50.0


Test Report No.: CTK-2015-00133

Date: 2015-02-05

Page 53 of 55







Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.159000	40.0	1000.0	9.000	On	N	9.7	25.5	65.5
0.159000	40.0	1000.0	9.000	Oli	IN	9.1	25.5	65.5
0.186000	36.8	1000.0	9.000	On	N	9.8	27.5	64.2
0.231000	32.8	1000.0	9.000	On	N	9.7	29.7	62.4
0.298500	27.4	1000.0	9.000	On	N	9.7	32.9	60.3
17.358000	29.2	1000.0	9.000	On	N	9.9	30.8	60.0
20.161500	37.7	1000.0	9.000	On	N	9.9	22.3	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)		
2.877000	11.9	1000.0	9.000	On	N	9.7	34.1	46.0		
12.106500	21.2	1000.0	9.000	On	N	9.9	28.8	50.0		
15.333000	20.7	1000.0	9.000	On	N	9.9	29.3	50.0		
16.138500	27.3	1000.0	9.000	On	N	9.9	22.7	50.0		
20.161500	34.2	1000.0	9.000	On	N	9.9	15.8	50.0		
28.230000	23.8	1000.0	9.000	On	N	10.1	26.2	50.0		

Page 54 of 55 Test Report No.: CTK-2015-00133



APPENDIX A – Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date
1	Spectrum Analyzer	Rohde & Schwarz	FSP-30	100994	2014-11-07	2015-11-07
2	Spectrum Analyzer	Rohde & Schwarz	FSP	100401	2014-09-12	2015-09-12
3	EMI Test Receiver	Rohde & Schwarz	ESCI7	100814	2014-12-05	2015-12-05
4	EMI Test Receiver	Rohde & Schwarz	ESCI7	100816	2014-12-05	2015-12-05
5	EMI Test Receiver	Rohde & Schwarz	ESU40	100336	2014-05-15	2015-05-15
6	Bilog Antenna	Schaffner	CBL6111C	2551	2014-05-08	2016-05-08
7	Double Ridged Guide Antenna	ETS-Lindgren	3117	00154525	2013-07-03	2015-07-03
8	Double Ridged Guide Antenna	ETS-Lindgren	3116	00062916	2013-03-20	2015-03-20
9	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-126	2014-05-19	2016-05-19
10	Attenuator	Rohde & Schwarz	DNF	272.4110.50-2	2014-11-07	2015-11-07
11	PREAMPLIFIER	Agilent	8449B	3008A02307	2014-10-24	2015-10-24
12	AMPLIFIER	Sonoma Instrument Co.	310	291721	2014-02-06	2015-02-06
13	Band Reject Filter	Wainwright Instruments GmbH	WRCGV 2400/2483- 2375/2505- 50/10EE	2	2014-08-25	2015-08-25
14	Signal Generator	Rohde & Schwarz	SMB100A	175528	2015-01-19	2016-01-19
15	LISN	Rohde & Schwarz	ENV216	101236	2014-07-30	2015-07-30
16	LISN	Rohde & Schwarz	ENV216	101235	2014-07-30	2015-07-30

Page 55 of 55 Test Report No.: CTK-2015-00133