



FCC Test Report

According to

47 CFR Part 22H, 24E

Equipment : SPEEDTRAC
Trade Name : ORION
Model No. : SP3610B
FCC ID : U6M-SP3610
Tx Frequency Range : GSM850 : 824.2 ~ 848.8MHz
PCS1900 : 1850.2 ~1909.8 MHz
Max. ERP/EIRP Power : GSM850 : 0.17 W
PCS1900 : 0.67 W
Emission Designator : 300KGXW
Applicant : Orion Technology LTD.
8F., No. 18, Sec. 1, Chang-An East Road, ZhongShan
District, Taipei City 104, Taiwan

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**
- The data shown in this test report were carried out on Mar. 10, 2008 at **Sporton International Inc. LAB.**
- Report No.: FG810406, Report Version: Rev. 01.

Roy Wu
Manager

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.



Table of Contents

History of This Test Report	ii
1. General Information	1
1.1 Applicant.....	1
1.2 Manufacturer	1
1.3 Basic Description of Equipment under Test.....	1
1.4 Feature of Equipment under Test	1
1.5 Report Date	1
2. Test Configuration of Equipment under Test	2
2.1 Test Manner	2
2.2 Test Mode	2
2.3 Connection Diagram of Test System	2
2.4 Ancillary Equipment List	2
3. General Information of Test Site.....	3
3.1 Test Voltage	3
3.2 Test Compliance.....	3
3.3 Frequency Range.....	3
3.4 Test Distance.....	3
4. Test Data and Test Result	4
4.1 List of Measurements and Examinations	4
4.2 RF Output Power.....	5
4.3 ERP / EIRP Measurement.....	6
4.4 Occupied Bandwidth and Band Edge Measurement	9
4.5 Conducted Emission.....	26
4.6 Field Strength of Spurious Radiation	36
4.7 Frequency Stability (Temperature Variation)	41
4.8 Frequency Stability (Voltage Variation)	43
5. List of Measurement Equipments.....	45
6. Uncertainty Evaluation	46
Appendix A - External Photographs of EUT	
Appendix B - Internal Photographs of EUT	
Appendix C - Setup Photographs	



History of This Test Report

Report Issue Date: Mar. 11, 2008

Report No.	Description



1. General Information

1.1 Applicant

Orion Technology LTD.

8F., No. 18, Sec. 1, Chang-An East Road, ZhongShan District, Taipei City 104, Taiwan

1.2 Manufacturer

Orion Technology LTD.

8F., No. 18, Sec. 1, Chang-An East Road, ZhongShan District, Taipei City 104, Taiwan

1.3 Basic Description of Equipment under Test

Equipment	SPEEDTRAC
Trade Name	ORION
Model Name	SP3610B
FCC ID	U6M-SP3610

Remark: Above EUT's information was declared by manufacturer. Please refer to the specifications of manufacturer or User's Manual for more detailed features description.

1.4 Feature of Equipment under Test

Product Feature & Specification	
DUT Type :	SPEEDTRAC
Trade Name :	ORION
Model Name :	SP3610B
FCC ID :	U6M-SP3610
Tx Frequency :	GSM850 : 824 MHz ~ 849 MHz PCS1900 : 1850 MHz ~1910 MHz
Rx Frequency :	GSM850 : 869 MHz ~ 894 MHz PCS1900 : 1930 MHz ~ 1990 MHz
Channel Spacing	200 KHz
Maximum Output Power to Antenna :	GSM850 : 32.44dBm PCS1900 : 29.98dBm
Maximum ERP/EIRP :	GSM850 : 0.17 W (22.22 dBm) PCS1900 : 0.67 W (28.29 dBm)
Type of Modulation :	GMSK
Type of Emission :	300KGXW
DUT Stage :	Identical Prototype

1.5 Report Date

EUT Received : Jan. 04, 2008

Report Date : Mar. 11, 2008

2. Test Configuration of Equipment under Test


2.1 Test Manner

1. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.
2. During all testings, EUT is in link mode with base station emulator at maximum power level.
3. Frequency range investigated: radiated emission 30 MHz to 9000 MHz for GSM850; 30MHz to 19000 MHz for PCS1900.

2.2 Test Mode

Application	GSM850	PCS1900
Radiated Emission	<input checked="" type="checkbox"/> Mode 1: GSM Link	<input checked="" type="checkbox"/> Mode 2: GSM Link
Conducted Measurement	<input checked="" type="checkbox"/> Mode 1: GSM Link	<input checked="" type="checkbox"/> Mode 2: GSM Link

2.3 Connection Diagram of Test System



2.4 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable / Power Code
1.	Base Station	R&S	CMU200	N/A	Unshielded, 1.8m
2.	Car Battery	YUASA	46B24R	N/A	N/A



3. General Information of Test Site

Test Site Location : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park,
Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
TEL : 886-3-327-3456
FAX : 886-3-328-4978
Test Site No : 03CH06-HY, TH02-HY

The chamber meets the characteristics of ANSI C63.4-2003. This site is on file with the FCC.

3.1 Test Voltage

DC 12V

3.2 Test Compliance

47 CFR Part 22H, 24E, Part 2

3.3 Frequency Range

- a. Radiation: from 30MHz to 9000MHz for GSM850.
- b. Radiation: from 30 MHz to 19000 MHz for PCS1900.

3.4 Test Distance

The test distance of radiated emission from antenna to EUT is 3 m.



4. Test Data and Test Result

4.1 List of Measurements and Examinations

FCC Rule	Description Of Test	Result	Section
§2.1046	RF Output Power	Passed	4.2
§ 22.913 §24.232	ERP / EIRP	Passed	4.3
§2.1049, § 22.917, § 24.238(b)	Occupied Bandwidth & Band Edge Measurement	Passed	4.4
§2.1051	Conducted Emission	Passed	4.5
§2.1053	Field Strength of Spurious Radiation	Passed	4.6
§2.1055, § 22.355, §24.235	Frequency Stability vs. Temperature	Passed	4.7
§2.1055, §22.355, §24.235	Frequency Stability vs. Voltage	Passed	4.8

4.2 RF Output Power


4.2.1 Measurement Instruments

As described in chapter 5 of this test report.

4.2.2 Test Procedure

- The transmitter output was connected to power meter and base station through power divider.
- Set EUT at PCL=5 for GSM850 and/or PCL=0 for PCS1900 maximum power through base station.
- Select lowest, middle, and highest channels for each band.

4.2.3 Test Setup Layout



4.2.4 Test Result

Bands	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM850	128	824.2 (Low)	31.70	1.479
	189	836.4 (Mid)	32.12	1.629
	251	848.8 (High)	32.44	1.754
PCS1900	512	1850.2 (Low)	29.98	0.995
	661	1880.0 (Mid)	29.86	0.968
	810	1909.8 (High)	29.79	0.953

4.3 ERP / EIRP Measurement

Equivalent isotropic radiated power measurements by substitution method according to ANSI/TIA/EIA-603-C.

4.3.1 Measurement Instruments

As described in chapter 5 of this test report.

4.3.2 Test Procedure

- a. The EUT was placed on a tutntable with 1.0 meter height in an fully anechoic chamber.
- b. The EUT was set 1.2 meters from the receiving antenna which was mounted on the antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiated power.
- d. The height of the receiving antenna is also kept at 1.0M height.
- e. Taking the record of maximum ERP/EIRP.
- f. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
- g. The conducted power at the terminal of the dipole antenna is measured.
- h. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
- i. $ERP/EIRP = Ps + Et - Es + Gs = Ps + Rt - Rs + Gs$

Ps (dBm) : Input power to substitution antenna.

Gs (dBi or dBd) : Substitution antenna Gain.

$Et = Rt + AF$


$Es = Rs + AF$

AF (dB/m) : Receive antenna factor

Rt : The highest received signal in Spectrum Analyzer for EUT.

Rs : The highest received signal in spectrum analyzer for substitution antenna.

4.3.3 Test Setup Layout of ERP/EIRP



**4.3.4 Test Result**

GSM850 Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-24.82	-48.12	0.00	-1.08	22.22	0.17
836.40	-25.89	-48.28	0.00	-0.93	21.46	0.14
848.80	-27.95	-48.35	0.00	-0.76	19.64	0.09
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-24.95	-47.97	0.00	-1.08	21.94	0.16
836.40	-27.55	-48.01	0.00	-0.93	19.53	0.09
848.80	-30.56	-48.05	0.00	-0.76	16.73	0.05

PCS1900 Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.55	-51.88	0.00	1.96	28.29	0.67
1880.00	-28.32	-52.99	0.00	2.00	26.67	0.46
1909.80	-28.69	-54.28	0.00	1.98	27.57	0.57
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-28.52	-52.13	0.00	1.96	25.57	0.36
1880.00	-30.58	-53.17	0.00	2.00	24.59	0.29
1909.80	-33.27	-54.13	0.00	1.98	22.84	0.19

4.4 Occupied Bandwidth and Band Edge Measurement


4.4.1 Measurement Instruments

As described in chapter 5 of this test report.

4.4.2 Test Procedure


- The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- The 99% occupied bandwidth of middle channel for the highest and lowest RF powers were measured.
- The bandedge of low and high channels for the highest RF powers within the transmitting frequency band were measured. Setting RBW as roughly BW/100.

4.4.3 Test Setup Layout



**4.4.4 Test Result**


- Mode 1
- Test Mode : GSM850 CH128 Lower Band Edge
- Power State : High



Date: 31.JAN.2008 11:05:25




- Test Mode : GSM850 CH128 99% Occupied Bandwidth
- Power State : High



Date: 31.JAN.2008 11:13:28




- Test Mode : GSM850 CH189 99% Occupied Bandwidth
- Power State : High



Date: 31.JAN.2008 11:15:01




- Test Mode : GSM850 CH 251 99% Occupied Bandwidth
- Power State : High



Date: 31.JAN.2008 11:12:01




- Test Mode : GSM850 CH128 26dB Bandwidth
- Power State : High



Date: 31.JAN.2008 10:53:00




- Test Mode : GSM850 CH189 26dB Bandwidth
- Power State : High



Date: 31.JAN.2008 10:55:04




- Test Mode : GSM850 CH 251 26dB Bandwidth
- Power State : High



Date: 31.JAN.2008 10:56:23




- Test Mode : GSM850 CH251 Higher Band Edge
- Power State : High



Date: 31.JAN.2008 10:58:21




- Mode 2
- Test Mode : PCS1900 CH512 Lower Band Edge
- Power State : High



Date: 31.JAN.2008 13:03:22




- Test Mode : PCS1900 CH512 99% Occupied Bandwidth
- Power State : High



Date: 31.JAN.2008 13:08:10




- Test Mode : PCS1900 CH661 99% Occupied Bandwidth
- Power State : High



Date: 31.JAN.2008 13:18:19




- Test Mode : PCS1900 CH810 99% Occupied Bandwidth
- Power State : High



Date: 31.JAN.2008 13:06:56




- Test Mode : PCS1900 CH512 26dB Bandwidth
- Power State : High



Date: 31.JAN.2008 11:26:22




- Test Mode : PCS1900 CH661 26dB Bandwidth
- Power State : High



Date: 31.JAN.2008 12:57:23




- Test Mode : PCS1900 CH810 26dB Bandwidth
- Power State : High



Date: 31.JAN.2008 12:59:18



- Test Mode : PCS1900 CH810 Higher Band Edge
- Power State : High



Date: 31.JAN.2008 13:00:50

4.5 Conducted Emission


4.5.1 Measurement Instruments

As described in chapter 5 of this test report.

4.5.2 Test Procedure

- The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- The middle channel for the highest RF power within the transmitting frequency was measured.
- The conducted spurious emission for the whole frequency range was taken.


4.5.3 Test Setup Layout





4.5.4 Test Result


- Mode 1
- Test Mode : GSM850 CH189
- Frequency Range : 30M-1G



Date: 10.MAR.2008 20:42:47




- Test Mode : GSM850 CH189
- Frequency Range : 1G-3G



Date: 10.MAR.2008 20:49:02




- Test Mode : GSM850 CH189
- Frequency Range : 3G-7G



Date: 10.MAR.2008 20:51:21




- Test Mode : GSM850 CH189
- Frequency Range : 7G-9G



Date: 10.MAR.2008 20:53:23




- Mode 2
- Test Mode : PCS1900 CH661
- Frequency Range : 30M-1G



Date: 10.MAR.2008 20:43:16




- Test Mode : PCS1900 CH661
- Frequency Range : 1G-3G



Date: 10.MAR.2008 20:45:23




- Test Mode : PCS1900 CH661
- Frequency Range : 3G-7G



Date: 10.MAR.2008 20:51:50




- Test Mode : PCS1900 CH661
- Frequency Range : 7G-13.6G



Date: 10.MAR.2008 20:54:57



- Test Mode : PCS1900 CH661
- Frequency Range : 13.6G-19.1G



Date: 10.MAR.2008 20:57:09

4.6 Field Strength of Spurious Radiation

Equivalent isotropic radiated Power Measurements by substitution method according to ANSI/TIA/EIA-603-C.


4.6.1 Measurement Instruments


As described in chapter 5 of this test report.

4.6.2 Test Procedure

- The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
- The EUT was set 3 meters from the receiving antenna which was mounted on the antenna tower.
- The table was rotated 360 degrees to determine the position of the highest spurious emission.
- The height of the receiving antenna is varied between one meter and four meters to reach the maximum spurious emission for both horizontal and vertical polarizations.
- Taking the record of maximum spurious emission.
- A Horn antenna was substituted in place of the EUT and was driven by a signal generator.
- Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- Taking the record of output power at antenna port.
- Repeat step 7 to step 8 for another polarization.
- Emission level (dBm) = output power + substitution Gain.

4.6.3 Test Setup Layout



**4.6.4 Test Data****4.6.4.1 Mode 1****Horizontal Polarization**


Site : 03CH06-HY
Condition : FCC PART22/24 EIRP-071107 HORIZONTAL
EUT : SPEEDTRAC
Power : 12Vdc
Model : FC 810406
Memo : GSM850 Link ; CH180 + DC 12V
Plane : E2
s/n : SP507C120025

Frequency (MHz)	ERP (dBm)	Limit (dBm)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-40.39	-13	-45.82	-39.54	5.05	6.35	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.




Vertical Polarization



Trace: (Discrete)
Site : 03CH06-HV
Condition : FCC PART22/24 ETRP-071107 VERTICAL
EUT : SPEEDTRAC
Power : 12Vdc
Model : FG 810406
Memo : GSM850 Link ; CH180 + DC 12V
Plane : E2
s/n : SP507C120025

Frequency (MHz)	ERP (dBm)	Limit (dBm)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-41.54	-13	-46.97	-40.69	5.05	6.35	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

**4.6.4.2 Mode 2****Horizontal Polarization**


Trace: (Discrete)
Site : 03CH06-HY
Condition : FCC PART22/24 EIRP-071107 HORIZONTAL
EUT : SPEEDTRAC
Power : 12Vdc
Model : FG 810406
Memo : PCS1900 Link ; CH661 + DC 12V
Plane : E2
s/n : SP507C120025

Frequency (MHz)	ERP (dBm)	Limit (dBm)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3756	-31.07	-13.00	-44.39	-35.00	7.17	11.10	H	Pass
5636	-42.71	-13.00	-59.74	-44.500	8.77	10.56	H	Pass
7516	-33.31	-13.00	-50.62	-30.5	10.21	7.40	H	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Vertical Polarization



Trace: (Discrete)

Site : 03CH06-HY
Condition : FCC PART22/24 ETRP-071107 VERTICAL
EUT : SPEEDTRAC
Power : 12Vdc
Model : FG 810406
Memo : PCS1900 Link ; CH661 + DC 12V
Plane : E2
s/n : SP507C120025

Frequency (MHz)	ERP (dBm)	Limit (dBm)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3756	-22.37	-13.00	-35.69	-26.30	7.17	11.10	V	Pass
5636	-36.21	-13.00	-53.24	-38.00	8.77	10.56	V	Pass
7516	-32.31	-13.00	-49.62	-29.50	10.21	7.40	V	Pass

Remark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

4.7 Frequency Stability (Temperature Variation)


4.7.1 Measurement Instrument

As described in chapter 5 of this test report.

4.7.2 Test Procedure

- The EUT and test equipment were set up as shown on the following section.
- With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
- With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
- The temperature tests were performed for the worst case.
- Test data was recorded.

4.7.3 Test Setup Layout



4.7.4 Test Result

▪ Test Mode : GSM850 CH189

Temperature(°C)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	66	0.03	2.5	Passed
-20	-58	-0.07		
-10	47	0.06		
0	35	0.04		
10	-22	-0.03		
20	34	0.04		
30	-33	-0.04		
40	44	0.05		
50	58	0.07		

▪ Test Mode : PCS1900 CH661

Temperature(°C)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
-30	-77	-0.04	2.5	Passed
-20	-66	-0.03		
-10	-55	-0.03		
0	28	0.01		
10	35	0.02		
20	-46	-0.02		
30	47	0.02		
40	-55	-0.03		
50	-58	-0.03		

4.8 Frequency Stability (Voltage Variation)


4.8.1 Measurement Instrument

As described in chapter 5 of this test report.

4.8.2 Test Procedure

- The EUT was placed in a temperature chamber at 25 ± 5 °C and connected as the following section.
- The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
- The variation in frequency was measured for the worst case.

4.8.3 Test Setup Layout



4.8.4 Test Result

- Test Mode : GSM850 CH189

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
12.0	25.0	0.03	2.5	Passed
BEP	21.0	0.02		
13.8	-33.0	-0.04		

- Test Mode : PCS1900 CH661

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
12.0	-37.0	-0.04	2.5	Passed
BEP	31.0	0.04		
13.8	-30.0	-0.04		

Remark:

- Normal Voltage = 12.0V.
- Battery End Point (BEP) = 10.2V.

- Test Mode : GSM850 CH189

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
24.0	27.0	0.03	2.5	Passed
BEP	28.0	0.03		
27.6	33.0	0.04		

- Test Mode : PCS1900 CH661

Voltage(Volt)	Change (Hz)	Change (ppm)	Limit (ppm)	Result
24.0	-28.0	-0.03	2.5	Passed
BEP	-24.0	-0.03		
27.6	22.0	0.03		

Remark:

- Normal Voltage = 24.0V.
- Battery End Point (BEP) = 20.4 V.



5. List of Measurement Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	Agilent	E4408B	MY44211028	9KHz-26.5GHz	Oct. 17, 2007	Oct. 16, 2008	Radiation (03CH06-HY)
EMI Test Receiver	R&S	ESCS30	100356	9KHz-2.75GHz	Jul. 26, 2007	Jul. 25, 2008	Radiation (03CH06-HY)
Bilog Antenna	SCHAFFNER	CBL6112B	2885	30MHz -2GHz	Dec. 01, 2007	Nov. 30, 2008	Radiation (03CH06-HY)
Double Ridge Horn Antenna	Com-Power	AH118	071025	1G~18G	Jun. 04, 2007	Jun. 03, 2008	Radiation (03CH06-HY)
SHF-EHF Horn	SCHWARZBECK	BBHA 9170	9170-251	14G - 40G	Oct. 17, 2007	Oct. 16, 2008	Radiation (03CH06-HY)
Pre Amplifier	Agilent	8449B	3008A01917	1G - 26.5G	Nov. 22, 2007	Nov. 21, 2008	Radiation (03CH06-HY)
PreAmplifier	EMEC	PA303	PA303-SMA-05	100K~3GHz	Nov. 26, 2007	Nov. 25, 2008	Radiation (03CH06-HY)
Base Station Simulator	R & S	CMU200	103937	Third-Band	Oct. 19, 2007	Oct. 18, 2008	Radiation (03CH06-HY)
Thermal Chamber	Tenyi technology	TTH-D35P	TBN-930701	N/A	Aug. 02, 2007	Aug. 01, 2008	Conduction (TH02-HY)
Spectrum	R&S	FSP40	100055	9KHz~40GHz	Jun. 25, 2007	Jun. 24, 2008	Conduction (TH02-HY)
Bluetooth Test	ANRITSU	MT8852A	6K00003939	N/A	N/A	N/A	Conduction (TH02-HY)
Power Divider	ARRA	5200-1	3871	N/A	Oct. 01, 2007	Sep. 30, 2008	Conduction (TH02-HY)
DC Power Supply	TOPWARD	3303D	740889	N/A	May 25, 2007	May 24, 2009	Conduction (TH02-HY)
Power Meter	Agilent	E4416A	GB41292344	N/A	Feb. 21, 2008	Feb. 20, 2009	Conduction (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	N/A	Feb. 21, 2008	Feb. 20, 2009	Conduction (TH02-HY)

6. Uncertainty Evaluation

Uncertainty of Radiated Emission Measurement (30MHz ~ 1000MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.41	Normal(k=2)	0.21
Antenna factor calibration	0.83	Normal(k=2)	0.42
Cable loss calibration	0.25	Normal(k=2)	0.13
Pre Amplifier Gain calibration	0.27	Normal(k=2)	0.14
RCV/SPA specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site imperfection	1.43	Rectangular	0.83
Mismatch	+0.39/-0.41	U-shaped	0.28
Combined standard uncertainty Uc(y)	1.27		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.54		

Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

Contribution	Uncertainty of x_i		$u(x_i)$	C_i	$C_i * u(x_i)$
	dB	Probability Distribution			
Receiver reading	±0.10	Normal(k=1)	0.10	1	0.10
Antenna factor calibration	±1.70	Normal(k=2)	0.85	1	0.85
Cable loss calibration	±0.50	Normal(k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20 \log(1 - \Gamma_1 * \Gamma_2 * \Gamma_3)$	+0.34/-0.35	U-shaped	0.244	1	0.244
Combined standard uncertainty Uc(y)	2.36				
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	4.72				

END OF TEST REPORT