

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 74 SUBPART H REQUIREMENT**

OF

Wireless Microphone

MODEL No.: USX-800H

BRAND NAME: Wharfedale Pro

FCC ID: U6UUSX

REPORT NO: E0703086F

ISSUE DATE: April 05, 2007

Prepared for

**Sanecore Musical Instrument (Shenzhen) Co., Ltd.
Sanecore Science&Technology Industry park, Jiuwei Village Xixiang Town,
Shenzhen, Guangdong, China**

Prepared by

SHENZHEN EMTEK CO., LTD

**Bldg 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China**

TEL: 86-755-26954280

FAX: 86-755-26954282

VERIFICATION OF COMPLIANCE

Applicant:	Sanecore Musical Instrument (Shenzhen) Co., Ltd. Sanecore Science&Technology Industry park, Jiuwei Village Xixiang Town, Shenzhen, Guangdong, China
Product Description:	Wireless Microphone
Brand Name:	Wharfedale Pro
Model Number:	USX-800H
Serial Number:	USX-900W
File Number:	E0703086F
Date of Test:	March 20, 2007 to April 05, 2007

We hereby certify that:

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2003) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 74 Subpart H.

The test results of this report relate only to the tested sample identified in this report.

Approved By



**David Lee / Q.A. Manager
SHENZHEN EMTEK CO., LTD.**

Table of Contents

1.	GENERAL INFORMATION	5
1.1	Product Description	5
1.2	Related Submittal(s) / Grant (s)	5
1.3	Test Methodology	5
1.4	Special Accessories.....	6
1.5	Equipment Modifications	6
1.6	Test Facility	7
2.	SYSTEM TEST CONFIGURATION	8
2.1	EUT Configuration	8
2.2	EUT Exercise	8
2.3	General Technical Requirements	8
2.4	Configuration of Tested System.....	9
3.	SUMMARY OF TEST RESULTS	10
4.	DESCRIPTION OF TEST MODES	10
5.	MAXIMUM TRANSMITTER POWER	11
5.1	Provisions Applicable	11
5.4	Measurement Equipment Used:.....	13
5.4	Measurement Result	13
6.	MODULATION CHARACTERISTICS	15
6.1	PROVISIONS APPLICABLE	15
6.2	MEASUREMENT METHOD	15
6.3	Measurement instruments	16
6.4	Measurement Result.....	16
7.	FREQUENCY TOLERANCE.....	22
7.1	Provisions Applicable.....	22
7.2	Measurement Procedure.....	22
7.3	Test Setup Block diagram(Block diagram of configuration).....	23
7.4	Test Equipment used:	23
7.5	Test Result.....	23
8.	EMISSION BANDWIDTH	26
8.1	Provisions Applicable.....	26
8.2	MEASUREMENT PROCEDURE.....	26
8.3	TEST SETUP BLOCK DIAGRAM (Block Diagram of Configuration)	26
8.4	Measurement Equipment used:	26
8.5	Measurement Result:.....	27
9.	UNWANTED RADIATION.....	30
9.1	Provisions applicable	30

9.2 MEASUREMENT PROCEDURE.....	30
9.3 Test Setup Block Diagram(block diagram of configuration)	31
9.4 Measurement Equipment used:	32
9.5 Measurement Results:	32
9.6 Radiation Emission Mask:	33
APPENDIX 1	36
APPENDIX 2	38

1. GENERAL INFORMATION

1.1 Product Description

The Sanecore Musical Instrument (Shenzhen) Co., Ltd. Model: USX-800H (referred to as the EUT in this report). The EUT is a UHF Wireless Microphone designed as Low Power Auxiliary Stations for transmitting voice only. It is designed by may of utilizing the FM modulation achieves the system operating.

A major technical descriptions of EUT is described as following:

- A). Frequency Tolerance: 0.00065%(0.005%)
- B). Modulation: FM
- C). Max. Deviation Range: $\pm 68\text{KHz}$ (Limit $<\pm 75\text{KHz}$)
- E). Spurious Emissions: $<-55\text{dBc}$
- F). RF Output Power: $<10\text{mW}$ (limit: 250mW)
- G). Frequency Adjustment: Automatic Channel Setting
- B). Operation Frequency: 740-752MHz
- C). Power Supply: 1.5V (AA) $\times 2$

USX-800H WIRELESS FREQUENCY MATRIX (F06 code) (MHz)				
GROUP CHANNEL	1	2	3	4
1	740.125	740.125	740.125	740.125
2	741.500	741.950	741.225	740.800
3	743.375	743.500	742.925	741.825
4	744.600	745.675	744.325	743.075
5	746.325	747.400	745.425	745.125
6	748.500	748.625	746.875	746.675
7	750.050	750.500	748.925	747.675
8	751.875	751.875	750.175	749.075
9			751.200	750.775
10			751.875	751.875

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: U6UUSX filing to comply with FCC Part 74, Subpart H Rules.

1.3 Test Methodology

The radiated emission testing was performed according to the procedures of ANSI TIA/EIA 603 and FCC CFR 47 2.1046, 2.1047, 2.1051, 2.1053, 2.1055 and 2.1057

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

1.6 Test Facility

Site Description
EMC Lab.

: Accredited by CNAL, 2005.11.02
The certificate is valid until 2010.11
The Laboratory has been assessed and proved to be in compliance
with CNAL/AC01:2003(identical to ISO/IEC17025:1999)
The Certificate Registration Number is L2291

Accredited by TUV Rheinland Guangzhou, 2005.1
The certificate is valid until 2008.2
The Laboratory has been assessed according to the requirements
ISO/IEC 17025:1999

Accredited by FCC, July 07, 2005
The Certificate Registration Number is 709623.

Accredited by Industry Canada, August 30, 2005
The Certificate Registration Number is 46405-4480

Name of Firm
Site Location

: SHENZHEN EMTEK CO., LTD
: Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 General Technical Requirements

- a). Section 74.861(e)-1: Maximum Transmitter power less than 250mW
- b). Section 74.861(e)-3: Peak Frequency Deviation less than 75KHz
- c). Section 74.861(e)-4: Frequency Tolerance less than 0.005%
- d). Section 74.861(e)-5: Emission Bandwidth shall less than 200KHz
- e). Section 74.861(e)-6: Unwanted radiation

According to Section 74.861(1)-6, the mean power of emission shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- 1). At least 25dB on any frequency removed from the center of the authorized bandwidth by more than 50% up to and including 100% of the authorized bandwidth.
- 2). At least 35dB on any frequency removed from the center of the authorized bandwidth by more than 100% up to and including 250% of the authorized bandwidth.
- 3). At least $43+10\log_{10}(T)$ dB on any frequency removed from the center of the authorized bandwidth by more than 250%.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System

Wireless
microphone
(EUT)

Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	Wireless Microphone	Wharfedale Pro	USX-800H	UM78BLN	N/A	EUT

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment.

3. Summary Of Test Results

FCC Rules	Description Of Test	Result
§ 74.861(e)-1	Carrier Power	Compliant
§ 74.861(e)-3	Frequency Deviation	Compliant
§ 74.861(e)-4	Frequency Tolerance	Compliant
§ 74.861(e)-5	Operating Bandwidth	Compliant
§ 74.861(e)-6	Unwanted Radiation	Compliant

4. Description of test modes

The EUT (Wireless Microphone) has been tested under normal operating condition.

Three channels of EUT (the lowest channel, the middle channel and the highest channel) have been chosen for testing under Normal Operating condition. In this report, all the measured datum of the three channels have been reported. No software used to control the EUT for staying in continuous transmitting mode for testing.

1. For lowest channel : 740.125MHz(Group 1 Channel 1)
2. For middle channel : 745.675MHz(Group 2 Channel 4)
3. For highest channel: 751.875MHz(Group 4 Channel 10)

5. Maximum Transmitter Power

5.1 Provisions Applicable



According to FCC Part 74 Section 74.861(e)-1: The power of the measured unmodulated carrier power at the output of the transmitter power amplifier may not exceed 50mW.

5.2 Measurement Procedure

- 1). On a test site, the EUT shall be placed on a turntable and in the position closest to the normal use as declared by the user.
- 2). The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- 3). The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- 4). The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- 5). The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- 6). The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- 7). The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- 8). The maximum signal level detected by the measuring receiver shall be noted.
- 9). Replace the antenna with a proper Antenna (substitution antenna).
- 10). The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- 11). The substitution antenna shall be connected to a calibrated signal generator.
- 12). If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- 13). The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- 14). The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- 15). The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- 16). The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.
- 17). The measure of the effective radiated power is the larger of the two levels recorded, at the input to the substitution antenna, corrected for the gain of the substitution antenna if necessary.

5.3 Test SET-UP (Block Diagram of Configuration)

TEST SETUP OF SUBSTITUTION METHOD:



5.4 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	ANRITSU	MS2661C	6200140915	05/29/2006	05/29/2007
EMI Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2006	05/29/2007
Pre-Amplifier	HP	8447D	2944A07999	05/29/2006	05/29/2007
Bilog Antenna	Schwarzbeck	VULB9163	142	05/29/2006	05/29/2007
Loop Antenna	ARA	PLA-1030/B	1029	05/29/2006	05/29/2007

5.4 Measurement Result

The Output Power of Wireless Microphone

Operation Mode: Trimester
Test Item: Output power
Test Result: PASS

Test Date : March 20, 2007
Temperature : 28 °C
Humidity : 65 %
Test By: Andy

The bottom channel -740.125MHz(Group 1 Channel 1)

Freq.	Ant. Pol.	Reading	SGO/P	Ant. Gain	Dipole Gain	Cable	Corrected power		Limit
(MHz)	H/V	(dBuV)	(dBm)	(dB)	(dB)	(dB)	(dBm)	(mW)	(W)
740.125	V	23.45	-2.10	12.12	0	1.61	8.41	6.93	0.25
740.125	H	28.79	-3.81	12.12	0	1.61	6.70	4.67	0.25

The middle channel -745.675MHz(Group 2 Channel 4)

Freq.	Ant. Pol.	Reading	SGO/P	Ant. Gain	Dipole Gain	Cable	Corrected power		Limit
(MHz)	H/V	(dBuV)	(dBm)	(dB)	(dB)	(dB)	(dBm)	(mW)	(W)
740.125	V	25.12	-2.40	11.52	0	1.50	7.62	5.78	0.25
740.125	H	29.78	-3.15	11.52	0	1.50	6.87	4.86	0.25

The top channel -751.875MHz(Group 4 Channel 10)

Freq.	Ant.Pol.	Reading	SGO/P	Ant. Gain	Dipole Gain	Cable	Corrected power		Limit
(MHz)	H/V	(dBuV)	(dBm)	(dB)	(dB)	(dB)	(dBm)	(mW)	(W)
740.125	V	28.90	-1.50	11.13	0	1.42	8.21	6.62	0.25
740.125	H	24.85	-1.89	11.13	0	1.42	7.82	6.05	0.25

Remark:

(1) Corrected Power (dBm) = SG O/P-Cable + Ant Gain

6. Modulation Characteristics

6.1 PROVISIONS APPLICABLE

a).According to CFR 47 section 2.1047(a), for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

b). According to CFR 47 section 74.861(e)-3, any form of modulation may be used. A maximum deviation of ± 75 KHz is permitted when frequency modulation is employed.

6.2 MEASUREMENT METHOD

6.2.1 Modulation Limit

1). Configure the EUT as shown in figure 1, adjust the audio input for 60% of rated system deviation at 1KHz using this level as a reference (0dB) and vary the input level from -20 to $+20$ dB. Record the frequency deviation obtained as a function of the input level.

2). Repeat step 1 with input frequency changing to 300,1000,3000, and 14000Hz in sequence.

6.2.2 Audio Frequency Response

1). Configure the EUT as shown in figure 1.

2). Adjust the audio input for 20% of rated system deviation at 1 KHz using this level as a reference (0 dB).

3). Vary the Audio frequency from 100 Hz to 30 KHz and record the frequency deviation.




Figure 1: Modulation characteristic measurement configuration

6.3 Measurement instruments


EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	ANRITSU	MS2661C	6200140915	05/29/2006	05/29/2007
Audio Signal Generator	HP	3325A	2561540502	05/29/2006	05/29/2007
Attenuator	MINI CIRCUITS	8920B	2484357000	05/29/2006	05/29/2007

6.4 Measurement Result

a). Modulation Limit:


The top channel -751.875MHz(Group 4 Channel 10)

Modulation Level (dB)	Peak Freq. Deviation At 300Hz(KHz)	Peak Freq. Deviation At 1000Hz(KHz)	Peak Freq. Deviation At 3000Hz(KHz)	Peak Freq. Deviation At 11000Hz(KHz)
-20	6.10	6.38	8.35	10.29
-15	11.80	12.25	14.25	15.78
-10	15.84	17.58	20.10	22.48
-5	18.54	21.89	25.88	28.85
0	20.47	23.50	27.80	30.80
+5	23.87	26.85	31.57	34.48
+10	25.89	27.58	33.87	35.87
+15	26.78	29.57	34.87	36.78
+20	27.80	31.50	36.10	38.95




The middle channel -745.675MHz(Group 2 Channel 4)

Modulation Level (dB)	Peak Freq. Deviation At 300Hz(KHz)	Peak Freq. Deviation At 1000Hz(KHz)	Peak Freq. Deviation At 3000Hz(KHz)	Peak Freq. Deviation At 11000Hz(KHz)
-20	5.10	6.40	8.75	11.29
-15	11.15	12.50	14.56	16.78
-10	14.52	16.80	19.11	21.41
-5	17.56	20.18	24.13	27.81
0	19.80	22.45	27.81	30.18
+5	22.82	25.40	30.14	33.14
+10	24.50	28.58	32.45	35.98
+15	25.78	30.10	33.42	36.17
+20	27.10	31.17	35.12	39.40



The bottom channel -740.125MHz(Group 1 Channel 1)

Modulation Level (dB)	Peak Freq. Deviation At 300Hz(KHz)	Peak Freq. Deviation At 1000Hz(KHz)	Peak Freq. Deviation At 3000Hz(KHz)	Peak Freq. Deviation At 11000Hz(KHz)
-20	7.75	7.89	9.43	11.78
-15	12.85	13.45	14.08	15.81
-10	17.89	19.12	20.78	23.84
-5	21.5	23.17	25.35	29.55
0	24.71	25.14	27.86	32.78
+5	26.45	27.4	30.14	34.65
+10	28.67	29.78	32.48	36.54
+15	29.4	31.48	34.78	37.91
+20	30.1	33.46	36.97	39.78



b). Audio Frequency Response:**The top channel -751.875MHz(Group 4 Channel 10)**

Frequency(Hz)	Deviation(KHz)
100	3.15
200	3.89
300	4.25
400	4.89
500	5.10
600	5.20
700	5.48
800	6.05
900	6.20
1000	6.89
1200	7.12
1400	7.23
1600	7.52
1800	7.68
2000	7.98
2400	8.15
2800	8.21
3200	8.22
3600	8.63
4000	8.98
4500	9.10
5000	9.56
5500	9.64
6000	9.78
6500	9.89
7000	10.12
8000	10.18
9000	10.21
10000	10.34
12000	10.58
14000	10.06
16000	9.78
18000	9.42
20000	8.45
25000	8.10
30000	7.12

The middle channel -745.675MHz(Group 2 Channel 4)

Frequency(Hz)	Deviation(KHz)
100	3.14
200	3.85
300	4.21
400	4.78
500	5.01
600	5.18
700	5.42
800	6.08
900	6.20
1000	6.87
1200	7.13
1400	7.10
1600	7.45
1800	7.68
2000	7.97
2400	8.12
2800	8.19
3200	8.28
3600	8.67
4000	8.97
4500	9.15
5000	9.58
5500	9.67
6000	9.79
6500	9.82
7000	10.08
8000	10.20
9000	10.23
10000	10.25
12000	10.47
14000	10.10
16000	9.84
18000	9.39
20000	8.44
25000	8.08
30000	7.10

The bottom channel -740.125MHz(Group 1 Channel 1)

Frequency(Hz)	Deviation(KHz)
100	3.15
200	3.87
300	4.13
400	4.88
500	5.11
600	5.19
700	5.48
800	6.10
900	6.22
1000	6.87
1200	7.13
1400	7.23
1600	7.51
1800	7.67
2000	7.97
2400	8.15
2800	8.22
3200	8.53
3600	8.76
4000	8.92
4500	9.13
5000	9.58
5500	9.69
6000	9.77
6500	9.98
7000	10.12
8000	10.15
9000	10.23
10000	10.36
12000	10.51
14000	10.08
16000	9.76
18000	9.41
20000	8.45
25000	8.11
30000	7.10

7. Frequency Tolerance

7.1 Provisions Applicable

- a). According to FCC Part 2 Section 2.1055(a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$ centigrade.
- b). According to FCC Part 2 Section 2.1055(d)(2), for hand carried battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacture.
- c). According to FCC Part 74 Section 74.861(e)-4, the frequency tolerance must be maintained within 0.005%.

7.2 Measurement Procedure

7.2.1 Frequency stability versus environmental temperature

1. Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
2. Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1KHz and Video Resolution Bandwidth to 1KHz and Frequency Span to 50KHz. Record this frequency as reference frequency.
3. Set the temperature of chamber to 50°C . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
4. Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured; Record all measured frequencies on each temperature step.

7.2.2 Frequency stability versus input voltage

1. Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15°C to 25°C . Otherwise, an environment chamber set for a temperature of 20°C shall be used. Install new battery in the EUT.
2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1KHz and Video Resolution Bandwidth to 1KHz. Record this frequency as reference frequency.
3. For battery operated only device, supply the EUT primary voltage at the operating end point, which is specified by manufacturer, and record the frequency.

7.3 Test Setup Block diagram(Block diagram of configuration)




Figure 1

7.4 Test Equipment used:

EQUIPMENT TYPE	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Advantest Spectrum Analyzer	R3132	120901472	05/29/2006	05/29/2007
Shihin Temperature Chamber	BM50-CB	908	05/29/2006	05/29/2007
Huber+Suhner low loss cable	WYK-605	N/A	05/29/2006	05/29/2007
Monopole Antenna	N/A	N/A	05/29/2006	05/29/2007

7.5 Test Result

a. Frequency Stability versus input voltage(battery operation end point voltage is 2.7V)

Wireless Microphone	Reference Frequency (MHz)	Frequency Measured at end point voltage	Frequency Error (%)	Limit (%)
Top Channel	751.8750	751.8610	0.00186	0.005
Middle Channel	745.6750	745.6580	0.00228	0.005
Bottom Channel	740.1250	740.1110	0.00189	0.005

b. Frequency stability versus ambient temperature

The top channel -751.875MHz(Group 4 Channel 10)

Reference Frequency: 751.875		Limit (%) $\pm 0.005\%$	
Environment Temperature($^{\circ}\text{C}$)	Power Supply	Frequency deviation measured with time Elapse(30 minutes)	
		(MHz)	%
50	New Battery	751.88103	0.000802
40	New Battery	751.88002	0.000668
30	New Battery	751.87352	-0.000197
20	New Battery	751.87245	-0.000339
10	New Battery	751.87186	-0.000418
0	New Battery	751.87150	-0.000466
-10	New Battery	751.86980	-0.000692
-20	New Battery	751.86900	-0.000798
-30	New Battery	751.86890	-0.000811

The middle channel -745.675MHz(Group 2 Channel 4)

Reference Frequency: 745.675MHz		Limit (%) $\pm 0.005\%$	
Environment Temperature($^{\circ}\text{C}$)	Power Supply	Frequency deviation measured with time Elapse(30 minutes)	
		(MHz)	%
50	New Battery	745.68021	0.000699
40	New Battery	745.68013	0.000688
30	New Battery	745.66912	-0.000789
20	New Battery	745.66895	-0.000811
10	New Battery	745.66838	-0.000888
0	New Battery	745.66821	-0.000911
-10	New Battery	745.66810	-0.000925
-20	New Battery	745.67952	0.000606
-30	New Battery	745.67905	0.000543

The bottom channel -740.125MHz(Group 1 Channel 1)

Reference Frequency: 740.125MHz		Limit (%) $\pm 0.005\%$	
Environment Temperature($^{\circ}\text{C}$)	Power Supply	Frequency deviation measured with time Elapse(30 minutes)	
		(MHz)	%
50	New Battery	740.12812	0.000422
40	New Battery	740.12789	0.000390
30	New Battery	740.12680	0.000243
20	New Battery	740.12600	0.000135
10	New Battery	740.12420	-0.000108
0	New Battery	740.12415	-0.000115
-10	New Battery	740.12300	-0.000270
-20	New Battery	740.12150	-0.000473
-30	New Battery	740.12089	-0.000555

8. Emission Bandwidth


8.1 Provisions Applicable

According to FCC Part 74 Section 74.861(e)-5: The operation bandwidth shall not exceed 200 KHz

8.2 MEASUREMENT PROCEDURE

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). Set EUT as normal operation
- 3). Set SPA Center Frequency = fundamental frequency , RBW,VBW= 1 KHz, Span =200 KHz.
- 4). Set SPA Max hold. Mark peak, -26dB.

8.3 TEST SETUP BLOCK DIAGRAM (Block Diagram of Configuration)



8.4 Measurement Equipment used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	ANRITSU	MS2661C	6200140915	05/29/2006	05/29/2007
EMI Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2006	05/29/2007
Pre-Amplifier	HP	8447D	2944A07999	05/29/2006	05/29/2007
Bilog Antenna	Schwarzbeck	VULB9163	142	05/29/2006	05/29/2007

8.5 Measurement Result:

The Occupied bandwidth's plot is presented on the following pager, which illustrates compliance with the rules.

Calculation of Necessary Bandwidth (Bn)

$B_n = 2M + 2KD$

M=Max.Modulation Frequency =11KHz

D=Peak Frequency Deviation=39.78KHz (Page 18).

K=1

$B_n = 101.56\text{KHz}$

Emission Type: F3E

Emission designator: 101K56F3E.


Refer to attached data chart

The High channel 26dB Bandwidth is 128.5KHz.


The Middle channel 26dB Bandwidth is 115.0KHz.

The Bottom channel 26dB Bandwidth is 115.0KHz.

The top channel -751.875MHz(Group 4 Channel 10)



The middle channel -745.675MHz(Group 2 Channel 4)



The bottom channel -740.125MHz(Group 1 Channel 1)



9. Unwanted Radiation

9.1 Provisions applicable


According to Section 74.861(e)-6, The mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- 1). On any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: at least 25 dB;
- 2). On any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: at least 35 dB;
- 3). On any frequency removed from the operating frequency.


9.2 MEASUREMENT PROCEDURE

- 1). On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- 2). The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- 3). The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- 4). The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- 5). The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- 6). The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- 7). The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- 8). The maximum signal level detected by the measuring receiver shall be noted.
- 9). The measurement shall be repeated with the test antenna set to horizontal polarization.
- 10). Replace the antenna with a proper Antenna (substitution antenna).
- 11). The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- 12). The substitution antenna shall be connected to a calibrated signal generator.
- 13). If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- 14). The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
- 15). The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
- 16). The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
- 17). The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.


9.3 Test Setup Block Diagram(block diagram of configuration)



Radiation below 1GHz



Radiation above 1GHz



9.4 Measurement Equipment used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	ANRITSU	MS2661C	6200140915	05/29/2006	05/29/2007
EMI Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/29/2006	05/29/2007
Pre-Amplifier	HP	8447D	2944A07999	05/29/2006	05/29/2007
Bilog Antenna	Schwarzbeck	VULB9163	142	05/29/2006	05/29/2007
Horn Antenna	ARA	DRG-118/A	105	05/29/2006	05/29/2007

9.5 Measurement Results:

Calculation: Limit(dBm)= EL-43-10log10(TP)

Notes: EL is the emission level of the output power expressed in dBm, in this application. The EL is 8.41dBm.

Limit(dBm)= 8.41-43-10log10(0.00693)=-13


Top Channel & Middle channel & Bottom Channel

Frequency (MHz)	Reading level (dBm)	Antena Polarization	S.G (dBm)	Cable loss (Db)	Ant.Gain (dB)	Emission Level (dBm)	Limit (dBm)	Margin (dB)
1503.75		V	-45.89	1.91	12.21	-35.59	-13	-22.59
1503.75		H	-37.10	1.91	12.21	-26.80	-13	-13.80
1491.35		V	-43.10	1.93	12.15	-32.88	-13	-19.88
1491.35		H	-36.10	1.93	12.15	-25.88	-13	-12.88
1480.25		V	-50.40	1.98	12.03	-40.35	-13	-27.35
1480.25		H	-44.89	1.98	12.03	-34.84	-13	-21.84
*	*						-13	


Note: * means the output power of all the spurious frequency is at least 20dB down to the limit.

9.6 Radiation Emission Mask:


The top channel -751.875MHz(Group 4 Channel 10)



The middle channel -745.675MHz(Group 2 Channel 4)



The bottom channel -740.125MHz(Group 1 Channel 1)



APPENDIX 1

PHOTOGRAPHS OF SET UP



APPENDIX 2

PHOTOGRAPHS OF EUT

UP View of EUT




Bottom View of EUT




Side of EUT




Internal of EUT




Internal of EUT




Internal of EUT



Internal of EUT



Internal of EUT



Internal of EUT

