

Report No.: HCTR1006FR15-2 FCC ID: U88GSR-2630D1-SPR DATE : Sep 04, 2010

11. RF EXPOSURE STATEMENT

1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range	Electric field	Magnetic field	Power density	Averaging time
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm²)	(minutes)
0.3 - 1.34	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/ f²) 0.2 f/1500 1.0	30 30 30 30 30

F = frequency in MHz

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$S = PG/4\pi R^2$

- S = Power density
- P = power input to antenna
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna

^{* =} Plane-wave equivalent power density



Report No.: HCTR1006FR15-2 FCC ID: U88GSR-2630D1-SPR DATE : Sep 04, 2010

Max Peak output Power at antenna input terminal	30.32000	dBm
Max Peak output Power at antenna input terminal	1076.46521	mW
Prediction distance	40.00000	cm
Prediction frequency	2640.50000	MHz
Antenna Gain(typical)	12.00000	dBi
Antenna Gain(numeric)	15.84893	_
Power density at prediction frequency (S)	0.99171	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.00000	mW/cm ²

3. RESULTS

The power density level at 40 cm is 0.99171 mW/cm², which is below the uncontrolled exposure limit of 1.0 mW/cm² at 2640.5 MHz for BRS band.

Warning: In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, it must also have a minimum distance of 40 cm from the body during normal operation.