

FCC TEST REPORT

REPORT NO.: RF120730E04

MODEL NO.: MAX BR1, MAX, Surf Pro, AP One, AP Pro,
Device Connector, Express, Balance,
Pismo 730

FCC ID: U8G-P1710

RECEIVED: July 30, 2012

TESTED: Aug. 06 to 16, 2012

ISSUED: Aug. 28, 2012

APPLICANT: Pismo Labs Technology Limited

ADDRESS: 1703A, 17/F, PARK BUILDING 476 CASTLE PEAK
ROAD CHEUNG SHA WAN HONG KONG

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan,
R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by TAF
or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Table of Contents

RELEASE CONTROL RECORD	4
1. CERTIFICATION	5
2. SUMMARY OF TEST RESULTS	6
2.1 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	10
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	11
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
3.4 DESCRIPTION OF SUPPORT UNITS.....	15
3.5 CONFIGURATION OF SYSTEM UNDER TEST	16
4. TEST TYPES AND RESULTS	19
4.1 CONDUCTED EMISSION MEASUREMENT	19
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	19
4.1.2 TEST INSTRUMENTS.....	19
4.1.3 TEST PROCEDURES	20
4.1.4 DEVIATION FROM TEST STANDARD	20
4.1.5 TEST SETUP	21
4.1.6 EUT OPERATING CONDITIONS	21
4.1.7 TEST RESULTS (MODE 1)	22
4.1.8 TEST RESULTS (MODE 2)	24
4.1.9 TEST RESULTS (MODE 3)	26
4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT	28
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	28
4.2.2 TEST INSTRUMENTS.....	29
4.2.3 TEST PROCEDURES	30
4.2.4 DEVIATION FROM TEST STANDARD	30
4.2.5 TEST SETUP	31
4.2.6 EUT OPERATING CONDITIONS	31
4.2.7 TEST RESULTS	32
4.3 6dB BANDWIDTH MEASUREMENT	45
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	45
4.3.2 TEST INSTRUMENTS.....	45
4.3.3 TEST PROCEDURE.....	45
4.3.4 DEVIATION FROM TEST STANDARD	45
4.3.5 TEST SETUP	45
4.3.6 EUT OPERATING CONDITIONS	45
4.3.7 TEST RESULTS	46
4.4 CONDUCTED OUTPUT POWER MEASUREMENT	47
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	47



A D T

4.4.2	INSTRUMENTS.....	47
4.4.3	TEST PROCEDURES	47
4.4.4	DEVIATION FROM TEST STANDARD	47
4.4.5	TEST SETUP	47
4.4.6	EUT OPERATING CONDITIONS	47
4.4.7	TEST RESULTS	48
4.5	POWER SPECTRAL DENSITY MEASUREMENT.....	49
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	49
4.5.2	TEST INSTRUMENTS.....	49
4.5.3	TEST PROCEDURE.....	49
4.5.4	DEVIATION FROM TEST STANDARD	49
4.5.5	TEST SETUP	49
4.5.6	EUT OPERATING CONDITION.....	49
4.5.7	TEST RESULTS	50
4.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	51
4.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	51
4.6.2	TEST INSTRUMENTS.....	51
4.6.3	TEST PROCEDURE.....	51
4.6.4	DEVIATION FROM TEST STANDARD	52
4.6.5	TEST SETUP	52
4.6.6	EUT OPERATING CONDITION.....	52
4.6.7	TEST RESULTS	52
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	57
6.	INFORMATION ON THE TESTING LABORATORIES	58
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	59



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120730E04	Original release	Aug. 28, 2012

1. CERTIFICATION

PRODUCT: Pepwave, Peplink, Pismo Wireless Product

BRAND NAME: Pepwave, Peplink, Pismo

MODEL NO.: MAX BR1, MAX, Surf Pro, AP One, AP Pro, Device Connector, Express, Balance, Pismo 730

TEST SAMPLE: R&D SAMPLE

APPLICANT: Pismo Labs Technology Limited

TESTED: Aug. 06 to 16, 2012

STANDARDS: **FCC Part 15, Subpart C (Section 15.247)**
ANSI C63.10-2009

The above equipment (Model: MAX BR1) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Phoenix Huang , **DATE:** Aug. 28, 2012
(Phoenix Huang, Specialist)

APPROVED BY : May Chen , **DATE:** Aug. 28, 2012
(May Chen, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -3.09dB at 0.21641MHz
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -0.8dB at 2390.00MHz and 4924.00MHz
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is IPEX not a standard connector.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.98 dB
Radiated emissions (30MHz-1GHz)	5.59 dB
Radiated emissions (1GHz-6GHz)	3.56 dB
Radiated emissions (6GHz-18GHz)	4.10 dB
Radiated emissions (18GHz-40GHz)	4.24 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Pepwave, Peplink, Pismo Wireless Product
MODEL NO.	MAX BR1, MAX, Surf Pro, AP One, AP Pro, Device Connector, Express, Balance, Pismo 730
POWER SUPPLY	DC 12V from power adapter or DC 10~30V from terminal block
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: Up to 11Mbps 802.11g: Up to 54Mbps 802.11n (HT20, 800ns GI): Up to 65Mbps 802.11n (HT40, 800ns GI): Up to 135Mbps 802.11n (HT20, 400ns GI): Up to 72.2Mbps 802.11n (HT40, 400ns GI): Up to 150Mbps
OPERATING FREQUENCY	2.412 ~ 2.462GHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
MAXIMUM OUTPUT POWER	802.11b: 489.779mW 802.11g: 977.237mW 802.11n (HT20): 954.993mW 802.11n (HT40): 537.032mW
ANTENNA TYPE	Please see NOTE
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	NA

NOTE:

- The EUT has three product names, three brand name and nine model names, which are identical to each other in all aspects except for the following table:

Product name	Pepwave, Peplink, Pismo Wireless Product
Brand Name	Pepwave, Peplink, Pismo
Model Name	MAX BR1, MAX, Surf Pro, AP One, AP Pro, Device Connector, Express, Balance, Pismo 730

2. The antennas provided to the EUT, please refer to the following table:

WLAN Antenna Spec.						
No	Brand	Model	Antenna Type	Gain(dBi)	Connector Type	Frequency range (GHz)
1	WNC	9E.XCI15.001	Dipole	5.1	I-PEX	2.4 ~ 2.5
GPS Antenna Spec.						
No	Brand	Model	Antenna Type	Gain(dBi)	Connector Type	Frequency range (GHz)
1	Chang Hong	GPS-01	Magnetic	-1	R-SMA Male	1.57542 (+/- 1.023)
LTE Antenna Spec.						
No	Brand	Model	Antenna Type	Gain(dBi)	Connector Type	Frequency range (MHz)
1	Pulse	SPDA24700/2700	Dipole	2	R-SMA	698-960/1710-2170/2500-2700
2	Pulse	SPDA24700/2700	Dipole	2	R-SMA	698-960/1710-2170/2500-2700

3. The EUT must be supplied with a power adapter as following table:

BRAND	Ten Pao
MODEL	S024EM1200200
INPUT POWER	AC 100-240V, 50/60Hz, 600mA
OUTPUT POWER	DC 12V, 2000mA DC Cable: 1.5m shielded with one core

4. The EUT incorporates a SISO function without beam forming.

MODULATION MODE	TX/RX FUNCTION
802.11b	1Tx/1Rx
802.11g	1Tx/1Rx
802.11n (HT20)	1Tx/1Rx
802.11n (HT40)	1Tx/1Rx

5. Conducted emission and Radiated emission of the simultaneous operation has been evaluated and no non-compliance found. (WLAN and LTE technology can transmit at same time.)

6. The EUT inside has one LTE Module which FCC ID: N7NMC7700

7. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 7.

8. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	APCM	OB	
1	√	√	√	√	√	30V _{dc} (from terminal block)
2	√	-	-	-	-	10V _{dc} (from terminal block)
3	√	-	-	-	-	12V _{dc} (from power adapter)

Where **PLC**: Power Line Conducted Emission **RE < 1G**: Radiated Emission below 1GHz
RE ≥ 1G: Radiated Emission above 1GHz **APCM**: Antenna Port Conducted Measurement
OB: Conducted Out-Band Emission Measurement

NOTE: The EUT had been pre-tested input power of 12V_{dc} (from power adapter), 10V_{dc} (from terminal block) and 30V_{dc} (from terminal block). The radiated emission worst case was found when input power of 30V_{dc} (from power supply).

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	BPSK	6

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	BPSK	6

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5



A D T

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
PLC	25deg. C, 65%RH	120Vac, 60Hz	Kyle Huang
	25deg. C, 65%RH	120Vac, 60Hz (SYSTEM)	Kyle Huang
RE<1G	26deg. C, 67%RH	DC 30V	Robert Cheng
RE ³ 1G	25deg. C, 65%RH	DC 30V	Robert Cheng
APCM	25deg. C, 60%RH	DC 30V	Rex Huang
OB	25deg. C, 60%RH	DC 30V	Rex Huang

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

558074 D01 DTS Meas Guidance v01

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	FSLB32S	FCC DoC
2	NOTEBOOK COMPUTER	DELL	PP32LA	GSLB32S	FCC DoC
3	HUB	ZyXEL	ES-116P	S060H0200021 5	FCC DoC
4	DC POWER SUPPLY	Topward	6603D	795558	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	UTP cable, 10m
2	UTP cable, 10m
3	UTP cable, 10m
4	DC cable, 2m


NOTE: All power cords of the above support units are non shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST


For Conducted Emission (Mode 3) test:



For Conducted Emission (Mode 1 ~ 2) test:



For other test items:



4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS 30	100287	Feb. 29, 2012	Feb. 28, 2013
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK 8127	8127-523	Sep. 20, 2011	Sep. 19, 2012
Line-Impedance Stabilization Network (for Peripheral) ROHDE & SCHWARZ	ESH3-Z5	848773/004	Nov. 01, 2011	Oct. 31, 2012
RF Cable (JYEBAO)	5DFB	COACAB-002	Aug. 05, 2012	Aug. 04, 2013
50 ohms Terminator	50	4	Nov. 12, 2011	Nov. 11, 2012
Software ADT	BV ADT_Cond_V7.3.7 .3	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. A.
3. The VCCI Con A Registration No. is C-817.
4. Tested Date: Aug. 16, 2012

4.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

Note: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

1. Placed the EUT on testing table.
2. Controlling software (art.exe [v0.9B21]) has been activated to set the EUT under transmission/receiving condition continuously.


4.1.7 TEST RESULTS (MODE 1)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16441	0.06	60.68	40.41	60.74	40.47	65.24	55.24	-4.50	-14.77
2	0.34141	0.07	55.22	24.20	55.29	24.27	59.17	49.17	-3.88	-24.90
3	0.50156	0.08	51.74	23.42	51.82	23.50	56.00	46.00	-4.18	-22.50
4	0.95469	0.12	50.09	29.10	50.21	29.22	56.00	46.00	-5.79	-16.78
5	1.28516	0.14	41.26	23.29	41.40	23.43	56.00	46.00	-14.60	-22.57
6	2.51172	0.21	42.45	32.97	42.66	33.18	56.00	46.00	-13.34	-12.82

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	0.07	60.82	40.62	60.89	40.69	65.38	55.38	-4.49	-14.69
2	0.21641	0.07	59.79	28.50	59.86	28.57	62.96	52.96	-3.09	-24.38
3	0.34531	0.08	54.99	24.12	55.07	24.20	59.07	49.07	-4.01	-24.88
4	0.48984	0.09	52.15	28.37	52.24	28.46	56.17	46.17	-3.93	-17.71
5	0.82969	0.11	51.72	23.17	51.83	23.28	56.00	46.00	-4.17	-22.72
6	1.14063	0.13	44.37	23.60	44.50	23.73	56.00	46.00	-11.50	-22.27

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.1.8 TEST RESULTS (MODE 2)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16597	0.06	61.38	40.18	61.44	40.24	65.16	55.16	-3.72	-14.92
2	0.28281	0.06	57.15	33.94	57.21	34.00	60.73	50.73	-3.52	-16.73
3	0.37266	0.07	53.62	21.57	53.69	21.64	58.44	48.44	-4.75	-26.80
4	0.62266	0.09	45.22	17.78	45.31	17.87	56.00	46.00	-10.69	-28.13
5	0.84922	0.11	40.67	18.48	40.78	18.59	56.00	46.00	-15.22	-27.41
6	2.57422	0.21	43.72	33.75	43.93	33.96	56.00	46.00	-12.07	-12.04

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	0.07	61.50	40.70	61.57	40.77	65.38	55.38	-3.81	-14.61
2	0.21641	0.07	59.11	27.91	59.18	27.98	62.96	52.96	-3.77	-24.97
3	0.38828	0.08	52.30	20.89	52.38	20.97	58.10	48.10	-5.72	-27.13
4	0.56797	0.09	46.46	20.09	46.55	20.18	56.00	46.00	-9.45	-25.82
5	0.80625	0.11	40.70	15.01	40.81	15.12	56.00	46.00	-15.19	-30.88
6	2.52734	0.20	40.04	31.03	40.24	31.23	56.00	46.00	-15.76	-14.77

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.1.9 TEST RESULTS (MODE 3)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	0.06	53.75	45.62	53.81	45.68	65.18	55.18	-11.37	-9.50
2	0.21641	0.06	48.92	38.15	48.98	38.21	62.96	52.96	-13.97	-14.74
3	0.25156	0.06	44.94	34.27	45.00	34.33	61.71	51.71	-16.70	-17.37
4	0.50156	0.08	44.50	40.88	44.58	40.96	56.00	46.00	-11.42	-5.04
5	12.80859	0.47	34.32	29.26	34.79	29.73	60.00	50.00	-25.21	-20.27
6	18.24219	0.58	34.46	29.64	35.04	30.22	60.00	50.00	-24.96	-19.78

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	0.07	56.59	46.00	56.66	46.07	65.38	55.38	-8.72	-9.31
2	0.25547	0.07	43.49	34.71	43.56	34.78	61.58	51.58	-18.01	-16.79
3	0.49766	0.09	41.93	37.58	42.02	37.67	56.04	46.04	-14.02	-8.37
4	1.72656	0.16	34.00	29.85	34.16	30.01	56.00	46.00	-21.84	-15.99
5	6.91797	0.31	34.49	29.51	34.80	29.82	60.00	50.00	-25.20	-20.18
6	14.21094	0.48	35.05	30.61	35.53	31.09	60.00	50.00	-24.47	-18.91

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer Agilent	E4446A	MY48250254	July 09, 2012	July 08, 2013
Pre-Selector Agilent	N9039A	MY46520311	July 09, 2012	July 08, 2013
Signal Generator Agilent	N5181A	MY49060517	July 09, 2012	July 08, 2013
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-03	Nov. 15, 2011	Nov. 14, 2012
Pre-Amplifier Agilent	8449B	3008A02578	June 26, 2012	June 25, 2013
Pre-Amplifier SPACEK LABS	SLKKA-48-6	9K16	Nov. 15, 2011	Nov. 14, 2012
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-360	Apr. 09, 2012	Apr. 08, 2013
Horn_Antenna AISL	AIH.8018	0000320091110	Nov. 14, 2011	Nov. 13, 2012
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Oct. 07, 2011	Oct. 06, 2012
RF Cable	NA	RF104-201 RF104-203 RF104-204	Dec. 26, 2011	Dec. 25, 2012
RF Cable	NA	CHGCAB_001	Oct. 07, 2011	Oct. 06, 2012
Software	ADT_Radiated _V8.7.05	NA	NA	NA
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
5. The VCCI Site Registration No. is G-137.
6. The CANADA Site Registration No. is IC 7450H-2.
7. Tested Date: Aug. 06 to 16, 2012

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

802.11g

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	200.05	38.9 QP	43.5	-4.6	1.50 H	238	27.73	11.16
2	214.86	38.7 QP	43.5	-4.8	1.50 H	254	26.92	11.81
3	250.03	37.4 QP	46.0	-8.6	1.00 H	59	24.02	13.35
4	399.95	35.9 QP	46.0	-10.1	1.00 H	306	18.05	17.86
5	608.97	39.6 QP	46.0	-6.4	1.50 H	360	16.85	22.77
6	750.01	33.1 QP	46.0	-12.9	1.50 H	314	8.15	24.91
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	33.67	35.9 QP	40.0	-4.1	1.00 V	80	22.98	12.96
2	55.93	34.3 QP	40.0	-5.7	1.00 V	103	20.51	13.83
3	106.74	35.4 QP	43.5	-8.1	1.50 V	278	24.64	10.79
4	250.03	38.0 QP	46.0	-8.0	1.00 V	307	24.69	13.35
5	399.95	35.5 QP	46.0	-10.6	1.00 V	257	17.59	17.86
6	599.97	43.3 QP	46.0	-2.7	1.50 V	332	20.62	22.66

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

ABOVE 1GHz DATA

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2386.30	57.9 PK	74.0	-16.1	1.12 H	322	25.93	31.97
2	2386.30	47.5 AV	54.0	-6.5	1.12 H	322	15.53	31.97
3	*2412.00	102.2 PK			1.12 H	322	70.15	32.05
4	*2412.00	99.8 AV			1.12 H	322	67.75	32.05
5	4824.00	49.0 PK	74.0	-25.0	1.47 H	135	9.42	39.58
6	4824.00	40.2 AV	54.0	-13.8	1.47 H	135	0.62	39.58
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2386.23	60.8 PK	74.0	-13.2	1.09 V	36	28.83	31.97
2	2386.23	52.9 AV	54.0	-1.1	1.09 V	36	20.93	31.97
3	*2412.00	107.2 PK			1.09 V	36	75.15	32.05
4	*2412.00	104.7 AV			1.09 V	36	72.65	32.05
5	4824.00	51.5 PK	74.0	-22.5	1.87 V	358	11.92	39.58
6	4824.00	45.2 AV	54.0	-8.8	1.87 V	358	5.62	39.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	106.4 PK			1.09 H	319	74.28	32.12
2	*2437.00	104.5 AV			1.09 H	319	72.38	32.12
3	4874.00	54.5 PK	74.0	-19.5	1.48 H	227	14.80	39.70
4	4874.00	50.9 AV	54.0	-3.1	1.48 H	227	11.20	39.70
5	7311.00	54.4 PK	74.0	-19.6	1.04 H	205	6.81	47.59
6	7311.00	41.9 AV	54.0	-12.1	1.04 H	205	-5.69	47.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2389.36	58.0 PK	74.0	-16.0	1.11 V	157	26.02	31.98
2	2389.36	48.0 AV	54.0	-6.0	1.11 V	157	16.06	31.98
3	*2437.00	112.4 PK			1.11 V	157	80.28	32.12
4	*2437.00	110.2 AV			1.11 V	157	78.08	32.12
5	2484.85	57.5 PK	74.0	-16.5	1.11 V	157	25.26	32.24
6	2484.85	45.4 AV	54.0	-8.6	1.11 V	157	13.16	32.24
7	4874.00	55.9 PK	74.0	-18.1	1.88 V	327	16.20	39.70
8	4874.00	53.1 AV	54.0	-0.9	1.88 V	327	13.40	39.70
9	7311.00	54.3 PK	74.0	-19.7	1.00 V	125	6.71	47.59
10	7311.00	41.6 AV	54.0	-12.4	1.00 V	125	-5.99	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.4 PK			1.10 H	317	71.22	32.18
2	*2462.00	101.1 AV			1.10 H	317	68.92	32.18
3	2487.68	57.8 PK	74.0	-16.2	1.10 H	317	25.55	32.25
4	2487.68	46.3 AV	54.0	-7.7	1.10 H	317	14.05	32.25
5	4924.00	53.4 PK	74.0	-20.6	1.44 H	236	13.56	39.84
6	4924.00	47.0 AV	54.0	-7.0	1.44 H	236	7.16	39.84
7	7386.00	54.7 PK	74.0	-19.3	1.00 H	214	7.18	47.52
8	7386.00	41.5 AV	54.0	-12.5	1.00 H	214	-6.02	47.52
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.3 PK			1.05 V	277	78.12	32.18
2	*2462.00	107.8 AV			1.05 V	277	75.62	32.18
3	2487.69	59.8 PK	74.0	-14.2	1.05 V	277	27.55	32.25
4	2487.69	51.8 AV	54.0	-2.2	1.05 V	277	19.55	32.25
5	4924.00	55.9 PK	74.0	-18.1	1.85 V	327	16.06	39.84
6	4924.00	53.2 AV	54.0	-0.8	1.85 V	327	13.36	39.84
7	7386.00	54.1 PK	74.0	-19.9	1.00 V	125	6.58	47.52
8	7386.00	41.4 AV	54.0	-12.6	1.00 V	125	-6.12	47.52

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.8 PK	74.0	-12.2	1.08 H	320	29.82	31.98
2	2390.00	48.4 AV	54.0	-5.6	1.08 H	320	16.42	31.98
3	*2412.00	106.2 PK			1.08 H	320	74.15	32.05
4	*2412.00	96.4 AV			1.08 H	320	64.35	32.05
5	4824.00	46.5 PK	74.0	-27.5	1.49 H	148	6.92	39.58
6	4824.00	34.5 AV	54.0	-19.5	1.49 H	148	-5.08	39.58
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.0 PK	74.0	-4.0	1.08 V	32	38.02	31.98
2	2390.00	52.8 AV	54.0	-1.2	1.08 V	32	20.82	31.98
3	*2412.00	111.0 PK			1.08 V	32	78.95	32.05
4	*2412.00	100.3 AV			1.08 V	32	68.25	32.05
5	4824.00	51.1 PK	74.0	-22.9	1.87 V	329	11.52	39.58
6	4824.00	34.6 AV	54.0	-19.4	1.87 V	329	-4.98	39.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	109.1 PK			1.09 H	325	76.98	32.12
2	*2437.00	99.0 AV			1.09 H	325	66.88	32.12
3	4874.00	50.4 PK	74.0	-23.6	1.49 H	212	10.70	39.70
4	4874.00	37.3 AV	54.0	-16.7	1.49 H	212	-2.40	39.70
5	7311.00	53.9 PK	74.0	-20.1	1.01 H	190	6.31	47.59
6	7311.00	41.4 AV	54.0	-12.6	1.01 H	190	-6.19	47.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	113.4 PK			1.10 V	155	81.28	32.12
2	*2437.00	103.2 AV			1.10 V	155	71.08	32.12
3	4874.00	51.2 PK	74.0	-22.8	1.90 V	336	11.50	39.70
4	4874.00	37.4 AV	54.0	-16.6	1.90 V	336	-2.30	39.70
5	7311.00	53.9 PK	74.0	-20.1	1.01 V	131	6.31	47.59
6	7311.00	41.5 AV	54.0	-12.5	1.01 V	131	-6.09	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.5 PK			1.07 H	311	74.32	32.18
2	*2462.00	96.6 AV			1.07 H	311	64.42	32.18
3	2483.50	60.6 PK	74.0	-13.4	1.07 H	311	28.36	32.24
4	2483.50	47.1 AV	54.0	-6.9	1.07 H	311	14.86	32.24
5	4924.00	48.9 PK	74.0	-25.1	1.47 H	244	9.06	39.84
6	4924.00	36.4 AV	54.0	-17.6	1.47 H	244	-3.44	39.84
7	7386.00	55.3 PK	74.0	-18.7	1.05 H	220	7.78	47.52
8	7386.00	41.8 AV	54.0	-12.2	1.05 H	220	-5.72	47.52
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	112.4 PK			1.05 V	276	80.22	32.18
2	*2462.00	102.1 AV			1.05 V	276	69.92	32.18
3	2483.50	68.8 PK	74.0	-5.2	1.05 V	276	36.56	32.24
4	2483.50	53.1 AV	54.0	-0.9	1.05 V	276	20.86	32.24
5	4924.00	51.8 PK	74.0	-22.2	1.85 V	313	11.96	39.84
6	4924.00	36.5 AV	54.0	-17.5	1.85 V	313	-3.34	39.84
7	7386.00	54.7 PK	74.0	-19.3	1.01 V	121	7.18	47.52
8	7386.00	41.6 AV	54.0	-12.4	1.01 V	121	-5.92	47.52

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.9 PK	74.0	-12.1	1.11 H	328	29.92	31.98
2	2390.00	49.1 AV	54.0	-4.9	1.11 H	328	17.12	31.98
3	*2412.00	105.5 PK			1.11 H	328	73.45	32.05
4	*2412.00	95.8 AV			1.11 H	328	63.75	32.05
5	4824.00	46.4 PK	74.0	-27.6	1.49 H	160	6.82	39.58
6	4824.00	34.1 AV	54.0	-19.9	1.49 H	160	-5.48	39.58
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.1 PK	74.0	-3.9	1.10 V	33	38.12	31.98
2	2390.00	53.2 AV	54.0	-0.8	1.10 V	33	21.22	31.98
3	*2412.00	110.2 PK			1.10 V	33	78.15	32.05
4	*2412.00	99.7 AV			1.10 V	33	67.65	32.05
5	4824.00	51.0 PK	74.0	-23.0	1.81 V	341	11.42	39.58
6	4824.00	34.7 AV	54.0	-19.3	1.81 V	341	-4.88	39.58

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	111.0 PK			1.11 H	332	78.88	32.12
2	*2437.00	98.3 AV			1.11 H	332	66.18	32.12
3	4874.00	50.3 PK	74.0	-23.7	1.44 H	214	10.60	39.70
4	4874.00	37.5 AV	54.0	-16.5	1.44 H	214	-2.20	39.70
5	7311.00	53.4 PK	74.0	-20.6	1.02 H	181	5.81	47.59
6	7311.00	41.0 AV	54.0	-13.0	1.02 H	181	-6.59	47.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.4 PK	74.0	-9.6	1.13 V	35	32.42	31.98
2	2390.00	47.9 AV	54.0	-6.1	1.13 V	35	15.92	31.98
3	*2437.00	113.6 PK			1.13 V	157	81.48	32.12
4	*2437.00	103.4 AV			1.13 V	157	71.28	32.12
5	2483.50	61.7 PK	74.0	-12.3	1.07 V	281	29.46	32.24
6	2483.50	47.2 AV	54.0	-6.8	1.07 V	281	14.96	32.24
7	4874.00	51.3 PK	74.0	-22.7	1.86 V	340	11.60	39.70
8	4874.00	37.5 AV	54.0	-16.5	1.86 V	340	-2.20	39.70
9	7311.00	53.3 PK	74.0	-20.7	1.00 V	123	5.71	47.59
10	7311.00	41.0 AV	54.0	-13.0	1.00 V	123	-6.59	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	105.7 PK			1.08 H	316	73.52	32.18
2	*2462.00	95.6 AV			1.08 H	316	63.42	32.18
3	2483.50	60.1 PK	74.0	-13.9	1.08 H	316	27.86	32.24
4	2483.50	47.3 AV	54.0	-6.7	1.08 H	316	15.06	32.24
5	4924.00	49.5 PK	74.0	-24.5	1.46 H	239	9.66	39.84
6	4924.00	36.8 AV	54.0	-17.2	1.46 H	239	-3.04	39.84
7	7386.00	54.8 PK	74.0	-19.2	1.00 H	220	7.28	47.52
8	7386.00	41.4 AV	54.0	-12.6	1.00 H	220	-6.12	47.52
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.6 PK			1.07 V	279	79.42	32.18
2	*2462.00	101.3 AV			1.07 V	279	69.12	32.18
3	2483.50	70.7 PK	74.0	-3.3	1.06 V	279	38.46	32.24
4	2483.50	52.9 AV	54.0	-1.1	1.06 V	279	20.66	32.24
5	4924.00	52.3 PK	74.0	-21.7	1.82 V	309	12.46	39.84
6	4924.00	36.9 AV	54.0	-17.1	1.82 V	309	-2.94	39.84
7	7386.00	54.4 PK	74.0	-19.6	1.01 V	132	6.88	47.52
8	7386.00	41.4 AV	54.0	-12.6	1.01 V	132	-6.12	47.52

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.3 PK	74.0	-12.7	1.12 H	317	29.32	31.98
2	2390.00	48.8 AV	54.0	-5.2	1.12 H	317	16.82	31.98
3	*2422.00	100.3 PK			1.12 H	317	68.22	32.08
4	*2422.00	89.9 AV			1.12 H	317	57.82	32.08
5	4844.00	49.2 PK	74.0	-24.8	1.47 H	233	9.57	39.63
6	4844.00	36.5 AV	54.0	-17.5	1.47 H	233	-3.13	39.63
7	7266.00	55.8 PK	74.0	-18.2	1.01 H	220	8.20	47.60
8	7266.00	42.0 AV	54.0	-12.0	1.01 H	220	-5.60	47.60
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.8 PK	74.0	-8.2	1.08 V	34	33.82	31.98
2	2390.00	53.1 AV	54.0	-0.9	1.08 V	34	21.12	31.98
3	*2422.00	105.3 PK			1.08 V	34	73.22	32.08
4	*2422.00	95.1 AV			1.08 V	34	63.02	32.08
5	4844.00	51.7 PK	74.0	-22.3	1.86 V	301	12.07	39.63
6	4844.00	36.7 AV	54.0	-17.3	1.86 V	301	-2.93	39.63
7	7266.00	55.1 PK	74.0	-18.9	1.00 V	122	7.50	47.60
8	7266.00	42.1 AV	54.0	-11.9	1.00 V	122	-5.50	47.60

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.9 PK			1.11 H	317	71.78	32.12
2	*2437.00	92.8 AV			1.11 H	317	60.68	32.12
3	4874.00	49.0 PK	74.0	-25.0	1.43 H	258	9.30	39.70
4	4874.00	36.5 AV	54.0	-17.5	1.43 H	258	-3.20	39.70
5	7311.00	55.1 PK	74.0	-18.9	1.07 H	213	7.51	47.59
6	7311.00	41.3 AV	54.0	-12.7	1.07 H	213	-6.29	47.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.2 PK	74.0	-6.8	1.11 V	233	35.22	31.98
2	2390.00	52.6 AV	54.0	-1.4	1.11 V	233	20.62	31.98
3	*2437.00	108.5 PK			1.10 V	231	76.38	32.12
4	*2437.00	97.9 AV			1.10 V	231	65.78	32.12
5	2483.50	64.2 PK	74.0	-9.8	1.10 V	231	31.96	32.24
6	2483.50	49.1 AV	54.0	-4.9	1.10 V	231	16.86	32.24
7	4874.00	52.0 PK	74.0	-22.0	1.83 V	301	12.30	39.70
8	4874.00	36.5 AV	54.0	-17.5	1.83 V	301	-3.20	39.70
9	7311.00	54.1 PK	74.0	-19.9	1.07 V	105	6.51	47.59
10	7311.00	41.2 AV	54.0	-12.8	1.07 V	105	-6.39	47.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	102.8 PK			1.08 H	315	70.64	32.16
2	*2452.00	92.4 AV			1.08 H	315	60.24	32.16
3	2483.50	60.6 PK	74.0	-13.4	1.08 H	315	28.36	32.24
4	2483.50	47.7 AV	54.0	-6.3	1.08 H	315	15.46	32.24
5	4904.00	48.5 PK	74.0	-25.5	1.53 H	228	8.73	39.77
6	4904.00	36.1 AV	54.0	-17.9	1.53 H	228	-3.67	39.77
7	7356.00	54.8 PK	74.0	-19.2	1.09 H	229	7.25	47.55
8	7356.00	41.5 AV	54.0	-12.5	1.09 H	229	-6.05	47.55
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	108.4 PK			1.08 V	283	76.24	32.16
2	*2452.00	97.2 AV			1.08 V	283	65.04	32.16
3	2483.50	69.0 PK	74.0	-5.0	1.08 V	283	36.76	32.24
4	2483.50	52.8 AV	54.0	-1.2	1.08 V	283	20.56	32.24
5	4904.00	52.1 PK	74.0	-21.9	1.81 V	327	12.33	39.77
6	4904.00	36.8 AV	54.0	-17.2	1.81 V	327	-2.97	39.77
7	7356.00	55.3 PK	74.0	-18.7	1.00 V	123	7.75	47.55
8	7356.00	42.0 AV	54.0	-12.0	1.00 V	123	-5.55	47.55

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP40	100036	Dec. 14, 2011	Dec. 13, 2012

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 13, 2012


4.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	12.59	0.5	PASS
6	2437	12.49	0.5	PASS
11	2462	12.60	0.5	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.59	0.5	PASS
6	2437	16.67	0.5	PASS
11	2462	16.61	0.5	PASS

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.84	0.5	PASS
6	2437	17.80	0.5	PASS
11	2462	17.77	0.5	PASS

802.11n (HT40)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	36.55	0.5	PASS
6	2437	36.68	0.5	PASS
9	2452	36.49	0.5	PASS

4.4 CONDUCTED OUTPUT POWER MEASUREMENT

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Power Meter	ML2495A	0824006	May 10, 2012	May 09, 2013
Peak Power Sensor	MA2411B	0738172	May 10, 2012	May 09, 2013

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 13, 2012


4.4.3 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	177.828	22.50	30	PASS
6	2437	489.779	26.90	30	PASS
11	2462	275.423	24.40	30	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	407.380	26.10	30	PASS
6	2437	977.237	29.90	30	PASS
11	2462	575.440	27.60	30	PASS

802.11n (HT20)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
1	2412	380.189	25.80	30	PASS
6	2437	954.993	29.80	30	PASS
11	2462	457.088	26.60	30	PASS

802.11n (HT40)

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
3	2422	245.471	23.90	30	PASS
6	2437	537.032	27.30	30	PASS
9	2452	446.684	26.50	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP40	100036	Dec. 14, 2011	Dec. 13, 2012

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 13, 2012

4.5.3 TEST PROCEDURE

1. Set the RBW = 100 kHz, VBW =300 kHz, Detector = peak.
2. Sweep time = auto couple.
3. Trace mode = max hold.
4. Allow trace to fully stabilize.
5. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
6. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(3 \text{ kHz}/100\text{kHz})$

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS

802.11b

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	13.18	-2.05	8	PASS
6	2437	17.78	2.55	8	PASS
11	2462	15.09	-0.14	8	PASS

802.11g

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	9.65	-5.58	8	PASS
6	2437	13.82	-1.41	8	PASS
11	2462	11.44	-3.79	8	PASS

802.11n (HT20)

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	9.07	-6.16	8	PASS
6	2437	13.28	-1.95	8	PASS
11	2462	10.61	-4.62	8	PASS

802.11n (HT40)

Channel	FREQ. (MHz)	PSD (dBm/100kHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
3	2422	3.64	-11.59	8	PASS
6	2437	7.22	-8.01	8	PASS
9	2452	7.10	-8.13	8	PASS



A D T

4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP40	100036	Dec. 14, 2011	Dec. 13, 2012

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Aug. 13, 2012

4.6.3 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.


MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.7 TEST RESULTS


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.




A D T

802.11b


CH 1



CH 6



CH 11









A D T

802.11g



CH 1



CH 6



CH 11









A D T

802.11n (HT20)



CH 1



CH 6



CH 11







A D T

802.11n (HT40)


CH 3



CH 6



CH 9



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



A D T

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---