

# **RF Exposure Report**

Report No.: SA150703E06

FCC ID: U8G-P1AC1

Test Model: AP One Enterprise

Series Model: Pismo AC1

Received Date: July 03, 2015

**Test Date:** Aug. 13, 2015

**Issued Date:** Aug. 24, 2015

Applicant: Pismo Labs Technology Limited

Address: FLAT/RM A5, 5/F, HK SPINNERS IND BLDG PHASE 6, 481 CASTLE PEAK

ROAD, CHEUNG SHA WAN, HONG KONG.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

Lab Address: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin

Chu Hsien 307, Taiwan R.O.C.

Test Location (1): No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin

Chu Hsien 307, Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin

Chu Hsien 307, Taiwan R.O.C.

Test Location (3): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



# **Table of Contents**

Re	Release Control Record				
1	Certificate of Conformity	4			
2	RF Exposure	5			
	1 Limits for Maximum Permissible Exposure (MPE)	5			
3	Calculation Result of Maximum Conducted Power	6			



## **Release Control Record**

Issue No.	Description	Date Issued
SA150703E06	Original release.	Aug. 24, 2015



## 1 Certificate of Conformity

Product: Pepwave / Peplink / Pismo Wireless Product

Brand: Pepwave / Peplink / Pismo

Test Model: AP One Enterprise

Series Model: Pismo AC1

Sample Status: MASS-PRODUCTION

Applicant: Pismo Labs Technology Limited

Test Date: Aug. 13, 2015

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03

**IEEE C95.1** 

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Approved by:

May Chen Manager

Aug. 24, 2015

Report No.: SA150703E06 Page No. 4 / 6 Report Format Version: 6.1.1



### 2 RF Exposure

# 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
300-1500			F/1500	30				
1500-100,000			1.0	30				

F = Frequency in MHz

### 2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$ 

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Report No.: SA150703E06 Page No. 5 / 6 Report Format Version: 6.1.1



#### 3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm²)
2412-2462	270.521	8.74	20	0.40265	1
5180-5240, 5745-5825	121.128	10.57	20	0.27477	1

Note:

2.4GHz: Directional gain = 10 log[ $(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3$ ] = 8.74dBi 5GHz: Directional gain = 10 log[ $(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3$ ] = 10.57dBi

### **Conclusion:**

Both of the 2.4GHz and 5GHz WLAN can transmit simultaneously, the formula of calculated the MPE is:

CPD<sub>1</sub> / LPD<sub>1</sub> + CPD<sub>2</sub> / LPD<sub>2</sub> + .....etc. < 1

**CPD = Calculation power density** 

LPD = Limit of power density

Therefore, the worst-case situation is 0.40265 / 1 + 0.27477 / 1 = 0.677, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---