

Maximum Permissible Exposure 1

Maximum Permissible Exposure 1.1

1.1.1 **Limit of Maximum Permissible Exposure**

Limits for Occupational / Controlled Exposure					
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ², H ² or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1,842 / f	4.89 / f	(900 / f ²)*	6	
30-300	61.4	0.163	1.0	6	
300-1,500			F/300	6	
1,500-100,000			5	6	

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ², H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1,500			F/1500	30
1,500-100,000			1.0	30

Note 1: f = frequency in MHz; *Plane-wave equivalent power density

Note 2: For the applicable limit, see FCC 1.1310

1.1.2 MPE Calculation Method

$$E (V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$

E = Electric field (V/m)

G = EUT Antenna numeric gain (numeric) The formula can be changed to

 $Pd = \frac{30 \times P \times G}{}$

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

Power Density: Pd (W/m²) = $\frac{E^2}{377}$

P = RF output power (W)

d = Separation distance between radiator and human body (m)

Report No.: FA461201

SPORTON INTERNATIONAL INC. Page No. : 1 of 2 TEL: 886-3-327-3456 Report Version : Rev. 01

FAX: 886-3-327-0973

1.1.3 Result of Maximum Permissible Exposure

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	Number of Transmit Chains (N _{TX})	RF Output Power (dBm)
2400-2483.5	b	2412-2462	1-11 [11]	1	17.66
2400-2483.5	g	2412-2462	1-11 [11]	1	13.78
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	16.02
Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.					

Report No. : FA461201

Worst Maximum RF Output Power Result						
Exposure Environment		General Population / Uncontrolled Exposure				
Separation Distance (cm)		20				
Condition		RF Output Power (dBm)				
Modulation Mode	N _{TX}	RF Output Power (dBm)	Ant. Gain (dBi)	EIRP Power	PD (S) (mW/cm²)	
11b	1	17.66	5.00	22.66	0.037	
Maximum Permissible Exposure Limit (mW/cm²)				1		
Note 1: N _{TX} = Number of	Trans	mit Chains				

SPORTON INTERNATIONAL INC. Page No. : 2 of 2
TEL: 886-3-327-3456 Report Version : Rev. 01

FAX: 886-3-327-0973